**PSEUDOCODE**

*-PRASANGA RAJBHANDARI*

```
1. CREATE a dictionary called services with service names and prices

2. CREATE an empty list called bookings

3. DEFINE FUNCTION show_services:
    DISPLAY "Available Services"
    FOR EACH service in services:
        DISPLAY service name and price

4. DEFINE FUNCTION book_appointment:
    TRY:
        ASK user for name
        FORMAT name

        CALL show_services

        ASK user to enter multiple services (comma separated)
        SPLIT input into a list of selected services

        ASK user to enter time (am/pm format)

        IF time does not contain "am" or "pm":
            DISPLAY "Invalid time format"
            STOP FUNCTION

        FOR EACH existing booking in bookings:
            IF booking time is the same:
```

```
            DISPLAY "Time already booked"
            STOP FUNCTION

        SET total cost to 0
        CREATE empty list for valid services

        FOR EACH selected service:
            IF service exists in dictionary:
                ADD service to valid services list
                ADD price to total cost
            ELSE:
                DISPLAY "Invalid service"
                STOP FUNCTION

        CREATE booking record with:
            name, list of services, time, total cost

        ADD booking to bookings list

        DISPLAY receipt:
            name, time, selected services, total cost

    EXCEPT:
        DISPLAY error message

5. DEFINE FUNCTION show_bookings:
    TRY:
        IF bookings list is empty:
            DISPLAY "No bookings available"
            STOP FUNCTION
```

```
        FOR EACH booking:
            DISPLAY name, services, time, total cost

    EXCEPT:
        DISPLAY error message

6. START MAIN LOOP:
    DISPLAY menu:
        1. Book
        2. View
        3. Exit

    TRY:
        ASK user for choice

        IF choice is 1:
            CALL book_appointment

        ELSE IF choice is 2:
            CALL show_bookings

        ELSE IF choice is 3:
            DISPLAY goodbye message
            END program

        ELSE:
            DISPLAY "Invalid choice"

    EXCEPT:
```

DISPLAY "Invalid input"

7. REPEAT loop until user exits