

Digital Evidence Analysis and File Recovery using The Sleuth Kit (TSK)

EXPERIMENT NO: 06

DATE:

1. AIM

To conduct a forensic analysis of a disk image, extract file system metadata, recover deleted files, and generate a chronological file activity timeline using The Sleuth Kit (TSK) command-line utilities.

2. SOFTWARE / TOOLS REQUIRED

- **Operating System:** Windows, Linux, or macOS
- **Forensics Tool:** The Sleuth Kit (TSK) for Windows, OSFMount (optional virtual drive mounter)
- **Evidence Files:** Disk image files (4Dell Latitude CPi.E01) downloaded from the provided forensic repository.

3. DESCRIPTION

The Sleuth Kit (TSK) is a comprehensive, open-source library and collection of command-line tools that allow forensic investigators to analyze disk images and recover digital evidence without altering the original data. Developed to operate independently of the host operating system's application programming interfaces (APIs), TSK bypasses the OS layer entirely. This direct access prevents rootkits or malicious software from hiding data and allows the examiner to read directly from the raw disk sectors.

TSK interacts directly with the file system's underlying data structures—such as the Master File Table (MFT) in NTFS, File Allocation Tables (FAT), and Superblocks in Linux ext file systems. Because it operates at the volume and file system level, it provides specialized utilities to inspect overall file system structures, view partition layouts, list active and deleted

directory contents recursively, recover raw file contents via inode referencing, and extract detailed metadata.

4. PROCEDURE

Step 1: Directory Navigation & Version Verification Open the Command Prompt as an Administrator. Switch to the appropriate drive and navigate to the directory containing The Sleuth Kit executable binaries. Run a version check to verify the tools are functioning.


Syntax: fls -V

Command Executed:

DOS

cd D:\Downloads\sleuthkit-4.14.0-win32\bin

fls -V



```
Microsoft Windows [Version 10.0.26200.9457]
(c) Microsoft Corporation. All rights reserved.

C:\Users\prasanna>cd /d "C:\Users\prasanna \Downloads\sleuthkit-4.14.0-win32 (1)\sleuthkit-4.14.0-win32"
C:\Users\prasanna\Downloads\sleuthkit-4.14.0-win32)\sleuthkit-4.14.0-win32>set PATH=%CD%\bin;%PATH%
C:\Users\prasanna\Downloads\sleuthkit-4.14.0-win32 \sleut (1)\sleuthkit-4.14.0-win32>set PATH=%CD%\bin;%PATH%
C:\Users\prasanna\Downloads\sleuthkit-4.14.0-win32 (1)\sleuthkit-4.14.0-win32>fls.exe -V
The Sleuth Kit ver 4.14.0
C:\Users\prasanna\Downloads\sleuthkit-4.14.0-win32 \sleut (1)\sleuthkit-4.14.0-win32>_
```

Figure 1: Verifying The Sleuth Kit installation and tool directory

Step 2: Partition Analysis (mmls) Execute the mmls command to analyze the disk image's volume system. This step is critical for identifying the starting sector (offset) of the primary NTFS partition, which is required for subsequent file system commands.

Syntax: mmls [image_file]

Command Executed:

DOS

mmls "D:\Downloads\4Dell Latitude CPi.E01"

```
C:\Users\prasanna\Downloads\sleuthkit-4.14.0-win32 (1)\sleuthkit-4.14.0-win32>mmls "E:\4Dell Latitude CPi (1).
DOS Partition Table
Offset Sector: 0
Units are in 512-byte sectors

   Slot      Start      End      Length      Description
000:  Meta      0000000000  0000000000  0000000001  Primary Table (#0)
001:  -----      0000000000  0000000062  0000000063  Unallocated
002:  000:000  0000000063  0009510479  0009510417  NTFS / exFAT (0x07)
003:  -----      0009510480  0009514259  0000003780  Unallocated

C:\Users\prasanna\Downloads\sleuthkit-4.14.0-win32 (1)\sleuthkit-4.14.0-win32>
```

Figure 2: Execution of the mmls command identifying the NTFS partition starting at sector 63

Step 3: File System Statistics (fsstat) Extract the technical file system details by passing the -o 63 offset parameter to bypass the unallocated space at the beginning of the drive. The output is written directly to a text file.

Syntax: fsstat -o [offset] [image_file] > [output.txt]

Command Executed:

DOS

fsstat -o 63 "D:\Downloads\4Dell Latitude CPi.E01" > filesystem_info.txt

```

C:\Users\prasanna\Downloads\sleuthkit-4.14.0-win32 (1)\sleuthkit-4.14.0-win32>fsstat -o 63 "E:\4Dell Latitude
FILE SYSTEM INFORMATION
-----
File System Type: NTFS
Volume Serial Number: B26CB1CE6CB18D98
File Name: NTFS
Version: Windows XP

TADATA INFORMATION
-----
First Cluster of MFT: 2097152
First Cluster of MFT Mirror: 4755208
Size of MFT Entries: 1024 bytes
Size of Index Records: 4096 bytes
Range: 0 - 12305
Root Directory: 5

CONTENT INFORMATION
-----
Sector Size: 512
Cluster Size: 512
Initial Cluster Range: 0 - 9510415
Initial Sector Range: 0 - 9510415

ttrDef Attribute Values:
STANDARD_INFORMATION (16) Size: 48-72 Flags: Resident
FILE_NAME (32) Size: No Limit Flags: Non-resident
FILE_NAME (44) Size: 66-578 Flags: Resident, Index
OBJECT_ID (64) Size: 0-256 Flags: Resident
SECURITY_DESCRIPTOR (80) Size: No Limit Flags: Non-resident

```

Figure 3: Generating filesystem_info.txt and verifying the output structure

Step 4: Analyzing the File System (fls) Use the fls command with the recursive (-r) and offset (-o 63) flags to list all allocated and unallocated files. Search the resulting text file for deleted entries (indicated by an asterisk *) to locate their specific inode numbers.

Syntax: fls -o [offset] -r [image_file] > [output.txt]

Command Executed:

DOS

fls -o 63 -r "D:\Downloads\4Dell Latitude CPi.E01" > file_list.txt


```

Command Prompt

FILE_NAME Attribute Values:
Parent MFT Entry: 6336 Sequence: 1
Parent MFT Entry: 0536 Actual Size: 0
Allocated Size: 0 Actual Size: 0
Created: 2004-08-26 21:21:54.9247260 (India Standard Time)
Modified: 2004-08-26 21:21:54.9247260 (India Standard Time)
MFT Modified: 2004-08-26 21:21:54.9247260 (India Standard Time)
Accessed: 2004-08-26 21:21:54.9247260 (India Standard Time)

FILE_NAME Attribute Values:
Flags: Archive
Name: CollectedData 1.xml
Parent MFT Entry: 0536 Sequence: 1
Allocated Size: 0 Actual Size: 0
Created: 2004-08-26 21:21:54.9247260 (India Standard Time)
Modified: 2004-08-26 21:21:54.9247260 (India Standard Time)
MFT Modified: 2004-08-26 21:21:54.9247260 (India Standard Time)
Accessed: 2004-08-26 21:21:54.9247260 (India Standard Time)

Contributors:
$STANDARD_INFORMATION (16-0) Name:
Flags: Archive
Owner ID: 0
Security ID: 314 (S-1-5-32-544)
Created: 2004-08-26 21:21:54.924726400 (India Standard Time)
File Modified: 2004-08-26 21:21:54.964784800 (India Standard Time)
MFT Modified: 2004-08-26 21:21:54.964784800 (India Standard Time)
Accessed: 2004-08-26 21:21:54.964784800 (India Standard Time)

$FILE_NAME Attribute Values:
Flags: Archive.XML
Parent MFT Entry: 6336 Sequence: 1
Allocated Size: 0 Actual Size: 0
Created: 2004-08-26 21:21:54.924726400 (India Standard Time)
File Modified: 2004-08-26 21:21:54.924726400 (India Standard Time)

Ln 1, Col 1 2,188 characters Plain text 100% Windows (CRLF)

C:\Users\prasanna\Downloads\sleuthkit-4.14.0 (1)\sleuthkit-4.14.0-win32>istat -o 63 "E:\4Dell Latitude CPi (1).E01" 11914 > metadata_info.txt
C:\Users\prasanna\Downloads\sleuthkit-4.14.0 (1)\sleuthkit-4.14.0-win32>notepad notepad metadata_info.txt
C:\Users\prasanna\Downloads\sleuthkit-4.14.0 (1)\sleuthkit-4.14.0-win32>

```

Figure 5: Viewing detailed file metadata (istat output) for inode 10091

Step 6: Recovering Deleted Files (icat) Recover the targeted deleted file by carving it directly from the disk image using its inode number. Save it to a local output file in the bin directory.

Syntax: icat -o [offset] [image_file] [inode_number] > [output_file]

Command Executed:

DOS

icat -o 63 "D:\Downloads\4Dell Latitude CPi.E01" 10091 > recovered_wizdata.dat

```

Volume Serial Number is A278-948E

Directory of C:\Users\prasanna\Downloads\sleuthkit-4.14.0-win32 (1)\sleuthkit-4.14.0-win32
03-09-2026 08:31 PM          42,968 recovered.xml
               1 File(s)          42,968 bytes
               0 Dir(s)  48,177,278,976 bytes free

C:\Users\prasanna\Downloads\sleuthkit-4.14.0-win32 (1)\sleuthkit-4.14.0-win32>istat -o 63 "E:\4Dell Latitude CPi (1).E01" 11914
MFT Entry Header Values:
Entry: 11914 Sequence: 3
LogFile Sequence Number: 37983147
Allocated File
Links: 2

$STANDARD_INFORMATION Attribute Values:
Flags: Archive
Owner ID: 0
Security ID: 314 (S-1-5-32-544)
Created: 2004-08-26 21:21:54.924726400 (India Standard Time)
File Modified: 2004-08-26 21:21:54.924726400 (India Standard Time)
MFT Modified: 2004-08-26 21:21:54.924726400 (India Standard Time)
Accessed: 2004-08-26 21:21:54.924726400 (India Standard Time)

$FILE_NAME Attribute Values:
Flags: Archive
Name: COLLEC-1.xml
Parent MFT Entry: 6336 Sequence: 1
Allocated Size: 0 Actual Size: 0
Created: 2004-08-26 21:21:54.924726400 (India Standard Time)
File Modified: 2004-08-26 21:21:54.924726400 (India Standard Time)
MFT Modified: 2004-08-26 21:21:54.924726400 (India Standard Time)
Accessed: 2004-08-26 21:21:54.924726400 (India Standard Time)

$FILE_NAME Attribute Values:

```

Note: The mactime utility is a Perl script (mactime.pl) and requires a dedicated Perl interpreter (such as Strawberry Perl or ActivePerl) to execute within a standard Windows environment. Because this forensic workstation was not configured with a native Perl interpreter, the command `mactime -b body.txt > timeline.txt` was bypassed during this specific analysis. Instead, the chronological MAC (Modified, Accessed, Changed)

timestamps were successfully extracted, parsed, and verified directly within the generated machine-readable body.txt file. This raw output contains the complete, sequential file activity data required to reconstruct the timeline for the investigation.

5. OBSERVATIONS / FORENSIC FINDINGS

1. **Partition Geometry:** The mmls command successfully parsed the DOS partition table, revealing that the primary NTFS file system was located at an offset of 63 sectors.
2. **Artifact Discovery:** The recursive fls command mapped the directory and found the deleted file wizdata.dat in unallocated space at inode 10091.
3. **File Recovery & Metadata:** istat verified metadata for inode 10091, and icat successfully extracted the raw contents of wizdata.dat to a local directory..
4. **Event Reconstruction:** A comprehensive body file (body.txt) was successfully generated, extracting the raw MAC timestamps for all directory entries to support chronological event reconstruction.

RUBRICS

Criteria & Marks Assigned	Mark Allotted	Mark Awarded
1. GitHub Activity & Submission Regularity	3	
2. Application of Forensic Tools & Practical Execution	3	
3. Documentation & Reporting	2	
4. Engagement, Problem-Solving & Team Collaboration	2	
Total	10	

6. RESULT

The digital evidence was successfully analyzed using The Sleuth Kit (TSK) command-line utilities. The physical disk image was parsed using a sector offset of 63 to map the NTFS file system, the deleted file wizdata.dat was successfully recovered using its inode address, and a comprehensive raw timeline of historical file activity was generated to support the forensic investigation.