

14 October 2024

Document Title/(Short Description): Reports

Audience: All Testing team or anyone playing the role of Tester or Test Lead at Navistar International.

Classification: Soft Rail

SNOW Article Number: KB0015361

(Summary/Description): Reports present complex data and insights in a more understandable and actionable format. Reports further empower analysts to share timely and relevant information with key stakeholders, such as management, security teams, and other relevant parties.

Navistar supports the following types of reports:

- **Standard Reports:** Leverage saved searches, CQL queries, and filters to access specific data sets and build reports based on the selected parameters.
- **Advanced Reports:** Leverage widgets, tables, queries, filters, and images to access data and present them in an understandable and visually appealing format.

Supported Version

Navistar Threat Intelligence eXchange 3.6.2

Supported Content Types

By default, all NTIX APIs support the application/json content type.

Authentication

Generate API credentials

Generate the API credentials to get the access ID, secret key, and base URL of your NTIX application. You can generate Open API credentials to integrate navistar Exchange in a third-party application for a defined period.

Before you Start

Ensure that you have **Create** and **Update** permission for **NTIX Integrators**.

Steps

To generate the open API credentials, follow these steps:

1. Go to **Administration > Integration Management**.
2. Click **NTIX Integrators** under **Third Party Developers**.
3. Click **Add New**.
4. Enter the following details:
 - **Name:** Enter a unique title within 50 characters for the API.
 - **Description:** Enter a description within 1000 characters.
 - **Expiry Date:** Select an expiry date for API keys. You can select **Expires On** and select the date. You can select **Never Expire**.
5. Click **Add New**.
6. Click **Download** to download the API credentials in CSV format. You can also click **Copy** to copy the Endpoint URL, Secret Key, or Access ID.

Note: It is recommended to download the API credentials since you cannot recover the credentials later.

Define Open API rate limits

Define rate limits for your APIs to ensure that all your API users are getting a fair share of the application resources. This also ensures that APIs and servers run smoothly and efficiently.

You can define how many requests your API users can make in a defined time period. A tenant can have many API users with API credentials defined for each of them. This is a global setting, and it applies to all your API users who have configured API integration with NTIX.

1. Sign in to the NTIX application.

2. From the **Administration** module, select **Configuration**.
3. Select **API** and click **Edit**.
4. In the Per minute rate limit box, enter the number of requests that the user can make in a minute.
5. In the Per hour rate limit box, enter the number of requests that the user can make in an hour.
6. In the Per day rate limit box, enter the number of requests that the user can make in a day.
7. Click **Save**.

POST Create Report

Creates a basic (standard) report in Navistar.

`{{server_url}}/ingestion/reports/?type=basic`

Note: Do not use this endpoint to create advanced reports.

Request Parameters

Parameters	Type	Required	Description
schedule	JSON Object	Optional	Pass the schedule details such as repeat type, start date and time, duration time, duration value, and repeat value.
schedule: start_datetime	Timestamp	Mandatory	Enter the start time of the report in EPOCH format.
schedule: repeat_type	String	Mandatory	Pass the frequency of the schedule. Allowed values: once daily weekly monthly

Parameters	Type	Required	Description
schedule: ends_on	JSON Object	Mandatory	Pass the end time of the report.
schedule: ends_on: type	String	Mandatory	Pass the schedule end type. Allowed values: never end_date occurrences
schedule: ends_on: value	Timestamp (If the ends_on: type is end_date) Integer (If the ends_on: type is occurrences)	Mandatory	Pass the end time in EPOCH format or the number of occurrences.
schedule: duration_value	Integer	Mandatory	Pass the time frame in days to include the data in the report.
saved_search	JSON Object	Mandatory	Pass the saved search or custom query details used for generating the report.
saved_search: id (To create a report using a saved search)	String	Mandatory	Pass the ID of a saved search to generate the report.
saved_search: query (To create a report using custom filters)	String	Mandatory	Pass the query to generate the report.
saved_search: meta_data (To create a report using custom filters)	String	Optional	Pass any metadata to include.

Parameters	Type	Required	Description
query_key	String	Optional	Pass the key to sort data in the report: <code>ctix_created</code> (Default): Data in the report is sorted based on the system created date. <code>ctix_modified</code> : Data in the report is sorted based on the system modified date.
name	String	Mandatory	Pass the name of the report.
columns	Array of JSON objects	Mandatory	Pass the list of columns to be displayed in a basic report.
file_types	Array	Mandatory	Pass the report type, such as <code>csv</code> , <code>xls</code> .
type	String	Mandatory	Pass the type of report to be created, such as standard or advanced. Allowed value: <code>basic</code> (to create standard reports)
shared_type	String	Mandatory	Pass the share type value. Allowed values: <code>private</code> <code>global</code>
internal_recipients	JSON Object	Optional	Pass the list of internal recipients with whom to share the report.
external_recipients	JSON Object	Optional	Pass the list of external recipients with whom to share the report.

Response Parameters

Parameter	Type	Description
basic_report_type	String	Returns the type of basic report, such as saved or custom.
schedule: id	String	Returns the unique ID of the schedule.
schedule: repeat_type	String	Returns the time interval for the re-run of the report.
schedule: start_datetime	Timestamp	Returns the starting date and time in EPOCH format from which the report captures the received data.
schedule: repeat_value	Integer	Returns the schedule frequency.
schedule: duration_type	String	Returns the end duration interval for the captured data.
schedule: duration_value	Integer	Returns the duration in days to capture data in the report.
query_key	String	Returns the sorting type in basic reports: <code>ctix_created</code> : Data in the report is sorted based on the system created date. <code>ctix_modified</code> : Data in the report is sorted based on the system modified date.
name	String	Returns the name of the report.
id	String	Returns the unique ID of the report.
columns	Array of JSON objects	Returns the list of columns in a report.

Parameter	Type	Description
internal_recipients	JSON Object	Returns the list of internal recipients with whom to share the report.
external_recipients	JSON Object	Returns the list of external recipients with whom to share the report.
type	String	Returns the type of report, such as basic or advanced.
file_types	Array	Returns the report formats, such as CSV, XLS.
shared_type	String	Returns the shared type, such as global or private.
date_last_run	Timestamp	Returns the date and time in EPOCH format at which the report was manually run.
schedule_last_run	Timestamp	Returns the scheduled date and time in EPOCH format of the report generation.
saved_search	JSON Object	Returns the search object saved for the corresponding report used for generating the report.
created_by	JSON Object	Returns the details of the user who created the report.

PARAMS

Type

basic

[Mandatory] Pass the type of report to be created. Allowed value: basic

Body (json)

```
{
  "name": "ut atque exercitationem",
  "type": "basic",
  "basic_report_type": "custom",
  "shared_type": "global",
  "saved_search": {
    "meta_data": "{\"panelFilters\":{\"type\":{\"value\":[\"indicator\",\"malware\"]}},\"object_type\":[\"indicator\",\"malware\"]}\",
    "name": "tесеett",
    "query": "type = \"malware\""
  },
  "schedule": {
    "repeat_type": "daily",
    "start_datetime": 1638124200,
    "duration_value": 2,
    "repeat_value": 2
  },
  "file_types": [
    "csv"
  ],
  "columns": [{"key": "valid_until", "label": "Valid Until"}, {"key": "tags", "label": "Tags"}],
  "internal_recipients": {
    "to": [
```



```
{
  "user_id": "3504aa4a-1e56-40c6-89d7-fc3c6adc2b03",
  "first_name": "Aakriti",
  "last_name": "Arya",
  "email": "aakriti@cyware.com"
},
"cc": [],
"bcc": []
},
"query_key" : "ctix_created",
"external_recipients": {
  "to": [
    "bca@cyware.com"
  ],
  "cc": [],
  "bcc": []
}
}
```

Example Request

```
curl --location -g '{{server_url}}ingestion/reports/?type=basic' \
```

```
--data-raw '{
  "name": "Vulnerability Report",
  "type": "basic",
  "basic_report_type": "custom",
  "shared_type": "global",
  "saved_search": {
    "id": "57d957a8-c468-4a94-8c23-b74aa3540fb0"
  },
  "schedule": {
    "repeat_type": "daily",
    "start_datetime": 1638124200,
    "duration_type": "daily",
    "duration_value": 2,
    "repeat_value": 2
  },
  "file_types": [
    "csv"
  ],
  "columns": [{"key": "valid_until", "label": "Valid Until"}, {"key": "tags", "label": "Tags"}],
  "query_key" : "ctix_created",
  "external_recipients": {
    "to": [
```

```
"bca@cyware.com"
],
"cc": [],
"bcc": []
}
}'
```

Example Response

```
{
  "basic_report_type": "custom",
  "columns": [
    {
      "key": "valid_until",
      "label": "Valid Until"
    },
    {
      "key": "tags",
      "label": "Tags"
    }
  ],
  "created": 1692188813,
  "created_by": {
```

```
"email": "john.doe@cyware.com",
"first_name": "john",
"id": "0d4408bd-9f94-47ec-98eb-6f32ecfd8b13",
"last_name": ""
},
"date_last_run": null,
"external_recipients": {
  "bcc": [],
  "cc": [],
  "to": [
    "bca@cyware.com"
  ]
},
"file_types": [
  "csv"
],
"id": "334c3ff3-bfcc-402c-ad6a-e13cb830a602",
"internal_recipients": {
  "bcc": [],
  "cc": [],
  "to": [
    {
```

```
"user": null
}
],
{
  "modified": 1692188813,
  "modified_by": {
    "email": "john.doe@cyware.com",
    "first_name": "john",
    "id": "0d4408bd-9f94-47ec-98eb-6f32ecfd8b13",
    "last_name": "doe"
  },
  "name": "Vulnerability Report",
  "query_key": "ctix_created",
  "saved_search": {
    "created_by": {
      "email": "john.doe@cyware.com",
      "first_name": "john",
      "id": "76fbe1c3-5fd0-4674-9666-69921edafb94",
      "last_name": "doe"
    },
    "description": null,
    "editable": false,
```

```

"id": "57d957a8-c468-4a94-8c23-b74aa3540fb0",
"is_threat_data_search": true,
"meta_data":
{"object_type":["vulnerability"],"query":{"length":32,"dataKey":{"id":{"type":"","type":{"select","addAll":true,"reset":true,"multiple":true,"value":{"id","label":"Object Type"},"values":{"id":{"indicator","name":"Indicator"},"id":{"malware","name":"Malware"},"id":{"threat-actor","name":"Threat Actor"},"id":{"vulnerability","name":"Vulnerability"},"id":{"attack-pattern","name":"Attack Pattern"},"id":{"campaign","name":"Campaign"},"id":{"course-of-action","name":"Course of Action"},"id":{"identity","name":"Identity"},"id":{"infrastructure","name":"Infrastructure"},"id":{"intrusion-set","name":"Intrusion Set"},"id":{"location","name":"Location"},"id":{"malware-analysis","name":"Malware Analysis"},"id":{"observed-data","name":"Observed Data"},"id":{"opinion","name":"Opinion"},"id":{"tool","name":"Tool"},"id":{"report","name":"Report"},"id":{"custom-object","name":"Custom Object"},"id":{"observable","name":"Observable"},"id":{"incident","name":"Incident"}}},"key":"","ObjectType":"","keyType":"select","dataOperator":{"id":"","label":"","operator":"","dataValue":{"id":{"vulnerability","name":"Vulnerability"},"value":"","Vulnerability"}}}},
"name": "Vulnerability",
"order": 1,
"pinned": false,
"query": "type = \"vulnerability\"",
"shared_type": "global",
"shared_users": [],
"type": "cql
},
"schedule": {
"duration_value": 2,
"ends_on": {
"attempts_left": 10,

```

```
"type": "occurrences",  
  "value": 10  
},  
"id": "37bbeaac-a8d2-4571-a259-ee710342213e",  
"repeat_on": null,  
"repeat_type": "daily",  
"start_datetime": 1638124200  
},  
"shared_type": "global",  
"type": "basic"  
}
```

GET List Reports

Retrieves a list of reports from the Navistar application.

{{server_url}}/ingestion/reports/

Request Parameters

This API endpoint does not require any request parameter.

Response Parameters

Parameter	Type	Description
next	String	Returns the URL link to the next page.
previous	String	Returns the URL link of the previous page.
page_size	Integer	Returns the size of the requested page.
results	JSON Object	Returns results in JSON objects for each report.
schedule	JSON Object	Returns the details of the scheduled runs.
schedule: id	String	Returns the unique ID of the schedule.
schedule: repeat_type	String	Returns the time interval for the re-run of the report.
schedule: start_datetime	Timestamp	Returns the starting date and time in EPOCH format from which the report captures the received data.
schedule: repeat_value	Integer	Returns the number of times a report has to run during the provided interval.
schedule: ends_on	JSON Object	Returns the end type, number of attempts left, and end time.
schedule: duration_value	Integer	Returns the duration in days to capture data in the report.
query_key	String	Returns the sorting type in basic reports: ctix_created: Data in the report is sorted based on the system created date.

Parameter	Type	Description
		ctix_modified: Data in the report is sorted based on the system modified date.
name	String	Returns the title of the report.
id	String	Returns the unique ID of the report.
columns	Array of JSON objects	Returns the list of columns in a basic report.
internal_recipients	JSON Object	Returns the list of internal recipients with whom to share the report.
external_recipients	JSON Object	Returns the list of external recipients with whom to share the report.
type	String	Returns the type of report, such as a basic or advanced.
file_types	Array	Returns the report format, such as CSV and XLS for basic reports and PDF for advanced reports.
shared_type	String	Returns the shared type, such as global or private.
date_last_run	Timestamp	Returns the date and time in EPOCH format at which the report was the last run.
created_by	JSON Object	Returns the details of the user who created the report.
modified_by	JSON Object	Returns the details of the user who last modified the report.

PARAMS

type	<i>basic</i> Pass the type of report to filter reports. Allowed values: basic, advanced
page	<i>1</i> Pass the page number to retrieve reports.
page_size	<i>10</i> Pass the number of reports to retrieve per page.
repeat_type	<i>daily</i> Pass the frequency of the report run schedule. Allowed values: daily, weekly, monthly. Default: none
shared_type	<i>global</i> Pass the visibility of the reports. Allowed values: private, global
modified_by	<i>0d0f1f5b-752a-4987-a806-8a42822256b4</i> Pass the ID of the user who modified the reports.
created_from	<i>1650882890</i> Pass the created from time of the reports in EPOCH format.
created_to	<i>1650882898</i> Pass the created to time of the reports in EPOCH format.
modified_from	<i>1650882890</i> Pass the modified from time of the reports in EPOCH format.
modified_to	<i>1650882898</i> Pass the modified to time of the reports in EPOCH format.
date_last_run_from	<i>1651318940</i> Pass the last run from time of the reports in EPOCH format.
date_last_run_to	<i>1651318942</i> Pass the last run to time of the reports in EPOCH format.

Example Request

```
curl --location -g '{{server_url}}ingestion/reports/?type=basic&page_size=2'
```

Example Response

Body:

```
{
  "next": "reports/?page=2&page_size=2&type=basic",
  "page_size": 2,
  "previous": null,
  "results": [
    {
      "basic_report_type": "saved",
      "columns": [
        {
          "key": "name",
          "label": "Value"
        },
        {
          "key": "t1p",
          "label": "TLP"
        },
        {
          "key": "type",
          "label": "Type"
        },
        {
          "key": "confidence_score",
```

```
"label": "Conf Score"
},
{
  "key": "sources",
  "label": "Source"
},
{
  "key": "ctix_created",
  "label": "System Created Date"
},
{
  "key": "ctix_modified",
  "label": "System Modified Date"
},
{
  "key": "source_confidence",
  "label": "Source Confidence"
}
],
"created": 1690977181,
"created_by": {
  "email": "john.doe@cyware.com",
```

```
"first_name": "john",
"id": "0d4408bd-9f94-47ec-98eb-6f32ecfd8bxx",
"last_name": "doe"
},
"date_last_run": 1690977526,
"external_recipients": {
  "bcc": [],
  "cc": [],
  "to": []
},
"file_types": [
  "csv"
],
"id": "243558ea-b0e5-4290-a1dc-688d830f6e81",
"internal_recipients": {
  "bcc": [],
  "cc": [],
  "to": [
    {
      "user": null
    }
  ]
}
```

```
{,
  "modified": 1690977526,
  "modified_by": {
    "email": "john.doe@cyware.com",
    "first_name": "john",
    "id": "0d4408bd-9f94-47ec-98eb-6f32ecfd8b13",
    "last_name": "doe"
  },
  "name": "Malware report",
  "query_key": null,
  "saved_search": {
    "created_by": {
      "email": "john.doe@cyware.com",
      "first_name": "john",
      "id": "76fbe1c3-5fd0-4674-9666-69921edafb94",
      "last_name": "doe"
    },
    "description": null,
    "editable": false,
    "id": "a8a01156-d63a-42ed-810f-041b5b8bc4e3",
    "is_threat_data_search": true,
    "meta_data":
    "{\\"object_type\\":[\\"malware\\"],\\"query\\":[{\\"length\\":26,\\"dataKey\\":{\\"id\\":\\"type\\",\\"type\\":\\"select\\",\\"addAll\\":true,\\"reset\\":true,\\"mul
```

```

tiple\":true,\"value\\\":\\\"id\\\",\\\"label\\\":\\\"Object
Type\\\",\\\"values\\\":[{\\\"id\\\":\\\"indicator\\\",\\\"name\\\":\\\"Indicator\\\"},{\\\"id\\\":\\\"malware\\\",\\\"name\\\":\\\"Malware\\\"},{\\\"id\\\":\\\"threat-
actor\\\",\\\"name\\\":\\\"Threat Actor\\\"},{\\\"id\\\":\\\"vulnerability\\\",\\\"name\\\":\\\"Vulnerability\\\"},{\\\"id\\\":\\\"attack-pattern\\\",\\\"name\\\":\\\"Attack
Pattern\\\"},{\\\"id\\\":\\\"campaign\\\",\\\"name\\\":\\\"Campaign\\\"},{\\\"id\\\":\\\"course-of-action\\\",\\\"name\\\":\\\"Course of
Action\\\"},{\\\"id\\\":\\\"identity\\\",\\\"name\\\":\\\"Identity\\\"},{\\\"id\\\":\\\"infrastructure\\\",\\\"name\\\":\\\"Infrastructure\\\"},{\\\"id\\\":\\\"intrusion-
set\\\",\\\"name\\\":\\\"Intrusion Set\\\"},{\\\"id\\\":\\\"location\\\",\\\"name\\\":\\\"Location\\\"},{\\\"id\\\":\\\"malware-analysis\\\",\\\"name\\\":\\\"Malware
Analysis\\\"},{\\\"id\\\":\\\"observed-data\\\",\\\"name\\\":\\\"Observed
Data\\\"},{\\\"id\\\":\\\"opinion\\\",\\\"name\\\":\\\"Opinion\\\"},{\\\"id\\\":\\\"tool\\\",\\\"name\\\":\\\"Tool\\\"},{\\\"id\\\":\\\"report\\\",\\\"name\\\":\\\"Report\\\"},{\\\"id\\\":\\\"custo
m-object\\\",\\\"name\\\":\\\"Custom
Object\\\"},{\\\"id\\\":\\\"observable\\\",\\\"name\\\":\\\"Observable\\\"},{\\\"id\\\":\\\"incident\\\",\\\"name\\\":\\\"Incident\\\"}]]},\\\"key\\\":\\\"Object
Type\\\",\\\"keyType\\\":\\\"select\\\",\\\"dataOperator\\\":{\\\"id\\\":\\\"=\\\",\\\"label\\\":\\\"=\\\",\\\"operator\\\":\\\"=\\\",\\\"dataValue\\\":{\\\"id\\\":\\\"malware\\\",\\\"name\\\":
\\\"Malware\\\"},{\\\"value\\\":\\\"\\\"\\\"Malware\\\"\\\"}}}],

  \"name\": \"Malware\",

  \"order\": 3,

  \"pinned\": false,

  \"query\": \"type = \\\"malware\\\"\",

  \"shared_type\": \"global\",

  \"shared_users\": [],

  \"type\": \"cql\"

},

\"schedule\": {

  \"duration_value\": 7,

  \"ends_on\": {

    \"attempts_left\": 10,

    \"type\": \"occurrences\",

    \"value\": 10

  },


```

```
"id": "36d479a0-6d8e-4722-bb98-c0ea6ec1808f",
"repeat_on": null,
"repeat_type": "once",
"start_datetime": 1690977183
},
"shared_type": "private",
"type": "basic"
},
{
  "basic_report_type": "custom",
  "columns": [
    {
      "key": "name",
      "label": "Value"
    },
    {
      "key": "tlp",
      "label": "TLP"
    },
    {
      "key": "type",
      "label": "Type"
    }
  ]
}
```



```
    },  
    {  
      "key": "confidence_score",  
      "label": "Conf Score"  
    },  
    {  
      "key": "sources",  
      "label": "Source"  
    },  
    {  
      "key": "ctix_created",  
      "label": "System Created Date"  
    },  
    {  
      "key": "ctix_modified",  
      "label": "System Modified Date"  
    },  
    {  
      "key": "source_confidence",  
      "label": "Source Confidence"  
    }  
  ],
```

```
"created": 1691401618,
"created_by": {
  "email": "john.doe@cyware.com",
  "first_name": "john",
  "id": "9381304d-0a09-43d3-bdb4-7be41104d281",
  "last_name": "doe"
},
"date_last_run": 1691401852,
"external_recipients": {
  "bcc": [],
  "cc": [],
  "to": []
},
"file_types": [
  "csv"
],
"id": "6cfb45f7-ff9a-43ac-8956-c550f781046d",
"internal_recipients": {
  "bcc": [],
  "cc": [],
  "to": [
    {
```

```
"user": null
}
],
{
  "modified": 1691491233,
  "modified_by": {
    "email": "john.doe@cyware.com",
    "first_name": "john",
    "id": "9381304d-0a09-43d3-bdb4-7be41104d281",
    "last_name": "doe"
  },
  "name": "Infra Report",
  "query_key": null,
  "saved_search": {
    "created_by": {
      "email": "john.doe@cyware.com",
      "first_name": "john",
      "id": "9381304d-0a09-43d3-bdb4-7be41104d281",
      "last_name": ""
    },
    "description": null,
    "editable": false,
```

```

"id": "bc683ffa-0063-46ad-b619-a4cab6a4b3f0",
"is_threat_data_search": false,
"meta_data":
{"object_type": [], "query": [{"length": 33, "dataKey": {"id": "type", "type": "select", "subProperty": true, "addAll": true, "reset": true, "multiple": true, "value": "id", "label": "Object Type", "key": "Object Type", "keyType": "select", "dataOperator": {"id": "=", "label": "=", "operator": "=", "dataValue": {"id": "infrastructure", "name": "Infrastructure"}, "value": "\\\\"Infrastructure\\""}}, {"name": "f42d2b9f-1d54-4a24-8cd1-c8dd74efc420",
"order": -1,
"pinned": false,
"query": "type = \"infrastructure\"",
"shared_type": "private",
"shared_users": [],
"type": "cql"
},
"schedule": {
"duration_value": 7,
"ends_on": {
"attempts_left": 10,
"type": "occurrences",
"value": 10
},
},
"id": "b7ae91d4-babc-49b6-938a-4382c308ae91",
"repeat_on": null,

```

```
{
  "repeat_type": "once",
  "start_datetime": 1691401621
},
{
  "shared_type": "global",
  "type": "basic"
}
],
"total": 6
}
```

PUT Update Report

Updates specific fields of a report.

```
{{server_url}}ingestion/reports/:report_id/?type=basic
```

Request Parameters

Parameters	Type	Required	Description
schedule	JSON Object	Optional	Pass the schedule details such as repeat type, start date and time, duration time , duration value, and repeat value.
schedule: start_datetime	Timestamp	Mandatory	Enter the start time of the report in EPOCH format.
schedule: repeat_type	String	Mandatory	Pass the frequency of the schedule. Allowed values: once daily weekly monthly
schedule: ends_on	JSON Object	Mandatory	Pass the end time of the report.
schedule: ends_on: type	String	Mandatory	Pass the schedule end type. Allowed values: never end_date occurrences

schedule: ends_on: value	Timestamp (If the ends_on: type is end_date) Integer (If the ends_on: type is occurrences)	Mandatory	Pass the end time in EPOCH format or the number of occurrences.
schedule: duration_value	Integer	Mandatory	Pass the time frame in days to include the data in the report.
query_key	String	Optional	Pass the key to sort data in the report: ctix_created (Default): Data in the report is sorted based on the system created date. ctix_modified: Data in the report is sorted based on the system modified date.
saved_search	JSON Object	Optional	Pass the saved search or custom query details used for generating the report.
saved_search: id (To create a report using a saved search)	String	Mandatory	Pass the ID of a saved search to generate the report.
saved_search: query (To create a report using custom filters)	String	Mandatory	Pass the query to generate the report.
saved_search: meta_data (To create a report using custom filters)	String	Optional	Pass any metadata to include.
name	String	Optional	Pass the name of the report.
columns	Array of JSON Objects	Optional	Pass the list of columns of the report.
file_types	Array	Optional	Pass the report type, such as csv, xls.
type	String	Optional	Pass the type of report. Allowed value: basic (to update standard reports)
shared_type	String	Optional	Pass the share type value. Allowed values: private global
internal_recipients	JSON Object	Optional	Pass the list of internal recipients with whom to share the report.

external_recipients	JSON Object	Optional	Pass the list of external recipients with whom to share the report.
schedule: ends_on: type	String	Mandatory	Pass the schedule end type. Allowed values: never end_date occurrences
schedule: ends_on: value	Timestamp (If the ends_on: type is end_date) Integer (If the ends_on: type is occurrences)	Mandatory	Pass the end time in EPOCH format or the number of occurrences.
schedule: duration_value	Integer	Mandatory	Pass the time frame in days to include the data in the report.
query_key	String	Optional	Pass the key to sort data in the report: ctix_created (Default): Data in the report is sorted based on the system created date. ctix_modified: Data in the report is sorted based on the system modified date.
internal_recipients	JSON Object	Optional	Pass the list of internal recipients with whom to share the report.
external_recipients	JSON Object	Optional	Pass the list of external recipients with whom to share the report.

Response Parameters

Parameter	Type	Description
basic_report_type	String	Returns the type of basic report, such as saved or custom.
schedule: id	String	Returns the unique ID of the schedule.
schedule: repeat_type	String	Returns the time interval for the re-run of the report.

Parameter	Type	Description
schedule: start_datetime	Timestamp	Returns the starting date and time in EPOCH format from which the report captures the received data.
schedule: repeat_value	Integer	Returns the schedule frequency.
schedule: duration_type	String	Returns the end duration interval for the captured data.
schedule: duration_value	Integer	Returns the duration in days to capture data in the report.
columns	Array of JSON Objects	Returns the list of columns in a report.
internal_recipients	JSON Object	Returns the list of internal recipients with whom to share the report.
external_recipients	JSON Object	Returns the list of external recipients with whom to share the report.
type	String	Returns the type of report, such as basic or advanced.
file_types	Array	Returns the report formats, such as CSV, XLS.
shared_type	String	Returns the shared type, such as global or private.
date_last_run	Timestamp	Returns the date and time in EPOCH format at which the report was manually run.

Parameter	Type	Description
schedule_last_run	Timestamp	Returns the scheduled date and time in EPOCH format of the report generation.
saved_search	JSON Object	Returns the saved search object for the corresponding report used for generating the report.
created_by	JSON Object	Returns the details of the user who created the report.
columns	Array of JSON Objects	Returns the list of columns in a report.

PARAMS

type

basic

[Mandatory] Pass the type of report to be created. Allowed value: basic

PATH VARIABLES

report_id

{{report_id}}

Pass the ID of a report (87c07bb3-b60c-4279-a5ec-8a38f73f7ea4)

Body (json)

```
{  
  "schedule": {  
    "repeat_type": "monthly",
```

```
"start_datetime": 1638124200,
"repeat_value": 2,
"duration_value": 2
},
"name": "test_edited",
"query_key": "ctix_created",
"columns": [
  {
    "key": "valid_until",
    "label": "Valid Until"
  }
],
"internal_recipients": {
  "to": [
    {
      "user_id": "3504aa4a-1e56-40c6-89d7-fc3c6adc2b03",
      "first_name": "Aakriti",
      "last_name": "Arya",
      "email": "aakriti@cyware.com"
    }
  ],
  "cc": [],
```

```
"bcc": []
},
"external_recipients": {
  "to": [
    "bca@cyware.com"
  ],
  "cc": [],
  "bcc": []
},
"type": "basic",
"file_types": [
  "csv"
],
"shared_type": "global",
"saved_search": {
  "name": "test_edited",
  "type": "cql",
  "query": "type = \"malware\"",
  "meta_data": "{\"panelFilters\":{\"type\":{\"value\":[\"indicator\",\"malware\"]}},\"object_type\":[\"indicator\",\"malware\"]}"
}
}
```

Example Request

```
curl --location --request PATCH 'https://zeus.mycyware.com/ctixapi/ingestion/reports/d9cf071b-e0cf-42f1-8d7d-cc6e1cffd1f6/' \
--data-raw '{
  "name": "Vulnerability Report",
  "type": "basic",
  "basic_report_type": "custom",
  "shared_type": "global",
  "saved_search": {
    "id": "57d957a8-c468-4a94-8c23-b74aa3540fb0"
  },
  "schedule": {
    "repeat_type": "daily",
    "start_datetime": 1638124200,
    "duration_type": "daily",
    "duration_value": 2,
    "repeat_value": 2
  },
  "file_types": [
    "csv"
  ],
  "columns": [{"key": "valid_until", "label": "Valid Until"}, {"key": "tags", "label": "Tags"}],
  "query_key" : "ctix_created",
```

```
"external_recipients": {  
  "to": [  
    "bca@cyware.com"  
  ],  
  "cc": [],  
  "bcc": []  
}  
'
```

Example Response

```
{  
  "basic_report_type": "custom",  
  "columns": [  
    {  
      "key": "valid_until",  
      "label": "Valid Until"  
    },  
    {  
      "key": "tags",  
      "label": "Tags"  
    }  
  ],  
  "created": 1692188813,
```

```
"created_by": {  
  "email": "john.doe@cyware.com",  
  "first_name": "john",  
  "id": "0d4408bd-9f94-47ec-98eb-6f32ecfd8b13",  
  "last_name": ""  
},  
"date_last_run": null,  
"external_recipients": {  
  "bcc": [],  
  "cc": [],  
  "to": [  
    "bca@cyware.com"  
  ]  
},  
"file_types": [  
  "csv"  
],  
"id": "334c3ff3-bfcc-402c-ad6a-e13cb830a602",  
"internal_recipients": {  
  "bcc": [],  
  "cc": [],  
  "to": [
```

```
{
  "user": null
}
],
"modified": 1692188813,
"modified_by": {
  "email": "john.doe@cyware.com",
  "first_name": "john",
  "id": "0d4408bd-9f94-47ec-98eb-6f32ecfd8b13",
  "last_name": "doe"
},
"name": "Vulnerability Report",
"query_key": "ctix_created",
"saved_search": {
  "created_by": {
    "email": "john.doe@cyware.com",
    "first_name": "john",
    "id": "76fbe1c3-5fd0-4674-9666-69921edafb94",
    "last_name": "doe"
  },
  "description": null,
```

```

"editable": false,

"id": "57d957a8-c468-4a94-8c23-b74aa3540fb0",

"is_threat_data_search": true,

"meta_data":
"{\"object_type\": [\"vulnerability\"], \"query\": {\"length\": 32, \"dataKey\": {\"id\": \"type\", \"type\": \"select\", \"addAll\": true, \"reset\": true, \"multiple\": true, \"value\": \"id\", \"label\": \"Object Type\", \"values\": [{\"id\": \"indicator\", \"name\": \"Indicator\"}, {\"id\": \"malware\", \"name\": \"Malware\"}, {\"id\": \"threat-actor\", \"name\": \"Threat Actor\"}, {\"id\": \"vulnerability\", \"name\": \"Vulnerability\"}, {\"id\": \"attack-pattern\", \"name\": \"Attack Pattern\"}, {\"id\": \"campaign\", \"name\": \"Campaign\"}, {\"id\": \"course-of-action\", \"name\": \"Course of Action\"}, {\"id\": \"identity\", \"name\": \"Identity\"}, {\"id\": \"infrastructure\", \"name\": \"Infrastructure\"}, {\"id\": \"intrusion-set\", \"name\": \"Intrusion Set\"}, {\"id\": \"location\", \"name\": \"Location\"}, {\"id\": \"malware-analysis\", \"name\": \"Malware Analysis\"}, {\"id\": \"observed-data\", \"name\": \"Observed Data\"}, {\"id\": \"opinion\", \"name\": \"Opinion\"}, {\"id\": \"tool\", \"name\": \"Tool\"}, {\"id\": \"report\", \"name\": \"Report\"}, {\"id\": \"custom-object\", \"name\": \"Custom Object\"}, {\"id\": \"observable\", \"name\": \"Observable\"}, {\"id\": \"incident\", \"name\": \"Incident\"}]}}, \"key\": \"Object Type\", \"keyType\": \"select\", \"dataOperator\": {\"id\": \"=\", \"label\": \"=\"}, \"operator\": \"=\", \"dataValue\": {\"id\": \"vulnerability\", \"name\": \"Vulnerability\"}, \"value\": \"\\\"\\\"Vulnerability\\\"\\\"}}\",

"name": "Vulnerability",

"order": 1,

"pinned": false,

"query": "type = \"vulnerability\"",

"shared_type": "global",

"shared_users": [],

"type": "cql"
},

"schedule": {
  "duration_value": 2,

  "ends_on": {

```



```
"attempts_left": 10,
"type": "occurrences",
"value": 10
},
"id": "37bbeaac-a8d2-4571-a259-ee710342213e",
"repeat_on": null,
"repeat_type": "daily",
"start_datetime": 1638124200
},
"shared_type": "global",
"type": "basic"
}
```

POST Run Report

Runs a report and sends the file to the recipients.

{{server_url}}/ingestion/reports/:report_id/run/?type=basic

Request Parameters

Parameter	Type	Required	Description
starttime	Timestamp	Mandatory	Pass the start date and time in EPOCH format from which the report captures data available in CTIX.

Parameter	Type	Required	Description
endtime	Timestamp	Mandatory	Pass the end date and time in EPOCH format untill which the report captures data available in CTIX.
file_types	Array	Mandatory	Pass the report types. Allowed values: csv xls
internal_recipients	JSON Object	Optional (At least one internal or external recipient is required)	Pass the list of email addresses of the internal users to share the report.
external_recipients	JSON Object	Optional (At least one internal or external recipient is required)	Pass the list of email addresses of the external users to share the report.

Response Parameters

Parameter	Type	Description
result	String	Returns the following success message: "Your Report will be mailed to you as soon as it is ready."

PARAMS**type**

basic

[Mandatory] Pass the type of report to run. Allowed value: basic, advanced

PATH VARIABLES

report_id {{report_id}}

Pass the ID of a report (87c07bb3-b60c-4279-a5ec-8a38f73f7ea4)

Body (json)

```
{
  "start_date": 1596825599,
  "end_date": 1676825599,
  "file_types": [
    "csv"
  ],
  "query_key": "ctix_created"
}
```

Example Request

```
curl --location -g '{{server_url}}'ingestion/reports/02bb8724-219d-4014-9462-6337718e95b5/run/?type=basic' \
--data-raw '{
  "starttime": 1596825599,
  "endtime": 1676825599,
  "file_types": [
    "csv"
  ],
  "query_key": "ctix_created",
}
```

```
"internal_recipients": {  
  "to": [  
    {  
      "user_id": "3504aa4a-1e56-40c6-89d7-fc3c6adc2b03",  
      "first_name": "John",  
      "last_name": "Doe",  
      "email": "john.doe@cyware.com"  
    }  
  ],  
  "cc": [],  
  "bcc": []  
}  
'
```

Example Response

```
{  
  "result": "Your Report will be mailed to you as soon as it is ready."  
}
```

DELETE Delete Report

Deletes a report from the Navistar application.

`{{server_url}}/ingestion/reports/:report_id/?type=basic`

Request Parameters

This API does not require any request parameter.

Response Parameters

Status code 204: The report id deleted successfully.

PARAMS

Type	basic
	[Mandatory] Pass the type of report to be deleted. Allowed value: basic, advanced

PATH VARIABLES

report_id	{{report_id}}
	Pass the ID of a report to delete(87c07bb3-b60c-4279-a5ec-8a38f73f7ea4)

Example Request

```
curl --location -g --request DELETE '{{server_url}}ingestion/reports/0c7d5ba4-0c6c-4873-a67a-9f14887c94d1/'
```

Example Response

No response body

This request doesn't return any response body

PROCESS ENDS

References/ Related Content Links: Share links to related standard work documents here.

Article	Type of Article	Link	Description
		[SNOW permalink or hyperlink if it exists. If not published add link to be updated once published in SNOW]	

Change Log:

Name	Edits Made	Date
Prasanna Swain	Initial Draft	09/30/2024