

```
> Frame 28832: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface \Device\NPF_{F675CD0E-D640-41B7-B09E-A722035F73CE}, id 0
> Ethernet II, Src: Netgear_bf:4f:3e (c8:ff:d4:bf:4f:3e), Dst: IPv4mcast_01 (01:00:5e:00:00:01)
> Internet Protocol Version 4, Src: 172.18.57.11, Dst: 224.0.0.1
v Internet Control Message Protocol
  Type: 9 (Mobile IP Advertisement)
  Code: 0 (Normal router advertisement)
  Checksum: 0x09d8 [correct]
  [Checksum Status: Good]
  Number of addresses: 1
  Address entry size: 2
  Lifetime: 1800 (30 minutes)
  Router address: 172.18.57.11
  Preference level: 0
```

```
0000 01 00 5e 00 00 01 c0 ff d4 bf 4f 3e 08 00 45 00  ^-----D>--E-
0010 00 24 20 1c 00 00 01 01 d4 9e ac 12 39 0b e0 00  $-----9---
0020 00 01 09 00 09 d8 01 02 07 08 ac 12 39 0b 00 00  -----9---
0030 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  -----
```