JS. Day 2

1. Var:

1. var student_id = 10
console.log('Initialization -' + student_id);

var student_id
console.log ('Re declaration -' + student_id);

var student_id = 20
console.log('re assign -' + student_id);

2. var teacher_name
console.log ('Declaration -' + teacher_name);

teacher_name = 'John'
console.log ('Initialization -' + teacher_name);

teacher_name = 'snow'
console.log ('re assign -' + teacher_name);

var teacher_name
console.log ('Re declaration -' + teacher_name);

3. var librarycard_number
console.log ('Declaration -' + librarycard_number);
librarycard_number = 1
console.log ('Initialization -' + library card number);

library card number = 100
console.log ('Re assign -' + library card number);

4. var exam_score:
console.log('Declaration' + exam_score);

~~var~~ exam_score = 50
console.log('Initilization:' + exam_score);

exam_score = 100
console.log('Re assigns -' + exam_score);

var exam_score
console.log('Re declaration:' + exam_score);

5. var department_name;
console.log('Declaration-' + department_name);
~~vo~~ department_name = 'computer Science
console.log('Initialization-' + department_name)
department_name = 'Information_Technology'
console.log('Re assign -' + department name
var department_name =
console.log('Re declare -' + department_name);

Conclusion:

→ var allows declaration, initialization, re assign and re declaration.

2. let:

1. let delivery_address;
console.log('Declaration -' + delivery_address);
delivery_address = 'Chennai'
console.log('Initialization -' + delivery_address);
delivery_address = 'Namakkal'
console.log('Reassign -' + delivery address)

2. let Payment_method
console.log('Declaration -' + Payment_method);
Payment_method = 'Creditcard'
console.log('Initialization -' + paymentmethod);
Payment_method = 'Debit card'
console.log('Reassign -' + Payment_method)

3. let product_category
console.log('Declaration -' + product_category)
Productcategory = 'Electronics'
Console.log('Initialization -' + Product_category)
Product_Category = 'Clothing'
console.log('reassign -' + Product_category)

Conclusion

let does not allow re declaration

const:

1. const company_name = 'Accenture'
console.log('Initialization -' + company_name)

2. const office_location = 'Perungalathur'
console.log('Initialization -' + office_location)

3. const support_email = 'support@accenture.com'
console.log('Initialization -' + support_email)

4. const website_url = 'www.accenture.com'
console.log('Initialization -' + website_url)

5. const founding_year = 1989
console.log('Initialization -' + founding_year);

6. const ceo_name = 'Julie Sweet'
console.log('Initialization -' + ceo_name)

7. const business_type = 'Consulting'
console.log('Initialization -' + business_type)

8. const employee_count = 500000
console.log('Initialization -' + employee_count)

9. const annual_revenue = '₹5000 crores
console.log('Initialization - + annual_revenue)

10. const communication_language = 'English'
console.log ('Initialization -' + communication_language)

11. const time_zone = 'IST'
console.log ('Initialization -' + time_zone);

12. ~~Password~~
const Password_minlength = 8
console.log ('Initialization -' + Password_minlength);

13. const app_version = 'v6'
console.log ('Initialization -' + app_version)

14. const login_attempts = 10
console.log ('Initialization -' + login attempts)

15 const hike_percentage = 10
console.log ('Initialization -' + hike_Percentage + '%')

Conclusion:

const allow only initialization

task 2

1. What is type conversion

-) Type conversion means changing a value from one data type to another

2. Bugs in JS

-) Assignment instead of comparision
-) Type coercion
-) undefined variable
-) Global variable
-) floating point precision
-) Missing break in switch
-) Null vs undefined
-) Hoisting
-) NaN
-) Case sensitivity

3. Explicit and implicit:

Explicit :

-) developer do the type conversion manually

Implicit :

-) system do the typeconversion automatically

4. Falsy values

- false
- 0
- null
- ""
- undefined
- NaN

Truthy values:

- "any content"
- 1 (~~any numb~~
- -5
- []
- {}
- true
- "0"

5. NaN

- Invalid mathematical operation with a string
- ~~0/0~~ 0÷0
- converting non numeric string to numb
- Parsing invalid numbers

-) using math functions with invalid inputs

-) arithmetic operations with NaN

-) Multiplying non numeric strings