

## **AWS EC2**

## Instance Purchasing Options

- On-Demand Instances – Pay, by the second, for the instances that you launch.
- Reserved Instances – Purchase, at a significant discount, instances that are always available, for a term from one to three years.
  - Reserved Instances are not physical instances, but rather a billing discount applied to the use of On-Demand Instances in your account.
  - Reserved instance limit:
    - For region: 20
    - For each AZ: 60 (20\*3)
    - Total: 20+60 = 80
  - RI Types:
    - Standard RIs: These provide the most significant discount (up to 75% off On-Demand) and are best suited for steady-state usage.
    - Convertible RIs: These provide a discount (up to 54% off On-Demand) and the capability to change the attributes of the RI
    - Scheduled RIs: These are available to launch within the time windows you reserve.
- Scheduled Instances – Purchase instances that are always available on the specified recurring schedule, for a one-year term.
- Spot Instances – Request unused EC2 instances, which can lower your Amazon EC2 costs significantly.
- Dedicated Hosts – Pay for a physical host that is fully dedicated to running your instances, and bring your existing per-socket, per-core, or per-VM software licenses to reduce costs.
- Capacity Reservations – Reserve capacity for your EC2 instances in a specific Availability Zone for any duration.

## Instance Types:

### *Accelerated Computer Instances: (EBS optimized)*

- Uses hardware accelerators or co-processors to perform some function more efficiently rather than software.
  - Eg:
    - Floating point calculation
    - Graphics Processing.
  - Types
    - GPU: Graphical Processing Unit.
    - GPU compute instances for general-purpose computing (P3/p2)
      - P3
        - Next gen parallel processing NVIDIA Volta GV100
        - P3 can only be used under VPC. Old EC2 Classic N/W can't be used.
      - P2
        - Used for General Purpose using CUDA and OpenCL
        - NVIDIA Tesla K80
      - Used for
        - Artificial intelligence (AI),
        - Machine learning (ML),
        - Deep learning (DL)
        - High performance computing (HPC) applications
    - GPU graphics instances for graphics intensive applications (G3)
      - G3
        - use NVIDIA Tesla M60 GPUs
        - Provide a high-performance platform for graphics applications using DirectX or OpenGL.
        -

- FPGA programmable/Customizable hardware computes instances for advanced scientific workloads. (F1)
- Field programmable gate arrays (FPGAs).
- AFI: Amazon FPGA Image.
- While using remote desktop use a different remote access tool, such as VNC.

### *Compute Optimized instances (EBS optimized)*

- Designed for applications that benefit from high compute power.
- Used for
  - High-performance web servers
  - High-performance computing (HPC)
  - Distributed analytics and machine learning inference
- Can change the Processor State Control of C4.8XLarge instance.
- Types:
  - C5
  - C4
- C5 instance EBS as storage volume
- C5 instances access EBS volumes via PCI attached NVM Express (NVMe) interfaces.
- C5 instances use the Elastic Network Adapter (ENA) for networking
- C5 instances support a maximum for 27 EBS volumes for all Operating systems.

### *General Purpose instances*

- M5:

## *Memory Optimized*

- Memory-optimized instances offer large memory size for memory intensive applications
- Types
  - X1 & X1e: Used for running in-memory databases like SAP HANA, big data processing engines like Apache Spark
  - R5,R5a,R4,Z1d

## *Storage Optimized Instances (EBS-optimized instances)*

- Used for
  - Applications that require high sequential read/write access and low cost storage for very large data sets
- Dense Storage (D2):
  - Designed for workloads that require high sequential read and write access to very large data sets
    - Eg:
      - Hadoop
      - log processing applications
  - Low price
  - HDD-based instance storage. So need external support for fault tolerance and redundancy.
  - Can be launched in both EC2-Classic and Amazon VPC
- H1
  - Can only be launched in Amazon VPC.
  - Used for:
    - Kafka
    - HDFS
    - log

➤ I3:

- Provides Non-Volatile Memory Express (NVMe) SSD-backed instance storage optimized for
  - low latency
  - very high random I/O performance
  - high sequential read throughput and provide high IOPS at a low cost.
- Use Cases:
  - No-SQL database
  - In-memory database
- I3 instances support TRIM (Command to wipe out unused data)

## EBS

- Used to create storage volume and attach to EC2 instance.
- We will specify AZ Only
- Placed in specific AZ to protect from failures.
- Not automatically replicated to different AZ.

### EBS volume types

- General Purpose SSD (GP2)
  - General purpose balances both price and performance.
- Provisioned IOPS SSD (IO1)
  - Used for application such as large relational or NoSQL DB.
- Throughput Optimized HDD (ST1)
  - For frequently accessing
  - Can't be a boot Volume.
  - Magnetic storage.
  - Used for
    - Big Data
    - Log processing
    - Data warehousing
- Cold HDD (SC1)
  - Lowest cost storage for infrequently accessed records.
  - Can't be a boot Volume.
- Magnetic (Standard)
  - Bootable
  - Lowest cost/GB

- Can't Mount 1 EBS volume to multiple EC2 instances.

## Amazon Machine Image (AMI)

- Snapshots of virtual machine.
- Types of virtualization
  - HVM
  - Para-virtual

## Security Group Points

- While creating a security group, we will specify the VPC .
- Any rule that added/removed to security group will reflect immediately.
- Security Groups are “state-full”: Any rule added to inbound will auto reflect in outbound.  
No need to specify in outbound folder.
- All inbound traffics are “blocked” by default. We need to specify the rules to allow it.
- You can specify allow rules not deny rules.
- RDP port number: 3389
- MySQL : 3306
- We can't block specific IP address using Security Group. For that we need to use NAL.

## EBS Volume

- We can't attach Ec2 instance in one AZ to EBS volumes from another AZ.
- For creating one EBS volume in another AZ, First need to create a snapshot from existing volume and then create EBS volume with another AZ.
- While creating we will select the AZ.
- We can't modify only magnetic disk size on fly.

- | EC2 Instance replacement |                             |                  |
|--------------------------|-----------------------------|------------------|
| First Step               | AZ1 - AZ2                   | Region1 -Region2 |
| Create Snapshot          | Create new volume in<br>AZ2 | Do Copy          |



EBS Volume Methods	Create Volume	Copy	Create Image
Create Snapshot			
	AZ1-AZ2	Region1 - Region2	Will create new AMI and from there you can create new Ec2 instance

2.

## RAID Volumes (Redundant Array of Independent Disk)

- Used to improve DISK I/O performance.
- RAID types:
  - RAID-0: Striped, Good Performance, but no redundancy.
  - RAID-1: Mirrored , redundancy
  - RAID-5: Good for read, Bad for write,
  - RAID-10: RAID-1 + RAID-0
- Where to use RAID: Suppose any service that aws not support (Cassandra) and to use in your EC2 instance.
- Before RAID SnapShot:
  - Freeze the Filesystem.
  - Unmount the RAID array.
  - Shutdown the EC2 instance.

## AMI Types

- Instance Store
  - a. We can't attach additional instance store volumes after launching Ec2 instance.
    - i. But can attach EBS volume
  - b. We can't stop the instance.
  - c. Once failed, data will get lost.
- EBS
- You can reboot both.

## ELB

- ELB Types
  - Application LB : Flexible application management
  - Network LB: extreme performance and static IP
  - Classic LB: application is built within the EC2 Classic network
- Inservice-outservice.
- We only get DNS name while creating the LB. We will not get any public IP address.
- Create health check html file (Index.html or any other)
- you cannot convert one load balancer type into another, but can migrate.
- AWS WAF: used to protect web applications behind a load balancer from web attacks

## Cloud Watch

- For monitoring (Logs).
- Can create Alarm
- Pre-Instance Matrices in EC2
  - CPU based
  - Disk based
  - N/w based
  - Status based

## Instance Metadata:

CURL <http://169.254.169.254/latest/metadata/>

CURL <http://169.254.169.254/latest/metadata/public-ipv4>

## Launch Configuration and Auto Scaling

### Placement Group:

- Logical Grouping of instances within a single AZ.
- Imp Points:
  - Can't span across multiple AZ.
  - Placement group name must be unique in our A/C.
  - Can't merge Placement group.
  - Can't move existing instance into placement group.

### Auto-Scaling:

- Can choose multiple AZ under one vpc.
- Can Add rule.

## Elastic File System

- File storage service. Instances connect to a file system by using a network interface called a mount target
- EFS file system can be created and attached to VPC + { Subnet1,Subnet2} + Security Group.
- EFS file system grows and shrinks automatically as you add and remove files
- Data is stored across multiple AZ's in a region.
- Using as centralized repo. In between ec2 instances.
- EFS allow multiple instances to connect but EBS NOT.

- You can use AWS Backup to schedule automatic, incremental backups of your Amazon EFS file systems.
- Accessing file system:
  - Within Same VPC
    - Ec2 instance can directly access.
  - Within another VPC
    - VPC peering or VPC transit gateway.
  - Outside VPC/Ec2-classic:
    - Can mount via ClassicLink
  - On premises
    - Can mount your file systems via an AWS Direct Connect or AWS VPN connection to your VPC or AWS DataSync
- AWS DataSync does not support copying EFS data between AWS Regions.

## Lambda

- One region { API gateway + Lambda}
- Lambda Edge { Cloudfront + lambda}
- If lambda connected to vpc, by default it will not get the internet. We have to manage this by adding NAT gateway.

## LAB Points:

- One subnet = One AZ
- For SSH, we will use the public ip address.
- Types of Status Checks
  - a. System Status Check: Monitor the AWS system where EC2 instance runs.
  - b. Instance Status Check: Monitor the Software and N/W config. on our instance runs.
- We can't encrypt the root device volume by default (But you can do it ).

- Termination Protection turned off by default.
- Default behavior of security group: Inbound traffic is denied and outbound traffic is allowed.
- Instance volume can't be stopped.
- IAM Roles can be attached even after instance is launched. Roles are global..