# ANU API endpoint reference

*Main LMS and Medica service routes*

30 October 2026

This reference lists the registered HTTP APIs in the project, grouped by feature. Use the method and full endpoint together to call an API. The request columns preserve the field names used in the code, including older spellings and aliases.

Main LMS: 194 method and endpoint combinations from server/v1/app.js. Medica companion: 49 combinations from Medica/v1/app.js. They are separate services even when endpoint paths match. Aliases are counted separately. The empty server/v2/login files define no API. One additional route file is not mounted and is listed separately.

## How to call an endpoint

Full URL = service base URL + endpoint. For local main LMS development, the default base is http://localhost:4004, unless PORT is changed. Use the configured deployment host in production. Medica also declares port 4004 in its own app, so give the services distinct hosts or ports if both run together.

Example: GET http://localhost:4004/api/v1/get-trainees?page=1&limit=10

Bearer endpoints require Authorization: Bearer <access_token>. JSON requests use Content-Type: application/json. File requests use multipart/form-data; let the client create its boundary. A :parameter in a path must be replaced with the real value and URL-encoded as necessary.

## Reading the reference

Bearer means the route is behind the shared authentication middleware. Role, institution, ownership and assignment checks can still restrict access. Roles in this project are 99 super admin, 101 institution admin, 102 instructor and 103 trainee. A listed field is read by the code; it is not automatically required. Conditional or nested payload rules are explained for key submissions below.

No shared bearer middleware describes route registration, not a guarantee that the controller permits every request. Optional decoded token identifies the activity tracker’s soft-auth path. Refresh-token cookie identifies the refresh route. Status codes shown are literal codes found in the traced handler path, not an exhaustive response contract; middleware, validation and database errors may add other responses.

The endpoint list follows source registration and does not certify deployment or successful execution. Response structures vary across older and newer routes. No universal response envelope should be assumed.

## Main LMS service checks

2 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
| --- | --- | --- | --- |
| GET | /health | Check whether the service responds.<br>Access: No shared bearer middleware | No named request fields identified in the traced handler.<br>Observed status codes: 200<br>Source: server/v1/app.js:129 |
| GET | /test | Return authenticated test-route and user information.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 401<br>Source: server/v1/app.js:172 |

## Main LMS login account verification and device sessions

12 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/login | Sign in and receive tokens plus account and device context.<br>Access: No shared bearer middleware | Body: email, password, user_email, user_mail, user_password<br>Observed status codes: 200, 400, 401, 404, 500<br>Source: Auth.js:5 |
| POST | /api/v1/forgot-password | Record a password-recovery request and attempt an email.<br>Access: No shared bearer middleware | Body: reset_password_mail<br>Observed status codes: 200, 400, 404, 500<br>Source: forgotpRoute.js:5 |
| POST | /api/v1/account-verification/request | Request an activation or reactivation phone OTP.<br>Access: No shared bearer middleware | Body: email, purpose<br>Observed status codes: 400<br>Source: accountVerificationRoute.js:5 |
| POST | /api/v1/account-verification/verify | Verify an account activation or reactivation OTP.<br>Access: No shared bearer middleware | Body: email, otp, purpose<br>Observed status codes: 400, 500<br>Source: accountVerificationRoute.js:6 |
| POST | /api/v1/refresh-token | Issue a new access token using the refresh-token cookie.<br>Access: Refresh-token cookie | No named request fields identified in the traced handler.<br>Observed status codes: 401, 500<br>Source: refreshTokenRouter.js:5 |
| GET | /api/v1/sessions/validate | Retrieve sessions validate.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Status / payload follows handler and shared error handling.<br>Source: sessionRoute.js:13 |
| GET | /api/v1/sessions/me | Retrieve sessions me.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 403, 404<br>Source: sessionRoute.js:37 |
| GET | /api/v1/sessions/users | Retrieve sessions users.<br>Access: Bearer | Query: search<br>Observed status codes: 403<br>Source: sessionRoute.js:56 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
| --- | --- | --- | --- |
| GET | /api/v1/sessions/users/:email | Retrieve sessions users selected item.<br>Access: Bearer | Path: email<br>Observed status codes: 403, 404<br>Source: sessionRoute.js:71 |
| DELETE | /api/v1/sessions/users/:email/:id | Delete sessions users selected item selected item.<br>Access: Bearer | Path: email, id<br>Observed status codes: 400, 403, 404<br>Source: sessionRoute.js:89 |
| POST | /api/v1/sessions/users/:email/logout-all | Create or execute sessions users selected item logout-all.<br>Access: Bearer | Path: email<br>Observed status codes: 403, 404<br>Source: sessionRoute.js:103 |
| POST | /api/v1/sessions/logout | Create or execute sessions logout.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Status / payload follows handler and shared error handling.<br>Source: sessionRoute.js:115 |

Current SMTP message is placeholder text; this route does not complete a secure password reset.

## Main LMS queries and notifications

5 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/send | Create an in-app notification.<br>Access: No shared bearer middleware | Body: link, message, receiverId, senderId<br>Observed status codes: 200, 400, 500<br>Source: notificationRoutes.js:4 |
| POST | /api/v1/queries | Create Query.<br>Access: Bearer | Body: instructor_id, message, subject<br>Observed status codes: 200, 400, 500<br>Source: queriesRoute.js:5 |
| GET | /api/v1/queries | Get Queries.<br>Access: Bearer | Query: limit, page<br>Observed status codes: 200, 500<br>Source: queriesRoute.js:6 |
| PUT | /api/v1/queries/:query_id/status | Update Query Status.<br>Access: Bearer | Path: query_id<br>Body: status<br>Observed status codes: 200, 400, 500<br>Source: queriesRoute.js:7 |
| DELETE | /api/v1/queries/:query_id | Delete Query.<br>Access: Bearer | Path: query_id<br>Observed status codes: 200, 500<br>Source: queriesRoute.js:8 |

No shared bearer middleware is mounted on this route in app.js.

## Main LMS headset streaming and live viewing

5 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/tokenn | Create a headset publisher session and IVS participant token.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200<br>Source: tokenIvsRoute.js:15 |
| POST | /api/v1/streaming/publisher-session/:sessionId/activate | Activate a published headset session and its replication.<br>Access: Bearer | Path: sessionId<br>Observed status codes: 204<br>Source: streamingSessionRoute.js:15 |
| DELETE | /api/v1/streaming/publisher-session/:sessionId | Stop the headset publisher session.<br>Access: Bearer | Path: sessionId<br>Observed status codes: 204<br>Source: streamingSessionRoute.js:16 |
| POST | /api/v1/streaming/self-viewer-session | Create a trainee self-preview viewer session.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 201<br>Source: streamingSessionRoute.js:17 |
| POST | /api/v1/streaming/viewer-session | Create an institution viewer session.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 201<br>Source: streamingSessionRoute.js:18 |

Main LMS contract ignores client-provided stage/user/capability choices. Medica is a separate implementation.

## Main LMS curriculum certifications modules resources and progress

27 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/user-completion | Progress Update.<br>Access: Bearer | Body: course_id, isCompleted, module_id, user_id<br>Observed status codes: 200, 500<br>Source: progressRoute.js:4 |
| GET | /api/v1/get-vr-data/:data_check | Return authenticated user context and the supplied data_check value.<br>Access: Bearer | Path: data_check<br>Observed status codes: 200, 500<br>Source: getVrDataRoute.js:4 |
| DELETE | /api/v1/delete-cur/:curiculum_id | Delete Cur.<br>Access: Bearer | Path: curiculum_id<br>Observed status codes: 200, 500<br>Source: deleteCuriculumRoute.js:4 |
| POST | /api/v1/create-curiculum | Create Cur.<br>Access: Bearer | Body: curiculum_name<br>Observed status codes: 200, 500<br>Source: curiculamRoute.js:4 |
| GET | /api/v1/get-curiculum | Get Cur.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getCuriculumRoute.js:4 |
| POST | /api/v1/create-course | Course.<br>Access: Bearer | Body: certificate_name, curiculum_id<br>Observed status codes: 200, 500<br>Source: createCourseRoute.js:4 |
| GET | /api/v1/get-courses | Get Courses.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: GetCourseRoute.js:4 |
| GET | /api/v1/get-cours-cur/:curiculum_id | Get Courses By Cur.<br>Access: Bearer | Path: curiculum_id<br>Observed status codes: 200, 500<br>Source: getCoursesByCurRoute.js:4 |
| DELETE | /api/v1/delete-course/:course_id | Course Deletion.<br>Access: Bearer | Path: course_id<br>Observed status codes: 200, 500<br>Source: deleteCourseRoute.js:4 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/tag-course | Tag Course.<br>Access: Bearer | Body: certificate_id, user_id<br>Observed status codes: 200, 403, 500<br>Source: TagCourseRoute.js:4 |
| POST | /api/v1/request-course | Request Course.<br>Access: Bearer | Body: course_id<br>Observed status codes: 200, 403, 500<br>Source: RequestCourseRoute.js:4 |
| POST | /api/v1/create-module | Create a chapter using chapter_name and course_id.<br>Access: Bearer | Body: chapter_name, course_id<br>Observed status codes: 200, 400, 500<br>Source: createModuleRoute.js:4 |
| GET | /api/v1/get-module | Get Module.<br>Access: Bearer | Query: chapter_id<br>Observed status codes: 200, 500<br>Source: getModuleRoute.js:4 |
| POST | /api/v1/create-new-module | Create a module underneath a chapter.<br>Access: Bearer | Body: chapter_id, module_name<br>Observed status codes: 200, 400, 500<br>Source: newModuleRoute.js:4 |
| POST | /api/v1/sub-module | Sub Module.<br>Access: Bearer | Body: module_id, submod_name<br>Observed status codes: 200, 400, 500<br>Source: subModuleRoute.js:4 |
| GET | /api/v1/resource-completion | Mark resource completion through query parameters.<br>Access: Bearer | Query: is_completed, r_id<br>Observed status codes: 200, 500<br>Source: moduleCompleteUserRoute.js:4 |
| GET | /api/v1/get-chapter | Get Chapters.<br>Access: Bearer | Query: course_id<br>Observed status codes: 200, 500<br>Source: getChapterRouter.js:4 |
| POST | /api/v1/create-resource | Create Resource.<br>Access: Bearer | Body: learning_module_id, resource_name, resource_type, topic<br>Observed status codes: 200, 400, 500<br>Source: createResourceRoute.js:4 |
| GET | /api/v1/get-resources | Get Resources.<br>Access: Bearer | Query: learning_module_id<br>Observed status codes: 200<br>Source: getResourcesRoute.js:4 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/resources-mId | Get Resources By Module Ids.<br>Access: Bearer | Body: module_id<br>Observed status codes: 200, 500<br>Source: getResourcesByModuleIdsRoute.js:4 |
| GET | /api/v1/get-cert/:curiculum_id | Get Certification By Cur.<br>Access: Bearer | Path: curiculum_id<br>Observed status codes: 200<br>Source: getCertByCurRoute.js:4 |
| GET | /api/v1/get-certdetails/:certification_id | Get Certification Details By Ids.<br>Access: Bearer | Path: certification_id<br>Observed status codes: 200<br>Source: GetCertificationDetailsByIdRoute.js:4 |
| POST | /api/v1/create-learning-module | Create Learning.<br>Access: Bearer | Body: certificate_id, course_name, module_name, unit_name<br>Observed status codes: 200, 400<br>Source: CreateLearningModuleRoute.js:4 |
| GET | /api/v1/get-lmid/:certificate_id | Get Learning By Id.<br>Access: Bearer | Path: certificate_id<br>Observed status codes: 200<br>Source: GetLearningModuleByIdRoute.js:4 |
| POST | /api/v1/mark-testscores | Calc Test Score.<br>Access: Bearer | Body: diagnostic_interpretation, image_optimization, measurement, plane_identification, r_id<br>Observed status codes: 200, 400, 500<br>Source: calTestScoreRoute.js:4 |
| GET | /api/v1/get-resource-lmandrt | Get Resource Bylmandrt.<br>Access: Bearer | Query: learning_module_id, r_type<br>Observed status codes: 200<br>Source: getResourceBylmandrtRoute.js:4 |
| PUT | /api/v1/mark-testscores-re | Update reattempt scores using query parameters.<br>Access: Bearer | Query: diagnostic_interpretation, image_optimization, measurement, plane_identification, r_id<br>Observed status codes: 200, 500<br>Source: attemptTestRouter.js:4 |

This GET route changes completion state. Query keys are shown exactly as implemented.

This PUT route reads the score fields from query parameters.

## Main LMS batches

7 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| DELETE | /api/v1/delete-batch/:batch_id | Delete Batchc.<br>Access: Bearer | Path: batch_id<br>Observed status codes: 200, 500<br>Source: deleteBatchRoute.js:4 |
| POST | /api/v1/create-batch | Batch Creation.<br>Access: Bearer | Body: batch_end_date, batch_name, batch_start_date, certification_data, curiculum_name<br>Observed status codes: 200, 500<br>Source: createBatchRoute.js:5 |
| GET | /api/v1/get-batches | Get Batch Data.<br>Access: Bearer | Query: limit, page<br>Observed status codes: 200, 500<br>Source: getBatchesRoute.js:4 |
| POST | /api/v1/associate-batch | Associate Batchc.<br>Access: Bearer | Body: batch_id, user_id<br>Observed status codes: 200, 500<br>Source: associateBatchRoute.js:4 |
| GET | /api/v1/batch-filter | Filter Batch.<br>Access: Bearer | Query: batch_name, instructor_name<br>Observed status codes: 200, 500<br>Source: filterBatchRoute.js:4 |
| GET | /api/v1/batch-individual/:batch_id | Individual Batch.<br>Access: Bearer | Path: batch_id<br>Observed status codes: 200, 500<br>Source: IndBatchProfileRoute.js:4 |
| PUT | /api/v1/update-batch-data | Update Batch.<br>Access: Bearer | Body: batch_id, new_batch_name, new_end_date, new_start_date<br>Observed status codes: 200, 500<br>Source: updateBatchRouter.js:4 |

## Main LMS profiles dashboards and analytics

9 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/profile | Profile.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 500<br>Source: profileRoute.js:5 |
| GET | /api/v1/get-dashboard-data | Get Dashboard.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: dashboardRoute.js:4 |
| GET | /api/v1/get-gender-ratio | Gender Ratio.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getGendersRoutes.js:5 |
| GET | /api/v1/user-stats | User Stats.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: UserStatusRoute.js:4 |
| GET | /api/v1/instructor-ind | Ins Data Analysis.<br>Access: Bearer | Query: people_id<br>Observed status codes: 200, 500<br>Source: getInstructorDataAnalysisRoute.js:4 |
| GET | /api/v1/interactions-attempt-stats | Interactions Attempt Stats.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: InteractionsAttemptStats.js:5 |
| GET | /api/v1/activity-last-scores | Activity Last Scores.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: activityLastScoresRoute.js:5 |
| GET | /api/v1/skill-competency | Skill Competency.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: skillCompetencyRoute.js:6 |
| GET | /api/v1/performance-metrics | Performance Metrics.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: performanceMetricsRoute.js:6 |

## Main LMS trainees instructors and user accounts

11 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/get-trainees | Trainee.<br>Access: Bearer | Query: limit, page<br>Observed status codes: 200, 500<br>Source: getTraineesRoute.js:5 |
| PATCH | /api/v1/disable-trainee/:user_mail/:status | Disable Trainee.<br>Access: Bearer | Path: user_mail, status<br>Observed status codes: 200, 400, 500<br>Source: disableTraineeRoute.js:5 |
| GET | /api/v1/get-instructors | Get Instructor Data.<br>Access: Bearer | Query: limit, page<br>Observed status codes: 200, 500<br>Source: getInstructorRoute.js:4 |
| POST | /api/v1/create-trainee | Create Trainee.<br>Access: Bearer | Body: description, institution_name, status, user_batch, user_batch[], user_contact_num, user_dob, user_email, user_gender, user_name, user_password, user_role<br>Files: file<br>Send multipart/form-data.<br>Observed status codes: 200, 404, 422, 500, 501<br>Source: createtraineeRoute.js:6 |
| DELETE | /api/v1/delete-trainee/:user_mail | Delete Traineec.<br>Access: Bearer | Path: user_mail<br>Observed status codes: 200, 500<br>Source: deleteTraineeRoute.js:4 |
| DELETE | /api/v1/delete-ins/:user_mail | Instructor.<br>Access: Bearer | Path: user_mail<br>Observed status codes: 200, 500<br>Source: deleteInstructorRoute.js:4 |
| GET | /api/v1/get-admins | Get Admin.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getAdminsRoute.js:4 |
| GET | /api/v1/trainee/:people_id | Induuid.<br>Access: Bearer | Path: people_id<br>Query: isVr<br>Observed status codes: 200, 500<br>Source: induuidRoute.js:4 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| PUT | /api/v1/trainee/update | Update trainee batch association using query parameters.<br>Access: Bearer | Query: batch_id, user_id<br>Observed status codes: 200, 500<br>Source: updateTraineeRoute.js:4 |
| PUT | /api/v1/instructor/update | Update Instructor.<br>Access: Bearer | Body: batch_id, user_id<br>Observed status codes: 200, 500<br>Source: updateInstructorRoute.js:4 |
| GET | /api/v1/instructor-as-per-batch | Instructor Batch.<br>Access: Bearer | Query: people_id<br>Observed status codes: 200, 400, 500<br>Source: getInstructorAsPerBatch.js:4 |

This PUT route reads user_id and batch_id from the query, not a JSON body.

## Main LMS targeted learning

4 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/create-targeted-learning | Create Targeted Learning.<br>Access: Bearer | Body: certificate_id, curiculum_id, end_date, learning_module_id, resource_type, resources_id, start_date, tar_name, trainee_id<br>Observed status codes: 200, 400, 500<br>Source: CreateTargetedLearningRoute.js:4 |
| GET | /api/v1/tllist | Get Targeted Learning.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getTargetedLearningRoute.js:4 |
| DELETE | /api/v1/tl-delete/:targeted_learning_id | Delete Targeted Learning.<br>Access: Bearer | Path: targeted_learning_id<br>Observed status codes: 200, 500<br>Source: deleteTargetedLearningRoute.js:4 |
| GET | /api/v1/tllist-ind | In TLList.<br>Access: Bearer | Query: email, user_mail<br>Observed status codes: 200, 500<br>Source: getIndividualTLRoute.js:4 |

## Main LMS volumes placement reference recordings and downloads

20 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/sv-upload | Volume.<br>Access: Bearer | Body: description, trimester, volume_fetal_presentation, volume_ga, volume_name, volume_type<br>Files: file<br>Send multipart/form-data.<br>Observed status codes: 200, 400, 403, 404, 406, 500<br>Source: svUploadRouter.js:26 |
| PUT | /api/v1/update-volume | Update Volume.<br>Access: Bearer | Body: description, trimester, volume_fetal_presentation, volume_ga, volume_id, volume_name, volume_type<br>Observed status codes: 200, 406, 500<br>Source: svUploadRouter.js:27 |
| GET | /api/v1/get-volumes | Get Volume Data.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getVolumeDataRoute.js:4 |
| PATCH | /api/v1/approve-volume/:status_approval/:volume_id | Volume Approval.<br>Access: Bearer | Path: status_approval, volume_id<br>Observed status codes: 200, 404<br>Source: VolumeApprovalRoute.js:4 |
| GET | /api/v1/get-volumes-by-instructor | Get Volume Instructor View.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getVolumeByInstructorRoute.js:4 |
| GET | /api/v1/volumes/:volume_id/download | Get Volume Download.<br>Access: Bearer | Path: volume_id<br>Query: file<br>Observed status codes: 200, 400, 404, 502<br>Source: getVolumeByInstructorRoute.js:5 |
| GET | /api/v1/volumes/:volume_id/recordings | Get Volume Recording Download List.<br>Access: Bearer | Path: volume_id<br>Observed status codes: 200, 400, 403, 404, 500<br>Source: getVolumeByInstructorRoute.js:6 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/volumes/:volume_id/recordings/:recording_id/download | Get Volume Recording Download.<br>Access: Bearer | Path: volume_id, recording_id<br>Query: file, index<br>Observed status codes: 200, 400, 404, 502<br>Source: getVolumeByInstructorRoute.js:7 |
| PUT | /api/v1/convert-vol/:volume_id | Update Volume Con.<br>Access: Bearer | Path: volume_id<br>Observed status codes: 200, 400, 404, 409, 429, 500<br>Source: UpdateVolumeConRouter.js:5 |
| GET | /api/v1/converted-volumes | Get Conv Volume List.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getConvVolumeListRoute.js:4 |
| GET | /api/v1/volume-placements/:volume_id | Get Volume Placements By Volume Id.<br>Access: Bearer | Path: volume_id<br>Query: volume_id<br>Observed status codes: 200, 400, 500<br>Source: volumePlacementRoute.js:6 |
| GET | /api/v1/volume-placements | Get Volume Placements.<br>Access: Bearer | Query: volume_id<br>Observed status codes: 200, 500<br>Source: volumePlacementRoute.js:7 |
| POST | /api/v1/volume-placement | Volume Placement.<br>Access: Bearer | Body: volume_id<br>Files: placed_file<br>Send multipart/form-data.<br>Observed status codes: 200, 400, 404, 500<br>Source: volumePlacementRoute.js:8 |
| GET | /api/v1/recordings | Get Recordings.<br>Access: Bearer | Query: volume_id<br>Observed status codes: 200, 400, 500<br>Source: volumeRecordingRoute.js:15 |
| POST | /api/v1/uploadvolumerecording | Vol Recording.<br>Access: Bearer | Body: recording_name, recording_type, volume_id<br>Files: audio_file, images, manifest_file, recording_file<br>Send multipart/form-data.<br>Observed status codes: 200, 400, 404, 500<br>Source: volumeRecordingRoute.js:19 |
| POST | /api/v1/associateVolume | Assoc Volume.<br>Access: Bearer | Body: r_id, shadowrec_id, steprec_id, volume_id<br>Observed status codes: 200, 404, 500<br>Source: associateVolumeRouter.js:4 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/shadow-recordings | Shadow Recording Data.<br>Access: Bearer | Query: volume_id<br>Observed status codes: 200, 500<br>Source: GetShadowRecordingRoute.js:4 |
| GET | /api/v1/shadow-recording-counts | Volume Recording Counts.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: GetShadowRecordingRoute.js:5 |
| GET | /api/v1/volume-recording-counts | Volume Recording Counts.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: GetShadowRecordingRoute.js:6 |
| GET | /api/v1/get-assovol | Get Associated Volume.<br>Access: Bearer | Query: r_id<br>Observed status codes: 200, 500<br>Source: getAssoVolumeRoute.js:4 |

## Main LMS volume course mappings

3 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/course-mappings | Create Course Mapping.<br>Access: Bearer | Body: anatomy_type, course_name, course_type, description, doctor_name, module_name, shadow_recording_id, step_recording_id, trimester, volume_name<br>Observed status codes: 201, 400, 500<br>Source: courseMappingRoute.js:10 |
| GET | /api/v1/course-mappings | Get Course Mappings.<br>Access: Bearer | Query: anatomy_type, course_type, module_name, trimester, volume_name<br>Observed status codes: 200, 500<br>Source: courseMappingRoute.js:11 |
| GET | /api/v1/course-mappings/with-recordings | Get Course Mappings With Recordings.<br>Access: Bearer | Query: anatomy_type, course_type, module_name, trimester, volume_name<br>Observed status codes: 200, 500<br>Source: courseMappingRoute.js:12 |

## Main LMS volume clusters and cluster recordings

28 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/clusters | Get Clusters.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: clusterRoute.js:27 |
| GET | /api/v1/get-clusters | Get Clusters.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: clusterRoute.js:28 |
| GET | /api/v1/cluster | Get Clusters.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: clusterRoute.js:29 |
| GET | /api/v1/clusters/recording-counts | Get Cluster Recording Counts.<br>Access: Bearer | Query: cluster_id<br>Observed status codes: 200, 500<br>Source: clusterRoute.js:32 |
| GET | /api/v1/cluster-recording-counts | Get Cluster Recording Counts.<br>Access: Bearer | Query: cluster_id<br>Observed status codes: 200, 500<br>Source: clusterRoute.js:33 |
| GET | /api/v1/clusters/recordings | Get Cluster Recordings.<br>Access: Bearer | Query: cluster_id, recording_type<br>Observed status codes: 200, 400, 500<br>Source: clusterRoute.js:34 |
| GET | /api/v1/cluster-recordings | Get Cluster Recordings.<br>Access: Bearer | Query: cluster_id, recording_type<br>Observed status codes: 200, 400, 500<br>Source: clusterRoute.js:35 |
| GET | /api/v1/clusters/:cluster_id/recordings | Get Cluster Recordings.<br>Access: Bearer | Path: cluster_id<br>Query: cluster_id, recording_type<br>Observed status codes: 200, 400, 500<br>Source: clusterRoute.js:36 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/clusters/:cluster_id/shadow-recordings | Retrieve clusters selected item shadow-recordings.<br>Access: Bearer | Path: cluster_id<br>Query: cluster_id<br>Observed status codes: 200, 400, 500<br>Source: clusterRoute.js:37 |
| GET | /api/v1/clusters/:cluster_id/step-recordings | Retrieve clusters selected item step-recordings.<br>Access: Bearer | Path: cluster_id<br>Query: cluster_id<br>Observed status codes: 200, 400, 500<br>Source: clusterRoute.js:41 |
| GET | /api/v1/clusters/:cluster_id/recording-counts | Get Cluster Recording Counts.<br>Access: Bearer | Path: cluster_id<br>Query: cluster_id<br>Observed status codes: 200, 500<br>Source: clusterRoute.js:45 |
| GET | /api/v1/clusters/:cluster_id/recordings/:recording_id/download | Get Cluster Recording Download.<br>Access: Bearer | Path: cluster_id, recording_id<br>Query: file, index<br>Observed status codes: 200, 400, 404, 500<br>Source: clusterRoute.js:46 |
| POST | /api/v1/clusters/:cluster_id/recordings | Upload Cluster Recording.<br>Access: Bearer | Path: cluster_id<br>Body: cluster_id, recording_name, recording_type, volume_id<br>Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files<br>Send multipart/form-data.<br>Observed status codes: 200, 400, 404, 500<br>Source: clusterRoute.js:61 |
| PUT | /api/v1/clusters/:cluster_id/recordings/:recording_id | Replace Cluster Recording.<br>Access: Bearer | Path: cluster_id, recording_id<br>Body: cluster_id, recording_id, recording_name, recording_type<br>Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files<br>Send multipart/form-data.<br>Observed status codes: 200, 400, 403, 404, 500<br>Source: clusterRoute.js:67 |
| POST | /api/v1/clusters/:cluster_id/recordings/replace | Replace Cluster Recording.<br>Access: Bearer | Path: cluster_id<br>Body: cluster_id, recording_id, recording_name, recording_type<br>Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files<br>Send multipart/form-data.<br>Observed status codes: 200, 400, 403, 404, 500<br>Source: clusterRoute.js:72 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| PUT | /api/v1/clusters/:cluster_id/recordings/replace | Replace Cluster Recording.<br>Access: Bearer | Path: cluster_id<br>Body: cluster_id, recording_id, recording_name, recording_type<br>Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files<br>Send multipart/form-data.<br>Observed status codes: 200, 400, 403, 404, 500<br>Source: clusterRoute.js:77 |
| POST | /api/v1/clusters/recordings/replace | Replace Cluster Recording.<br>Access: Bearer | Body: cluster_id, recording_id, recording_name, recording_type<br>Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files<br>Send multipart/form-data.<br>Observed status codes: 200, 400, 403, 404, 500<br>Source: clusterRoute.js:82 |
| PUT | /api/v1/clusters/recordings/replace | Replace Cluster Recording.<br>Access: Bearer | Body: cluster_id, recording_id, recording_name, recording_type<br>Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files<br>Send multipart/form-data.<br>Observed status codes: 200, 400, 403, 404, 500<br>Source: clusterRoute.js:87 |
| GET | /api/v1/clusters/:cluster_id | Get Cluster By Id.<br>Access: Bearer | Path: cluster_id<br>Observed status codes: 200, 500<br>Source: clusterRoute.js:93 |
| GET | /api/v1/cluster/:cluster_id | Get Cluster By Id.<br>Access: Bearer | Path: cluster_id<br>Observed status codes: 200, 500<br>Source: clusterRoute.js:94 |
| POST | /api/v1/clusters | Create Cluster.<br>Access: Bearer | Body: cluster_id, cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids<br>Observed status codes: 500<br>Source: clusterRoute.js:95 |
| POST | /api/v1/cluster | Create Cluster.<br>Access: Bearer | Body: cluster_id, cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids<br>Observed status codes: 500<br>Source: clusterRoute.js:96 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/create-cluster | Create Cluster.<br>Access: Bearer | Body: cluster_id, cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids<br>Observed status codes: 500<br>Source: clusterRoute.js:97 |
| POST | /api/v1/add-cluster | Create Cluster.<br>Access: Bearer | Body: cluster_id, cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids<br>Observed status codes: 500<br>Source: clusterRoute.js:98 |
| PUT | /api/v1/clusters/:cluster_id | Update Cluster.<br>Access: Bearer | Path: cluster_id<br>Body: cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids<br>Observed status codes: 500<br>Source: clusterRoute.js:99 |
| PUT | /api/v1/cluster/:cluster_id | Update Cluster.<br>Access: Bearer | Path: cluster_id<br>Body: cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids<br>Observed status codes: 500<br>Source: clusterRoute.js:100 |
| DELETE | /api/v1/clusters/:cluster_id | Delete Cluster.<br>Access: Bearer | Path: cluster_id<br>Observed status codes: 500<br>Source: clusterRoute.js:101 |
| DELETE | /api/v1/cluster/:cluster_id | Delete Cluster.<br>Access: Bearer | Path: cluster_id<br>Observed status codes: 500<br>Source: clusterRoute.js:102 |

## Main LMS course access publication assignments and migration

15 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/courses | List Courses.<br>Access: Bearer | Query: view<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:6 |
| POST | /api/v1/courses | Create Course.<br>Access: Bearer | Body: courseKind, curriculumId, name<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:7 |
| PATCH | /api/v1/courses/:courseId | Update Course.<br>Access: Bearer | Path: courseId<br>Body: curriculumId, name<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:8 |
| POST | /api/v1/courses/:courseId/publish | Publish Course.<br>Access: Bearer | Path: courseId<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:9 |
| POST | /api/v1/courses/:courseId/archive | Archive Course.<br>Access: Bearer | Path: courseId<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:10 |
| POST | /api/v1/courses/:courseId/draft | Draft Course.<br>Access: Bearer | Path: courseId<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:11 |
| PUT | /api/v1/courses/:courseId/institution-access | Set Institution Access.<br>Access: Bearer | Path: courseId<br>Body: institutionIds, mode<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:12 |
| PUT | /api/v1/courses/:courseId/assignments | Replace Assignments.<br>Access: Bearer | Path: courseId<br>Body: assignedTraineeIds, batchIds, excludedTraineeIds<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:13 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
| --- | --- | --- | --- |
| GET | /api/v1/courses/:courseId/assignments | Get Assignments.<br>Access: Bearer | Path: courseId<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:14 |
| GET | /api/v1/courses/:courseId/effective-access | Get Effective Access.<br>Access: Bearer | Path: courseId<br>Query: institutionId<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:15 |
| GET | /api/v1/me/courses | List My Courses.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:16 |
| GET | /api/v1/migration-review | List Migration Review.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:17 |
| PUT | /api/v1/migration-review/courses/:courseId | Resolve Course Ownership.<br>Access: Bearer | Path: courseId<br>Body: courseKind, institutionId<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:18 |
| PUT | /api/v1/migration-review/volumes/:volumeId | Resolve Volume Ownership.<br>Access: Bearer | Path: volumeId<br>Body: institutionId, ownerScope<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:19 |
| POST | /api/v1/migration-review/course-mappings/:mappingId | Migrate Course Mapping.<br>Access: Bearer | Path: mappingId<br>Body: courseKind<br>Status / payload follows handler and shared error handling.<br>Source: contentAccessRoute.js:20 |

## Main LMS headset content packages and recording validation

5 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/mr/workspace | Retrieve the requester's permitted headset content workspace.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Status / payload follows handler and shared error handling.<br>Source: mrContentRoute.js:6 |
| GET | /api/v1/mr/courses | Retrieve courses available to the headset content workspace.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Status / payload follows handler and shared error handling.<br>Source: mrContentRoute.js:7 |
| GET | /api/v1/mr/courses/:courseId/package | Retrieve the authorized course content package.<br>Access: Bearer | Path: courseId<br>Status / payload follows handler and shared error handling.<br>Source: mrContentRoute.js:8 |
| PUT | /api/v1/recordings/:recordingId/validation | Validate Recording.<br>Access: Bearer | Path: recordingId<br>Body: state<br>Status / payload follows handler and shared error handling.<br>Source: mrContentRoute.js:9 |
| POST | /api/v1/courses/:courseId/content | Attach Content.<br>Access: Bearer | Path: courseId<br>Body: resourceId, shadowRecordingId, stepRecordingId, volumeId<br>Status / payload follows handler and shared error handling.<br>Source: mrContentRoute.js:10 |

## Main LMS institutions and platform administration

15 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/institutions | Get Scan Centers.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 401, 500<br>Source: institutionRoute.js:6 |
| POST | /api/v1/institutions | Create Scan Center.<br>Access: Bearer | Body: center_address, center_email, center_name, center_phone, status<br>Observed status codes: 201, 400, 401, 500<br>Source: institutionRoute.js:7 |
| POST | /api/v1/institutions/:institutionId/admins | Add Institution Admin.<br>Access: Bearer | Path: institutionId<br>Body: user_contact_num, user_email, user_name<br>Observed status codes: 500<br>Source: institutionRoute.js:8 |
| GET | /api/v1/super-admins | Retrieve super-admins.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200<br>Source: superAdminRoute.js:5 |
| POST | /api/v1/super-admins | Create or execute super-admins.<br>Access: Bearer | Body: user_contact_num, user_email, user_name<br>Observed status codes: 201<br>Source: superAdminRoute.js:6 |
| GET | /api/v1/superadmin/stats | Retrieve superadmin stats.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200<br>Source: superAdminRoute.js:7 |
| GET | /api/v1/superadmin-stats | Retrieve superadmin-stats.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200<br>Source: superAdminRoute.js:8 |
| GET | /api/v1/super-admin/statistics | Retrieve super-admin statistics.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200<br>Source: superAdminRoute.js:11 |
| GET | /api/v1/superadmin/statistics | Retrieve superadmin statistics.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200<br>Source: superAdminRoute.js:12 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/super-admin/activity-summary | Retrieve super-admin activity-summary.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200<br>Source: superAdminRoute.js:14 |
| GET | /api/v1/superadmin/activity-summary | Retrieve superadmin activity-summary.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200<br>Source: superAdminRoute.js:15 |
| GET | /api/v1/super-admin/recent-activities | Retrieve super-admin recent-activities.<br>Access: Bearer | Query: limit, module, page, role, status<br>Observed status codes: 200<br>Source: superAdminRoute.js:17 |
| GET | /api/v1/superadmin/recent-activities | Retrieve superadmin recent-activities.<br>Access: Bearer | Query: limit, module, page, role, status<br>Observed status codes: 200<br>Source: superAdminRoute.js:18 |
| POST | /api/v1/create-scan-center | Create Scan Center.<br>Access: Bearer | Body: center_address, center_email, center_name, center_phone, status<br>Observed status codes: 201, 400, 401, 500<br>Source: createScanCentersRoute.js:5 |
| GET | /api/v1/get-scan-centers | Get Scan Centers.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 401, 500<br>Source: getScanCenterRoute.js:4 |

## Main LMS activity tracking

4 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/activity-logs/track | Track Client Activity.<br>Access: Optional decoded token | Query: isVR, isVr, isvr<br>Body: action, isVR, isVr, isvr, metadata, module, role, status, targetId, targetType, userId<br>Observed status codes: 201, 400, 500<br>Source: activityTrackerRoute.js:38 |
| GET | /api/v1/activity-logs/statistics | Get Statistics.<br>Access: No shared bearer middleware | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: activityTrackerRoute.js:39 |
| GET | /api/v1/activity-logs/recent | Get Recent.<br>Access: No shared bearer middleware | Query: limit, module, page, role, status<br>Observed status codes: 200, 500<br>Source: activityTrackerRoute.js:40 |
| GET | /api/v1/activity-logs/summary | Get Summary.<br>Access: No shared bearer middleware | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: activityTrackerRoute.js:41 |

softAuth decodes a supplied token; it does not verify its signature in this route middleware.

## Main LMS mindspark ob booster and challenges

12 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/mind-spark-options | Save a legacy MindSpark option response.<br>Access: Bearer | Body: correct_opt, r_id, status, user_opt<br>Observed status codes: 200, 500<br>Source: mindSparkRoute.js:4 |
| POST | /api/v1/mind-spark-questions | Create Questions.<br>Access: Bearer | Body: mindsparkNo, mindspark_no, questions, resource_id<br>Observed status codes: 200, 400, 401, 500<br>Source: questionsRoute.js:18 |
| POST | /api/v1/mind-spark-question-assets | Upload Asset.<br>Access: Bearer | Files: image<br>Send multipart/form-data.<br>Observed status codes: 200, 400, 401, 500<br>Source: questionsRoute.js:19 |
| GET | /api/v1/mind-spark-questions | Get Questions.<br>Access: Bearer | Query: include_inactive, mindspark_no, resource_id<br>Observed status codes: 200, 400, 401, 500<br>Source: questionsRoute.js:20 |
| GET | /api/v1/mind-spark-attempt-details | Get Attempt Details.<br>Access: Bearer | Query: resource_id, session_id<br>Observed status codes: 200, 400, 401, 500<br>Source: questionsRoute.js:21 |
| PUT | /api/v1/mind-spark-questions/:question_id | Update Question.<br>Access: Bearer | Path: question_id<br>Body: answer, assets, correctAnswer, correct_answer, feedbackCorrect, feedbackWrong, feedback_correct, feedback_wrong, isActive, is_active, metadata, mindsparkNo, mindspark_no, options, options_available, prompt, question, questionNo, questionType, question_no, question_query, question_type<br>Observed status codes: 200, 400, 401, 404, 500<br>Source: questionsRoute.js:22 |
| DELETE | /api/v1/mind-spark-questions/:question_id | Delete Question.<br>Access: Bearer | Path: question_id<br>Observed status codes: 200, 400, 401, 404, 500<br>Source: questionsRoute.js:23 |
| POST | /api/v1/create-question | Create Questions.<br>Access: Bearer | Body: mindsparkNo, mindspark_no, questions, resource_id<br>Observed status codes: 200, 400, 401, 500<br>Source: questionsRoute.js:25 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/submit-msob | Submit a MindSpark or OB Booster activity result.<br>Access: Bearer | Body: hasTakenClue, isCorrect, optionChosen, payload, questionNo, resourceId, resourceType, sessionId, timeTaken, totalTimeTaken<br>Observed status codes: 200, 400, 500<br>Source: lrobRoute.js:14 |
| GET | /api/v1/challenges/questions | Get Challenge Questions.<br>Access: Bearer | Query: all, challenge_name, challenge_number, module_name, resource_id<br>Observed status codes: 500<br>Source: challengeRoute.js:10 |
| POST | /api/v1/challenges/submit | Submit Challenge.<br>Access: Bearer | Body: choose_option, isCorrect, question_number, resource_id, session_id<br>Observed status codes: 400, 500<br>Source: challengeRoute.js:11 |
| GET | /api/v1/challenges/attempt-details | Get Challenge Attempt Details.<br>Access: Bearer | Query: resource_id, session_id<br>Observed status codes: 400, 500<br>Source: challengeRoute.js:12 |

Fields depend on resourceType. See the activity payload guide below.

## Main LMS image interpretation practice tests and submissions

8 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/submit-ii | Submit an image-interpretation, annotation or measurement result.<br>Access: Bearer | Body: caliperPlacementInterpretation, correctLabelCount, interpretation, isCorrect, optionChosen, partial, questionNo, questionType, resource_id, session_id, unusedLabelCount, value, wrongLabelCount<br>Files: userImage<br>Send multipart/form-data.<br>Observed status codes: 400<br>Source: iivrRoutes.js:6 |
| POST | /api/v1/start-ii-prac | Start an image-interpretation practice or test session.<br>Access: Bearer | Body: resource_id<br>Observed status codes: 200, 500<br>Source: iivrStartTestRoute.js:4 |
| PUT | /api/v1/end-ii-prac | End an image-interpretation session using test_id.<br>Access: Bearer | Body: test_id<br>Observed status codes: 200, 500<br>Source: iivrEndTestRoute.js:4 |
| GET | /api/v1/practice-i-ii | Get Practices By User.<br>Access: Bearer | Query: resource_id<br>Observed status codes: 200, 400, 401, 500<br>Source: practiceRoute.js:4 |
| POST | /api/v1/practice-i-ii | Bulk Create Practice Results.<br>Access: Bearer | Body: practice_id, practice_number, practiceresults, resource_id<br>Observed status codes: 201, 400, 401, 500<br>Source: practiceRoute.js:5 |
| POST | /api/v1/submit-prac-test | Prac Test.<br>Access: Bearer | Body: payload, resource_id, sessionNumber, sessionType, session_id<br>Files: expertImage_1, expertImage_2, expertImages_1, expertImages_2, userImage_1, userImage_2, userImages_1, userImages_2<br>Send multipart/form-data.<br>Observed status codes: 400, 500<br>Source: pracTestRoute.js:23 |
| GET | /api/v1/prac-test-attempt-details/:resource_id | Get Prac Test Attempt Details.<br>Access: Bearer | Path: resource_id<br>Observed status codes: 500<br>Source: pracTestRoute.js:38 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
| --- | --- | --- | --- |
| GET | /api/v1/get-submissions | Get Submissions.<br>Access: Bearer | Query: resource_id<br>Observed status codes: 500<br>Source: getSubmissionsRoute.js:5 |

Required fields depend on questionType; see the submission guide below.

## Main LMS reattempt settings

2 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/reatt-data | Create Reatt Data.<br>Access: Bearer | Body: certificate_id, course_id, max_reattempt_count, resource_id, resource_type, unit_name, uploaded_by<br>Observed status codes: 400, 500<br>Source: reattRoute.js:9 |
| GET | /api/v1/reatt-data | Get Reatt Data.<br>Access: Bearer | Query: certificate_id, course_id, unit_name, resource_type, resource_id<br>Observed status codes: 500<br>Source: reattRoute.js:10 |

## Medica companion service checks

1 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /test | Return authenticated test-route and user information.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 401, 403<br>Source: Medica/v1/app.js:100 |

## Medica companion login account verification and device sessions

3 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/login | Sign in and receive tokens plus account and device context.<br>Access: No shared bearer middleware | Body: user_mail, user_password<br>Observed status codes: 200, 400, 401, 404, 500<br>Source: Auth.js:5 |
| POST | /api/v1/forgot-password | Record a password-recovery request and attempt an email.<br>Access: No shared bearer middleware | Body: reset_password_mail<br>Observed status codes: 200, 400, 404, 500<br>Source: forgotpRoute.js:5 |
| POST | /api/v1/token | Refresh Token.<br>Access: No shared bearer middleware | Body: token<br>Observed status codes: 401, 403<br>Source: refreshTokenRouter.js:5 |

Current SMTP message is placeholder text; this route does not complete a secure password reset.

## Medica companion queries and notifications

1 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
| --- | --- | --- | --- |
| POST | /api/v1/send | Create an in-app notification.<br>Access: No shared bearer middleware | Body: link, message, receiverId, senderId<br>Observed status codes: 200, 400, 500<br>Source: notificationRoutes.js:4 |

No shared bearer middleware is mounted on this route in app.js.

## Medica companion headset streaming and live viewing

3 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/ivs-ind | Get Individual Streaming Data.<br>Access: No shared bearer middleware | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: individualIvsRoute.js:6 |
| POST | /api/v1/tokenn | Create a headset publisher session and IVS participant token.<br>Access: No shared bearer middleware | Body: attributes, capabilities, duration, stageArn, userId<br>Observed status codes: 200, 500<br>Source: tokenIvsRoute.js:4 |
| POST | /api/v1/get-active-people-room | Get Active People.<br>Access: No shared bearer middleware | Body: roomId<br>Observed status codes: 200, 500<br>Source: activePeopleRoomRoute.js:4 |

Main LMS contract ignores client-provided stage/user/capability choices. Medica is a separate implementation.

# Medica companion curriculum certifications modules resources and progress

20 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/user-completion | Progress Update.<br>Access: Bearer | Body: course_id, isCompleted, module_id, user_id<br>Observed status codes: 200, 500<br>Source: progressRoute.js:4 |
| GET | /api/v1/get-vr-data/:data_check | Return authenticated user context and the supplied data_check value.<br>Access: Bearer | Path: data_check<br>Observed status codes: 200, 500<br>Source: getVrDataRoute.js:4 |
| DELETE | /api/v1/delete-cur/:curiculum_id | Delete Cur.<br>Access: Bearer | Path: curiculum_id<br>Observed status codes: 200, 500<br>Source: deleteCuriculumRoute.js:4 |
| POST | /api/v1/create-curiculum | Create Cur.<br>Access: Bearer | Body: curiculum_name<br>Observed status codes: 200, 500<br>Source: curiculamRoute.js:4 |
| GET | /api/v1/get-curiculum | Get Cur.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getCuriculumRoute.js:4 |
| POST | /api/v1/create-course | Course.<br>Access: Bearer | Body: course_name, curiculum_id<br>Observed status codes: 200, 500<br>Source: createCourseRoute.js:4 |
| GET | /api/v1/get-courses | Get Courses.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: GetCourseRoute.js:4 |
| GET | /api/v1/get-cours-cur/:curiculum_id | Get Courses By Cur.<br>Access: Bearer | Path: curiculum_id<br>Observed status codes: 200, 500<br>Source: getCoursesByCurRoute.js:4 |
| DELETE | /api/v1/delete-course/:course_id | Course Deletion.<br>Access: Bearer | Path: course_id<br>Observed status codes: 200, 500<br>Source: deleteCourseRoute.js:4 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/tag-course | Tag Course.<br>Access: Bearer | Body: course_id, user_id<br>Observed status codes: 200, 403, 500<br>Source: TagCourseRoute.js:4 |
| POST | /api/v1/request-course | Request Course.<br>Access: Bearer | Body: course_id<br>Observed status codes: 200, 403, 500<br>Source: RequestCourseRoute.js:4 |
| POST | /api/v1/create-module | Create a chapter using chapter_name and course_id.<br>Access: Bearer | Body: chapter_name, course_id<br>Observed status codes: 200, 400, 500<br>Source: createModuleRoute.js:4 |
| GET | /api/v1/get-module | Get Module.<br>Access: Bearer | Query: chapter_id<br>Observed status codes: 200, 500<br>Source: getModuleRoute.js:4 |
| POST | /api/v1/create-new-module | Create a module underneath a chapter.<br>Access: Bearer | Body: chapter_id, module_name<br>Observed status codes: 200, 400, 500<br>Source: newModuleRoute.js:4 |
| POST | /api/v1/sub-module | Sub Module.<br>Access: Bearer | Body: module_id, submod_name<br>Observed status codes: 200, 400, 500<br>Source: subModuleRoute.js:4 |
| GET | /api/v1/resource-completion | Mark resource completion through query parameters.<br>Access: Bearer | Query: is_completed, r_id<br>Observed status codes: 200, 500<br>Source: moduleCompleteUserRoute.js:4 |
| GET | /api/v1/get-chapter | Get Chapters.<br>Access: Bearer | Query: course_id<br>Observed status codes: 200, 500<br>Source: getChapterRouter.js:4 |
| POST | /api/v1/create-resource | Create Resource.<br>Access: Bearer | Body: module_id, resource_name<br>Observed status codes: 200, 400, 500<br>Source: createResourceRoute.js:4 |
| GET | /api/v1/get-resources | Get Resources.<br>Access: Bearer | Query: module_id<br>Observed status codes: 200<br>Source: getResourcesRoute.js:4 |

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
| --- | --- | --- | --- |
| POST | /api/v1/resources-mId | Get Resources By Module Ids.<br>Access: Bearer | Body: module_id<br>Observed status codes: 200, 500<br>Source: getResourcesByModuleIdsRoute.js:4 |

This GET route changes completion state. Query keys are shown exactly as implemented.

## Medica companion batches

5 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| DELETE | /api/v1/delete-batch/:batch_id | Delete Batchc.<br>Access: Bearer | Path: batch_id<br>Observed status codes: 200, 500<br>Source: deleteBatchRoute.js:4 |
| POST | /api/v1/create-batch | Batch Creation.<br>Access: Bearer | Body: batch_end_date, batch_name, batch_start_date, course_data, curiculum_name<br>Observed status codes: 200, 500<br>Source: createBatchRoute.js:5 |
| GET | /api/v1/get-batches | Get Batch Data.<br>Access: Bearer | Query: limit, page<br>Observed status codes: 200, 500<br>Source: getBatchesRoute.js:4 |
| POST | /api/v1/associate-batch | Associate Batchc.<br>Access: Bearer | Body: batch_id, user_id<br>Observed status codes: 200, 500<br>Source: associateBatchRoute.js:4 |
| GET | /api/v1/batch-filter | Filter Batch.<br>Access: Bearer | Query: batch_name, instructor_name<br>Observed status codes: 200, 500<br>Source: filterBatchRoute.js:4 |

## Medica companion profiles dashboards and analytics

4 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/profile | Profile.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 500<br>Source: profileRoute.js:5 |
| GET | /api/v1/get-dashboard-data | Get Dashboard.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: dashboardRoute.js:4 |
| GET | /api/v1/get-gender-ratio | Gender Ratio.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getGendersRoutes.js:5 |
| GET | /api/v1/user-stats | User Stats.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: UserStatusRoute.js:4 |

## Medica companion trainees instructors and user accounts

8 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| GET | /api/v1/get-trainees | Trainee.<br>Access: Bearer | Query: limit, page<br>Observed status codes: 200, 500<br>Source: getTraineesRoute.js:5 |
| PATCH | /api/v1/disable-trainee/:user_mail/:status | Disable Trainee.<br>Access: Bearer | Path: user_mail, status<br>Observed status codes: 200, 400, 500<br>Source: disableTraineeRoute.js:5 |
| GET | /api/v1/get-instructors | Get Instructor Data.<br>Access: Bearer | Query: limit, page<br>Observed status codes: 200, 500<br>Source: getInstructorRoute.js:4 |
| POST | /api/v1/create-trainee | Create Trainee.<br>Access: Bearer | Body: description, status, user_batch, user_contact_num, user_dob, user_email, user_gender, user_name, user_password, user_role<br>Files: file<br>Send multipart/form-data.<br>Observed status codes: 200, 404, 500, 501<br>Source: createtraineeRoute.js:6 |
| DELETE | /api/v1/delete-trainee/:user_mail | Delete Traineec.<br>Access: Bearer | Path: user_mail<br>Observed status codes: 200, 500<br>Source: deleteTraineeRoute.js:4 |
| DELETE | /api/v1/delete-ins/:user_mail | Instructor.<br>Access: Bearer | Path: user_mail<br>Observed status codes: 200, 500<br>Source: deleteInstructorRoute.js:4 |
| GET | /api/v1/get-admins | Get Admin.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getAdminsRoute.js:4 |
| GET | /api/v1/trainee/:people_id | Induuid.<br>Access: Bearer | Path: people_id<br>Observed status codes: 200, 500<br>Source: induuidRoute.js:4 |

## Medica companion targeted learning

4 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

| Method | Full endpoint | Purpose and access | Request details and observed status codes |
|---|---|---|---|
| POST | /api/v1/create-targeted-learning | Create Targeted Learning.<br>Access: Bearer | Body: chapter_id, course_id, curiculum_id, end_date, module_id, resources_id, start_date, tar_name, trainee_id<br>Observed status codes: 200, 400, 500<br>Source: CreateTargetedLearningRoute.js:4 |
| GET | /api/v1/tllist | Get Targeted Learning.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getTargetedLearningRoute.js:4 |
| DELETE | /api/v1/tl-delete/:targeted_learning_id | Delete Targeted Learning.<br>Access: Bearer | Path: targeted_learning_id<br>Observed status codes: 200, 500<br>Source: deleteTargetedLearningRoute.js:4 |
| GET | /api/v1/tllist-ind | In TLList.<br>Access: Bearer | No named request fields identified in the traced handler.<br>Observed status codes: 200, 500<br>Source: getIndividualTLRoute.js:4 |

# Request examples for main LMS

Replace placeholders with real authorized values. These examples illustrate the source contract; they have not been submitted to the running service.

### Sign in

POST /api/v1/login

```
{
  "user_mail": "trainee@example.com",
  "user_password": "<password>"
}
```

### Request verification OTP

POST /api/v1/account-verification/request

```
{
  "email": "trainee@example.com",
  "purpose": "activation"
}
```

### Verify an account

POST /api/v1/account-verification/verify

```
{
  "email": "trainee@example.com",
  "purpose": "activation",
  "otp": "123456"
}
```

### Start image interpretation practice

POST /api/v1/start-ii-prac

```
{
  "resource_id": "<resource-id>"
}
```

### End image interpretation practice

PUT /api/v1/end-ii-prac

```
{
  "test_id": "<test-id-returned-by-the-session-flow>"
}
```

### Create a query

POST /api/v1/queries

```
{
  "subject": "Learning activity question",
  "message": "Please clarify the expected plane."
}
```

### Create a modern course draft

POST /api/v1/courses

```
{
  "name": "Example course",
  "courseKind": "institution",
  "curriculumId": "<curriculum-id>"
}
```

### Set course assignments

PUT /api/v1/courses/:courseId/assignments

```
{
  "batchIds": [
    "<batch-id>"
  ],
  "assignedTraineeIds": [],
  "excludedTraineeIds": []
}
```

# Conditional submission payloads

### Image interpretation submission

POST /api/v1/submit-ii accepts questionType, questionNo, session_id and resource_id as the common required fields. isCorrect is required except for measurement. Upload userImage using multipart/form-data for type2, annotation1, annotation2 and measurement.

| questionType | Additional requirements |
|---|---|
| type1 | optionChosen is checked for question numbers below 6. No userImage is required by this branch. |
| type2 | userImage and isCorrect. |
| annotation1 or annotation2 | userImage, isCorrect, correctLabelCount, wrongLabelCount and unusedLabelCount. |
| measurement | userImage, partial, value, interpretation and caliperPlacementInterpretation. partial must be 0, 0.5 or 1. |

### MindSpark and OB Booster submission

POST /api/v1/submit-msob requires resourceType and resourceId. sessionId can be supplied; the controller generates a UUID when absent. Resource types are normalized to uppercase.

| resourceType | Activity specific fields |
|---|---|
| TYPE1 | questionNo, optionChosen, isCorrect |
| MATCHING | questionNo, payload, isCorrect |
| WORDSEARCH | questionNo, timeTaken, hasTakenClue |
| CROSSWORD | totalTimeTaken |
| PROBEMOVEMENTS | totalTimeTaken |

### Challenge submission

POST /api/v1/challenges/submit validates resource_id, session_id, question_number, choose_option and isCorrect. question_number must be numeric. choose_option can be a single value or an array and cannot be empty after normalization. isCorrect must parse as true or false.

# File uploads and headset communication

### File request rules

The file-field names in the endpoint tables are exact multipart keys. Ordinary form fields accompany them. The route may accept alternative file key names; aliases are not a requirement to send the same file multiple times.

Volume uploads use file. Placement uses placed_file. Volume-reference recording upload uses recording_file, audio_file, images and manifest_file. Cluster recording routes accept additional aliases shown in their table. Question image assets use image. Image-interpretation submissions use userImage. Practice-test submissions accept the numbered userImage and expertImage keys and plural aliases shown in the table.

The volume upload limit is environment-controlled. The tracked Lambda template sets MAX_VOLUME_UPLOAD_SIZE_MB to 8, while source defaults differ. Recording routes specify 50 MB per file and a total file-count limit of 61. Question assets default to 10 MB through MAX_MINDSPARK_ASSET_SIZE_MB. Deployed proxy limits can be lower; use the actual environment when choosing an upload size.

### Live headset sequence

1. Headset calls POST /api/v1/tokenn with its LMS bearer token.

2. The publisher token is returned at result.data.token and the application session ID at result.sessionId.

3. Headset joins IVS and publishes video and microphone.

4. Activation is retried in the background. The headset can call POST /api/v1/streaming/publisher-session/:sessionId/activate; a 409 means publishing is not yet visible and needs bounded retry.

5. Trainee browser calls POST /api/v1/streaming/self-viewer-session. Institution-admin browser calls POST /api/v1/streaming/viewer-session.

6. Headset calls DELETE /api/v1/streaming/publisher-session/:sessionId when publishing stops.

IVS media transport is separate from the REST API endpoints. A storage download endpoint generally prepares an authorized URL; the subsequent file transfer can occur directly from object storage.

### Socket events

The local main LMS also initializes Socket.IO. Client subscriptions are subscribe:superadmin and subscribe:user. Server events include activity:new, stats:update and session:revoked. These are event names, not standalone REST endpoints. The Lambda HTTP deployment does not by itself establish a persistent Socket.IO host.

## Routes not registered and reference sources

Main LMS defines GET / in server/v1/routes/GetPracticeResults.js:6, but its router is not mounted in the service app.js. No public full endpoint is assigned here.

server/v2/login/endpoint.js, authRoute.js, authController.js and authModel.js are empty. They contribute no endpoints. The volume converter is a Batch worker in the reviewed deployment and is not an additional HTTP service.

Primary sources are the two app.js files, their imported route modules, and the associated controllers, models and authentication middleware. The endpoint registration list excludes commented-out code and unmounted route files. The route inventory and source line numbers were generated from JavaScript syntax trees, then supplemented for conditional payloads.

Useful source documents: server/v1/STREAMING.md, server/v1/template.yaml, APIs/Submit_MSOB_API_Product_Guide.md, APIs/Volume_APIs.md and APIs/Challenges_API.md. Endpoint spellings are taken from the current route code when older documents differ.