ANU API endpoint reference

Main LMS and Medica service routes

30 October 2026

This reference lists the registered HTTP APIs in the project, grouped by feature. Use the method and full endpoint together to call an API. The request columns preserve the field names used in the code, including older spellings and aliases.

Main LMS: 194 method and endpoint combinations from server/v1/app.js. Medica companion: 49 combinations from Medica/v1/app.js. They are separate services even when endpoint paths match. Aliases are counted separately. The empty server/v2/login files define no API. One additional route file is not mounted and is listed separately.

How to call an endpoint

Full URL = service base URL + endpoint. For local main LMS development, the default base is http://localhost:4004, unless PORT is changed. Use the configured deployment host in production. Medica also declares port 4004 in its own app, so give the services distinct hosts or ports if both run together.

Example: GET http://localhost:4004/api/v1/get-trainees?page=1&limit=10

Bearer endpoints require Authorization: Bearer <access_token>. JSON requests use Content-Type: application/json. File requests use multipart/form-data; let the client create its boundary. A :parameter in a path must be replaced with the real value and URL-encoded as necessary.

Reading the reference

Bearer means the route is behind the shared authentication middleware. Role, institution, ownership and assignment checks can still restrict access. Roles in this project are 99 super admin, 101 institution admin, 102 instructor and 103 trainee. A listed field is read by the code; it is not automatically required. Conditional or nested payload rules are explained for key submissions below.

No shared bearer middleware describes route registration, not a guarantee that the controller permits every request. Optional decoded token identifies the activity tracker’s soft-auth path. Refresh-token cookie identifies the refresh route. Status codes shown are literal codes found in the traced handler path, not an exhaustive response contract; middleware, validation and database errors may add other responses.

The endpoint list follows source registration and does not certify deployment or successful execution. Response structures vary across older and newer routes. No universal response envelope should be assumed.

Main LMS service checks

2 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/health	Check whether the service responds. Access: No shared bearer middleware	No named request fields identified in the traced handler. Observed status codes: 200 Source: server/v1/app.js:129
GET	/test	Return authenticated test-route and user information. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 401 Source: server/v1/app.js:172

Main LMS login account verification and device sessions

12 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/login	Sign in and receive tokens plus account and device context. Access: No shared bearer middleware	Body: email, password, user_email, user_mail, user_password Observed status codes: 200, 400, 401, 404, 500 Source: Auth.js:5
POST	/api/v1/forgot-password	Record a password-recovery request and attempt an email. Access: No shared bearer middleware	Body: reset_password_mail Observed status codes: 200, 400, 404, 500 Source: forgotpRoute.js:5
POST	/api/v1/account-verification/request	Request an activation or reactivation phone OTP. Access: No shared bearer middleware	Body: email, purpose Observed status codes: 400 Source: accountVerificationRoute.js:5
POST	/api/v1/account-verification/verify	Verify an account activation or reactivation OTP. Access: No shared bearer middleware	Body: email, otp, purpose Observed status codes: 400, 500 Source: accountVerificationRoute.js:6
POST	/api/v1/refresh-token	Issue a new access token using the refresh-token cookie. Access: Refresh-token cookie	No named request fields identified in the traced handler. Observed status codes: 401, 500 Source: refreshTokenRouter.js:5
GET	/api/v1/sessions/validate	Retrieve sessions validate. Access: Bearer	No named request fields identified in the traced handler. Status / payload follows handler and shared error handling. Source: sessionRoute.js:13
GET	/api/v1/sessions/me	Retrieve sessions me. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 403, 404 Source: sessionRoute.js:37
GET	/api/v1/sessions/users	Retrieve sessions users. Access: Bearer	Query: search Observed status codes: 403 Source: sessionRoute.js:56

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/sessions/users/:email	Retrieve sessions users selected item. Access: Bearer	Path: email Observed status codes: 403, 404 Source: sessionRoute.js:71
DELETE	/api/v1/sessions/users/:email/:id	Delete sessions users selected item selected item. Access: Bearer	Path: email, id Observed status codes: 400, 403, 404 Source: sessionRoute.js:89
POST	/api/v1/sessions/users/:email/logout-all	Create or execute sessions users selected item logout-all. Access: Bearer	Path: email Observed status codes: 403, 404 Source: sessionRoute.js:103
POST	/api/v1/sessions/logout	Create or execute sessions logout. Access: Bearer	No named request fields identified in the traced handler. Status / payload follows handler and shared error handling. Source: sessionRoute.js:115

Current SMTP message is placeholder text; this route does not complete a secure password reset.

Main LMS queries and notifications

5 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/send	Create an in-app notification. Access: No shared bearer middleware	Body: link, message, receiverId, senderId Observed status codes: 200, 400, 500 Source: notificationRoutes.js:4
POST	/api/v1/queries	Create Query. Access: Bearer	Body: instructor_id, message, subject Observed status codes: 200, 400, 500 Source: queriesRoute.js:5
GET	/api/v1/queries	Get Queries. Access: Bearer	Query: limit, page Observed status codes: 200, 500 Source: queriesRoute.js:6
PUT	/api/v1/queries/:query_id/status	Update Query Status. Access: Bearer	Path: query_id Body: status Observed status codes: 200, 400, 500 Source: queriesRoute.js:7
DELETE	/api/v1/queries/:query_id	Delete Query. Access: Bearer	Path: query_id Observed status codes: 200, 500 Source: queriesRoute.js:8

No shared bearer middleware is mounted on this route in app.js.

Main LMS headset streaming and live viewing

5 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/tokenn	Create a headset publisher session and IVS participant token. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200 Source: tokenIvsRoute.js:15
POST	/api/v1/streaming/publisher-session/:sessionId/activate	Activate a published headset session and its replication. Access: Bearer	Path: sessionId Observed status codes: 204 Source: streamingSessionRoute.js:15
DELETE	/api/v1/streaming/publisher-session/:sessionId	Stop the headset publisher session. Access: Bearer	Path: sessionId Observed status codes: 204 Source: streamingSessionRoute.js:16
POST	/api/v1/streaming/self-viewer-session	Create a trainee self-preview viewer session. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 201 Source: streamingSessionRoute.js:17
POST	/api/v1/streaming/viewer-session	Create an institution viewer session. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 201 Source: streamingSessionRoute.js:18

Main LMS contract ignores client-provided stage/user/capability choices. Medica is a separate implementation.

Main LMS curriculum certifications modules resources and progress

27 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/user-completion	Progress Update. Access: Bearer	Body: course_id, isCompleted, module_id, user_id Observed status codes: 200, 500 Source: progressRoute.js:4
GET	/api/v1/get-vr-data/:data_check	Return authenticated user context and the supplied data_check value. Access: Bearer	Path: data_check Observed status codes: 200, 500 Source: getVrDataRoute.js:4
DELETE	/api/v1/delete-cur/:curiculum_id	Delete Cur. Access: Bearer	Path: curiculum_id Observed status codes: 200, 500 Source: deleteCuriculumRoute.js:4
POST	/api/v1/create-curiculum	Create Cur. Access: Bearer	Body: curiculum_name Observed status codes: 200, 500 Source: curiculamRoute.js:4
GET	/api/v1/get-curiculum	Get Cur. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getCuriculumRoute.js:4
POST	/api/v1/create-course	Course. Access: Bearer	Body: certificate_name, curiculum_id Observed status codes: 200, 500 Source: createCourseRoute.js:4
GET	/api/v1/get-courses	Get Courses. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: GetCourseRoute.js:4
GET	/api/v1/get-cours-cur/:curiculum_id	Get Courses By Cur. Access: Bearer	Path: curiculum_id Observed status codes: 200, 500 Source: getCoursesByCurRoute.js:4
DELETE	/api/v1/delete-course/:course_id	Course Deletion. Access: Bearer	Path: course_id Observed status codes: 200, 500 Source: deleteCourseRoute.js:4

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/tag-course	Tag Course. Access: Bearer	Body: certificate_id, user_id Observed status codes: 200, 403, 500 Source: TagCourseRoute.js:4
POST	/api/v1/request-course	Request Course. Access: Bearer	Body: course_id Observed status codes: 200, 403, 500 Source: RequestCourseRoute.js:4
POST	/api/v1/create-module	Create a chapter using chapter_name and course_id. Access: Bearer	Body: chapter_name, course_id Observed status codes: 200, 400, 500 Source: createModuleRoute.js:4
GET	/api/v1/get-module	Get Module. Access: Bearer	Query: chapter_id Observed status codes: 200, 500 Source: getModuleRoute.js:4
POST	/api/v1/create-new-module	Create a module underneath a chapter. Access: Bearer	Body: chapter_id, module_name Observed status codes: 200, 400, 500 Source: newModuleRoute.js:4
POST	/api/v1/sub-module	Sub Module. Access: Bearer	Body: module_id, submod_name Observed status codes: 200, 400, 500 Source: subModuleRoute.js:4
GET	/api/v1/resource-completion	Mark resource completion through query parameters. Access: Bearer	Query: is_completed, r_id Observed status codes: 200, 500 Source: moduleCompleteUserRoute.js:4
GET	/api/v1/get-chapter	Get Chapters. Access: Bearer	Query: course_id Observed status codes: 200, 500 Source: getChapterRouter.js:4
POST	/api/v1/create-resource	Create Resource. Access: Bearer	Body: learning_module_id, resource_name, resource_type, topic Observed status codes: 200, 400, 500 Source: createResourceRoute.js:4
GET	/api/v1/get-resources	Get Resources. Access: Bearer	Query: learning_module_id Observed status codes: 200 Source: getResourcesRoute.js:4

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/resources-mId	Get Resources By Module Ids. Access: Bearer	Body: module_id Observed status codes: 200, 500 Source: getResourcesByModuleIdsRoute.js:4
GET	/api/v1/get-cert/:curiculum_id	Get Certification By Cur. Access: Bearer	Path: curiculum_id Observed status codes: 200 Source: getCertByCurRoute.js:4
GET	/api/v1/get-certdetails/:certification_id	Get Certification Details By Ids. Access: Bearer	Path: certification_id Observed status codes: 200 Source: GetCertificationDetailsByIdRoute.js:4
POST	/api/v1/create-learning-module	Create Learning. Access: Bearer	Body: certificate_id, course_name, module_name, unit_name Observed status codes: 200, 400 Source: CreateLearningModuleRoute.js:4
GET	/api/v1/get-lmid/:certificate_id	Get Learning By Id. Access: Bearer	Path: certificate_id Observed status codes: 200 Source: GetLearningModuleByIdRoute.js:4
POST	/api/v1/mark-testscores	Calc Test Score. Access: Bearer	Body: diagnostic_interpretation, image_optimization, measurement, plane_identification, r_id Observed status codes: 200, 400, 500 Source: calTestScoreRoute.js:4
GET	/api/v1/get-resource-lmandrt	Get Resource Bylmandrt. Access: Bearer	Query: learning_module_id, r_type Observed status codes: 200 Source: getResourceBylmandrtRoute.js:4
PUT	/api/v1/mark-testscores-re	Update reattempt scores using query parameters. Access: Bearer	Query: diagnostic_interpretation, image_optimization, measurement, plane_identification, r_id Observed status codes: 200, 500 Source: attemptTestRouter.js:4

This GET route changes completion state. Query keys are shown exactly as implemented.

This PUT route reads the score fields from query parameters.

Main LMS batches

7 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
DELETE	/api/v1/delete-batch/:batch_id	Delete Batchc. Access: Bearer	Path: batch_id Observed status codes: 200, 500 Source: deleteBatchRoute.js:4
POST	/api/v1/create-batch	Batch Creation. Access: Bearer	Body: batch_end_date, batch_name, batch_start_date, certification_data, curiculum_name Observed status codes: 200, 500 Source: createBatchRoute.js:5
GET	/api/v1/get-batches	Get Batch Data. Access: Bearer	Query: limit, page Observed status codes: 200, 500 Source: getBatchesRoute.js:4
POST	/api/v1/associate-batch	Associate Batchc. Access: Bearer	Body: batch_id, user_id Observed status codes: 200, 500 Source: associateBatchRoute.js:4
GET	/api/v1/batch-filter	Filter Batch. Access: Bearer	Query: batch_name, instructor_name Observed status codes: 200, 500 Source: filterBatchRoute.js:4
GET	/api/v1/batch-individual/:batch_id	Individual Batch. Access: Bearer	Path: batch_id Observed status codes: 200, 500 Source: IndBatchProfileRoute.js:4
PUT	/api/v1/update-batch-data	Update Batch. Access: Bearer	Body: batch_id, new_batch_name, new_end_date, new_start_date Observed status codes: 200, 500 Source: updateBatchRouter.js:4

Main LMS profiles dashboards and analytics

9 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/profile	Profile. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 500 Source: profileRoute.js:5
GET	/api/v1/get-dashboard-data	Get Dashboard. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: dashboardRoute.js:4
GET	/api/v1/get-gender-ratio	Gender Ratio. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getGendersRoutes.js:5
GET	/api/v1/user-stats	User Stats. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: UserStatusRoute.js:4
GET	/api/v1/instructor-ind	Ins Data Analysis. Access: Bearer	Query: people_id Observed status codes: 200, 500 Source: getInstructorDataAnalysisRoute.js:4
GET	/api/v1/interactions-attempt-stats	Interactions Attempt Stats. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: InteractionsAttemptStats.js:5
GET	/api/v1/activity-last-scores	Activity Last Scores. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: activityLastScoresRoute.js:5
GET	/api/v1/skill-competency	Skill Competency. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: skillCompetencyRoute.js:6
GET	/api/v1/performance-metrics	Performance Metrics. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: performanceMetricsRoute.js:6

Main LMS trainees instructors and user accounts

11 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/get-trainees	Trainee. Access: Bearer	Query: limit, page Observed status codes: 200, 500 Source: getTraineesRoute.js:5
PATCH	/api/v1/disable-trainee/:user_mail/:status	Disable Trainee. Access: Bearer	Path: user_mail, status Observed status codes: 200, 400, 500 Source: disableTraineeRoute.js:5
GET	/api/v1/get-instructors	Get Instructor Data. Access: Bearer	Query: limit, page Observed status codes: 200, 500 Source: getInstructorRoute.js:4
POST	/api/v1/create-trainee	Create Trainee. Access: Bearer	Body: description, institution_name, status, user_batch, user_batch[], user_contact_num, user_dob, user_email, user_gender, user_name, user_password, user_role Files: file Send multipart/form-data. Observed status codes: 200, 404, 422, 500, 501 Source: createtraineeRoute.js:6
DELETE	/api/v1/delete-trainee/:user_mail	Delete Traineec. Access: Bearer	Path: user_mail Observed status codes: 200, 500 Source: deleteTraineeRoute.js:4
DELETE	/api/v1/delete-ins/:user_mail	Instructor. Access: Bearer	Path: user_mail Observed status codes: 200, 500 Source: deleteInstructorRoute.js:4
GET	/api/v1/get-admins	Get Admin. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getAdminsRoute.js:4
GET	/api/v1/trainee/:people_id	Induuid. Access: Bearer	Path: people_id Query: isVr Observed status codes: 200, 500 Source: induuidRoute.js:4

Method	Full endpoint	Purpose and access	Request details and observed status codes
PUT	/api/v1/trainee/update	Update trainee batch association using query parameters. Access: Bearer	Query: batch_id, user_id Observed status codes: 200, 500 Source: updateTraineeRoute.js:4
PUT	/api/v1/instructor/update	Update Instructor. Access: Bearer	Body: batch_id, user_id Observed status codes: 200, 500 Source: updateInstructorRoute.js:4
GET	/api/v1/instructor-as-per-batch	Instructor Batch. Access: Bearer	Query: people_id Observed status codes: 200, 400, 500 Source: getInstructorAsPerBatch.js:4

This PUT route reads user_id and batch_id from the query, not a JSON body.

Main LMS targeted learning

4 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/create-targeted-learning	Create Targeted Learning. Access: Bearer	Body: certificate_id, curiculum_id, end_date, learning_module_id, resource_type, resources_id, start_date, tar_name, trainee_id Observed status codes: 200, 400, 500 Source: CreateTargetedLearningRoute.js:4
GET	/api/v1/tllist	Get Targeted Learning. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getTargetedLearningRoute.js:4
DELETE	/api/v1/tl-delete/:targeted_learning_id	Delete Targeted Learning. Access: Bearer	Path: targeted_learning_id Observed status codes: 200, 500 Source: deleteTargetedLearningRoute.js:4
GET	/api/v1/tllist-ind	In TLList. Access: Bearer	Query: email, user_mail Observed status codes: 200, 500 Source: getIndividualTLRoute.js:4

Main LMS volumes placement reference recordings and downloads

20 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/sv-upload	Volume. Access: Bearer	Body: description, trimester, volume_fetal_presentation, volume_ga, volume_name, volume_type Files: file Send multipart/form-data. Observed status codes: 200, 400, 403, 404, 406, 500 Source: svUploadRouter.js:26
PUT	/api/v1/update-volume	Update Volume. Access: Bearer	Body: description, trimester, volume_fetal_presentation, volume_ga, volume_id, volume_name, volume_type Observed status codes: 200, 406, 500 Source: svUploadRouter.js:27
GET	/api/v1/get-volumes	Get Volume Data. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getVolumeDataRoute.js:4
PATCH	/api/v1/approve-volume/:status_approval/:volume_id	Volume Approval. Access: Bearer	Path: status_approval, volume_id Observed status codes: 200, 404 Source: VolumeApprovalRoute.js:4
GET	/api/v1/get-volumes-by-instructor	Get Volume Instructor View. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getVolumeByInstructorRoute.js:4
GET	/api/v1/volumes/:volume_id/download	Get Volume Download. Access: Bearer	Path: volume_id Query: file Observed status codes: 200, 400, 404, 502 Source: getVolumeByInstructorRoute.js:5
GET	/api/v1/volumes/:volume_id/recordings	Get Volume Recording Download List. Access: Bearer	Path: volume_id Observed status codes: 200, 400, 403, 404, 500 Source: getVolumeByInstructorRoute.js:6

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/volumes/:volume_id/recordings/:recording_id/download	Get Volume Recording Download. Access: Bearer	Path: volume_id, recording_id Query: file, index Observed status codes: 200, 400, 404, 502 Source: getVolumeByInstructorRoute.js:7
PUT	/api/v1/convert-vol/:volume_id	Update Volume Con. Access: Bearer	Path: volume_id Observed status codes: 200, 400, 404, 409, 429, 500 Source: UpdateVolumeConRouter.js:5
GET	/api/v1/converted-volumes	Get Conv Volume List. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getConvVolumeListRoute.js:4
GET	/api/v1/volume-placements/:volume_id	Get Volume Placements By Volume Id. Access: Bearer	Path: volume_id Query: volume_id Observed status codes: 200, 400, 500 Source: volumePlacementRoute.js:6
GET	/api/v1/volume-placements	Get Volume Placements. Access: Bearer	Query: volume_id Observed status codes: 200, 500 Source: volumePlacementRoute.js:7
POST	/api/v1/volume-placement	Volume Placement. Access: Bearer	Body: volume_id Files: placed_file Send multipart/form-data. Observed status codes: 200, 400, 404, 500 Source: volumePlacementRoute.js:8
GET	/api/v1/recordings	Get Recordings. Access: Bearer	Query: volume_id Observed status codes: 200, 400, 500 Source: volumeRecordingRoute.js:15
POST	/api/v1/uploadvolumerecording	Vol Recording. Access: Bearer	Body: recording_name, recording_type, volume_id Files: audio_file, images, manifest_file, recording_file Send multipart/form-data. Observed status codes: 200, 400, 404, 500 Source: volumeRecordingRoute.js:19
POST	/api/v1/associateVolume	Assoc Volume. Access: Bearer	Body: r_id, shadowrec_id, steprec_id, volume_id Observed status codes: 200, 404, 500 Source: associateVolumeRouter.js:4

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/shadow-recordings	Shadow Recording Data. Access: Bearer	Query: volume_id Observed status codes: 200, 500 Source: GetShadowRecordingRoute.js:4
GET	/api/v1/shadow-recording-counts	Volume Recording Counts. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: GetShadowRecordingRoute.js:5
GET	/api/v1/volume-recording-counts	Volume Recording Counts. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: GetShadowRecordingRoute.js:6
GET	/api/v1/get-assovol	Get Associated Volume. Access: Bearer	Query: r_id Observed status codes: 200, 500 Source: getAssoVolumeRoute.js:4

Main LMS volume course mappings

3 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/course-mappings	Create Course Mapping. Access: Bearer	Body: anatomy_type, course_name, course_type, description, doctor_name, module_name, shadow_recording_id, step_recording_id, trimester, volume_name Observed status codes: 201, 400, 500 Source: courseMappingRoute.js:10
GET	/api/v1/course-mappings	Get Course Mappings. Access: Bearer	Query: anatomy_type, course_type, module_name, trimester, volume_name Observed status codes: 200, 500 Source: courseMappingRoute.js:11
GET	/api/v1/course-mappings/with-recordings	Get Course Mappings With Recordings. Access: Bearer	Query: anatomy_type, course_type, module_name, trimester, volume_name Observed status codes: 200, 500 Source: courseMappingRoute.js:12

Main LMS volume clusters and cluster recordings

28 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/clusters	Get Clusters. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: clusterRoute.js:27
GET	/api/v1/get-clusters	Get Clusters. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: clusterRoute.js:28
GET	/api/v1/cluster	Get Clusters. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: clusterRoute.js:29
GET	/api/v1/clusters/recording-counts	Get Cluster Recording Counts. Access: Bearer	Query: cluster_id Observed status codes: 200, 500 Source: clusterRoute.js:32
GET	/api/v1/cluster-recording-counts	Get Cluster Recording Counts. Access: Bearer	Query: cluster_id Observed status codes: 200, 500 Source: clusterRoute.js:33
GET	/api/v1/clusters/recordings	Get Cluster Recordings. Access: Bearer	Query: cluster_id, recording_type Observed status codes: 200, 400, 500 Source: clusterRoute.js:34
GET	/api/v1/cluster-recordings	Get Cluster Recordings. Access: Bearer	Query: cluster_id, recording_type Observed status codes: 200, 400, 500 Source: clusterRoute.js:35
GET	/api/v1/clusters/:cluster_id/recordings	Get Cluster Recordings. Access: Bearer	Path: cluster_id Query: cluster_id, recording_type Observed status codes: 200, 400, 500 Source: clusterRoute.js:36

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/clusters/:cluster_id/shadow-recordings	Retrieve clusters selected item shadow-recordings. Access: Bearer	Path: cluster_id Query: cluster_id Observed status codes: 200, 400, 500 Source: clusterRoute.js:37
GET	/api/v1/clusters/:cluster_id/step-recordings	Retrieve clusters selected item step-recordings. Access: Bearer	Path: cluster_id Query: cluster_id Observed status codes: 200, 400, 500 Source: clusterRoute.js:41
GET	/api/v1/clusters/:cluster_id/recording-counts	Get Cluster Recording Counts. Access: Bearer	Path: cluster_id Query: cluster_id Observed status codes: 200, 500 Source: clusterRoute.js:45
GET	/api/v1/clusters/:cluster_id/recordings/:recording_id/download	Get Cluster Recording Download. Access: Bearer	Path: cluster_id, recording_id Query: file, index Observed status codes: 200, 400, 404, 500 Source: clusterRoute.js:46
POST	/api/v1/clusters/:cluster_id/recordings	Upload Cluster Recording. Access: Bearer	Path: cluster_id Body: cluster_id, recording_name, recording_type, volume_id Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files Send multipart/form-data. Observed status codes: 200, 400, 404, 500 Source: clusterRoute.js:61
PUT	/api/v1/clusters/:cluster_id/recordings/:recording_id	Replace Cluster Recording. Access: Bearer	Path: cluster_id, recording_id Body: cluster_id, recording_id, recording_name, recording_type Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files Send multipart/form-data. Observed status codes: 200, 400, 403, 404, 500 Source: clusterRoute.js:67
POST	/api/v1/clusters/:cluster_id/recordings/replace	Replace Cluster Recording. Access: Bearer	Path: cluster_id Body: cluster_id, recording_id, recording_name, recording_type Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files Send multipart/form-data. Observed status codes: 200, 400, 403, 404, 500 Source: clusterRoute.js:72

Method	Full endpoint	Purpose and access	Request details and observed status codes
PUT	/api/v1/clusters/:cluster_id/recordings/replace	Replace Cluster Recording. Access: Bearer	Path: cluster_id Body: cluster_id, recording_id, recording_name, recording_type Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files Send multipart/form-data. Observed status codes: 200, 400, 403, 404, 500 Source: clusterRoute.js:77
POST	/api/v1/clusters/recordings/replace	Replace Cluster Recording. Access: Bearer	Body: cluster_id, recording_id, recording_name, recording_type Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files Send multipart/form-data. Observed status codes: 200, 400, 403, 404, 500 Source: clusterRoute.js:82
PUT	/api/v1/clusters/recordings/replace	Replace Cluster Recording. Access: Bearer	Body: cluster_id, recording_id, recording_name, recording_type Files: audio_file, audio_files, image_files, images, manifest, manifest_file, rec_files, recording_file, recording_files Send multipart/form-data. Observed status codes: 200, 400, 403, 404, 500 Source: clusterRoute.js:87
GET	/api/v1/clusters/:cluster_id	Get Cluster By Id. Access: Bearer	Path: cluster_id Observed status codes: 200, 500 Source: clusterRoute.js:93
GET	/api/v1/cluster/:cluster_id	Get Cluster By Id. Access: Bearer	Path: cluster_id Observed status codes: 200, 500 Source: clusterRoute.js:94
POST	/api/v1/clusters	Create Cluster. Access: Bearer	Body: cluster_id, cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids Observed status codes: 500 Source: clusterRoute.js:95
POST	/api/v1/cluster	Create Cluster. Access: Bearer	Body: cluster_id, cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids Observed status codes: 500 Source: clusterRoute.js:96

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/create-cluster	Create Cluster. Access: Bearer	Body: cluster_id, cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids Observed status codes: 500 Source: clusterRoute.js:97
POST	/api/v1/add-cluster	Create Cluster. Access: Bearer	Body: cluster_id, cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids Observed status codes: 500 Source: clusterRoute.js:98
PUT	/api/v1/clusters/:cluster_id	Update Cluster. Access: Bearer	Path: cluster_id Body: cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids Observed status codes: 500 Source: clusterRoute.js:99
PUT	/api/v1/cluster/:cluster_id	Update Cluster. Access: Bearer	Path: cluster_id Body: cluster_name, fetal_presentation, selected_volume_ids, volume_id, volume_ids Observed status codes: 500 Source: clusterRoute.js:100
DELETE	/api/v1/clusters/:cluster_id	Delete Cluster. Access: Bearer	Path: cluster_id Observed status codes: 500 Source: clusterRoute.js:101
DELETE	/api/v1/cluster/:cluster_id	Delete Cluster. Access: Bearer	Path: cluster_id Observed status codes: 500 Source: clusterRoute.js:102

Main LMS course access publication assignments and migration

15 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/courses	List Courses. Access: Bearer	Query: view Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:6
POST	/api/v1/courses	Create Course. Access: Bearer	Body: courseKind, curriculumId, name Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:7
PATCH	/api/v1/courses/:courseId	Update Course. Access: Bearer	Path: courseId Body: curriculumId, name Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:8
POST	/api/v1/courses/:courseId/publish	Publish Course. Access: Bearer	Path: courseId Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:9
POST	/api/v1/courses/:courseId/archive	Archive Course. Access: Bearer	Path: courseId Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:10
POST	/api/v1/courses/:courseId/draft	Draft Course. Access: Bearer	Path: courseId Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:11
PUT	/api/v1/courses/:courseId/institution-access	Set Institution Access. Access: Bearer	Path: courseId Body: institutionIds, mode Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:12
PUT	/api/v1/courses/:courseId/assignments	Replace Assignments. Access: Bearer	Path: courseId Body: assignedTraineeIds, batchIds, excludedTraineeIds Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:13

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/courses/:courseId/assignments	Get Assignments. Access: Bearer	Path: courseId Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:14
GET	/api/v1/courses/:courseId/effective-access	Get Effective Access. Access: Bearer	Path: courseId Query: institutionId Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:15
GET	/api/v1/me/courses	List My Courses. Access: Bearer	No named request fields identified in the traced handler. Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:16
GET	/api/v1/migration-review	List Migration Review. Access: Bearer	No named request fields identified in the traced handler. Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:17
PUT	/api/v1/migration-review/courses/:courseId	Resolve Course Ownership. Access: Bearer	Path: courseId Body: courseKind, institutionId Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:18
PUT	/api/v1/migration-review/volumes/:volumeId	Resolve Volume Ownership. Access: Bearer	Path: volumeId Body: institutionId, ownerScope Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:19
POST	/api/v1/migration-review/course-mappings/:mappingId	Migrate Course Mapping. Access: Bearer	Path: mappingId Body: courseKind Status / payload follows handler and shared error handling. Source: contentAccessRoute.js:20

Main LMS headset content packages and recording validation

5 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/mr/workspace	Retrieve the requester's permitted headset content workspace. Access: Bearer	No named request fields identified in the traced handler. Status / payload follows handler and shared error handling. Source: mrContentRoute.js:6
GET	/api/v1/mr/courses	Retrieve courses available to the headset content workspace. Access: Bearer	No named request fields identified in the traced handler. Status / payload follows handler and shared error handling. Source: mrContentRoute.js:7
GET	/api/v1/mr/courses/:courseId/package	Retrieve the authorized course content package. Access: Bearer	Path: courseId Status / payload follows handler and shared error handling. Source: mrContentRoute.js:8
PUT	/api/v1/recordings/:recordingId/validation	Validate Recording. Access: Bearer	Path: recordingId Body: state Status / payload follows handler and shared error handling. Source: mrContentRoute.js:9
POST	/api/v1/courses/:courseId/content	Attach Content. Access: Bearer	Path: courseId Body: resourceId, shadowRecordingId, stepRecordingId, volumeId Status / payload follows handler and shared error handling. Source: mrContentRoute.js:10

Main LMS institutions and platform administration

15 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/institutions	Get Scan Centers. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 401, 500 Source: institutionRoute.js:6
POST	/api/v1/institutions	Create Scan Center. Access: Bearer	Body: center_address, center_email, center_name, center_phone, status Observed status codes: 201, 400, 401, 500 Source: institutionRoute.js:7
POST	/api/v1/institutions/:institutionId/admins	Add Institution Admin. Access: Bearer	Path: institutionId Body: user_contact_num, user_email, user_name Observed status codes: 500 Source: institutionRoute.js:8
GET	/api/v1/super-admins	Retrieve super-admins. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200 Source: superAdminRoute.js:5
POST	/api/v1/super-admins	Create or execute super-admins. Access: Bearer	Body: user_contact_num, user_email, user_name Observed status codes: 201 Source: superAdminRoute.js:6
GET	/api/v1/superadmin/stats	Retrieve superadmin stats. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200 Source: superAdminRoute.js:7
GET	/api/v1/superadmin-stats	Retrieve superadmin-stats. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200 Source: superAdminRoute.js:8
GET	/api/v1/super-admin/statistics	Retrieve super-admin statistics. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200 Source: superAdminRoute.js:11
GET	/api/v1/superadmin/statistics	Retrieve superadmin statistics. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200 Source: superAdminRoute.js:12

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/super-admin/activity-summary	Retrieve super-admin activity-summary. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200 Source: superAdminRoute.js:14
GET	/api/v1/superadmin/activity-summary	Retrieve superadmin activity-summary. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200 Source: superAdminRoute.js:15
GET	/api/v1/super-admin/recent-activities	Retrieve super-admin recent-activities. Access: Bearer	Query: limit, module, page, role, status Observed status codes: 200 Source: superAdminRoute.js:17
GET	/api/v1/superadmin/recent-activities	Retrieve superadmin recent-activities. Access: Bearer	Query: limit, module, page, role, status Observed status codes: 200 Source: superAdminRoute.js:18
POST	/api/v1/create-scan-center	Create Scan Center. Access: Bearer	Body: center_address, center_email, center_name, center_phone, status Observed status codes: 201, 400, 401, 500 Source: createScanCentersRoute.js:5
GET	/api/v1/get-scan-centers	Get Scan Centers. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 401, 500 Source: getScanCenterRoute.js:4

Main LMS activity tracking

4 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/activity-logs/track	Track Client Activity. Access: Optional decoded token	Query: isVR, isVr, isvr Body: action, isVR, isVr, isvr, metadata, module, role, status, targetId, targetType, userId Observed status codes: 201, 400, 500 Source: activityTrackerRoute.js:38
GET	/api/v1/activity-logs/statistics	Get Statistics. Access: No shared bearer middleware	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: activityTrackerRoute.js:39
GET	/api/v1/activity-logs/recent	Get Recent. Access: No shared bearer middleware	Query: limit, module, page, role, status Observed status codes: 200, 500 Source: activityTrackerRoute.js:40
GET	/api/v1/activity-logs/summary	Get Summary. Access: No shared bearer middleware	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: activityTrackerRoute.js:41

softAuth decodes a supplied token; it does not verify its signature in this route middleware.

Main LMS mindspark ob booster and challenges

12 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/mind-spark-options	Save a legacy MindSpark option response. Access: Bearer	Body: correct_opt, r_id, status, user_opt Observed status codes: 200, 500 Source: mindSparkRoute.js:4
POST	/api/v1/mind-spark-questions	Create Questions. Access: Bearer	Body: mindsparkNo, mindspark_no, questions, resource_id Observed status codes: 200, 400, 401, 500 Source: questionsRoute.js:18
POST	/api/v1/mind-spark-question-assets	Upload Asset. Access: Bearer	Files: image Send multipart/form-data. Observed status codes: 200, 400, 401, 500 Source: questionsRoute.js:19
GET	/api/v1/mind-spark-questions	Get Questions. Access: Bearer	Query: include_inactive, mindspark_no, resource_id Observed status codes: 200, 400, 401, 500 Source: questionsRoute.js:20
GET	/api/v1/mind-spark-attempt-details	Get Attempt Details. Access: Bearer	Query: resource_id, session_id Observed status codes: 200, 400, 401, 500 Source: questionsRoute.js:21
PUT	/api/v1/mind-spark-questions/:question_id	Update Question. Access: Bearer	Path: question_id Body: answer, assets, correctAnswer, correct_answer, feedbackCorrect, feedbackWrong, feedback_correct, feedback_wrong, isActive, is_active, metadata, mindsparkNo, mindspark_no, options, options_available, prompt, question, questionNo, questionType, question_no, question_query, question_type Observed status codes: 200, 400, 401, 404, 500 Source: questionsRoute.js:22
DELETE	/api/v1/mind-spark-questions/:question_id	Delete Question. Access: Bearer	Path: question_id Observed status codes: 200, 400, 401, 404, 500 Source: questionsRoute.js:23
POST	/api/v1/create-question	Create Questions. Access: Bearer	Body: mindsparkNo, mindspark_no, questions, resource_id Observed status codes: 200, 400, 401, 500 Source: questionsRoute.js:25

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/submit-msob	Submit a MindSpark or OB Booster activity result. Access: Bearer	Body: hasTakenClue, isCorrect, optionChosen, payload, questionNo, resourceId, resourceType, sessionId, timeTaken, totalTimeTaken Observed status codes: 200, 400, 500 Source: lrobRoute.js:14
GET	/api/v1/challenges/questions	Get Challenge Questions. Access: Bearer	Query: all, challenge_name, challenge_number, module_name, resource_id Observed status codes: 500 Source: challengeRoute.js:10
POST	/api/v1/challenges/submit	Submit Challenge. Access: Bearer	Body: choose_option, isCorrect, question_number, resource_id, session_id Observed status codes: 400, 500 Source: challengeRoute.js:11
GET	/api/v1/challenges/attempt-details	Get Challenge Attempt Details. Access: Bearer	Query: resource_id, session_id Observed status codes: 400, 500 Source: challengeRoute.js:12

Fields depend on resourceType. See the activity payload guide below.

Main LMS image interpretation practice tests and submissions

8 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/submit-ii	Submit an image-interpretation, annotation or measurement result. Access: Bearer	Body: caliperPlacementInterpretation, correctLabelCount, interpretation, isCorrect, optionChosen, partial, questionNo, questionType, resource_id, session_id, unusedLabelCount, value, wrongLabelCount Files: userImage Send multipart/form-data. Observed status codes: 400 Source: iivrRoutes.js:6
POST	/api/v1/start-ii-prac	Start an image-interpretation practice or test session. Access: Bearer	Body: resource_id Observed status codes: 200, 500 Source: iivrStartTestRoute.js:4
PUT	/api/v1/end-ii-prac	End an image-interpretation session using test_id. Access: Bearer	Body: test_id Observed status codes: 200, 500 Source: iivrEndTestRoute.js:4
GET	/api/v1/practice-i-ii	Get Practices By User. Access: Bearer	Query: resource_id Observed status codes: 200, 400, 401, 500 Source: practiceRoute.js:4
POST	/api/v1/practice-i-ii	Bulk Create Practice Results. Access: Bearer	Body: practice_id, practice_number, practiceresults, resource_id Observed status codes: 201, 400, 401, 500 Source: practiceRoute.js:5
POST	/api/v1/submit-prac-test	Prac Test. Access: Bearer	Body: payload, resource_id, sessionNumber, sessionType, session_id Files: expertImage_1, expertImage_2, expertImages_1, expertImages_2, userImage_1, userImage_2, userImages_1, userImages_2 Send multipart/form-data. Observed status codes: 400, 500 Source: pracTestRoute.js:23
GET	/api/v1/prac-test-attempt-details/:resource_id	Get Prac Test Attempt Details. Access: Bearer	Path: resource_id Observed status codes: 500 Source: pracTestRoute.js:38

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/get-submissions	Get Submissions. Access: Bearer	Query: resource_id Observed status codes: 500 Source: getSubmissionsRoute.js:5

Required fields depend on questionType; see the submission guide below.

Main LMS reattempt settings

2 registered method and endpoint combinations. Source paths below are relative to server/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/reatt-data	Create Reatt Data. Access: Bearer	Body: certificate_id, course_id, max_reattempt_count, resource_id, resource_type, unit_name, uploaded_by Observed status codes: 400, 500 Source: reattRoute.js:9
GET	/api/v1/reatt-data	Get Reatt Data. Access: Bearer	Query: uploaded_by, certificate_id, course_id, unit_name, resource_type, resource_id, max_reattempt_count Observed status codes: 500 Source: reattRoute.js:10

Medica companion service checks

1 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/test	Return authenticated test-route and user information. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 401, 403 Source: Medica/v1/app.js:100

Medica companion login account verification and device sessions

3 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/login	Sign in and receive tokens plus account and device context. Access: No shared bearer middleware	Body: user_mail, user_password Observed status codes: 200, 400, 401, 404, 500 Source: Auth.js:5
POST	/api/v1/forgot-password	Record a password-recovery request and attempt an email. Access: No shared bearer middleware	Body: reset_password_mail Observed status codes: 200, 400, 404, 500 Source: forgotpRoute.js:5
POST	/api/v1/token	Refresh Token. Access: No shared bearer middleware	Body: token Observed status codes: 401, 403 Source: refreshTokenRouter.js:5

Current SMTP message is placeholder text; this route does not complete a secure password reset.

Medica companion queries and notifications

1 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/send	Create an in-app notification. Access: No shared bearer middleware	Body: link, message, receiverId, senderId Observed status codes: 200, 400, 500 Source: notificationRoutes.js:4

No shared bearer middleware is mounted on this route in app.js.

Medica companion headset streaming and live viewing

3 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/ivs-ind	Get Individual Streaming Data. Access: No shared bearer middleware	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: individualIvsRoute.js:6
POST	/api/v1/tokenn	Create a headset publisher session and IVS participant token. Access: No shared bearer middleware	Body: attributes, capabilities, duration, stageArn, userId Observed status codes: 200, 500 Source: tokenIvsRoute.js:4
POST	/api/v1/get-active-people-room	Get Active People. Access: No shared bearer middleware	Body: roomId Observed status codes: 200, 500 Source: activePeopleRoomRoute.js:4

Main LMS contract ignores client-provided stage/user/capability choices. Medica is a separate implementation.

Medica companion curriculum certifications modules resources and progress

20 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/user-completion	Progress Update. Access: Bearer	Body: course_id, isCompleted, module_id, user_id Observed status codes: 200, 500 Source: progressRoute.js:4
GET	/api/v1/get-vr-data/:data_check	Return authenticated user context and the supplied data_check value. Access: Bearer	Path: data_check Observed status codes: 200, 500 Source: getVrDataRoute.js:4
DELETE	/api/v1/delete-cur/:curiculum_id	Delete Cur. Access: Bearer	Path: curiculum_id Observed status codes: 200, 500 Source: deleteCuriculumRoute.js:4
POST	/api/v1/create-curiculum	Create Cur. Access: Bearer	Body: curiculum_name Observed status codes: 200, 500 Source: curiculamRoute.js:4
GET	/api/v1/get-curiculum	Get Cur. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getCuriculumRoute.js:4
POST	/api/v1/create-course	Course. Access: Bearer	Body: course_name, curiculum_id Observed status codes: 200, 500 Source: createCourseRoute.js:4
GET	/api/v1/get-courses	Get Courses. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: GetCourseRoute.js:4
GET	/api/v1/get-cours-cur/:curiculum_id	Get Courses By Cur. Access: Bearer	Path: curiculum_id Observed status codes: 200, 500 Source: getCoursesByCurRoute.js:4
DELETE	/api/v1/delete-course/:course_id	Course Deletion. Access: Bearer	Path: course_id Observed status codes: 200, 500 Source: deleteCourseRoute.js:4

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/tag-course	Tag Course. Access: Bearer	Body: course_id, user_id Observed status codes: 200, 403, 500 Source: TagCourseRoute.js:4
POST	/api/v1/request-course	Request Course. Access: Bearer	Body: course_id Observed status codes: 200, 403, 500 Source: RequestCourseRoute.js:4
POST	/api/v1/create-module	Create a chapter using chapter_name and course_id. Access: Bearer	Body: chapter_name, course_id Observed status codes: 200, 400, 500 Source: createModuleRoute.js:4
GET	/api/v1/get-module	Get Module. Access: Bearer	Query: chapter_id Observed status codes: 200, 500 Source: getModuleRoute.js:4
POST	/api/v1/create-new-module	Create a module underneath a chapter. Access: Bearer	Body: chapter_id, module_name Observed status codes: 200, 400, 500 Source: newModuleRoute.js:4
POST	/api/v1/sub-module	Sub Module. Access: Bearer	Body: module_id, submod_name Observed status codes: 200, 400, 500 Source: subModuleRoute.js:4
GET	/api/v1/resource-completion	Mark resource completion through query parameters. Access: Bearer	Query: is_completed, r_id Observed status codes: 200, 500 Source: moduleCompleteUserRoute.js:4
GET	/api/v1/get-chapter	Get Chapters. Access: Bearer	Query: course_id Observed status codes: 200, 500 Source: getChapterRouter.js:4
POST	/api/v1/create-resource	Create Resource. Access: Bearer	Body: module_id, resource_name Observed status codes: 200, 400, 500 Source: createResourceRoute.js:4
GET	/api/v1/get-resources	Get Resources. Access: Bearer	Query: module_id Observed status codes: 200 Source: getResourcesRoute.js:4

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/resources-mId	Get Resources By Module Ids. Access: Bearer	Body: module_id Observed status codes: 200, 500 Source: getResourcesByModuleIdsRoute.js:4

This GET route changes completion state. Query keys are shown exactly as implemented.

Medica companion batches

5 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
DELETE	/api/v1/delete-batch/:batch_id	Delete Batchc. Access: Bearer	Path: batch_id Observed status codes: 200, 500 Source: deleteBatchRoute.js:4
POST	/api/v1/create-batch	Batch Creation. Access: Bearer	Body: batch_end_date, batch_name, batch_start_date, course_data, curiculum_name Observed status codes: 200, 500 Source: createBatchRoute.js:5
GET	/api/v1/get-batches	Get Batch Data. Access: Bearer	Query: limit, page Observed status codes: 200, 500 Source: getBatchesRoute.js:4
POST	/api/v1/associate-batch	Associate Batchc. Access: Bearer	Body: batch_id, user_id Observed status codes: 200, 500 Source: associateBatchRoute.js:4
GET	/api/v1/batch-filter	Filter Batch. Access: Bearer	Query: batch_name, instructor_name Observed status codes: 200, 500 Source: filterBatchRoute.js:4

Medica companion profiles dashboards and analytics

4 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/profile	Profile. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 500 Source: profileRoute.js:5
GET	/api/v1/get-dashboard-data	Get Dashboard. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: dashboardRoute.js:4
GET	/api/v1/get-gender-ratio	Gender Ratio. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getGendersRoutes.js:5
GET	/api/v1/user-stats	User Stats. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: UserStatusRoute.js:4

Medica companion trainees instructors and user accounts

8 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
GET	/api/v1/get-trainees	Trainee. Access: Bearer	Query: limit, page Observed status codes: 200, 500 Source: getTraineesRoute.js:5
PATCH	/api/v1/disable-trainee/:user_mail/:status	Disable Trainee. Access: Bearer	Path: user_mail, status Observed status codes: 200, 400, 500 Source: disableTraineeRoute.js:5
GET	/api/v1/get-instructors	Get Instructor Data. Access: Bearer	Query: limit, page Observed status codes: 200, 500 Source: getInstructorRoute.js:4
POST	/api/v1/create-trainee	Create Trainee. Access: Bearer	Body: description, status, user_batch, user_contact_num, user_dob, user_email, user_gender, user_name, user_password, user_role Files: file Send multipart/form-data. Observed status codes: 200, 404, 500, 501 Source: createtraineeRoute.js:6
DELETE	/api/v1/delete-trainee/:user_mail	Delete Traineec. Access: Bearer	Path: user_mail Observed status codes: 200, 500 Source: deleteTraineeRoute.js:4
DELETE	/api/v1/delete-ins/:user_mail	Instructor. Access: Bearer	Path: user_mail Observed status codes: 200, 500 Source: deleteInstructorRoute.js:4
GET	/api/v1/get-admins	Get Admin. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getAdminsRoute.js:4
GET	/api/v1/trainee/:people_id	Induuid. Access: Bearer	Path: people_id Observed status codes: 200, 500 Source: induuidRoute.js:4

Medica companion targeted learning

4 registered method and endpoint combinations. Source paths below are relative to Medica/v1/routes/ unless an app.js path is shown.

Method	Full endpoint	Purpose and access	Request details and observed status codes
POST	/api/v1/create-targeted-learning	Create Targeted Learning. Access: Bearer	Body: chapter_id, course_id, curiculum_id, end_date, module_id, resources_id, start_date, tar_name, trainee_id Observed status codes: 200, 400, 500 Source: CreateTargetedLearningRoute.js:4
GET	/api/v1/tllist	Get Targeted Learning. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getTargetedLearningRoute.js:4
DELETE	/api/v1/tl-delete/:targeted_learning_id	Delete Targeted Learning. Access: Bearer	Path: targeted_learning_id Observed status codes: 200, 500 Source: deleteTargetedLearningRoute.js:4
GET	/api/v1/tllist-ind	In TLList. Access: Bearer	No named request fields identified in the traced handler. Observed status codes: 200, 500 Source: getIndividualTLRoute.js:4

Request examples for main LMS

Replace placeholders with real authorized values. These examples illustrate the source contract; they have not been submitted to the running service.

Sign in

POST /api/v1/login

```
{
  "user_mail": "trainee@example.com",
  "user_password": "<password>"
}
```

Request verification OTP

POST /api/v1/account-verification/request

```
{
  "email": "trainee@example.com",
  "purpose": "activation"
}
```

Verify an account

POST /api/v1/account-verification/verify

```
{
  "email": "trainee@example.com",
  "purpose": "activation",
  "otp": "123456"
}
```

Start image interpretation practice

POST /api/v1/start-ii-prac

```
{
  "resource_id": "<resource-id>"
}
```

End image interpretation practice

PUT /api/v1/end-ii-prac

```
{
  "test_id": "<test-id-returned-by-the-session-flow>"
}
```

Create a query

POST /api/v1/queries

```
{
  "subject": "Learning activity question",
  "message": "Please clarify the expected plane."
}
```

Create a modern course draft

POST /api/v1/courses

```
{
  "name": "Example course",
  "courseKind": "institution",
  "curriculumId": "<curriculum-id>"
}
```

Set course assignments

PUT /api/v1/courses/:courseId/assignments

```
{
  "batchIds": [
    "<batch-id>"
  ],
  "assignedTraineeIds": [],
  "excludedTraineeIds": []
}
```

Conditional submission payloads

Image interpretation submission

POST /api/v1/submit-ii accepts questionType, questionNo, session_id and resource_id as the common required fields. isCorrect is required except for measurement. Upload userImage using multipart/form-data for type2, annotation1, annotation2 and measurement.

questionType	Additional requirements
type1	optionChosen is checked for question numbers below 6. No userImage is required by this branch.
type2	userImage and isCorrect.
annotation1 or annotation2	userImage, isCorrect, correctLabelCount, wrongLabelCount and unusedLabelCount.
measurement	userImage, partial, value, interpretation and caliperPlacementInterpretation. partial must be 0, 0.5 or 1.

MindSpark and OB Booster submission

POST /api/v1/submit-msob requires resourceType and resourceId. sessionId can be supplied; the controller generates a UUID when absent. Resource types are normalized to uppercase.

resourceType	Activity specific fields
TYPE1	questionNo, optionChosen, isCorrect
MATCHING	questionNo, payload, isCorrect
WORDSEARCH	questionNo, timeTaken, hasTakenClue
CROSSWORD	totalTimeTaken
PROBEMOVEMENTS	totalTimeTaken

Challenge submission

POST /api/v1/challenges/submit validates resource_id, session_id, question_number, choose_option and isCorrect. question_number must be numeric. choose_option can be a single value or an array and cannot be empty after normalization. isCorrect must parse as true or false.

File uploads and headset communication

File request rules

The file-field names in the endpoint tables are exact multipart keys. Ordinary form fields accompany them. The route may accept alternative file key names; aliases are not a requirement to send the same file multiple times.

Volume uploads use file. Placement uses placed_file. Volume-reference recording upload uses recording_file, audio_file, images and manifest_file. Cluster recording routes accept additional aliases shown in their table. Question image assets use image. Image-interpretation submissions use userImage. Practice-test submissions accept the numbered userImage and expertImage keys and plural aliases shown in the table.

The volume upload limit is environment-controlled. The tracked Lambda template sets MAX_VOLUME_UPLOAD_SIZE_MB to 8, while source defaults differ. Recording routes specify 50 MB per file and a total file-count limit of 61. Question assets default to 10 MB through MAX_MINDSPARK_ASSET_SIZE_MB. Deployed proxy limits can be lower; use the actual environment when choosing an upload size.

Live headset sequence

1. Headset calls POST /api/v1/tokenn with its LMS bearer token.

2. The publisher token is returned at result.data.token and the application session ID at result.sessionId.

3. Headset joins IVS and publishes video and microphone.

4. Activation is retried in the background. The headset can call POST /api/v1/streaming/publisher-session/:sessionId/activate; a 409 means publishing is not yet visible and needs bounded retry.

5. Trainee browser calls POST /api/v1/streaming/self-viewer-session. Institution-admin browser calls POST /api/v1/streaming/viewer-session.

6. Headset calls DELETE /api/v1/streaming/publisher-session/:sessionId when publishing stops.

IVS media transport is separate from the REST API endpoints. A storage download endpoint generally prepares an authorized URL; the subsequent file transfer can occur directly from object storage.

Socket events

The local main LMS also initializes Socket.IO. Client subscriptions are subscribe:superadmin and subscribe:user. Server events include activity:new, stats:update and session:revoked. These are event names, not standalone REST endpoints. The Lambda HTTP deployment does not by itself establish a persistent Socket.IO host.

Routes not registered and reference sources

Main LMS defines GET / in server/v1/routes/GetPracticeResults.js:6, but its router is not mounted in the service app.js. No public full endpoint is assigned here.

server/v2/login/endpoint.js, authRoute.js, authController.js and authModel.js are empty. They contribute no endpoints. The volume converter is a Batch worker in the reviewed deployment and is not an additional HTTP service.

Primary sources are the two app.js files, their imported route modules, and the associated controllers, models and authentication middleware. The endpoint registration list excludes commented-out code and unmounted route files. The route inventory and source line numbers were generated from JavaScript syntax trees, then supplemented for conditional payloads.

Useful source documents: server/v1/STREAMING.md, server/v1/template.yaml, APIs/Submit_MSOB_API_Product_Guide.md, APIs/Volume_APIs.md and APIs/Challenges_API.md. Endpoint spellings are taken from the current route code when older documents differ.