"To Do The Common Thing
Uncommonly Well Brings Success"

- Company Founder

Made in India :
Nexa Specialities
Plot No. 25, Odhav Farm,
Motapondha Road, Vapi – 396195.
Contact Customer Care Incharge
At Email Id : Finolube@gmail.com
Or Dial : +91 7226016057
Write At Above Address.

Certified by :
Brilliant Certification & Inspection Pvt. Ltd.
"LONDON"

MAKE IN INDIA

Finolube logo and trademark used under Licensed by Nexa Specialities (India) @ all right reserved

FINOLUBE®

Growing Together...

ABOUT US...

FINOLUBE is an established name in the Indian Petroleum Scene, today ranking amongst the Country's leading Manutacturers of Lubricants and Specialties confirming to high quality standards. we have modern facilities and infrastructure at our plant located at VAPI which uses sophisticated technology to produce an impressive range of premium quality products from Industrial Automotive Oils and Petroleum Specialities. FINOLUBE products meet the most stringent of the requirements of the customers. Liberalization has taught us to operate in a global economy in which parameters of quality, delivery, customer satisfaction and other operating factors are indicators of success.

At FINOLUBE, oil is biended from selected high quality base oil and imported additives to manufacture world class lubricant. We have a state-of-the-art laboratory to ensure monitor all the quality aspects right from raw material input to finished blended products. We have developed a wide range of optimum performance lubricants, greases and engine oil for both the automotive and industrial sectors. The entire range of products are environment friendly that ensures full value for money Our stringent quality control system and strong R&D base and endeavour towards qualities upgradation & product development has helped us maintain a lang term relationship with all our existing clients who depends on our experience for their critical needs.

FINOLUBE is ISO 9001:2008 certified company. From its very inception it has been committed to a total quality culture. It owes its success to this philosophy which it has inculcated in its personnel with a missionary zeal Drawing invaluable experience dealing with multinationals, TAURUS has laid a firm foundation for quality and service.

OUR VISION

Our vision is to become India's leading independent manufacturer of high-quality lubricants and associated products. Through the pursuit of service and technical excellence we aim to continuously meet and exceed the demands placed upon us by ourdiverse customer base.

OUR MISSION

Through continuous inward investment in core competencies it is our mission to grow both geographical and product markets to drive revenue growth Development of competencies within our distribution networks and enhanced customer understandingwill enable us to achieve our vision.

OUR CORE VALUES : We are extremely proud of the values we hold which have created the foundations on which our success has been built:

- Family-owned I Ledby a fifth generation family member, our culture is based upon strong relationships builton trust
- Highly-advanced Our sophisticated technology and product innovation ensures we remain ever-aligned with increasing market demands.
- Principled Our Business is running with an utmost degree of integrity from top management down to every single employee.
- Sustainable I We are committed to undertake processes and operations to ensure any impact on the environment is minimized.
- Diligent I Our management team leads by example and instils and encourages a strong work ethic across the whole workforce.
- Respectful I We treat every individual and organization, we work alongside with respect and consideration which builds strong relationships with ail-whether fellow team members, customers, or partners

OUR PROMISE TO YOU : We promise to provide continue :

- World-class products
- Innovative solutions to your challenges
- Industry-leading business development support to our distribution partners
- Expert technical advice and guidance
- Open, honest and transparent working practices
- First-Rate account management

DRIFT 4T - SM GRADE

Finolube Drift 4T SM is shear-stable, Multi-grade engine oil specifically designed for use in four stroke motorcycles and portable power equipment meeting requirement of API SM JASO MA2 lubricants, including high output engines operating in severe service. Proven Metallo-organic Anti-wear additive system reduces wear of highly stressed engine components under severe operating conditions. Under these conditions, motorcycle engines operate at extremely high temperatures, causing viscosity and thermal breakdown of motor oil. It is engineered to provide maximum protection against viscosity and thermal breakdown.

Performance Standard :

API - SM - JASO MA-2

Key Features & Benefits :

- Specialized with PBM (Performance Booster molecules) Technology, which ensures Performance, Power & Protection for Bike.
- Eliminates high temperature deposits on piston & rings.
- Possess excellent Anti-corrosion, Anti-oxidant & Anti-wear properties.
- Extended drain interval up to 10,000 km.
- Smooth Gear shift ensures superior power transfer and acceleration.
- Lower clutch slippage & Provides better fuel economy

Applications :

Finolube Drift 4T SM is recommended for use in all 4 stroke new age bikes plying under severe duty conditions like frequent stop & go, dusty environment, variable climatic conditions etc. Viz Honda, Hero Moto-Corp, Bajaj Auto, Yamaha, TVS, Suzuki, Duke, etc.

Characteristics :	4T SM
K. Viscosity, cSt @100˚C	14-16
Viscosity Index Min.	160
Flash Point (COC) ˚C min	220
Pour Point, ˚C, max	-21
TBN, mg, KOH/gm.	7 to 9

Pack Size : 800ml, 900ml, 1L, 1.2L, 20L, 50L, 55L, 210L.

RANGER 4T

Ranger 4T is high performance 4 stroke motorcycle oil manufactured with advanced additive technology to meet the stringent requirements of modern 4 stroke scooters and motorcycles. The advanced formulation protects Engine and Gear box while reducing Clutch slippage. These oils are blended from high viscosity index base stocks and contain additives to meet the stated performance standards.

Performance Standards :

- API SL
- JASO MA : 2

Key Features and Benefits :

- Superior high speed engine protection to extend engine life.
- Satisfies the lubrication requirements of a wide variety of engine cubic capacities.
- Extreme protection at high temperatures and heavy loads.
- Outstanding oil consumption control.
- Excellent wet clutch performance and protection of exhaust and catalyst systems

Applications :

- 4 Stroke Motorcycles / Scooters.
- Ranger 4T is meant for use in all the latest generation motorcycles manufactured by Honda, Bajaj, TVS, Mahindra, Yamaha etc

Characteristics	20w40	10w30
K.Viscosity, cSt@ 100˚C	11-14.5	8.5-11
Viscosity Index, min.	129	129
Pour Point, ˚C, max.	-11	-11
Flash Point, COC, ˚C, min	224	224
TBN, mg. KOH/gm.	6-7	6-7

Pack Size : 800ml, 900ml, 1L, 1.2L, 20L, 50L, 55L, 210L.

TURBO PLUS 15w40 CH-4 & DIAMOND 15w40 CI4 PLUS

Turbo Plus 15w40 is a commercial multipurpose diesel engine oil meeting API CH4 Specification. The oil is specifically designed for Topping up applications of modern, highly rated turbo charged diesel engines in the on-highway and also off-highway operations. This oil is readily compatible with most of the latest generation standard API CH4 oil is commercially available and will provide economic alternative to fully loaded high end oils in top-up applications while maintaining good shear stability and protection under high temperature operations.

Performance Standards : Turbo Plus 15w40 is specially tailored for providing an economical alternative to topping up operations in new generation commercial diesel vehicles on Heavy duty on-highway and off-highway equipments. While these oils are fully compatible with most of the standard commercially available CH4 Oils, Extreme care has to be exercise while using this oil for full sump replacement service.

Key Features And Benefits :

- Good engine cleanliness.
- Good protection from wear and deposits.
- All weather performance due to improved cold weather properties.
- Catalytic Converter compatible.
- Improved all round performance.

Applications : Turbo Plus 15w40 is recommended for use in the new generation turbo-charged engines in the tractors of Eicher, Escorts, HMT, John Deere, Mahindra & Mahindra, New Holland, Sonalika, Swaraj, TAFE & other manufacturers. It is also recommended for use in the diesel engines of 3-wheeler or 4-wheeler light and medium duty commercial vehicles, including APE (Piaggio), ACE (Tata Motors), CHAMPION (Mahindra), GC 1000 (Bajaj Auto), MINIDOR (Force Motors) and other models used in cargo as well as passenger applications. (Please refer user's manual for OEM recommendation.)

Characteristics	15w40 CH-4	15w40 CI-4 Plus
K. Viscosity, cSt@ 100˚C	14.5-16.5	13.8-17.2
Viscosity Index, min.	125	100
Pour Point, ˚C, max.	-7	-15
Flash Point COC, ˚C min.	223	230
TBN, mg. KOH/gm.	10-13.5	09.0-11.0

Pack Size : 500ml, 1L, 3L, 4L, 5L, 6L, 7.5L, 10L, 15L, 20L, 50L, 210L.

ROAD STAR 20W40

Road Star 20W-40 is a premium quality commercial multipurpose diesel engine oil meeting API CF4 Specification. The oil is designed to endure the most severe performance requirements of modern, highly rated turbo charged diesel engines in the onhighway and also off highway operations. The specialized additives in the oil provide protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. This oil has excellent shear stability to maintain viscosity under severe, high temperature operations.

Performance Standard :

- API-CF4
- Mack T 8A
- US Military MIL-L-2104 C performance levels
- IS: 13656-2002 Type EDL3

Key Features & Benefits :

- Excellent thermo-oxidative stability controls sludge build-up and deposits
- Good dispersants help in controlling soot related oil thickening and wear
- Optimum power in turbo charged engines
- Excellent engine cleanliness & engine durability
- Lower oil & fuel consumption
- Excellent all weather performance due to improved cold weather properties.

Applications : Recommended for use in TATA motors , Ashok Leyland, Eicher HCV & LCV & also recommended for use in tractors manufactured by Eicher, Escorts, HMT, John Deere, Mahindra & Mahindra, New Holland, Sonalika, Swaraj, TAFE and commercial vehicles manufactured by Bajaj ,TVS , Eicher, Mahindra & Mahindra, Swaraj, Excorts, Tata Motors, etc and gensets in both turbo and natural aspirated engines.

Characteristics	20w40
Viscosity, cSt @ 100˚C	12.5-15
Viscosity Index, min.	115
Pour Point, ˚C, max.	-6
Flash Point, COC, ˚C, min.	219
TBN, mg. KOH/gm.	7-11

Pack Size : 500ml, 1L, 5L, 6L, 7L, 7.5L, 10L, 20L, 50L, 210L.

GEAR EP-90, 140, 80w90 & 85w140

Finolube Gear EP 90 & 140 oils are multipurpose, extreme pressure, API GL-4 automotive gear lubricants specifically designed for use in automotive gears and transmission. The carefully balanced formulation is designed to minimize oxidative sludge and varnish formation, reduce wear, prevent scoring damage and protect against metal fatigue and spalling damage under shock-load conditions.

Performance Standards :

- API GL-4
- Mil-L-2105
- IS 1118: 1992

Key Features and Benefits :

- Excellent oxidation resistance and thermal stability to minimize sludge and varnish formation
- Satisfies the lubrication requirements of a wide variety of gears.
- Provides protection against wear, due to good EP characteristics.
- Gives long service life even under high temperature operation.
- Excellent thermal durability and extreme-pressure properties for extended gear life
- High load-carrying capacity for protection against scuffing and wear

Applications :

Finolube Gear oils are recommended for passenger car, bus and highway truck hypoid, spiral bevel and worm gear axles and also manual transmission for which an extreme pressure gear lubricant of this type is required. It is specially designed for power transmission units of vehicles operating at sub-zero temperatures.

Characteristics	90	140	80w90	85w140
Kinematic Viscosity, cSt@100˚C	16-20	26-34	12 to16	12to16
Viscosity Index, min.	90	90	95	95
Flash Point, COC, ˚C, min	210	210	210	210
Pour Point, ˚C, max.	-7	-7	-13	-14

Pack Size : 500ml, 1L, 5L, 20L, 50L, 210L.

ROYAL 4T 20W50 & CNG SPECIAL 20W50

Finolube Royal 4T 20W50 & CNG Special 20W50 has a higher viscosity reserve which provides engines with full protection under higher operating speeds, temperatures, and other adverse conditions. It is designed with the perfect synergy for less oil consumption, reduced engine internal friction and extreme pressure performance, for more power. Royal 4T possesses exceptional nitration resistance properties which is suitable for engines operating with dual fuel kit.

Performance Standard :

- ILSAC GF-5/API SN
- ACEA A2/B2
- IS 13656 - 2002
- API SF/CD

Key Features & Benefits :

- Superior dispersancy that fights sludge build-up
- Quicker engine start & longer battery life.
- Exceptional oil burn-off protection exceeding industry standards
- Advanced additives that minimize engine wear&Improves fuel economy

Applications :

- Strongly Recommended for use in Petrol, LPG & CNG engines of new generation passenger cars of all major manufacturers, including Ford, General Motors, Honda, Hyundai, Mahindra & Mahindra, Maruti Suzuki, Nissan, Renault, Tata Motors, etc
- Also recommended for gasoline fuelled automobiles and light duty trucks requiring an API SN, SM, SL or SJ.
- Also recommended for optimum performance in the high-end 4 stroke bike models of major manufacturers including Hero, Bajaj, Yamaha, Honda & TVS where 20W-50 oil is recommended.

Characteristic's :	20W50
K. Viscosity, cSt@100˚C	16.5 to 20
Viscosity Index, min	122
Flash Point, COC, ˚C, min.	233
Pour Point, ˚C, max TBN, mg. KOH/gm.	5-7.5

Pack Size :

500ml, 900ml, 1L, 3L, 20L, 50L, 210L.

TRACER 5W30 & SYNTHUP 5W40

Tracer 5w-30 is a range of top-tier motor oil that is formulated using the unique "FINOLUBE FLEXI MOLECULE TECHNOLOGY (FFMT)", yielding a motor oil that actively helps to keep engines clean. Finolube Flexi-Molecule Technology has always been the heart of Finolube. Starting with the Synthetic Technology, it allows the product to provide even higher levels of cleansing and protection. It's unsurpassed sludge protection – no other motor oil can keep your engine closer to factory clean.

Performance Standards :

Meets : API SN/ACEA-A3/B4 requirements.

Key Features & Benefits :

- Provides more stringent sludge control for piston & other engine parts
- Excellent start-up performance in low temperature & great durability at high temperature.
- Helps prevent deposits and sludge build-up to enable long engine life.
- Excellent overall lubrication and wear protection performance for many driving styles.
- Quick cold weather starting and ultra-fast protection.

Applications :

- Recommended for all modern high performance Petrol, CNG & diesel vehicles of Volkswagen, Skoda, Honda, Renault, Maruti, Hyundai, Toyota, Nissan, ford and also for diesel engines fitted with Diesel Particulate Filters (DPFs).

Characteristics :	5W30	5w40
Appearance	Clear & Bright	Clear Bright
K. Viscosity, cSt @100°C	10.5 – 12.5	10.5-12.5 11.5-13.5
Viscosity Index Min.	150	Min. 155-170
Flash Point (COC) °C min	210	230
Pour Point, °C, max	-35	8-10
TBN, mg, KOH/gm.	7 to 8	- 35

Pack Size : 600ml, 1L, 3.5L, 7L, 20L, 50L, 210L.

BRAKE OIL - DOT 3 & DOT 4

Finolube DOT3 Brake Fluid is formulated from mixed polyalkylene glycol ethers together with lubricity additives and corrosion inhibitors. The high level of protection against wear and corrosion offered by this product will prolong the service life of the system components making it especially suitable for use in hydraulic clutch systems.

Performance Standard :

- SAE J 1703
- US federal standard 116 DOT 3
- IS : 8654 – 2001 Type 1

Key Features & Benefits :

- Resistance to Oxidation and Thermal Degradation
- High performance additives offers excellent lubricity
- Prevents corrosion of metal parts in braking system
- High ERBP provides superior braking performance under conditions of severe braking pressure

Applications :

Finolube Brake Fluid DOT 3 is designed for use in all type of automotive vehicles such as 2/3 wheelers, passenger cars, light/ heavy commercial vehicles, agricultural tractors, etc. for disc and drum brake. This fluid is also suitable for use in hydraulic clutch systems

Characteristics :	Dot 3
Viscosity CST @ 100 DEG C Min:	1.5
CST @ (-) 30 DEG C	1300 - 1500
ERBP (Equilibrium Reflux Boiling Point).	240
Appearance	Bright clear liquid

Pack Size : 250ml, 100ml.

GEAR GUARD 75W90 GEAR OIL GL-5

FINOLUBE Gear Guard 75w90 is a superior multi-graded Gear oil manufactured from high quality base oil. It is formulated with EXTREME LOAD MANAGERS which ensures protection at extreme pressure point.

Performance Requirements:

- Outstanding anit-wear, anti scuffing & anti-corrosion protection
- Excellent Thermal And Oxidation Stability Helps Extend Gear And Bearing Life
- Good Anti-foam Behaviour Maintains Flim-strength For Reliable

Applications :

- Recommended by world-leading car manufacturers of cars running on Petrol /Diesel / CNG like Tata Motors, Hyundai Motors, Maruti, Datsun, Renault, Volkswagen, Skoda, Honda, Nissan, Toyota, Mercedes, BMW, Ford etc.

Typical Physical Characteristics :

Characteristics GEAR	GUARD 75W90
Kinematic Viscosity, cst@100 °C	14-16
Viscosity Index, min.	195
Pour Point, °C, max.	-30
Flash Point, COC, °C, min	225

Pack Size : 210L, 50L, 7L, 3.5L, 3L, 1L.

MAGNA 10W40

Magna 10w40 is formulated with special Flexi-Molecule detoxifiers in premium base oils that protect the engine from harmful carbon deposits in all types of conditions. Cold running deposits formed during city driving and hot running deposits during high speed driving conditions are arrested by these detoxifiers thereby keeping the engine clean.

Performance Standard :

- API SN/CF
- JASO T 903:2016 MA2

Key Features & Benefits :

- Meets the performance requirements of API SN, CF and ACEA A3/B4.
- Provides advanced deposit control for improved engine cleanliness.
- Contains Flexi-Molecule detoxifiers that continuously arrest engine deposits thereby keeping the engine clean and responsive
- It is recommended for modern petrol/diesel engines of new gen hatchbacks and entry to executive level sedans requiring 10W-40 grade

Applications :

Recommended by world-leading car manufacturers of cars running on Petrol /Diesel / CNG like Tata Motors, Hyundai Motors, Maruti, Datsun, Renault, Volkswagen, Skoda, Honda, Nissan , Toyota, Mercedes, BMW, Ford etc.

Characteristics	Magna 10w40
Kinematic Viscosity, cst@100 °C	14-16
Viscosity Index, min.	150
Pour Point, °C, max.	-28
Flash Point, COC, °C, min	235
TBN, mg. KOH/gm.	10 to 12

Packing : 210L, 50L, 7L, 3.5L, 3L.

CLASSIC 15W50 (API:SM)

Finolube Classic 15W-50 is specially formulated with synthetic technology and advanced additives to provide optimum performance and protection for a wide range of European and Japanese engine manufacturers. Finolube Classic 15w50 is formulated with advanced turbo charged formula, This feature is supported, by exceeding the toughest industry performance standards, it is proven in grueling racing applications

Performance Standard :

Meets : API SM / JASO MA2

Key Features & Benefits :

- Classic 4T 15w50 Meets or exceeds the requirements of: API SM, JASO MA2, ACEA A3/B3 4-Stroke.
- Exceptional anti-wear properties protect vital engine and gear components leading to reduced maintenance costs.
- Contains highly effective anti-wear additives that extend the life of your engine.
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

Applications :

- Recommended for use in Royal Enfield Bullets, Honda, Bajaj, TVS, Suzuki, Yamaha & for all leading global 4-stroke motorcycle manufacturers.

Characteristics :

Kinematic Viscosity, cst@100 ˚C	16-19
Viscosity Index, min.	153
Pour Point, ˚C, max.	-30
Flash Point, COC, ˚C, min	242
TBN, mg. KOH/gm.	7 to 9

Pack Size : 2.5L, 50L, 210L.

FORK Oil

Finolube Fork Oil is specially developed for application in front fork assemblies of two wheelers and is recommended for use in the front fork shock assembly of motorcycles. The oil is filled in each leg and oil is changed as per manufacturer's recommendation.

Key Features & Benefits :

- Excellent dampening effect
- Excellent seal compatibility
- Protection against wear, oxidation, corrosion and foaming
- Offers stunningly smooth ride over rough roads.
- Effective for tropical roads and for heavily loaded vehicles.

Applications :

Finolube Fork Oil is suitable for service fill use in the suspension forks of a large range of motorcycles and can be used in competitions such as Motocross, Racing and Trials, as well as normal on-road service.

Pack Size : 175ml, 350ml.

QUALITY CONTROL

ULTRA WET BRAKE UTTO

Finolube Ultra Wet Brake UTTO is a premium quality of multipurpose universal tractor transmission oil designed to lubricate tractor transmissions, differentials and final drive gears. It is blended from high quality hydro cracked base oils. Wet Brake UTTO is doped with Afton made additives specifically used for wet brake, hydraulic, clutch & transmission system in today's farm tractors & construction machinery.

Performance Standard :

- John Deere J20C, J20D
- Caterpillar TO-2
- Allison C-3 &C-4
- M2C134 - A/B/C/D

Key Features & Benefits :

- Superior Friction Durability & ensures Noise free Operation.
- Longer life of brake disc & component and extended oil life.
- Excellent Anti-wear properties & Extreme pressure properties
- Excellent detergency & balanced friction system for imparting friction stability to tractor oils
- Excellent protection against rust and corrosion.

Applications :

Recommended for use in heavy duty tractor transmission with Wet Brake, used in Off-Highway equipment's in agriculture, construction & quarrying. Also used in transmission application requiring API GL-4 Oil except in hypoid gear designs. Wet Brake UTTO is meant for use in Tractors of Mahindra & Mahindra, Eicher, TAFE, SAME, Swaraj, Fiat, Massey Ferguson, Escorts, Power Trac, HMT, Ford & New Holland having Wet Brake Systems & Immersed bake systems.

Characteristics	Wet Brake UTTO
K. Viscosity, cSt@100˚C	9.5 to 11.5
Viscosity Index, min	140
Rust Protection	No Rust
Pour Point, ˚C, max	-33

Pack Size : 1L, 5L, 10L, 20L, 50L, 210L.

ULTRA HYDROL 32,46,68

Ultra Hydrol AW series of oils are high performance oils meeting anti-wear hydraulic oil requirements. These oils are formulated with advanced technology additives blended in suitable Group II base oils. The balanced additive formulations which include antioxidants and corrosion-inhibitors provide good ageing and temperature resistance while ensuring optimal anti-wear properties and high load carrying capacity. Its excellent thermal and oxidation resistance coupled with high viscosity index delivers good performance at higher temperatures over extended operating intervals. The oil offers excellent foam control and good demulsibility. This oil is neutral toward ferrous metals and almost all nonferrous metals and gasket-materials. These oils are currently available in viscosity grades of 32, 46 and 68.

Performance Standards :

- DIN 51524, Part III DENISON HF-2
- IS: 10522:1983 (Reaffirmed 1993)

Key Features & Benefits :

- Low Compressibility, volatility and foaming tendency
- Good thermal capacity and conductivity
- Good viscosity temperature characteristics for wide operating temperatures.
- Excellent demulsibility and hydrolytic stability
- Outstanding anti-wear, anti-corrosion and antirust characteristics

Applications :

These oils are recommended for high pressure hydraulic systems using vane, piston or gear pumps on mobile and stationary equipment used in Industrial construction, Agriculture and Mining. Hydrex AW oils are also suitable for enclosed gears operating under medium to high load conditions as well as industrial circulating systems where Rust and oxidation inhibited oils are recommended. They also meet the requirement of Denison HF-O filterability requirement, Vickers 1-286-S and M-2950-S.

Characteristics	32	46	68
K.Viscosity, cSt @ 40˚C	29-35	43-49	62-72
Viscosity Index	97	97	97
Flash Point COC ˚C, Min.	200	210	210
Pour Point ˚C, Max	-2	-2	-2
Rust Test	Pass	Pass	Pass

Pack Size (Ltrs.) : 1L, 5L, 10L, 20L, 26L, 50L, 210L.

GALAXY 2-T

Finolube Galaxy 2T Motor Oil is a traditional mineral based motor oil. 2-Stroke Motor Oil is formulated from top quality solvent refined mineral based oils with affton additive technology designed to deliver optimum performance.

Performance Standard : • API: TC • MIL-L-2104B • JASO FB

Key Features & Benefits :

- Good Deposit Control, Good Anti-Sludge and Varnish Resistance
- Excellent Anti-Wear, Oxidation Stability and Corrosion Protection
- Dispersant/Detergent Properties & Resistance to High Sulphur Fuels.

Applications :

Galaxy 2-T is recommended for lubrication of scooters, autorickshaws, motorcycles and mopeds operating on two stroke engines, Also suitable for small engines used in sprayers, lawn movers, pumps, small generators.

Characteristic's :	Galaxy 2-T
K. Viscosity, cSt @100˚C	6 to 7
Kinematic Viscosity, cst@40 ˚C	55-60
Sulphated Ash % Wt	0.094
Pour Point, ˚C, max	-12

Pack Size : 500ml, 1L, 20L, 50L, 210L.

DELTA TQ

Delta TQ is a High Performance Power Steering Fluid. Finolube TQ is a high performance power steering fluid cum transmission oil with high viscosity Index, low pour point, high oxidation stability, good antiwear, adequate dispersancy, low foaming tendency and desired friction characteristics.

Key Features and Benefits :

- Works as a good PSF even in extremely arduous operating conditions
- Ensures quiet and smooth operation under all climatic conditions.
- It is a fluid with low co-efficient of friction thus permitting clutch plates to engage slowly and gradually as the transmission shifts.
- Compatible with seal materials used in transmission systems

Characteristics :	TQ
K. Viscosity, cSt@ 100˚C	7-8
Viscosity Index, min.	158
Pour Point, ˚C, max.	-10
Flash Point COC, ˚C min.	180

Pack Size (Ltrs.) : 500ml, 1L, 5L, 20L, 50L, 210L.

COOLEX COOLANT 1:4

Finolube Coolex Coolant is India's No.1 Biodegradable Coolant. It is an engine coolant with Ethylene Glycol base for use in radiators which provides efficient protection down to -36˚C during winter condition. This radiator coolant is made from synthetic base and is blended with selective Anti-Corrosion package. It meets ASTM-D 1384/2570 performance.

Performance Standard :

- ASTM –D1384/2570
- JISK -2234

Key Features & Benefits :

- Prevent winter freezing and summer overheating over a 2 years
- High boiling point & low freezing point, Easy miscibility with water & Effective cooling
- Protects radiator against rust & corrosion.
- Directions For Use
- To prepare coolant, dilute 1 part of Long Life 1 : 4 with 4 parts of distilled water

Pack Size : 1L, 3L, 5L, 20L, 210L.

PUMP SET OIL

Pumpset oil is Monograde engine oil specially formulated to meet the lubrication requirements of Diesel Engine fitted on Power tillers and Agricultural pump sets.

Performance Standards :

Pumpset Oil is recommended for lubrication of diesel engines fitted on all kinds of Agricultural pump sets and power tillers. The carefully selected additives ensure protection of engine components even during continuous and rough use.

Key Features and Benefits :

- Reduces Oil Thickening
- Less wear and tear and improved overall performance.
- It is recommended for all types of diesel pump sets particularly where they work under continuous operations over prolonged intervals of time.

Applications : Agricultural Pump Sets : Its selected additive technology allows running on virtually all types of engines in stationary applications. Power Tillers is ideally suited for the stop-start service found in power tillers and protects against bearing wear and deposit formation even under these severe conditions

FINOLUBE GREASES

FINOLUBE Greases are fulfilled with premium quality lithium soap based all purpose grease fortified with mild EP additives. It is specially formulated to enhance re-lubrication interval, up to 45,000 kms under ideal road condition, provides a cost effective lubrication film between moving surfaces for extended intervals and are easily pumped through hand pump or centralized greasing systems. It's good thermal, chemical and structural stability including water wash out properties, provides excellent lubrication and protection to the bearing parts over a wide temperature & pressure range under normal as well as adverse mechanical conditions.

Performance Standards : • IS 7623 - 1993 • NLGI - 3 Specification

Vintage AP-3

- Lower starting torque
- Wide opening temperature rate
- Excellent water resistance
- Protection against rusting and corrosion
- Oxidation inhibitors extend the life of the grease in high temperature applications minimizing the need for re-greasing.

Access AP- 3

- Wide operating temperature range
- Oxidation inhibitors extend the life of the in high temperature applications minimizing the need for re-greasing.
- It can be dispensed at low temperatures and will maintain adequate stay put property stability. at the higher temperatures encountered in service.

Long Life Jelly 70000

- Lasts four times longer than regular grease
- The ultimate grease for high speed bearings
- Highly reliable equipment protection, even in hostile environments, with less unanticipated downtime.
- Excellent high temperature oil bleed control

Pack Size : 500 Grm , 1Kg , 2 Kg, 3 Kg , 5 kg, 18 kg & 180 kg. M.S barrel.

Other Specialitiy products includes

- Chain Lube Spray 150ml
- Gear EP 220 (GL-5)
- Gear EP 320 GL-5
- Transformer Oil
- Transmission Oil
- Compresser Fluid 8K Oil
- EPL:2 special Crusher Grease, PD2, EP2, Chassis & other Speciality High Temp Grease