

Sales Analysis Using SQL



2015 Business Performance Snapshot



Total Revenue: \$817,860

Total Orders: 21,350

Total Pizzas Sold: 49,574

Top Revenue Gen: Thai Chicken Pizza (\$43,434)

SQL Query Showcase

[Home](#)[About](#)[Contact](#)

```
1 • CREATE DATABASE PIZZA;
2
3 • CREATE TABLE Orders(
4     Order_ID INT NOT NULL,
5     Order_Date DATE NOT NULL,
6     Order_Time TIME,
7     PRIMARY KEY(Order_ID));
8
9 • SELECT * FROM Orders;
10
11 • CREATE TABLE Orders_Details(
12     Order_Details_ID INT NOT NULL,
13     Order_ID INT NOT NULL,
14     Pizza_ID Text NOT NULL,
15     Quantity INT NOT NULL,
16     PRIMARY KEY(Order_Details_ID));
17
18 • SELECT * FROM Orders_Details;
```

SQL Query - 1

[Home](#)[About](#)[Contact](#)

```
1  -- Retrieve the total number of orders placed.  
2  
3  •  SELECT  
4      COUNT(Order_ID) AS Total_Orders  
5  FROM  
6      Orders;
```

Result Grid



Filter Rows:

Export:



Wrap Cell Content:



	Total_Orders
▶	21350

SQL Query - 2

[Home](#)[About](#)[Contact](#)

```
1  -- Calculate the total revenue generated from pizza sales.
2
3  •  SELECT
4      ROUND(SUM(pizzas.price * orders_details.Quantity),
5             2) AS Total_Revenue
6  FROM
7      pizzas
8      JOIN
9      orders_details
10     ON pizzas.pizza_id = orders_details.Pizza_ID;
```

Result Grid



Filter Rows:

Export:



Wrap Cell Content:



	Total_Revenue
▶	817860.05

SQL Query - 3

[Home](#)[About](#)[Contact](#)

```
1  -- Identify the highest-priced pizza.
2
3  •  SELECT
4      pizza_types.name, pizzas.price
5  FROM
6      pizza_types
7      JOIN
8      pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
9  ORDER BY price DESC
10 LIMIT 1;
```

Result Grid



Filter Rows:

Export:



Wrap Cell Content:



Fetch rows:



	name	price
▶	The Greek Pizza	35.95



SQL Query - 4

[Home](#)[About](#)[Contact](#)

```
1  -- Identify the most common pizza size ordered.
2
3  •  SELECT
4      pizzas.size,
5      COUNT(orders_details.Order_Details_ID) AS Order_Count
6  FROM
7      pizzas
8      JOIN
9      orders_details ON pizzas.pizza_id = orders_details.Pizza_ID
10 GROUP BY pizzas.size
11 ORDER BY ORDER_COUNT DESC;
```

Result Grid			Filter Rows:	Export:	Wrap Cell Content:
	size	Order_Count			
▶	L	18526			
	M	15385			
	S	14137			
	XL	544			
	XXL	28			

SQL Query - 5

[Home](#)[About](#)[Contact](#)

```
1  -- List the top 5 most ordered pizza types along with their quantities.
2
3  •  SELECT
4      pizza_types.name, SUM(orders_details.Quantity) AS Total
5  FROM
6      pizza_types
7      JOIN
8      pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
9      JOIN
10     orders_details ON orders_details.Pizza_ID = pizzas.pizza_id
11  GROUP BY pizza_types.name
12  ORDER BY Total DESC
13  LIMIT 5;
```

Result Grid			Filter Rows:	Export: 	Wrap Cell Content: 	Fetch rows: 
	name	Total				
▶	The Classic Deluxe Pizza	2453				
	The Barbecue Chicken Pizza	2432				
	The Hawaiian Pizza	2422				
	The Pepperoni Pizza	2418				
	The Thai Chicken Pizza	2371				

SQL Query - 6

[Home](#)[About](#)[Contact](#)

```
1  -- Join the necessary tables to find the total quantity of each pizza category ordered.
2
3  • SELECT
4      pizza_types.category,
5      SUM(orders_details.Quantity) AS Total_Quantity
6  FROM
7      pizza_types
8      JOIN
9      pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
10     JOIN
11     orders_details ON orders_details.Pizza_ID = pizzas.pizza_id
12 GROUP BY pizza_types.category
13 ORDER BY Total_Quantity DESC;
```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
	category	Total_Quantity	
▶	Classic	14888	
	Supreme	11987	
	Veggie	11649	
	Chicken	11050	

SQL Query - 7

[Home](#)[About](#)[Contact](#)

```
1  -- Determine the distribution of orders by hour of the day.
2
3  •  SELECT
4      HOUR(Order_Time) AS Hour_Of_Day,
5      COUNT(Order_ID) AS No_Of_Order
6  FROM
7      orders
8  GROUP BY Hour_Of_Day
9  ORDER BY Hour_Of_Day;
```

Result Grid |  Filter Rows: | Export:  | Wrap Cell Content: 

	Hour_Of_Day	No_Of_Order
▶	9	1
	10	8
	11	1231
	12	2520
	13	2455
	14	1472
	15	1468
	16	1920
	17	2336
	18	2222

Result 6 x

SQL Query - 8

[Home](#)[About](#)[Contact](#)

```
1  -- Join relevant tables to find the category-wise distribution of pizzas.
2
3  • SELECT
4      category, COUNT(name) As Total_Type
5  FROM
6      pizza_types
7  GROUP BY category;
```

Result Grid |   Filter Rows: | Export:  | Wrap Cell Content: 

	category	Total_Type
▶	Chicken	6
	Classic	8
	Supreme	9
	Veggie	9

SQL Query - 9

[Home](#)[About](#)[Contact](#)

```
1  -- Group the orders by date and calculate the average number of pizzas ordered per day.
2
3  •  SELECT
4      ROUND(AVG(Total_Pizza_Orders), 0) AS AVG_Pizza_Order_Per_Day
5  FROM
6      (SELECT
7          orders.Order_Date,
8          SUM(orders_details.Quantity) AS Total_Pizza_Orders
9      FROM
10         orders
11      JOIN orders_details ON orders.Order_ID = orders_details.Order_ID
12      GROUP BY Order_Date) AS Order_Quantity;
```

Result Grid



Filter Rows:

Export:



Wrap Cell Content: ☐

	AVG_Pizza_Order_Per_Day
--	-------------------------

▶	138
---	-----

SQL Query - 10

[Home](#)[About](#)[Contact](#)

```
1  -- Determine the top 3 most ordered pizza types based on revenue.
2
3  •  SELECT
4      pizza_types.name,
5      ROUND(SUM(orders_details.Quantity * pizzas.price),0) AS Total_Revenue
6  FROM
7      pizza_types
8      JOIN
9      pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
10     JOIN
11     orders_details ON orders_details.Pizza_ID = pizzas.pizza_id
12 GROUP BY pizza_types.name
13 ORDER BY Total_Revenue DESC
14 LIMIT 3;
```

Result GridFilter Rows:

Export:

Wrap Cell Content:

Fetch rows:

	name	Total_Revenue
▶	The Thai Chicken Pizza	43434
	The Barbecue Chicken Pizza	42768
	The California Chicken Pizza	41410

SQL Query - 11

[Home](#)[About](#)[Contact](#)

```
1  -- Calculate the percentage contribution of each pizza category type to total revenue.
2  ●  SELECT
3      pizza_types.category,
4      ROUND((SUM(orders_details.quantity * pizzas.price) /
5      (SELECT
6          SUM(orders_details.quantity * pizzas.price)
7      FROM
8          orders_details
9      JOIN
10         pizzas ON pizzas.pizza_id = orders_details.pizza_id)) * 100, 2) AS Total_Percentage
11  FROM
12      pizza_types
13  JOIN
14      pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
15  JOIN
16      orders_details ON orders_details.pizza_id = pizzas.pizza_id
17  GROUP BY pizza_types.category
18  ORDER BY total_percentage DESC;
```

Result GridFilter Rows:

Export:

Wrap Cell Content: ☐

	category	Total_Percentage
▶	Classic	26.91
	Supreme	25.46
	Chicken	23.96
	Veggie	23.68

SQL Query - 12

[Home](#)[About](#)[Contact](#)

```
1  -- Analyze the cumulative revenue generated over time.
2
3  SELECT Order_Date,
4  ROUND(SUM(Revenue) OVER (ORDER BY Order_Date),2) AS Cum_Revenue
5  FROM
6  (SELECT orders.Order_Date,
7   SUM(orders_details.Quantity * pizzas.price) AS Revenue
8   FROM orders JOIN orders_details
9   ON orders.Order_ID = orders_details.Order_ID
10  JOIN pizzas
11  ON pizzas.pizza_id = orders_details.Pizza_ID
12  GROUP BY orders.Order_Date) AS Sales;
```

Result Grid			Filter Rows:	Export:	Wrap Cell Content:
	Order_Date	Cum_Revenue			
▶	2015-01-01	2713.85			
	2015-01-02	5445.75			
	2015-01-03	8108.15			
	2015-01-04	9863.6			
	2015-01-05	11929.55			



THANK YOU

