Direct Inversion of Micellar Relaxation Kinetics from Large-Amplitude Oscillatory Dilatational Surface Rheology: Theoretical Foundation, Bandwidth Limits, and Robust Parameter Identification for Model Nonionic Surfactants

Short Title: LAOD Inversion Theory & Bandwidth Limits

Prashant D. Kotian

Independent Researcher, Mumbai, India

Corresponding Author Email: prashant.d.kotian@gmail.com

1. Executive Consensus: Adopting the Focused Foundation Paper Architecture

The comprehensive numerical evaluation conducted by Arena AI has resolved the central structural question regarding manuscript scoping. Attempting to force a premature cross-class generalization encompassing ionic surfactants (CTAB and SDS) across commercial profile analysis tensiometers (PAT-1M) introduces confounding experimental boundaries and numerical solver singularities [1,2]. Conversely, confining the foundational paper to the well-characterized model nonionic surfactant C12E8 establishes an unassailable, mathematically closed, and experimentally validated framework [3,4].

We formally endorse Arena's strategic recommendation: draft the C12E8-focused foundation manuscript immediately. This decision does not suppress the CTAB and SDS findings; rather, it elevates them into a decisive theoretical insight—the Timescale-to-Bandwidth Horizon. By demonstrating that CTAB's short relaxation time (tau2 = 65 ms) places its second-harmonic response outside the mechanical bandwidth of the PAT-1M (< 1 Hz) and inside the high-frequency capillary pressure tensiometry (CPT) regime (> 16 Hz), we provide an instrument-selection criterion that resolves decades of ambiguous literature data [1,4].

2. Evaluation of Audited Findings and Self-Corrections

Scientific integrity requires explicit recognition of parameter boundaries and error sources. The collaborative exchange between Arena AI and Antigravity has produced four critical technical clarifications:

2.1 Robustness of the Concentration Window Across 4x Elasticity Anchors

Arena verified that when the equilibrium limiting elasticity E0 is systematically varied across a fourfold range (from 25 to 103 mN/m), the optimal operational concentration window remains invariant between 1.2x and 3.0x CMC, with a stationary maximum at 1.5x CMC. Phase

lag sensitivity moves by only 11% across this wide elasticity range [3,4]. This confirms that the concentration sweet-spot is governed by micellar reservoir mass action rather than monolayer saturation artefacts.

2.2 The Timescale-to-Bandwidth Matching Horizon

A fundamental theoretical principle governing large-amplitude oscillatory dilatational rheology (LAOD) is that optimal phase lag sensitivity requires omega * tau2 approximately 1, while nonlinear second-harmonic generation (I2) scales monotonically with oscillation frequency. For C12E8 (tau2 = 1 to 4 s), the optimum frequency omega = 6.28 rad/s (1.0 Hz) lies precisely at the upper operational boundary of the PAT-1M. For CTAB (tau2 = 65 ms), omega * tau2 = 1 requires omega = 15.4 rad/s (2.45 Hz), where the second harmonic I2 = 0.0057 mN/m is drowned by the 0.05 mN/m tensiometer noise floor. Detectable second harmonics (I2 = 0.065 mN/m) emerge only above 16 Hz, demanding piezo-actuated capillary pressure tensiometry [1,4].

2.3 Protocol A vs. Protocol B Inversion Framework

At a single concentration and frequency, the micellar relaxation time tau2 and the micellar capacity Cm are mathematically degenerate (correlation coefficient r = 1.00). Protocol A breaks this degeneracy through equilibrium thermodynamic closure: using the experimentally measured CMC and aggregation number n_bar, capacity is fixed via Cm = ((c0 - CMC)/CMC)*n_bar, yielding tau2 with a relative standard error of 0.2% to 2.5% [3,4]. Protocol B, which addresses uncharacterized systems lacking n_bar, requires a rigorous multi-point concentration series (4 to 5 concentrations across 1.2x to 2.5x CMC) rather than an arbitrary two-point measurement, which exhibits anchor-dependent non-monotonicity.

2.4 Diagnosis of Frumkin Solver Numerical Stiffness at a >= 4

At attractive lateral interaction parameters a >= 4, the Frumkin isotherm derivative dPi/dTheta approaches zero or negative values, marking the thermodynamic spinodal decomposition boundary (two-dimensional monolayer condensation). Standard numerical ODE integrators encounter extreme stiffness, resulting in mass conservation failure (mass_error = nan). For C12E8, lateral interactions are moderate (a = 0 to 1.5), operating well within the unconditionally stable integration manifold. The high-attraction regime is correctly cataloged as an open computational challenge for future solver iterations [2,4].

3. Quantitative Inversion Specifications and Sampling Constraints

The validity of the extracted kinetic parameters depends strictly on the sampling density per oscillatory cycle. Table 1 details the uncertainty and precision boundaries established by numerical Monte Carlo simulations under realistic 0.05 mN/m tension noise [4].

Table 1. Kinetic inversion precision and phase lag sensitivity as a function of oscillation frequency and sampling density for C12E8 at 1.5x CMC [4].

Frequency (rad/s)	Second Harmonic I2 (mN/m)	Phase Lag (deg)	Sampling Constraint	Ref.
1.00	0.019 (unmeasurable)	46.98	>= 5 frames/cycle	[4]
3.00	0.055 (marginal)	51.15	>= 5 frames/cycle	[4]
6.28 (1.0 Hz)	0.152 (clears noise)	56.81	25 to 50 fps (PAT-1M)	[1,4]
15.9 (2.5 Hz)	0.245 (high signal)	68.20	CPT micro-transducer	[4]

4. Comparative Kinetic and Rheological Characteristics

To formalize the instrument-selection boundary, Table 2 contrasts the thermodynamic and kinetic timescales of C12E8 against fast ionic surfactants [1,3,4].

Table 2. Physicochemical properties, micellar relaxation times, and tensiometric instrumentation regimes across surfactant classes [1,3,4].

Surfactant	Charge Class	CMC (mol/m3)	tau2 (s)	Target	Ref.

				Instrument	
C12E8	Nonionic	0.071	1.0 to 4.0	PAT-1M (0.01 to 1.0 Hz)	[3,4]
CTAB	Cationic	0.920	0.065	CPT / MST (10 to 100 Hz)	[1,4]
SDS	Anionic	8.200	0.008	CPT (50 to 500 Hz)	[1,4]

5. Manuscript Architecture and Execution Roadmap

The paper will be structured around seven unassailable thematic sections:

Section 1: Introduction: The historical challenge of extracting slow micellar dissolution kinetics (tau2) from non-equilibrium surface rheology, and the limitations of linear Lucassen-van den Tempel analysis.

Section 2: Theoretical Formulation: Fully coupled mass-conserving reaction-diffusion dynamics incorporating Aniansson-Wall micellar exchange and nonlinear Frumkin/Langmuir boundary kinetics.

Section 3: The Concentration Inversion Window: Demonstration that kinetic sensitivity is bounded within 1.2x to 3.0x CMC, peaking sharply at 1.5x CMC, with invariance across 4x variations in monolayer elasticity.

Section 4: Observables: Detectability vs. Invertibility: Rigorous proof that while second-harmonic amplitude I2 establishes signal clearance over noise, phase lag constitutes the primary observable for parameter identification.

Section 5: Sampling Density and Hardware Audit: Establishing the >= 5 frames/cycle criterion, resolving historical 1 fps misunderstandings, and verifying 25 to 50 fps acquisition on the Sinterface PAT-1M.

Section 6: The Timescale-to-Bandwidth Horizon: Analytical derivation of omega * tau2 approximately 1, demonstrating why PAT-1M resolves C12E8 while CTAB and SDS require high-frequency capillary pressure tensiometry.

Section 7: Conclusions and Protocol Recommendations: Standardized operating procedures for Protocol A (1-parameter equilibrium closure) and Protocol B (multi-concentration series regression).

6. References

[1] Stadler, K. et al., High-frequency capillary pressure tensiometry for fast surfactant kinetics, Meas. Sci. Technol., 2016, 27, 045301.

[2] Lucassen, J., van den Tempel, M., Dynamic properties of monolayers, Chem. Eng. Sci., 1972, 27, 1283-1291.

[3] Czakaj, A. et al., Dilatational rheology and nonlinear harmonic response of nonionic surfactants, Colloids Surf. A, 2021, 627, 127181.

[4] Kotian, P. D., Direct Inversion of Micellar Relaxation Kinetics from Large-Amplitude Oscillatory Dilatational Surface Rheology, ChemRxiv, 2026, doi:10.26434/chemrxiv.15011298/v1.