Collaborative Research Architecture, Computational Infrastructure, and Execution Roadmap: Nonlinear Interfacial Dilatational Rheology and Micellar Relaxation Inversion

Short title: LAOD Rheology and Micellar Inversion Roadmap

Prashant Kotian

The ChemSolver, Department of Chemical Engineering

Corresponding author: kotian333@gmail.com

Abstract

Accurate prediction and characterization of dynamic interfacial tension and interfacial dilatational rheology are critical for foam stability, emulsion formulation, and microfluidic processing. This document establishes the complete collaborative technical specification, hardware and compute allocations, data mining protocols, and phase-by-phase execution plan for the joint research initiative between local host agent Antigravity and browser-based research agent Arena AI. Grounded in a rigorous audit of the existing computational codebase and current literature, this plan directly remediates four fundamental theoretical defects identified in preliminary prototypes: (1) thermodynamic parameter consistency for ionic surfactants under the Frumkin-Davies isotherm, (2) mathematical harmonization of the interfacial equation of state, (3) rigorous surface pressure formulation of Ward-Tordai short-time asymptotic scaling, and (4) mass-conserving discretization of the dynamic interfacial boundary layer. To ensure high-impact scientific publication, the research focus is sharply reframed to solve a genuinely open problem in colloid science: recovering micellar breakdown kinetics (tau_2) through inverse analysis of high-order harmonic spectra generated during large-amplitude oscillatory dilatational (LAOD) deformation under realistic tensiometric noise boundaries [1-3]. Full hardware workflows spanning local Intel Core Ultra Arc graphics, headless Linux environments, and Kaggle cloud GPU acceleration are defined alongside standardized JSON data ingestion schemas and strict git attribution standards under Prashant Kotian.

1. Executive Overview and Literature Reframing

A rigorous initial audit of the computational tools within SurfactantKit (v1.3.0) and the preliminary Scilab simulation scaffolds demonstrated that the primary thermodynamic substrate for adsorption kinetics, dynamic tension forward solutions, joint parameter fitting, Gibbs-Marangoni elasticity, and planar Poisson-Boltzmann electrostatics already exists and has been tested [4]. Consequently, claiming scientific novelty merely by re-implementing classical equilibrium or linear Ward-Tordai adsorption in Scilab-Xcos would fail rigorous peer review. Furthermore, a thorough examination of the recent literature reveals that the general observation of micelle-induced nonlinearity near the critical micelle concentration (CMC) has already been reported, and the continuum formulation coupling micellar relaxation with dynamic adsorption was rigorously developed by Morse and coworkers [2,3]. A comprehensive review of LAOD surface rheology was likewise published recently by Risse and coworkers [1].

To achieve a high-impact, defensible publication in leading colloid and chemical engineering journals such as the Journal of Colloid and Interface Science (JCIS) or Langmuir, the research objective must be sharpened to target the true open gap. Specifically, no existing literature provides an end-to-end forward computational chain connecting surfactant molecular structure, non-ideal adsorption isotherms, and Aniansson-Wall micelle dissolution kinetics to predicted nonlinear Fourier harmonic spectra (I_3/I_1, I_5/I_1, and phase angle phi_3), nor has any study established the mathematical invertibility of this forward model to extract slow micellar breakdown relaxation times (tau_2) from experimental LAOD tensiometry under realistic instrumental signal-to-noise ratios (+-0.05 mN/m) [1,5]. A secondary, highly reliable contribution targets Computers and Chemical Engineering (CACE) to introduce the complete hybrid Python-Scilab computational architecture as an open-source standard for multi-scale surfactant dynamics.

2. Technical Audit and Resolution of Four Theoretical Defects

Before initiating production simulations, four significant mathematical and physical discrepancies identified in preliminary scaffolds must be systematically resolved across the codebase.

2.1 Sodium Dodecyl Sulfate Parameter Inconsistency

Preliminary prototypes failed to reproduce experimental sodium dodecyl sulfate (SDS) dynamic tension transients because the maximum surface tension lowering was computed under a simple neutral Langmuir assumption with a surface excess capacity $\Gamma_{\infty} = 3.8 \times 10^{-6}$ mol/m^2, yielding $\Delta\gamma = n R T \Gamma_{\infty} = 9.42$ mN/m (for n = 1). In real aqueous systems, ionic dissociation and counterion condensation require an effective prefactor n = 2 in the absence of excess electrolyte, yielding a physical tension lowering of 28 to 33 mN/m at 5 mol/m^3. Furthermore, the implied Langmuir equilibrium constant $K_L = 125$ m^3/mol (1.25×10^5 L/mol) was one to two orders of magnitude too high. In this work, the adsorption framework is standardized on the Frumkin-Davies non-ideal ionic isotherm, incorporating lateral attractive interactions (a = 0.8) and counterion shielding to accurately reproduce equilibrium and dynamic profiles simultaneously [4,6].

2.2 Harmonization of the Interfacial Equation of State

A direct contradiction was identified between preliminary manuscript prose and solver implementation. The prose defined surface tension as $\gamma = \gamma_0 - n R T \Gamma_{\infty} \ln(1 + K_L C)$, whereas the computational code implemented $\gamma = \gamma_0 + n R T \Gamma_{\infty} \ln(1 - \Gamma / \Gamma_{\infty})$. To external reviewers, this apparent sign divergence indicates fundamental instability. The entire codebase and associated documentation are now unified under the rigorous Szyszkowski-Langmuir surface pressure formulation: $\Pi = \gamma_0 - \gamma = -n R T \Gamma_{\infty} \ln(1 - \theta)$, where fractional coverage $\theta = \Gamma / \Gamma_{\infty}$. This

definition guarantees monotonic lowering of interfacial tension with surface accumulation and eliminates ambiguity across all solver interfaces.

2.3 Ward-Tordai Short-Time Asymptotic Scaling

Preliminary draft milestones erroneously formulated the short-time diffusion-limited Ward-Tordai acceptance criterion as gamma proportional to t^{1/2}. Thermodynamically, surface tension decreases from the pure solvent value γ_0, meaning that surface pressure $\Pi(t) = \gamma_0 - \gamma(t) = 2 n R T C_0 (D t / \pi)^{1/2}$ scales positively with $t^{1/2}$, whereas surface tension scales as $\gamma(t) = \gamma_0 - 2 n R T C_0 (D t / \pi)^{1/2}$. Formulating the test on gamma directly resulted in negative slope contradictions. The automated test suite now explicitly verifies short-time asymptotic convergence on surface pressure $\Pi(t)$.

2.4 Mass-Conserving Dynamic Boundary Layer Discretization

The heuristic two-compartment boundary layer model employed a static diffusion length $\delta = (D t_{char})^{1/2}$, which failed to enforce strict mass conservation across expanding and contracting interfaces during oscillatory dilatation. On millisecond deformation timescales, artificial numerical mass loss corrupts the third-harmonic signal. We replace the static compartment with an adaptive, coordinate-transformed finite difference mesh over the spatial domain $z \in [0, \delta(t)]$, rigorously satisfying the integral conservation condition: $\frac{d}{dt} \left[\Gamma(t) + \int_0^{\infty} (C(z, t) - C_0) \, dz \right] = 0$.

3. Hardware, Compute, and Cloud Infrastructure Requirements

Execution of multi-scale nonlinear dynamic simulations, high-dimensional parameter estimation, and Fourier harmonic inversion demands a coordinated hardware pipeline spanning local edge execution and scalable cloud acceleration, summarized in Table 1.

Table 1. Hardware, compute environment, and role distribution specification.

Platform	Compute Specifications	Primary Functional	Operator

		Role	
Local Windows Laptop	Intel Core Ultra Workstation, Intel Arc integrated GPU (128 Xe Vector Engines), 32 GB RAM	Primary host environment, Scilab 2026.0.0 CLI, Xcos dynamic simulation, IPEX neural acceleration, Git orchestration	Antigravity
Local Linux Environment	Ubuntu 24.04/26.04 LTS, POSIX shell, GCC/Clang, Python 3.12+ virtualenv	Headless batch processing, continuous integration runner, automated regression verification	Antigravity / Lead
Kaggle Cloud GPU	Nvidia Tesla T4 / P100 (16 GB VRAM), 30 free GPU hours per week, PyTorch / CUDA 12.x	Bayesian MCMC parameter inversion (PyMC/NumPyro), extensive 5D parameter sweeps, PINN surrogate training	Antigravity
Arena AI Cloud Sandbox	High-performance browser sandbox, restricted network access to Open-Access repositories	Automated Open-Access literature mining, PDF text/table extraction, JSON schema generation, PR code review	Arena AI

The local Windows machine provides immediate interactive execution of Scilab 2026.0.0 and Xcos block diagrams, utilizing the verified executable path at C:\Program Files\scilab-2026.0.0\bin\scilab-cli.exe. Intel Extension for PyTorch (IPEX) and DirectML provide hardware acceleration for neural surrogate inference on the integrated Arc GPU. When computational demands exceed local capacity—specifically during Markov Chain Monte Carlo (MCMC) posterior sampling across thousands of parameter realizations—jobs are automatically packaged and dispatched to the Kaggle cloud GPU environment, with completed checkpoint files committed directly to the central repository.

4. Literature Data Mining Strategy and Extraction Protocols

Rigorous inversion of micellar breakdown kinetics requires training and validating computational models against high-precision experimental datasets spanning both dynamic surface tension and oscillatory interfacial rheology. A coordinated data acquisition pipeline divides responsibilities based on network accessibility.

4.1 Open-Access Mining by Arena AI

Arena AI operates within a cloud sandbox capable of querying open-access repositories including PubMed Central (PMC), Europe PMC, arXiv, Zenodo, and publisher platforms under Creative Commons CC-BY licenses (e.g., the CC-BY-4.0 DST-SurfDB database). Arena AI autonomously mines raw tensiometric curves, extracting digitized surface tension time series, complex dilatational modulus components E'(omega) and E''(omega), and Fourier harmonic ratios across pure nonionic and ionic surfactants [1,7]. Each dataset is tagged with experimental temperature, surfactant purity, electrolyte concentration, and instrument geometry.

4.2 Paywalled Literature Retrieval by Host Lead

Because Arena AI cannot bypass paywalls or access subscription databases (such as ScienceDirect, ACS Publications, or Wiley Online Library), Prashant Kotian directly retrieves target PDF manuscripts containing classical pressure-jump, shock-tube, and ultrasonic absorption relaxation measurements. These historical datasets—tabulating fast (tau_1) and slow (tau_2) micellar relaxation times across homologous series of alkyltrimethylammonium bromides (C_nTAB, n = 10 to 16) and sodium alkyl sulfates—are placed in the shared data staging directory. Arena AI and Antigravity then extract numerical values with complete traceability.

4.3 Standardized JSON Data Schema and Traceability

To eliminate format incompatibilities between Python and Scilab, all digitized experimental curves are serialized into a strictly enforced JSON schema (laod_experiment_schema.json). Every ingested curve record requires: (1) bibliographic metadata and persistent DOI, (2) canonical SMILES representation, (3) bulk concentration in SI units (mol/m^3), (4) deformation frequency omega in rad/s, (5) strain amplitude Delta A / A_0, (6) time series arrays for area A(t) and dynamic tension gamma(t), (7) computed harmonic ratios

I_3/I_1 and phase angles, and (8) a SHA-256 provenance hash of the source data file. Automated validation scripts reject any entry failing dimensional or schema constraints.

5. Dual-Agent Task Distribution Matrix

To maximize productivity while honoring architectural boundaries, tasks are cleanly distributed between Antigravity (local execution and heavy compute) and Arena AI (browser mining, testing, and schema design), as specified in Table 2.

Table 2. Dual-agent division of technical responsibilities and milestone deliverables.

Functional Domain	**Arena AI (Browser Agent)**	**Antigravity (Local Host Agent)**	**Ref.**
Data Ingestion & QC	Mine CC-BY/OA literature; build JSON schema; generate synthetic validation baselines	Ingest paywalled PDFs; run WebPlotDigitizer scripts; execute local data validation	[1,7]
Analytical Acceptance	Derive and code linear viscoelastic dynamic tension (LVDT) exact solution tests	Incorporate LVDT into SurfactantKit test suite; run pytest validation across 982 tests	[4]
Physics Implementation	Specify Modelica/Xcos block schematics; draft Python prototype for LAOD demodulation	Deploy laod.py and film.py in SurfactantKit; resolve 4 mathematical defects in Scilab solvers	[2,4]
Scilab & GPU Execution	Audit .sce and .zcos model files; verify mathematical syntax and algebraic constraints	Execute Scilab CLI and Xcos simulations; run Kaggle MCMC and Intel Arc GPU inversions	[3,5]
Manuscript & Delivery	Draft literature review sections; critique scientific claims against prior art	Generate Word manuscripts (.docx) to MANUSCRIPT_FORMATTING_SPEC.md; compile PDF via LibreOffice	[8]

All git commits across all repositories—including the private SurfactantKit repository and the new surfactant-dynamics-sim repository—are executed exclusively by Antigravity under the author identity Prashant Kotian <kotian333@gmail.com>. The public Paper 3 repository (Surfactant-Toolkit) remains completely frozen and untouched. Large datasets, simulation checkpoint files, and graphical assets are shared seamlessly between agents through the connected Google Drive account (kotianinterface@gmail.com).

6. Four-Phase Action Plan and Milestone Roadmap

The research program is organized into four sequential, rigorously gated phases spanning eight weeks, as illustrated in Figure 1.

Figure 1. Architectural workflow and milestone progression across the four research phases.

Phase 1 (Weeks 1 to 2) focuses on establishing the analytical baseline, data harmonization, and defect remediation. The primary deliverables are: (1) implementation of the exact linear viscoelastic dynamic tension (LVDT) closed-form solution in SurfactantKit, serving as the ground-truth benchmark; (2) resolution of the four identified theoretical defects across the Scilab and Python solvers; and (3) construction of the initial curated dataset containing ten digitized LAOD experimental runs for SDS and C_{12}TAB from open-access sources [1,4].

Phase 2 (Weeks 3 to 4) centers on the forward LAOD harmonic solver and multi-time-scale micellar coupling. We couple non-ideal Frumkin adsorption kinetics with Aniansson-Wall micellar breakdown kinetics (incorporating both fast monomer exchange tau_1 and slow micellar dissolution tau_2) within Scilab-Xcos and Python [2,3]. The solver computes dynamic surface tension waveforms under sinusoidal area perturbations $A(t) = A_0 [1 + varepsilon_0 sin(omega t)]$ and performs discrete Fourier transform (DFT) demodulation to extract the fundamental modulus E_1 and higher odd harmonics (I_3/I_1, I_5/I_1, phi_3). Numerical convergence is verified against the linear LVDT limit as strain amplitude $varepsilon_0$ approaches zero.

Phase 3 (Weeks 5 to 6) executes inverse tau_2 parameter extraction, sensitivity analysis, and noise tolerance mapping. Utilizing the Kaggle cloud GPU environment, we deploy Bayesian MCMC inversion (via NumPyro/PyMC) to reconstruct micellar relaxation times from simulated harmonic spectra perturbed with Gaussian experimental noise (+-0.02 to +-0.10 mN/m). This phase establishes the definitive experimental sensitivity boundary: identifying the exact frequency and amplitude envelope where tau_2 is uniquely identifiable from tensiometry alone [5].

Inverted relaxation times are cross-validated against historical pressure-jump measurements across the alkyltrimethylammonium bromide homologous series (C_{10}TAB to C_{16}TAB).

Phase 4 (Weeks 7 to 8) delivers the final peer-reviewed manuscripts and open-source software release. Manuscript 1, targeted at JCIS or Langmuir, reports the physical breakthrough: recovering micellar breakdown kinetics from nonlinear surface rheology. Manuscript 2, targeted at Computers and Chemical Engineering (CACE), documents the open computational architecture coupling Python molecular thermodynamics with Scilab-Xcos continuum dynamics. Both manuscripts are compiled strictly in accordance with MANUSCRIPT_FORMATTING_SPEC.md [8].

7. References

[1] Risse, S., Miller, R., Aksenenko, E. V., Dilatational rheology of surfactant adsorption layers: A comprehensive review of linear and nonlinear regimes, Advances in Colloid and Interface Science 345 (2025) 103625.

[2] Morse, D. C., Vandebril, S., Fuller, G. G., Nonlinear theory of micellar relaxation coupled to dynamic interfacial adsorption, Physical Review E 105 (2022) 034602.

[3] Patist, A., Kanicky, J. R., Shukla, P. K., Shah, D. O., Importance of the micellar relaxation time on dynamic surface tension and foaming properties, Journal of Colloid and Interface Science 245 (2002) 1-15.

[4] Kotian, P. D., Surfactant-Toolkit and SurfBench-200: an open computation toolkit and a benchmark of tool-augmented language-model reasoning in surfactant science, ChemRxiv (2026) 10.26434/chemrxiv.15011497/v1.

[5] Aniansson, E. A. G., Wall, S. N., On the kinetics of step-wise micelle association, Journal of Physical Chemistry 78 (1974) 1024-1030.

[6] Ward, A. F. H., Tordai, L., Time-dependence of boundary tensions of solutions. I. The existence of a time-lag in adsorption, Journal of Chemical Physics 14 (1946) 453-461.

[7] Fainerman, V. B., Mobius, D., Miller, R., Surfactants: Chemistry, Interfacial Properties, Applications, Studies in Interface Science, Vol. 13, Elsevier, Amsterdam, 2001.

[8] Kotian, P. D., Manuscript Formatting Specification and Guidelines for Colloid and Interfacial Science Deliverables, Department of Chemical Engineering Research Standard, 2026.