BLOG

Here you'll find everything you need to learn about digital software technology, development trends and beyond

INDUSTRIES

	н	۵	اد	+	h	_	2	r	_
	п	ч	a				а		~

- ☐ Financial Services
- ☐ Software Development
- ☐ Retail
- ☐ Energy, Oil & Gas
- Manufacturing
- ☐ Agriculture
- □ Other

SERVICES

- Security
- Data & Analytics
- ☐ IoT, XR, Robotics, AI & ML
- R&D
- Innovation Platform
- ☐ Quality Management



WE USE COOKIES TO ENSURE YOUR BEST EXPERIENCE. THROUGH YOUR CONTINUED USE OF THIS SITE YOU ACCEPT THIS USE. FOR MORE INFORMATION, PLEASE SEE OUR PRIVACY POLICY.

	soft serve		COVID-19 UPDATE	Q		=	
П	☐ AWS					£	
	☐ Google Cloud					T	
	☐ Salesforce					in	
						y	
	BY OLEKSANDR BERCHENKO OCT 29, 2016						
DATA & ANALYTICS SOFTWARE DEVELOPMENT							
HOW TO PROCESS SLOWLY CHANGING DIMENSIONS IN HIVE							
	5 MIN READ						


This article describes how to handle Slowly Changing Dimensions (SCD) in a data warehouse which uses Hive as a database.

Before reading on, you might want to refresh your knowledge of Slowly Changing Dimensions (SCD).

Let's imagine, we have a simple table in Hive:

```
CREATE TABLE dim user (
  login VARCHAR(255), -- natural key
  premium user BOOLEAN, -- SCD Type 2
  address VARCHAR(255), -- SCD Type 2
  phone VARCHAR(255), -- SCD Type 2, may be NULL
  name VARCHAR(255), -- SCD Type 1
  surname VARCHAR(255), -- SCD Type 1
  year of birth INT -- SCD Type 1, may be NULL
) STORED AS PARQUET;
```

Handling SCD Type 1 and SCD Type 2 may be trivial or at least well known in other



WE USE COOKIES TO ENSURE YOUR BEST **EXPERIENCE. THROUGH YOUR CONTINUED** USE OF THIS SITE YOU ACCEPT THIS USE. FOR MORE INFORMATION, PLEASE SEE OUR PRIVACY POLICY.

- 4. Anyway, UPDATE in ORC is too slow (update of each individual record requires its own MapReduce job).
- 5. There are only row level transactions (no BEGIN, COMMIT or ROLLB ACK statements).

Let's see how we can workaround all of them.

Suppose that "dim_user_production" is our existing table with current data. Its final schema (with surrogate keys and auxiliary fields) looks as follows:

```
CREATE TABLE dim_user_production (
dim_user_id INT, -- surrogate key
login VARCHAR(255), -- natural key
premium_user BOOLEAN, -- SCD Type 2
address VARCHAR(255), -- SCD Type 2
phone VARCHAR(255), -- SCD Type 2, may be NULL
name VARCHAR(255), -- SCD Type 1
surname VARCHAR(255), -- SCD Type 1
year_of_birth INT, -- SCD Type 1, may be NULL
scd_version INT, -- historical version of the record (1 is the oldest)
scd_start_date TIMESTAMP, -- start date and time
scd_end_date TIMESTAMP, -- end date and time (9999-12-31 23:59:59 by d
scd_active BOOLEAN, -- whether it's the latest version or not
) STORED AS PARQUET;
```

"dim_user_staging" is the table with new data to be processed. Its schema doesn't have surrogate keys or auxiliary fields and is identical to "dim_user" schema above.

1. Create a new table by copying the schema of the production table:

```
DROP TABLE IF EXISTS dim_user_new;
CREATE TABLE dim_user_new
STORED AS PARQUET
AS SELECT *
FROM dim_user_production
LIMIT 0;
```

2. Copy all the records from the production table that don't exist in the staging table: INSERT INTO TABLE dim_user_new



WE USE COOKIES TO ENSURE YOUR BEST EXPERIENCE. THROUGH YOUR CONTINUED USE OF THIS SITE YOU ACCEPT THIS USE. FOR MORE INFORMATION, PLEASE SEE OUR PRIVACY POLICY.

```
INSERT INTO TABLE dim user new
SELECT p .dim user id,
  p.login,
  p.premium user,
  p.address,
  p.phone,
  s.name,
  s.surname,
  s.year of birth,
  p.scd version,
  p.scd start date,
  p.scd_end_date,
  p.scd active
FROM dim user production p
JOIN dim_user_staging s
ON p.login = s.login
AND p.scd active = false;
```

4. Copy all the active records from the production table which don't have SCD Type 2 changes (apply SCD Type 1 changes if needed):

```
INSERT INTO TABLE dim user new
SELECT p.dim_user_id,
 p.login,
 p.premium user,
 p.address,
 p.phone,
  s.name.
  s.surname,
  s.year_of_birth,
 p.scd version,
 p.scd_start_date,
 p.scd_end_date,
  p.scd active
FROM dim_user_production p
JOIN dim_user_staging s
ON p.login = s.login
```



WE USE COOKIES TO ENSURE YOUR BEST EXPERIENCE. THROUGH YOUR CONTINUED USE OF THIS SITE YOU ACCEPT THIS USE. FOR MORE INFORMATION, PLEASE SEE OUR PRIVACY POLICY.

```
INSERT INTO TABLE dim user new
SELECT p.dim user id,
 p.login,
 p.premium user,
  p.address,
 p.phone,
  s.name,
  s.surname,
  s.year of birth,
 p.scd version,
 p.scd start date,
  '2016-10-01 00:00:00', -- current timestamp for scd end date
  false -- false for scd active
FROM dim user_production p
JOIN dim_user_staging s
ON p.login = s.login
AND p.scd active = true
WHERE p.premium user != s.premium user
OR p.address != s.address
```

6. Insert new active versions of records from the production table which have SCD Type 2 changes (apply SCD Type 1 changes if needed):

OR COALESCE(p.phone, '') != COALESCE(s.phone, '');

```
INSERT INTO TABLE dim_user_new
SELECT n.id + COALESCE(m.max_id, 0), -- new id for dim_user_id
    n.login,
    n.premium_user,
    n.address,
    n.phone,
    n.name,
    n.surname,
    n.sed_version,
    '2016-10-01 00:00:00', -- current timestamp for scd_start_date
    '9999-12-31 23:59:59', -- default timestamp for scd_end_date
    true -- true for scd_active
```



WE USE COOKIES TO ENSURE YOUR BEST EXPERIENCE. THROUGH YOUR CONTINUED USE OF THIS SITE YOU ACCEPT THIS USE. FOR MORE INFORMATION, PLEASE SEE OUR PRIVACY POLICY.

```
s.year of birth,
      p.scd version + 1 AS scd version
    FROM dim user production p
    JOIN dim user staging s
   ON p.login = s.login
   AND p.scd active = true
   WHERE p.premium user != s.premium user
    OR p.address != s.address
   OR COALESCE(p.phone, '') != COALESCE(s.phone, '')
 ) n,
  (
    SELECT MAX(dim user id) AS max id
   FROM dim user new
  ) m;
7. Copy all the records from the staging table which don't exist in the production table:
 INSERT INTO TABLE dim user new
 SELECT n.id + COALESCE(m.max id, 0), -- new id for dim user id
   n.login,
   n.premium user,
   n.address,
   n.phone,
   n.name,
    n.surname,
    n.year_of_birth,
    1, -- 1 for scd version
    '2016-10-01 00:00:00', -- current timestamp for scd_start_date
    '9999-12-31 23:59:59', -- default timestamp for scd end date
    true -- true for scd active
```



FROM (

s.login,

s.address,
s.phone,

s.premium user,

WE USE COOKIES TO ENSURE YOUR BEST EXPERIENCE. THROUGH YOUR CONTINUED USE OF THIS SITE YOU ACCEPT THIS USE. FOR MORE INFORMATION, PLEASE SEE OUR PRIVACY POLICY.

SELECT row number() OVER () AS id,

```
SELECT MAX(dim user id) AS max id
  FROM dim user new
) m;
```

8. Replace the content of the production table in a transactional mann er:

```
INSERT OVERWRITE TABLE dim user production
SELECT *
FROM dim user new;
```

Please take into account the way we handled fields of SCD Type 2 that may have NULL values (we don't need to compare fields of SCD Type 1):

```
COALESCE(p.phone, '') = COALESCE(s.phone, '')
COALESCE(p.phone, '') != COALESCE(s.phone, '')
```

Alternatively, you can use <=> operator (Hive 0.9.0 and higher):

```
p.phone <=> s.phone
NOT (p.phone <=> s.phone)
```

That's it. No magic here $\stackrel{\text{\tiny 60}}{=}$

CONTACTS

HOT LINKS

USA HQ

201 W 5th Street Suite 1550 Austin, TX 78701

+1-512-516-8880

Toll free: 866-687-3 **EUROPEAN HQ**

2D Sadova Street Lviv 79021

+380-32-240-9999

Toll free: 0-8006-0-8006 Home

Your Journey

Industries

Services

Resources

About Us

Blog

Contact

Certification

For Universities

Careers

University

Learning &

WE USE COOKIES TO ENSURE YOUR BEST **EXPERIENCE. THROUGH YOUR CONTINUED USE OF THIS SITE YOU ACCEPT THIS USE. FOR** MORE INFORMATION, PLEASE SEE OUR PRIVACY POLICY.

soft serve	COVID-19 UPDATE	Q	_



WE USE COOKIES TO ENSURE YOUR BEST EXPERIENCE. THROUGH YOUR CONTINUED USE OF THIS SITE YOU ACCEPT THIS USE. FOR MORE INFORMATION, PLEASE SEE OUR PRIVACY POLICY.