HelloPe

UPI API Integration

Technical Documentation
for Merchant Integration

LET'S INTEGRATE

KOLKATA, INDIA

www.hellope.co.in

Document Revision History

Version	Date	Version Description	Approving Authority
V1		Initial Draft	Product Manager

Disclaimer

This document is the intellectual property of HelloPe Financial Services Limited and should solely be used as a tool of knowledge exchange. We discourage any reproduction of the document under any circumstances.

All the values corresponding to all the fields in the document are dummy data. Any resemblance with any real-life data is purely coincidental. The data provided in the Request and Response Payloads are sample data. We encourage usage of own sample data for desired results.

UPI API Integration Document V1

1.1 Introduction

The purpose of this document is to outline the Staging Integration phase, which focuses on validating APIs related to transaction processing and transaction enquiry. This phase is intended to ensure that the complete transaction flow functions correctly, outcomes are accurately verified, and Webhook are properly handled before proceeding to production.

The following APIs are covered under this integration:

- Intent
- Dynamic QR
- Transaction Status Enquiry
- Webhook

These APIs enable the creation of payment requests, allow status checks on those transactions, and provide updates via Webhook.

1.2 Integration and Testing

A single round of integration testing will be conducted in the Staging environment. This testing is meant to validate the end-to-end transaction flow using the APIs mentioned above.

The testing should cover the following:

- Generation of Dynamic QR
- Initiation of transactions through the Intent API
- Checking the transaction status using the Status Enquiry API
- Receiving updates through the Webhook.
- Once this testing round is completed successfully and the APIs perform as expected, the system will be considered ready for production deployment.

1. (Token Request) API Authentication

API Tokens Obtaining

In order to perform any API call the access token must be obtained. To do this Merchant needs to send HTTP request to the API token endpoint. As a result Merchant will receive an ApiTokens JSON document containing a token pair and tokens lifetime values.

Note: The Production Base URL will be shared separately by the HelloPe team via email.

Request Format

- Production Base URL: <baseUrl>
- Endpoint: /api/v1/auth/token
- URL: <baseUrl>/api/v1/auth/token
- HTTP Method: POST
- Content-Type: application/json

Request Payload Parameter

API Name	Request Parameter	Response Parameter	Description
Api Token	merchantId	token	This API will be used for Generate a token
	accessKey	expiry	
	secretKey	result	
		resultMessage	

To find your accessKey and secretKey:

1. Log in to your Merchant Dashboard.
2. Select Settings from sidebar the dropdown menu.
3. Open the API Keys.
4. Click Show Credentials to view your.
5. Copy and store the keys securely.

Examples

Sample Curl Command

```
curl --location: Specified URL
--header 'Content-Type: application/json' \
--data '{
    "merchantId": "900000*****",
    "secretKey":
        "yb3IX0KIlFiuxKPRPzup1VBepNBSsZZN5lz8oAu2hmc",
    "accessKey": "sv8_eepeFwAhYDACBRQF-g"
}'
```

Response Example


```
{
    "token": "eyJhbGciOiJIUzM4NCJ9.
        eyJzdWIiOiI4MDAwMDAwMDAxIiwiYWNjZXNzS2V5IjoiRGNrazVja3VtY1RQOHZoc3JrVHlaZyIsInR5cG",
    "expiry": 3600,
    "result": true,
    "resultMessage": "Token generated successfully"
}
```

Authentication Errors

Descriptions for authentication or authorization related errors are listed here. They are classified by error name field.

Result	Result Message
true	Token Generated successfully
false	Invalid Merchant/Invalid Access Key or Secret Key

API Services Calling

Once tokens have been obtained, a required API service can be called. API uses Bearer authorization scheme, so to perform API call, an access token should be added to the Authorization header like:

Authorization: Bearer {token}

2. INTENT Request

Description

The Intent API provides an intent link that can be integrated within any merchant application to initiate a payment. When a customer chooses to pay using this method, they are redirected via the intent link to a supported payment app, where they can complete the transaction through a seamless and secure flow. The intent link is generated for a specific amount mentioned in the request to complete the payment.

Request Method: POST
URL: <baseUrl>/api/v1/collections/intent

Headers

Authorization: Bearer {token}

Request Body Parameters

Parameter	Description	Mandatory/Optional	Min Length	Max Length	Data Type
amount	Transaction amount for which the transaction is initiated/amount in Paisa	Mandatory	1	10	String
merchantId	Merchant ID	Mandatory	1	15	String
paymentPlatform	Payment Mode (INTENT)	Mandatory	2	10	String
meOrderNo	Unique Order No. needs to be generated by partner/Merchant for each new transaction	Mandatory	10	19	String
fullName	Full Name of customer	Optional	3	20	String
currency	INR	Mandatory	3	3	String
emailId	EmailId of customer	Optional	10	25	String
remark	Transaction Note	Mandatory	1	50	String
webhookUrl	Received callback URL	Mandatory	10	20	String
paymentType	UPI	Mandatory	3	3	String
mobileNo	Mobile Number of Customer	Mandatory	10	10	String

Sample Request Body

```
{
   "amount": "1000",
   "merchantId": "9000000**",
   "paymentPlatform": "INTENT",
   "meOrderNo": "ORD2026072403",
   "fullName": "John",
   "currency": "INR",
   "emailId": "Rohit@gmail.com",
   "remark": "HelloPe intent Test",
   "mobileNo": "9876543219",
   "webhookUrl": "http://localhost:8092/api/v0/collections/webhook",
   "paymentType": "UPI"
}
```

Response Body Parameters

Parameter	Description
qrData	UPI Intent Link
amount	Transaction amount for which transaction is initiated
payment_description	Payment Description
txn_ref_id	Unique Txn Ref Id Provided By HelloPe
meOrderNo	Unique Order No./ID needs to be generated by partner/Merchant for each new transaction
responseCode	Response Code to transaction
Status	Status of Transaction Initiation

Sample Response Body

SUCCESS


```
{
   "data": {
      "qrData": "upi://pay?pa=abc@icici&pn=Abc&tr=EZY123456789012&am=10.00&cu=INR&mc=5411",
      "amount": "10.00",
      "payment_description": "Payment initiated successfully",
      "txn_ref_id": "TXN260724471218241054703616"
   },
   "meOrderNo": "ORD2026072403",
   "responseCode": "P003",
   "status": "PENDING FOR AUTHORIZATION"
}
```

FAILED (amount is Invalid)


```
{
   "data": {
      "amount": "10",
      "message": "Invalid amount — minimum is 100 paisa (₹1.00)."
   },
   "meOrderNo": "ORD2026072415",
   "status": "FAILED",
   "responseCode": "F005"
}
```


NOTE: Any missing or invalid mandatory field will generate a Failed response.

Response Codes

Code	Status	Description
P003	PENDING FOR AUTHORIZATION	Intent String Generated Successfully
F005	FAILED	General Failed
F001	FAILED	General Failed

Note

- Generate and process the response only when the Response Code is P003.
- For all other response codes:
    - Treat the transaction as Pending or Failed (as applicable).
    - Do not consider the transaction successful.
    - Wait for the callback/webhook to receive the final transaction status.

3. Webhook API

Description

The Webhook API is used to receive real-time updates from the system whenever there is a status change in a transaction. Once configured, the system will automatically send callbacks with updated transaction data to the registered endpoint, eliminating the need for manual status checks.

Request Method: POST
URL: To be shared later.

HelloPe

THANK YOU

HelloPe Financial Services Pvt. Ltd.

www.hellope.co.in | info@hellope.co.in | support@hellope.co.in