

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

MySQL

INTRODUCTION

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

MySQL

CREATE A DATABASE USING PHP MYADMIN

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

MySQL

REMOTE MYSQL (1)

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

MySQL

REMOTE MYSQL (2)

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible"
content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>introduction</title>
```

```

        <link href="css/bootstrap.min.css"
rel="stylesheet">
        <style>
            h1{
                color:purple;
            }
            h3{
                color:#42d5ce;
            }
            .containingDiv{
                border:1px solid #7c73f6;
                margin-top: 100px;
                border-radius: 15px;
            }
        </style>

    </head>
    <body>
<div class="container-fluid">
    <div class="row">
        <div class="col-sm-offset-1 col-sm-10
containingDiv">
            <h1>Connect to database:</h1>
<?php
//mysqli_connect(host, username, password, dbname)
//$link = @mysqli_connect("mysql11.000webhost.com",
"a7099072_user", "Hellodevelopers1", "a7099072_db") or
die("ERROR: Unable to connect: " .
mysqli_connect_error());
//var_dump($link);
//
//
//echo "<p>Connected successfully to the database.</p>";

//connect
$link = new mysqli("mysql11.000webhost.com",
"a7099072_user", "Hellodevelopers1", "a7099072_db"); //
your host should be local if you are using my free web
hosting
//check connection

```

```
if($link->connect_errno > 0){
    die("Unable to connect: " . $link->connect_error);
}

echo "<p>Connected successfully to the database.</p>";
?>
    </div>
</div>
</div>
    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js"></script>
    <script src="js/bootstrap.min.js"></script>
</body>
</html>
```



CREATE A DATABASE USING PHP & MYSQL

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible"
content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>Create database</title>
    <link href="css/bootstrap.min.css"
rel="stylesheet">
    <style>
      h1{
        color:purple;
      }
      h3{
        color:#42d5ce;
      }
      .containingDiv{
        border:1px solid #7c73f6;
        margin-top: 100px;
        border-radius: 15px;
      }
    </style>
  </head>
```

```

        <body>
<div class="container-fluid">
    <div class="row">
        <div class="col-sm-offset-1 col-sm-10
containingDiv">
            <h1>Create database:</h1>
            <h3>Connect to server</h3>
<?php
//mysqli_connect(host, username, password, dbname)
$link = @mysqli_connect("mysql11.000webhost.com",
"a7099072_user", "Hellodevelopers1") or die("ERROR: Unable
to connect: " . mysqli_connect_error());
var_dump($link);

echo "<p>Connected successfully to the server.</p>";
?>
            <h3>Create a database</h3>
<?php
$sql = "CREATE DATABASE store";
if(mysqli_query($link, $sql)){
    echo "<p>Database store was created successfully</p>";
}else{
    echo "ERROR: Unable to execute $sql" .
mysqli_error($link);
}

?>
        </div>
    </div>
</div>
    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js"></script>
    <script src="js/bootstrap.min.js"></script>
</body>
</html>

```



ADD A TABLE TO A DATABASE

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible"
content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>Add a table to database</title>
    <link href="css/bootstrap.min.css"
rel="stylesheet">
    <style>
      h1{
        color:purple;
      }
      h3{
        color:#42d5ce;
      }
      .containingDiv{
        border:1px solid #7c73f6;
        margin-top: 100px;
        border-radius: 15px;
      }
    </style>
  </head>
```



```

        <body>
<div class="container-fluid">
    <div class="row">
        <div class="col-sm-offset-1 col-sm-10
containingDiv">
            <h1>Add a table to database:</h1>
            <h3>Connect to database</h3>

<?php
//mysqli_connect(host, username, password, dbname)
$link = @mysqli_connect("mysql11.000webhost.com",
"a7099072_user", "Hellodevelopers1", "a7099072_db") or
die("ERROR: Unable to connect: " .
mysqli_connect_error());

echo "<p>Connected successfully to the database.</p>";
?>

        <h3>Create table</h3>

<?php
$sql = "CREATE TABLE users(ID INT(4) NOT NULL PRIMARY KEY
AUTO_INCREMENT, firstname CHAR(20) NOT NULL, lastname
CHAR(20) NOT NULL, email VARCHAR(30), password
VARCHAR(40))";
if(mysqli_query($link, $sql)){
    echo "<p>Table users created successfully!</p>";
}else{
    echo "ERROR: Unable to execute $sql" .
mysql_error($link);
}
?>

        </div>
    </div>
</div>

    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js"></script>
    <script src="js/bootstrap.min.js"></script>
    </body>
</html>

```



POPULATE A DATABASE TABLE

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible"
content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>Populate table</title>
    <link href="css/bootstrap.min.css"
rel="stylesheet">
    <style>
      h1{
        color:purple;
      }
      h3{
        color:#42d5ce;
      }
      .containingDiv{
        border:1px solid #7c73f6;
        margin-top: 100px;
        border-radius: 15px;
      }
    </style>
  </head>
```

```

        <body>
<div class="container-fluid">
    <div class="row">
        <div class="col-sm-offset-1 col-sm-10
containingDiv">
            <h1>Add a table to database:</h1>
            <h3>Connect to database</h3>

<?php
//mysqli_connect(host, username, password, dbname)
$link = @mysqli_connect("mysql11.000webhost.com",
"a7099072_user", "Hellodevelopers1", "a7099072_db") or
die("ERROR: Unable to connect: " .
mysqli_connect_error());

echo "<p>Connected successfully to the database.</p>";
?>

        <h3>Populate table</h3>
<?php
$sql = "INSERT INTO users (firstname, lastname, email,
password) VALUES ('Mark', 'Zuckerberg',
'M.zuckerberg@gmail.com', 'password')";
if(mysqli_query($link, $sql)){
    echo "<p>New row added successfully!</p>";
}else{
    echo "ERROR: Unable to execute $sql" .
mysql_error($link);
}
?>

        </div>
    </div>
</div>

    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js"></script>
    <script src="js/bootstrap.min.js"></script>
    </body>
</html>

```



SEND DATA FROM AN HTML FORM TO A DATABASE APPLICATION: POPULATE A DATABASE TABLE ONCE THE USER SUBMITS A FORM

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible"
content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>Populate table using form</title>
    <link href="css/bootstrap.min.css"
rel="stylesheet">
    <style>
      h1{
        color:purple;
      }
      h3{
        color:#42d5ce;
      }
      .containingDiv{
        border:1px solid #7c73f6;
        margin-top: 100px;
        border-radius: 15px;
      }
    </style>
  </head>
```

```

        <body>
<div class="container-fluid">
    <div class="row">
        <div class="col-sm-offset-1 col-sm-10
containingDiv">
            <h1>Populate table using form:</h1>
            <h3>Connect to database:</h3>
<?php
//mysqli_connect(host, username, password, dbname)
$link = @mysqli_connect("mysql11.000webhost.com",
"a7099072_user", "Hellodevelopers1", "a7099072_db") or
die("ERROR: Unable to connect: " .
mysqli_connect_error());

echo "<p>Connected successfully to the database.</p>";
?>

        <h3>Send data to database:</h3>
<?php

//get user inputs
$id = $_POST["ID"];
$firstname = $_POST["firstname"];
$lastname = $_POST["lastname"];
$email = $_POST["email"];
$password = $_POST["password"];

//error messages
$missingFirstname = "<p><strong>Please enter your
firstname!</strong></p>";
$missingLastname = "<p><strong>Please enter your
lastname!</strong></p>";
$missingemail = "<p><strong>Please enter your
email!</strong></p>";
$invalidemail = "<p><strong>Please enter a valid email
address!</strong></p>";
$missingPassword = "<p><strong>Please enter a
password!</strong></p>";

if($_POST["submit"]){
    //check for errors
    if(!$firstname){

```

```

        $errors .= $missingFirstname;
    }else{
        $firstname = filter_var($firstname,
FILTER_SANITIZE_STRING);
    }
    if(!$lastname){
        $errors .= $missingLastname;
    }else{
        $lastname = filter_var($lastname,
FILTER_SANITIZE_STRING);
    }
    if(!$email){
        $errors .= $missingemail;
    }else{
        $email = filter_var($email,
FILTER_SANITIZE_EMAIL);
        if(!filter_var($email, FILTER_VALIDATE_EMAIL)){
            $errors .= $invalidemail;
        }
    }
    if(!$password){
        $errors .= $missingPassword;
    }

    if($errors){
        $resultMessage = '<div class="alert alert-
danger">' . $errors . '</div>';
        echo $resultMessage;
    }else{
        //no errors, prepare variables for the query
        $tblname = "users";
        $firstname = mysqli_real_escape_string($link,
$firstname);
        $lastname = mysqli_real_escape_string($link,
$lastname);
        $email = mysqli_real_escape_string($link, $email);
        $password = mysqli_real_escape_string($link,
$password);
        $password = md5($password);

        //execute insert query
        if(!$id){

```

```

        $sql = "INSERT INTO users (firstname,
lastname, email, password) VALUES ('$firstname',
'$lastname', '$email', '$password')";
    }else{
        $sql = "INSERT INTO users (ID, firstname,
lastname, email, password) VALUES ('$id', '$firstname',
'$lastname', '$email', '$password')";
    }
    if(mysqli_query($link, $sql)){
        $resultMessage = '<div class="alert alert-
success">Data added successfully to the database
table</div>';
        echo $resultMessage;
    }else{
        $resultMessage = '<div class="alert alert-
warning">ERROR: Unable to excecute: ' . $sql. ' ' .
mysqli_error($link). '</div>';
        echo $resultMessage;
    }
}
}
}

```

```

?>
        <form action="5.populatetableusingform.php"
method="post">
            <div class="form-group">
                <label for="ID">ID:</label>
                <input type="number" id="ID"
placeholder="ID" class="form-control" name="ID"
maxlength="4">
            </div>
            <div class="form-group">
                <label
for="firstname">Firstname:</label>
                <input type="text" id="firstname"
placeholder="Firstname" class="form-control"
name="firstname" maxlength="20">
            </div>
            <div class="form-group">
                <label
for="lastname">Lastname:</label>

```

```

        <input type="text" id="lastname"
placeholder="Lastname" class="form-control"
name="lastname" maxlength="20">
    </div>
    <div class="form-group">
        <label for="email">Email:</label>
        <input type="email" id="email"
placeholder="Email" class="form-control" name="email"
maxlength="30">
    </div>
    <div class="form-group">
        <label
for="password">Password:</label>
        <input type="password" id="password"
placeholder="Password" class="form-control"
name="password" maxlength="40">
    </div>
    <input type="submit" name="submit"
class="btn btn-success btn-lg" value="Send data">

    </form>

</div>
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js"></script>
    <script src="js/bootstrap.min.js"></script>
</body>
</html>

```




RETRIEVE DATA FROM A DATABASE APPLICATION: POPULATE AN HTML TABLE USING DATABASE DATA.

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible"
content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>Retrieve data</title>
    <link href="css/bootstrap.min.css"
rel="stylesheet">
    <style>
      h1{
        color:purple;
      }
      h3{
        color:#42d5ce;
      }
      .containingDiv{
        border:1px solid #7c73f6;
        margin-top: 100px;
        border-radius: 15px;
      }
    </style>
  </head>
```

```

        <body>
<div class="container-fluid">
    <div class="row">
        <div class="col-sm-offset-1 col-sm-10
containingDiv">
            <h1>Retrieve data from a table:</h1>
            <h3>Connect to database:</h3>

<?php
//mysqli_connect(host, username, password, dbname)
$link = @mysqli_connect("mysql11.000webhost.com",
"a7099072_user", "Hellodevelopers1", "a7099072_db") or
die("ERROR: Unable to connect: " .
mysqli_connect_error());

echo "<p>Connected successfully to the database.</p>";
?>

        <h3>Retrieve data from database:</h3>

<?php
$sql = "SELECT * FROM users";
//$sql = "SELECT * FROM users WHERE firstname = 'george'";
//$sql = "SELECT * FROM users ORDER BY lastname";
//$sql = "SELECT * FROM users ORDER BY lastname DESC";
if($result = mysqli_query($link, $sql)){
    print_r($result);
    if(mysqli_num_rows($result)>0){
        echo "<table class='table table-stripped table-
hover table-condensed table-bordered'>
            <tr>
            <th>ID</th>
            <th>firstname</th>
            <th>lastname</th>
            <th>email</th>
            <th>password</th>
            </tr>

            ";
//        $count = 0;
        while($row = mysqli_fetch_array($result,
MYSQLI_ASSOC)){
//            $count++;
//            echo "<p>Row number: $count</p>";
//            print_r($row);
            echo "<tr>";

```

```

        echo "<td>" . $row["ID"] . "</td>";
        echo "<td>" . $row["firstname"] . "</td>";
        echo "<td>" . $row["lastname"] . "</td>";
        echo "<td>" . $row["email"] . "</td>";
        echo "<td>" . $row["password"] . "</td>";
    echo "</tr>";

}
echo "</table>";
//close the result set
mysqli_free_result($result);
}else{
    echo "<p>mySQL returned an empty result set.</p>";
}
}else{
    echo "<p>Unable to excecute: $sql. " .
mysqli_error($link) . "</p>";
}
?>

</div>
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js"></script>
<script src="js/bootstrap.min.js"></script>
</body>
</html>

```

MySQL

UPDATE DATABASE DATA

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible"
content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>Update data</title>
    <link href="css/bootstrap.min.css"
rel="stylesheet">
    <style>
      h1{
        color:purple;
      }
      h3{
        color:#42d5ce;
      }
      .containingDiv{
        border:1px solid #7c73f6;
        margin-top: 100px;
        border-radius: 15px;
      }
    </style>
  </head>
```

```

        <body>
<div class="container-fluid">
    <div class="row">
        <div class="col-sm-offset-1 col-sm-10
containingDiv">
            <h1>Update data in a table:</h1>
            <h3>Connect to database:</h3>

<?php
//mysqli_connect(host, username, password, dbname)
$link = @mysqli_connect("mysql11.000webhost.com",
"a7099072_user", "Hellodevelopers1", "a7099072_db") or
die("ERROR: Unable to connect: " .
mysqli_connect_error());

echo "<p>Connected successfully to the database.</p>";
?>

        <h3>Update data:</h3>

<?php
$sql = "UPDATE users SET lastname='Wilson' WHERE
firstname='Peter' AND email='Taylor.ztest@gmail.com'";
if(mysqli_query($link,$sql)){
    echo "<p>Data was updated successfully!</p>";
}else{
    echo "<p>ERROR: Unable to execute $sql.".
mysqli_error($link) ." </p>";
}
?>

        </div>
    </div>
</div>

    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js"></script>
    <script src="js/bootstrap.min.js"></script>
</body>
</html>

```



DELETE DATABASE DATA

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible"
content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>Delete data</title>
    <link href="css/bootstrap.min.css"
rel="stylesheet">
    <style>
      h1{
        color:purple;
      }
      h3{
        color:#42d5ce;
      }
      .containingDiv{
        border:1px solid #7c73f6;
        margin-top: 100px;
        border-radius: 15px;
      }
    </style>
  </head>
```

```

        <body>
<div class="container-fluid">
    <div class="row">
        <div class="col-sm-offset-1 col-sm-10
containingDiv">
            <h1>Delete Data:</h1>
            <h3>Connect to database:</h3>

<?php
//mysqli_connect(host, username, password, dbname)
$link = @mysqli_connect("mysql11.000webhost.com",
"a7099072_user", "Hellodevelopers1", "a7099072_db") or
die("ERROR: Unable to connect: " .
mysqli_connect_error());

echo "<p>Connected successfully to the database.</p>";
?>

        <h3>Delete data:</h3>

<?php
$sql = "DELETE FROM users WHERE firstname='george'";
// $sql = "DROP users";
if(mysqli_query($link,$sql)){
    echo "<p>Data was deleted successfully!</p>";
}else{
    echo "<p>ERROR: Unable to execute $sql.".
mysqli_error($link) ." </p>";
}

//close connection
mysqli_close($link);
// $link->close($link);
?>

        </div>
    </div>
</div>

    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js"></script>
    <script src="js/bootstrap.min.js"></script>
    </body>
</html>

```

