BlockCert: A Decentralized, Privacy-Preserving Academic Credential Vault Featuring Authenticated Encryption and Deterministic Registry Recovery

Abstract The digital verification of academic credentials remains hindered by dual challenges: localized systemic failures in centralized databases and inherent privacy violations in nascent decentralized ledger solutions. While prior systems successfully utilized Ethereum and the InterPlanetary File System (IPFS) to prevent credential forgery, they dangerously exposed raw, unencrypted student data to public distributed networks. This paper presents **BlockCert**, an institutional-grade, zero-knowledge academic registry. By integrating a novel cryptographic middleware employing ChaCha20-Poly1305 Authenticated Encryption with Associated Data (AEAD) alongside ZLib compression, BlockCert ensures absolute data confidentiality before IPFS anchoring. Furthermore, we introduce the **Institutional Registry Vault**, a deterministic EIP-191 key-recovery architecture that eliminates the risk of permanently lost student credentials without centralizing decryption keys. Our performance evaluations indicate cryptographic processing times under 8 ms, a 58% reduction in IPFS storage footprints, and an optimized credential verification network latency of ~4.4 seconds. BlockCert definitively establishes that extreme data privacy and decentralized transparency are not mutually exclusive in modern educational record-keeping.

I. INTRODUCTION

1.1 Motivation

Credential fraud is a multi-billion dollar illicit industry with profound consequences for the global job market, regulatory compliance, and academic meritocracy. Traditional solutions rely heavily on centralized SQL databases operated by individual institutions or third-party clearinghouses. These systems present significant friction: they act as single points of failure, require recurring operational costs, suffer from bureaucratic latency, and are prominent targets for sophisticated cyber-attacks.

The advent of blockchain technology, specifically Turing-complete networks like Ethereum, has spurred the development of decentralized verifications systems. Frameworks such as *ElimuChain* have successfully utilized IPFS for distributed storage, mathematically anchoring the file contents to immutable ledgers.

1.2 The Privacy Gap and the Lost Key Dilemma

Despite their integrity guarantees, current generation systems suffer from two fatal architectural flaws:

1. **Public Data Exposure:** Archiving direct, unencrypted academic PDFs onto IPFS means that anyone with the unique Content Identifier (CID) can view a student's personally identifiable information (PII). This violates global privacy compliance frameworks, including the GDPR and FERPA.
2. **Key Permanence Failure:** Systems that mandate payload encryption traditionally yield the sole decryption key to the student. If the student loses their private key, the encrypted IPFS payload becomes forever unreadable, defeating the purpose of an immutable academic record.

This paper introduces BlockCert to directly solve both crises through specialized cryptographic and smart-contract workflows.

1.3 Research Contributions and Novelty

To bridge the critical gaps in decentralized academic registries, BlockCert introduces three major novelties to the blockchain literature:

1. **Zero-Knowledge Cryptographic Middleware:** Unlike prior systems that leave storage payloads exposed, BlockCert employs real-time client-side ZLib compression (yielding a ~58% payload reduction) paired with **ChaCha20-Poly1305 (AEAD)** symmetric encryption prior to IPFS anchoring.
2. **The Institutional Registry Vault:** Resolves the notoriously fatal "Lost Key Dilemma" in Web3 architectures utilizing **EIP-191 Deterministic Signatures**. This empowers issuing authorities to dynamically and deterministically regenerate lost student encryption keys without maintaining vulnerable centralized key databases.
3. **Deep-Linked QR Verification Automations:** Replaces manual Hash/ID input methodologies with Universal Branded QR Codes. This verification architecture uniquely bundles the IPFS CID and the ChaCha20 decryption key within standard URLs, executing zero-friction, one-tap validation strictly in the verifier's browser memory.

II. SYSTEM ARCHITECTURE

BlockCert operates strictly across three decoupled, trust-minimized tiers:

2.1 The Distributed Storage Layer (IPFS via Pinata)

Instead of storing vulnerable plain-text PDFs, BlockCert utilizes IPFS exclusively as a decentralized host for **Zero-Knowledge Ciphertexts**. The frontend processes all documents locally before pushing them to the network. The result is a highly volatile, globally redundant storage system that is entirely useless to an attacker lacking the precise symmetric key.

2.2 The Blockchain Layer (Ethereum / BSC)

The immutable core relies on a Solidity smart contract (`CertificateRegistry.sol`) utilizing rigid Role-Based Access Control (RBAC).

- **Issuance and Revocation Registry:** The contract maintains granular boolean flags (`revoked`) and `expiryDate` timestamps, allowing institutional admin wallets to void fraudulent credentials in real-time.
- **Merkle Batch Issuance:** To sidestep prohibitive gas fees tied to high-volume university graduations, the contract features `issueBatch()` . By anchoring only an aggregated Merkle Root to the ledger, the contract supports processing thousands of certificates simultaneously while permitting individual O(log N) verification proofs.

2.3 The Cryptographic Middleware (Frontend)

The React.js frontend handles secure, client-side processing encompassing ZLib synchronization and AEAD ciphering prior to IPFS transmission.

III. METHODOLOGY AND CRYPTOGRAPHIC PIPELINE

3.1 ZLib Optimization and ChaCha20-Poly1305 AEAD

The performance bottleneck of IPFS routing is highly sensitive to payload size. Prior to encryption, BlockCert aggressively compresses the chosen credential (PDF/Image) utilizing **ZLib**, achieving an average storage reduction of 58%.

The compressed binary is then subjected to **ChaCha20-Poly1305 (RFC 8439)** encryption. ChaCha20 was explicitly selected over AES-GCM due to its superior performance on standard mobile devices lacking

dedicated cryptographic hardware accelerations, guaranteeing low-latency decryption for verifiers utilizing mobile phones.



3.2 Protocol Versioning (BCV2 Marker)

To guarantee forward-compatibility over decades of institutional record-keeping, the resulting ciphertexts are prepended with a 4-byte Magic Marker (`0x42 0x43 0x56 0x32` , representing "BCV2"). This allows the client software to intuitively trigger different cipher logic if future protocols are upgraded, ensuring seamless legacy support without explicit smart-contract state bloating.

3.3 The Institutional Registry Vault

The most significant contribution of BlockCert is its deterministic key recovery framework. To resolve the "Lost Key Dilemma," BlockCert does not store keys in a database. Instead:

1. **Deterministic Derivation:** The issuing institution utilizes their Ethereum private key to sign a strict algorithmic string via the EIP-191 standard: `[BlockCert Registry] Master Recovery Key for Student: {ADDRESS}` .
2. **Keccak Hashing:** This signature is hashed using `keccak256` , producing a mathematically guaranteed 256-bit symmetric key. Because the institution's private key is mathematically bound to its public identity, the registrar can infinitely and securely regenerate any student's decryption key on-demand directly in their browser—without ever centralizing the vulnerability.

3.4 Universal Web Verification Token

To bridge the gap between complex Web3 flows and traditional human-resources verification pipelines, BlockCert bundles the resulting Smart Contract ID and the ChaCha20 key into a Unified Deep-Link encoded within a Branded QR Code. Verifiers simply scan the QR to execute a zero-friction, one-tap validation against the blockchain.

IV. PERFORMANCE EVALUATION

4.1 Automated Benchmarking Suite

To scientifically quantify the cryptographic overhead of our privacy-first methodology, an automated Node.js benchmark simulating standard PDF credentials (12.95 KB) was executed against the protocol pipeline.

Resulting Latencies:

- **ZLib Compression Time:** < 5.0 ms
- **ChaCha20-Poly1305 Encryption:** < 3.0 ms
- **IPFS Pinning (Pinata API):** ~1.55 seconds
- **ChaCha20 Decryption:** < 14.0 ms
- **ZLib Decompression:** < 6.0 ms

4.2 Network Retrieval and Metadata Transparency

The benchmarks confirm that the entirety of the local cryptography demands less than **30 milliseconds**. The only observable latency stems from IPFS gateway retrieval, which averaged **4.4 seconds** through dedicated Pinata pathways (while standard public nodes often hit 10s timeouts during initial DHT propagation).

To preempt this 4.4-second IPFS fetch delay for verifiers, BlockCert implements the **Metadata Transparency Protocol**. Even before IPFS payload initiation, the Verifier UI queries the contract's Ethereum nodes, yielding provenance data (Issuer ID, Issue Date, Revocation Status) in **under 125 ms**.

V. SECURITY ANALYSIS

By adopting ChaCha20 AEAD, modifying the underlying IPFS payload becomes impossible without throwing an authentication tag error locally. Additionally:

- **Separation of Concerns:** The Smart Contract holds metadata integrity; IPFS holds the ciphertext; the QR token holds the decryption mapping. A bad actor must compromise all three decoupled environments simultaneously to forge a credential.
- **Zero Database Vulnerabilities:** By utilizing EIP-191 signatures for key recovery, there are no cloud "Key Vaults" susceptible to SQL injection or traditional API exfiltration.

VI. CONCLUSION

The BlockCert platform fundamentally advances the viability of decentralized credential registries. Through the implementation of client-side highly-optimized ZLib compression and ChaCha20-Poly1305 encryption, the system successfully patches the glaring public-data privacy flaws found in generic IPFS implementations like ElimuChain. Furthermore, the Institutional Registry Vault safely solves key management without compromising true decentralization. With a proven validation latency of <125ms for metadata and fully secure payload decryption executed in milliseconds, BlockCert delivers a robust, scalable, and GDPR-compliant architecture ready for global educational institutional adoption.

References

1. Said, S. H. et al., "A Comprehensive Blockchain-Based System for Educational Qualifications Management," *IEEE Access*, 2025.
2. Nir, Y., and Langley, A., "ChaCha20 and Poly1305 for IETF Protocols," *RFC 8439*, 2018.

3. Nakamoto, S., "Bitcoin: A Peer-to-Peer Electronic Cash System," 2008.
4. Antonopoulos, A. M., & Wood, G. "Mastering Ethereum," *O'Reilly Media*, 2018.