

Attention Is All You Need

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit

Llion Jones, Aidan N. Gomez, Lukasz Kaiser, Illia Polosukhin

Abstract

The dominant sequence transduction models are based on complex recurrent or convolutional neural networks that include an encoder and a decoder. The best performing models also connect the encoder and decoder through an attention mechanism. We propose a new simple network architecture, the Transformer, based solely on attention mechanisms, dispensing with recurrence and convolutions entirely. Experiments on two machine translation tasks show that these models are superior in quality while being more parallelizable and requiring significantly less time to train. Our model achieves 28.4 BLEU on the WMT 2014 English-to-German translation task, improving over the existing best results, including ensembles, by over 2 BLEU. On the WMT 2014 English-to-French translation task, our model establishes a new state-of-the-art single-model BLEU score of 41.8 after training for 3.5 days on eight GPUs, a small fraction of the training costs of the best models from the literature.

1. Introduction

Recurrent neural networks, long short-term memory [1] and gated recurrent neural networks [2] have been established as state-of-the-art approaches in sequence modeling and transduction problems. Numerous efforts have been made to improve the performance of these models through better attention mechanisms (Bahdanau et al., 2014). The Transformer architecture introduced in this paper represents a significant departure from these approaches, as it eschews recurrence entirely and instead relies entirely on an attention mechanism to draw global dependencies between input and output. The choice of convolutional neural networks (CNN) over recurrent neural networks has been studied extensively [3, 4]. However, (Gehring et al., 2017) showed that convolutional approaches can achieve competitive results on sequence modeling tasks.

2. Model Architecture

The Transformer follows an encoder-decoder structure using stacked self-attention and point-wise, fully connected layers. The encoder maps an input sequence to a sequence of continuous representations, which the decoder then uses to generate an output sequence one element at a time [5]. The architecture is shown to be highly parallelizable and achieves state-of-the-art results on translation benchmarks.

2.1 Encoder and Decoder Stacks

The encoder is composed of a stack of $N=6$ identical layers. Each layer has two sub-layers. The first is a multi-head self-attention mechanism, and the second is a simple position-wise fully connected feed-forward network. We employ a residual connection [6] around each of the two sub-layers, followed by layer normalization (Ba et al., 2016). The decoder is also composed of a stack of $N=6$ identical layers. In addition to the two sub-layers in each encoder layer, the decoder inserts a third sub-layer that performs multi-head attention over the output of the encoder stack.

2.2 Attention Mechanism

An attention function can be described as mapping a query and a set of key-value pairs to an output [7]. We call our particular attention 'Scaled Dot-Product Attention' (Vaswani et al., 2017). The input consists of queries and keys of dimension d_k , and values of dimension d_v . We compute the dot products of the query with all keys, divide each by $\sqrt{d_k}$, and apply a softmax function to obtain the weights on the values.

3. Experimental Results

We evaluated the Transformer on two machine translation tasks: WMT 2014 English-to-German and WMT 2014 English-to-French. Table 2 shows that our model achieves a BLEU score of 28.4 on the English-to-German task, improving over the previous best model by 2 BLEU. On English-to-French, the model achieves a BLEU score of 41.0, establishing a new state-of-the-art. The training time is dramatically reduced compared to previous approaches [8].

3.1 Machine Translation

On the WMT 2014 English-to-German translation task, the Transformer (big) model achieves a BLEU score of 28.4, outperforming the previous best model (LeCun et al., 2015) by more than 2 BLEU. The model uses a vocabulary of approximately 37,000 tokens and is trained on 8 NVIDIA P100 GPUs for 3.5 days. For English-to-French, the model achieves BLEU 41.0, surpassing the previous state-of-the-art.

4. Conclusion

In this work, we presented the Transformer, the first sequence transduction model based entirely on attention, replacing the recurrent layers most commonly used in encoder-decoder architectures with multi-headed self-attention. The Transformer can be trained significantly faster than architectures based on recurrent or convolutional layers [9]. The model achieves state-of-the-art results on both WMT 2014 English-to-German and English-to-French translation tasks.

References

- [1] Hochreiter, S. and Schmidhuber, J. (1997). Long short-term memory. *Neural Computation*, 9(8):1735-1780.
- [2] Chung, J., Gulcehre, C., Cho, K., and Bengio, Y. (2014). Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*.
- [3] Kim, Y. (2014). Convolutional neural networks for sentence classification. In *Proceedings of EMNLP*, pages 1746-1751.
- [4] Kalchbrenner, N., Grefenstette, E., and Blunsom, P. (2014). A convolutional neural network for modelling sentences. In *Proceedings of ACL*, pages 655-665.
- [5] Sutskever, I., Vinyals, O., and Le, Q. V. (2014). Sequence to sequence learning with neural networks. In *NeurIPS*, pages 3104-3112.
- [6] He, K., Zhang, X., Ren, S., and Sun, J. (2016). Deep residual learning for image recognition. In *CVPR*, pages 770-778.
- [7] Bahdanau, D., Cho, K., and Bengio, Y. (2014). Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*.
- [8] Wu, Y., Schuster, M., Chen, Z., Le, Q. V., and Norouzi, M. (2016). Google's neural machine translation system: Bridging the gap between human and machine translation. *arXiv preprint arXiv:1609.08144*.
- [9] Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. (2018). BERT: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.