

PeriDEM – High-fidelity modeling of granular media consisting of deformable complex-shaped particles

Prashant K. Jha ¹

¹ Department of Mechanical Engineering, South Dakota School of Mines and Technology, Rapid City, SD 57701, USA

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Accurate simulation of granular materials under extreme mechanical conditions, such as crushing, fracture, and large deformation, remains a significant challenge in geotechnical, manufacturing, and mining applications. Classical discrete element method (DEM) models typically treat particles as rigid or nearly rigid bodies, limiting their ability to capture internal deformation and fracture. The PeriDEM library, first introduced in (Jha et al., 2021), addresses this limitation by modeling particles as deformable solids using peridynamics, a nonlocal continuum theory that naturally accommodates fracture and significant deformation. Inter-particle contact is handled using DEM-inspired local laws, enabling realistic interaction between complex-shaped particles.

Implemented in C++, PeriDEM is designed for extensibility and ease of deployment. It relies on a minimal set of external libraries, supports multithreaded execution, and includes demonstration examples involving compaction, fracture, and rotational dynamics. The framework facilitates granular-scale simulations, supports the development of constitutive models, and serves as a foundation for multi-fidelity coupling in real-world applications.

Statement of Need

Granular materials play a central role in many engineered systems, but modeling their behavior under high loading, deformation, and fragmentation remains an open problem. Popular open-source DEM codes such as YADE (Smilauer et al., 2021), BlazeDEM (Govender et al., 2016), Chrono DEM-Engine (Zhang et al., 2024), and LAMMPS (Thompson et al., 2022) are widely used but typically treat particles as rigid, limiting their accuracy in scenarios involving internal deformation and breakage. A recent review by Dosta et al. (Dosta et al., 2024) compares several DEM libraries. Meanwhile, peridynamics-based codes such as Peridigm (Littlewood et al., 2024) and NLMech (Jha & Diehl, 2021) are designed to simulate deformation and fracture within a single structure, with limited support for multi-structure simulations.

PeriDEM fills this gap by integrating state-based peridynamics for intra-particle deformation with DEM-style contact laws for particle interactions. This hybrid approach enables direct simulation of particle fragmentation, stress redistribution, and dynamic failure propagation—capabilities essential for modeling granular compaction, attrition, and crushing.

Recent multiscale approaches, including DEM-continuum and DEM-level-set coupling methods (Harmon et al., 2021), aim to bridge scales but often rely on homogenization assumptions. Sand crushing in geotechnical systems, for example, has been modeled using micro-CT-informed FEM or phenomenological laws (Chen et al., 2023). PeriDEM offers a particle-resolved alternative that allows bottom-up investigation of granular failure and shape evolution, especially in systems where fragment dynamics are critical.

41 Brief Introduction to PeriDEM Model




Figure 1: Motion of particle system.

42 Consider a fixed frame of reference and $\{e_i\}_{i=1}^d$ are orthonormal bases. Consider a collection
43 of N_P particles $\Omega_0^{(p)}$, $1 \leq p \leq N_P$, where $\Omega_0^{(p)} \subset \mathbb{R}^d$ with $d = 2, 3$ represents the initial
44 configuration of particle p . Suppose $\Omega_0 \supset \bigcup_{p=1}^{N_P} \Omega_0^{(p)}$ is the domain containing all particles; see
45 Figure 1. The particles in Ω_0 are dynamically evolving due to external boundary conditions and
46 internal interactions; let $\Omega_t^{(p)}$ denote the configuration of particle p at time $t \in (0, t_F]$, and
47 $\Omega_t \supset \bigcup_{p=1}^{N_P} \Omega_t^{(p)}$ domain containing all particles at that time. The motion $x^{(p)} = x^{(p)}(X^{(p)}, t)$
48 takes point $X^{(p)} \in \Omega_0^{(p)}$ to $x^{(p)} \in \Omega_t^{(p)}$, and collectively, the motion is given by $x = x(X, t) \in$
49 Ω_t for $X \in \Omega_0$. We assume the media is dry and not influenced by factors other than
50 mechanical loading (e.g., moisture and temperature are not considered). The configuration of
51 particles in Ω_t at time t depends on various factors, such as material and geometrical properties,
52 contact mechanism, and external loading. Essentially, there are two types of interactions
53 present in the media:

- 54 ■ *Intra-particle interaction* that models the deformation and internal forces in the particle
55 and
- 56 ■ *Inter-particle interaction* that accounts for the contact between particles and the boundary
57 of the domain in which the particles are contained.

58 In DEM, the first interaction is ignored, assuming that particle deformation is insignificant
59 compared to inter-particle interactions. On the other hand, PeriDEM accounts for both
60 interactions.

61 The balance of linear momentum for particle p , $1 \leq p \leq N_P$, takes the form:

$$\rho^{(p)} \ddot{u}^{(p)}(X, t) = f_{int}^{(p)}(X, t) + f_{ext}^{(p)}(X, t), \quad \forall (X, t) \in \Omega_0^{(p)} \times (0, t_F), \quad (1)$$

62 where $\rho^{(p)}$, $f_{int}^{(p)}$, and $f_{ext}^{(p)}$ are density, and internal and external force densities. The
63 above equation is complemented with initial conditions, $u^{(p)}(X, 0) = u_0^{(p)}(X)$, $\dot{u}^{(p)}(X, 0) =$
64 $\dot{u}_0^{(p)}(X)$, $X \in \Omega_0^{(p)}$.

65 Internal force – State-based peridynamics

66 The internal force term $f_{int}^{(p)}(X, t)$ in the momentum balance governs intra-particle deformation
67 and fracture. In PeriDEM, this term is modeled using a simplified state-based peridynamics
68 formulation that accounts for nonlocal interactions over a finite horizon. The underlying model
69 and its numerical implementation are discussed in detail in [(Jha et al., 2021)], Sections 2.1
70 and 2.3].

71 DEM-inspired contact forces

72 The external force term $f_{ext}^{(p)}(X, t)$ includes body forces, wall-particle interactions, and contact
73 forces from other particles. Contact is modeled using a spring-dashpot-slider formulation

74 applied locally when particles come within a critical distance; see Figure 2. This approach
75 introduces nonlinear normal forces, damping, and friction without relying on particle convexity
76 or geometric simplifications. The full formulation of contact detection, force assembly, and
77 implementation is detailed in [(Jha et al., 2021), Section 2.2].




Figure 2: High-resolution contact approach in the PeriDEM model for granular materials between arbitrarily shaped particles. The spring dashpot slider system represents normal contact elasticity, normal damping, and tangential friction between material points x and y . Adapted from Jha et al. (2021).

78 Implementation

79 PeriDEM is implemented in C++ and hosted on GitHub. It depends on a minimal set of external
80 libraries, most of which are bundled in the external directory. Key dependencies include
81 Taskflow (Huang et al., 2021) for multithreaded parallelism, nanoflann (Blanco & Rai, 2014)
82 for efficient neighborhood search, and VTK for output. The numerical strategies for neighbor
83 search, peridynamic integration, damage evaluation, and time stepping follow those introduced
84 in [(Jha et al., 2021), Section 3]. The core simulation model is implemented in `src/model/dem`,
85 with the class `DEMModel` managing particle states, force calculations, and time integration.
86 This work builds on earlier research in the analysis and numerical methods for peridynamics;
87 see (Jha et al., 2025; Jha & Lipton, 2018a, 2018b, 2019; Jha & Lipton, 2020).

88 Features

- 89 ■ Combines peridynamics and DEM to model intra-particle deformation and inter-particle
90 contact
- 91 ■ Simulates deformation and breakage of single particles under complex loading conditions
- 92 ■ Supports arbitrarily shaped particles for realistic granular systems
- 93 ■ Ongoing development of MPI-based parallelism and adaptive modeling strategies to
94 improve efficiency without sacrificing accuracy
- 95 ■
- 96 ■
- 97 ■

98 Examples

99 Example cases are described in [examples/README.md](#). One key simulation demonstrates
100 the compression of over 500 circular and hexagonal particles in a rectangular container by
101 displacing the top wall. The stress on the wall becomes increasingly nonlinear with penetration
102 depth as damage accumulates and the medium yields (see Figure 3a).

103 Preliminary performance tests show that compute time increases exponentially with particle
104 count due to the nonlocal nature of both peridynamic and contact interactions—highlighting

a computational bottleneck. This motivates future integration of MPI-based parallelism and a multi-fidelity modeling framework. Additional examples include attrition of non-circular particles in a rotating cylinder (Figure 3c).




Figure 3: (a) Nonlinear response under compression, (b) exponential growth of compute time due to nonlocality of internal and contact forces, and (c) rotating cylinder with nonspherical particles. Adapted from Jha et al. (2021).

Acknowledgements

Current efforts on the development and enhancement of the PeriDEM library are supported by the U.S. National Science Foundation through the Engineering Research Initiation (ERI) program under Grant No. 2502279.

References

- Blanco, J. L., & Raj, P. K. (2014). *Nanoflann: A C++ header-only fork of FLANN, a library for nearest neighbor (NN) with KD-trees*. <https://github.com/jlblancoc/nanoflann>.
- Chen, Q., Li, Z., Dai, Z., Wang, X., Zhang, C., & Zhang, X. (2023). Mechanical behavior and particle crushing of irregular granular material under high pressure using discrete element method. *Scientific Reports*, 13(1), 7843. <https://doi.org/10.1038/s41598-023-35022-w>
- Dosta, M., André, D., Angelidakis, V., Caulk, R. A., Celigueta, M. A., Chareyre, B., Dietiker, J.-F., Girardot, J., Govender, N., Hubert, C., & others. (2024). Comparing open-source DEM frameworks for simulations of common bulk processes. *Computer Physics Communications*, 296, 109066. <https://doi.org/10.1016/j.cpc.2023.109066>
- Govender, N., Wilke, D. N., & Kok, S. (2016). Blaze-DEMGPU: Modular high performance DEM framework for the GPU architecture. *SoftwareX*, 5, 62–66. <https://doi.org/10.1016/j.softx.2016.04.004>
- Harmon, J. M., Karapiperis, K., Li, L., Moreland, S., & Andrade, J. E. (2021). Modeling connected granular media: Particle bonding within the level set discrete element method. *Computer Methods in Applied Mechanics and Engineering*, 373, 113486. <https://doi.org/10.1016/j.cma.2020.113486>

- 129 Huang, T.-W., Lin, D.-L., Lin, C.-X., & Lin, Y. (2021). Taskflow: A lightweight parallel and
130 heterogeneous task graph computing system. *IEEE Transactions on Parallel and Distributed
131 Systems*, 33(6), 1303–1320. <https://doi.org/10.1109/TPDS.2021.3104255>
- 132 Jha, P. K., Desai, P. S., Bhattacharya, D., & Lipton, R. (2021). Peridynamics-based discrete
133 element method (PeriDEM) model of granular systems involving breakage of arbitrarily
134 shaped particles. *Journal of the Mechanics and Physics of Solids*, 151, 104376. <https://doi.org/10.1016/j.jmps.2021.104376>
- 136 Jha, P. K., & Diehl, P. (2021). NLMech: Implementation of finite difference/meshfree
137 discretization of nonlocal fracture models. *Journal of Open Source Software*, 6(65), 3020.
138 <https://doi.org/10.21105/joss.03020>
- 139 Jha, P. K., Diehl, P., & Lipton, R. (2025). Nodal finite element approximation of peridynamics.
140 *Computer Methods in Applied Mechanics and Engineering*, 434, 117519. <https://doi.org/10.1016/j.cma.2024.117519>
- 142 Jha, P. K., & Lipton, R. (2018a). Numerical analysis of nonlocal fracture models in holder
143 space. *SIAM Journal on Numerical Analysis*, 56(2), 906–941. <https://doi.org/10.1137/17M1112236>
- 145 Jha, P. K., & Lipton, R. (2018b). Numerical convergence of nonlinear nonlocal continuum
146 models to local elastodynamics. *International Journal for Numerical Methods in Engineering*,
147 114(13), 1389–1410. <https://doi.org/10.1002/nme.5791>
- 148 Jha, P. K., & Lipton, R. (2019). Numerical convergence of finite difference approximations for
149 state based peridynamic fracture models. *Computer Methods in Applied Mechanics and
150 Engineering*, 351, 184–225. <https://doi.org/10.1016/j.cma.2019.03.024>
- 151 Jha, P. K., & Lipton, R. P. (2020). Kinetic relations and local energy balance for LEFM from
152 a nonlocal peridynamic model. *International Journal of Fracture*. <https://doi.org/10.1007/s10704-020-00480-0>
- 154 Littlewood, D. J., Parks, M. L., Foster, J. T., Mitchell, J. A., & Diehl, P. (2024). The
155 peridigm meshfree peridynamics code. *Journal of Peridynamics and Nonlocal Modeling*,
156 6(1), 118–148. <https://doi.org/10.1007/s42102-023-00100-0>
- 157 Smilauer, V., Angelidakis, V., Catalano, E., Caulk, R., Chareyre, B., Chèvremont, W., Doro-
158 feenko, S., Duriez, J., Dyck, N., Elias, J., Er, B., Eulitz, A., Gladky, A., Guo, N., Jakob, C.,
159 Kneib, F., Kozicki, J., Marzougui, D., Maurin, R., ... Yuan, C. (2021). Yade documentation
160 (3rd edition). *Zenodo*. <https://doi.org/10.5281/zenodo.5705394>
- 161 Thompson, A. P., Aktulga, H. M., Berger, R., Bolintineanu, D. S., Brown, W. M., Crozier, P.
162 S., in 't Veld, P. J., Kohlmeyer, A., Moore, S. G., Nguyen, T. D., Shan, R., Stevens, M. J.,
163 Tranchida, J., Trott, C., & Plimpton, S. J. (2022). LAMMPS - a flexible simulation tool for
164 particle-based materials modeling at the atomic, meso, and continuum scales. *Computer
165 Physics Communications*, 271, 108171. <https://doi.org/10.1016/j.cpc.2021.108171>
- 166 Zhang, R., Tagliafierro, B., Vanden Heuvel, C., Sabarwal, S., Bakke, L., Yue, Y., Wei, X.,
167 Serban, R., & Negruț, D. (2024). Chrono DEM-Engine: A discrete element method dual-
168 GPU simulator with customizable contact forces and element shape. *Computer Physics
169 Communications*, 300, 109196. <https://doi.org/10.1016/j.cpc.2024.109196>