

R documentation

of all in ‘.’

December 20, 2014

R topics documented:

BN_Data_Generator-package	2
big_letters	2
BN_Data_Generator	3
check_cardinalities	5
C_M_WO_WC	7
fromto_to_mat	9
gen_asia	9
is.acyclic	10
is.DAG	11
make_Collapse	12
make_Diamond	13
make_Line	14
make_PseudoLoop	15
make_Rhombus	16
make_Star	17
mat_to_fromto	18
real_alarm	19
real_asia	20
real_hailfinder	21
real_insurance	22
real_lizards	23
toss_value	24
Index	25

BN_Data_Generator-package

What the package does (short line) ~~ package title ~~

Description

More about what it does (maybe more than one line) ~~ A concise (1-5 lines) description of the package ~~

Details

Package: BN_Data_Generator
Type: Package
Version: 1.0
Date: 2014-12-21
License: What license is it under?

~~ An overview of how to use the package, including the most important ~~ functions ~~

Author(s)

Who wrote it

Maintainer: Who to complain to <yourfault@somewhere.net> ~~ The author and/or maintainer of the package ~~

References

~~ Literature or other references for background information ~~

See Also

~~ Optional links to other man pages, e.g. ~~ <pkg> ~~

Examples

~~ simple examples of the most important functions ~~

big_letters

Usage

big_letters(size)

Arguments

size

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (size)
{
  letters_list = list()
  letters_list[[1]] = letters
  while (TRUE) {
    num_of_letters = 0
    len_letters_list = length(letters_list)
    for (i in 1:len_letters_list) {
      num_of_letters = num_of_letters + length(letters_list[[i]])
    }
    if (num_of_letters < size) {
      merge_mat = merge(letters, letters_list[[len_letters_list]])
      letters_list[[len_letters_list + 1]] = sort(paste(merge_mat[,
        1], merge_mat[, 2], sep = ""))
    }
    else {
      break
    }
  }
  result = NULL
  for (i in 1:length(letters_list)) {
    result = c(result, letters_list[[i]])
  }
  result = sort(result)
  return(result[1:size])
}
```

BN_Data_Generator

Usage

```
BN_Data_Generator(arcs, input_Probs, n, node_names = NULL, cardinalities = NULL)
```

Arguments

arcs

input_Probs

n

```
node_names
cardinalities
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (arcs, input_Probs, n, node_names = NULL, cardinalities = NULL)
{
  if (n <= 0) {
    stop("Sample size 'n' must be greater than 0.")
  }
  if (n < 10000) {
    temp_n = 1000
  }
  else {
    temp_n = n
  }
  num_of_nodes = dim(arcs)[1]
  result_mat = matrix(0, temp_n, num_of_nodes)
  dimnames(result_mat)[[2]] = node_names
  checker = check_cardinalities(arcs = arcs, node_names = node_names,
    cardinalities = cardinalities)
  cardinalities = checker$cardinalities
  node_names = checker$node_names
  list_parent_nodes = checker$list_parent_nodes
  num_of_probs = checker$num_of_probs
  num_of_parent_nodes = checker$num_of_parent_nodes
  num_of_root_nodes = checker$num_of_root_nodes
  input_prob_len = length(input_Probs)
  for (i in 1:input_prob_len) {
    if (as.numeric(length(input_Probs[[i]])) != as.numeric(num_of_probs[i])) {
      stop("Input Probs != num_of_probs!")
    }
  }
  for (i in 1:num_of_root_nodes) {
    p = input_Probs[[i]]
    mat_values = merge("Value", c(1:cardinalities[i]))
    mat_values = paste(mat_values[, 1], mat_values[, 2],
      sep = "")
    result_mat[, i] = sample(mat_values, temp_n, prob = c(p,
      1 - sum(p)), rep = T)
  }
  init = num_of_root_nodes + 1
  mat = NULL
  for (i in init:num_of_nodes) {
    p = input_Probs[[i]]
    temp_list_of_pn = as.numeric(list_parent_nodes[[i]])
    num_of_c_cases = prod(cardinalities[temp_list_of_pn])
```

```

temp_cases = list()
cases = NULL
for (j in 1:length(temp_list_of_pn)) {
  temp_cases[[j]] = toss_value(1, cardinalities[temp_list_of_pn[j]])
  if (is.null(cases)) {
    cases = temp_cases[[j]]
    names(cases) = 1
  }
  else {
    cases = merge(cases, temp_cases[[j]])
    names(cases) = c(1:dim(cases)[2])
  }
}
cases = as.matrix(cases)
mat_values = merge("Value", c(1:cardinalities[i]))
mat_values = sort(paste(mat_values[, 1], mat_values[,
  2], sep = ""))
stack = 1
for (j in 1:dim(cases)[1]) {
  mat = t(t(as.matrix(result_mat[, temp_list_of_pn])) ==
    cases[j, ])
  mat = (apply(mat, 1, sum) == dim(mat)[2])
  if (cardinalities[i] == 2) {
    temp_p = p[j]
  }
  else {
    temp_p = p[stack:(stack + cardinalities[i] -
      2)]
  }
  len = length(which(mat))
  result_mat[which(mat), i] = sample(mat_values, len,
    prob = c(temp_p, 1 - sum(temp_p)), rep = T)
  stack = stack + (cardinalities[i] - 1)
}
}
if (n < 1000) {
  result_mat = result_mat[sample(c(1:1000), size = n),
    ]
}
res = list(data = data.frame(result_mat), node_names = node_names,
  num_of_nodes = num_of_nodes, num_of_parent_nodes = num_of_parent_nodes,
  list_parent_nodes = list_parent_nodes)
return(res)
}

```

check_cardinalities

Usage

```
check_cardinalities(arcs, node_names = NULL, cardinalities = NULL)
```

Arguments

arcs
node_names
cardinalities

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (arcs, node_names = NULL, cardinalities = NULL)
{
  check_dag_arcs = as.matrix(arcs)
  if (is.DAG(check_dag_arcs) == FALSE) {
    stop("arcs must a DAG")
  }
  num_of_nodes = dim(arcs)[1]
  if (is.null(node_names)) {
    node_names = big_letters(num_of_nodes)
  }
  if (is.null(cardinalities)) {
    cardinalities = rep(2, num_of_nodes)
  }
  else if (sum(cardinalities < 2) > 0) {
    stop("All cardinality must be at least 2.")
  }
  else if (num_of_nodes != length(cardinalities)) {
    stop("Wrong length of cardinalities")
  }
  num_of_parent_nodes = apply(arcs, 2, sum)
  list_parent_nodes = list()
  for (m in 1:num_of_nodes) {
    if (length(which(arcs[, m] == 1)) == 0) {
      list_parent_nodes[[m]] = NULL
    }
    else {
      list_parent_nodes[[m]] = which(arcs[, m] == 1)
    }
  }
  num_of_root_nodes = sum(num_of_parent_nodes == 0)
  num_of_probs = NULL
  for (k in 1:num_of_nodes) {
    num_of_probs[k] = (cardinalities[k] - 1) * prod(cardinalities[list_parent_nodes[[k]])]
  }
  text_of_probs = list()
  for (i in 1:length(num_of_parent_nodes)) {
    temp_text = NULL
    present_cardinality = as.matrix(toss_value(1, cardinalities[i]))
    if (num_of_parent_nodes[i] == 0) {
```

```

    for (j in 1:(cardinalities[i] - 1)) {
      temp_text = c(temp_text, paste("P(", node_names[i],
        " = ", present_cardinality[j, 1], ") ", sep = ""))
    }
  }
  else {
    temp_list_of_pn = as.numeric(list_parent_nodes[[i]])
    for (j in 1:(cardinalities[i] - 1)) {
      temp_cases = list()
      cases = NULL
      for (k in 1:length(temp_list_of_pn)) {
        temp_cases[[k]] = toss_value(1, cardinalities[temp_list_of_pn[k]])
        if (is.null(cases)) {
          cases = temp_cases[[k]]
          names(cases) = 1
        }
        else {
          cases = merge(cases, temp_cases[[k]])
          names(cases) = c(1:dim(cases)[2])
        }
      }
      cases = as.matrix(cases)
      for (k in 1:dim(cases)[1]) {
        temp_text_conditional = NULL
        for (m in 1:dim(cases)[2]) {
          case_value = paste(node_names[temp_list_of_pn[m]],
            " = ", cases[k, m], sep = "")
          if (m == 1) {
            temp_text_conditional = case_value
          }
          else {
            temp_text_conditional = paste(temp_text_conditional,
              paste(", ", case_value), sep = "")
          }
        }
        temp_text = c(temp_text, paste("P(", node_names[i],
          " = ", present_cardinality[j, 1], "|", temp_text_conditional,
          ")", sep = ""))
      }
    }
  }
  text_of_probs[[i]] = temp_text
}
res = list(cardinalities = cardinalities, node_names = node_names,
  num_of_root_nodes = num_of_root_nodes, num_of_probs = num_of_probs,
  num_of_parent_nodes = num_of_parent_nodes, list_parent_nodes = list_parent_nodes,
  list_of_probs = text_of_probs)
return(res)
}

```

Usage

```
C_M_WO_WC(target_arcs_mat, learnt_arcs_mat)
```

Arguments

```
target_arcs_mat
```

```
learnt_arcs_mat
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (target_arcs_mat, learnt_arcs_mat)
{
  nodes = dim(target_arcs_mat)[2]
  C = 0
  M = 0
  WO = 0
  WC = 0
  for (i in 1:nodes) {
    C = C + abs(sum((target_arcs_mat[, i] == 1) & (learnt_arcs_mat[,
      i] == 1) & (target_arcs_mat[, i] == learnt_arcs_mat[,
      i])))
    M = M + abs(sum((target_arcs_mat[, i] == 1) & (learnt_arcs_mat[,
      i] == 0) & (target_arcs_mat[, i] != learnt_arcs_mat[,
      i])) - sum((target_arcs_mat[, i] == 1) & (learnt_arcs_mat[i,
      ] == 1) & (target_arcs_mat[, i] == learnt_arcs_mat[i,
      ])))
    WO = WO + abs(sum((target_arcs_mat[, i] == 1) & (learnt_arcs_mat[i,
      ] == 1) & (target_arcs_mat[, i] == learnt_arcs_mat[i,
      ])))
    WC = WC + abs(sum((target_arcs_mat[, i] == 0) & (learnt_arcs_mat[,
      i] == 1) & (target_arcs_mat[, i] != learnt_arcs_mat[,
      i])) - sum((target_arcs_mat[i, ] == 0) & (learnt_arcs_mat[i,
      ] == 1) & (target_arcs_mat[i, ] != learnt_arcs_mat[i,
      ])))
  }
  result = t(as.matrix(c(C, M, WO, WC)))
  dimnames(result)[[2]] = c("C", "M", "WO", "WC")
  return(result)
}
```

`fromto_to_mat`

Usage`fromto_to_mat(input_arcs, node_names)`**Arguments**`input_arcs``node_names`**Examples**

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (input_arcs, node_names)
{
  if (dim(input_arcs)[1] == 0) {
    stop("It has not any arc")
  }
  num_of_nodes = length(node_names)
  arcs_mat = matrix(0, num_of_nodes, num_of_nodes)
  arcs_order_mat = cbind(node_names, c(1:length(node_names)))
  temp_arcs = cbind(match(input_arcs[, 1], arcs_order_mat),
    match(input_arcs[, 2], arcs_order_mat))
  if (length(temp_arcs) > 0) {
    for (i in 1:dim(temp_arcs)[1]) {
      from = as.numeric(temp_arcs[i, 1])
      to = as.numeric(temp_arcs[i, 2])
      arcs_mat[from, to] = arcs_mat[from, to] + 1
    }
  }
  dimnames(arcs_mat)[[1]] = node_names
  dimnames(arcs_mat)[[2]] = node_names
  return(arcs_mat)
}
```

`gen_asia`

Usage`gen_asia()`

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function ()
{
  arcs = rbind(c(0, 0, 1, 0, 0, 0, 0, 0), c(0, 0, 0, 1, 1,
    0, 0, 0), c(0, 0, 0, 0, 0, 1, 0, 0), c(0, 0, 0, 0, 0,
    1, 0, 0), c(0, 0, 0, 0, 0, 0, 0, 1), c(0, 0, 0, 0, 0,
    0, 1, 1), c(0, 0, 0, 0, 0, 0, 0, 0), c(0, 0, 0, 0, 0,
    0, 0, 0))
  node_names = c("A", "S", "T", "L", "B", "E", "X", "D")
  dimnames(arcs)[[1]] = node_names
  dimnames(arcs)[[2]] = node_names
  input_Probs = list(c(0.01), c(0.5), c(0.05, 0.01), c(0.1,
    0.01), c(0.6, 0.3), c(1, 1, 1, 0), c(0.98, 0.05), c(0.9,
    0.7, 0.8, 0.1))
  num_of_nodes = length(node_names)
  cardinalities = rep(2, num_of_nodes)
  result = list(arcs_mat = arcs, Probs = input_Probs, node_names = node_names,
    cardinalities = cardinalities, num_of_nodes = num_of_nodes)
  return(result)
}
```

is.acyclic

Usage

```
is.acyclic(amat)
```

Arguments

amat

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (amat)
{
  transClos = function(amat) {
    if (nrow(amat) == 1)
      return(amat)
  }
}
```

```

    A = amat
    diag(A) = 1
    repeat {
      B = sign(A %*% A)
      if (all(B == A))
        break
      else A = B
    }
    diag(A) = 0
    A
  }
  B = transClos(amat)
  l = B[lower.tri(B)]
  u = t(B)[lower.tri(t(B))]
  com = (l & u)
  return(all(!com))
}

```

is.DAG

Usage

```
is.DAG(amat)
```

Arguments

amat

Examples

```

##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.

## The function is currently defined as
function (amat)
{
  unmakeMG = function(amat) {
    d = nrow(amat)
    ug = dg = bg = amat
    M = expand.grid(dg = 0:1, ug = 0:1, bg = 0:1)
    i = strtoi(as.character(amat), 2)
    GG = M[i + 1, ]
    ug[, ] = GG[, 2]
    dg[, ] = GG[, 1]
    bg[, ] = GG[, 3]
    if (any(ug != t(ug)))
      stop("Undirected edges are wrongly coded.")
    if (any(bg != t(bg)))

```

```

        stop("Undirected edges are wrongly coded.")
    return(list(dg = dg, ug = ug, bg = bg))
}
comp = unmakeMG(amat)
ug = comp$ug
dag = comp$dg
bg = comp$bg
out = TRUE
if (any(amat > 100)) {
    warning("There are double edges.")
    out = FALSE
}
if (!is.acyclic(dag)) {
    warning("Not acyclic.")
    out = FALSE
}
return(out)
}

```

make_Collapse

Usage

```
make_Collapse(nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
```

Arguments

```

nodes
input_Probs
node_names
cardinalities

```

Examples

```

##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
{
    if (nodes < 3) {
        stop("Need More Nodes!")
    }
    arcs = matrix(0, nodes, nodes)
    arcs[, nodes] = 1
    arcs[nodes, nodes] = 0
    checker = check_cardinalities(arcs = arcs, node_names = node_names,

```

```

        cardinalities = cardinalities)
cardinalities = checker$cardinalities
num_of_probs = checker$num_of_probs
node_names = checker$node_names
if (is.null(input_Probs) & is.null(cardinalities)) {
  input_Probs = list()
  for (i in 1:(nodes - 1)) {
    input_Probs[[i]] = runif(1)
  }
  input_Probs[[nodes]] = runif(2^(nodes - 1))
}
else if (is.null(input_Probs)) {
  input_Probs = list()
  for (i in 1:length(num_of_probs)) {
    input_Probs[[i]] = runif(num_of_probs[i])
  }
}
result = list(arcs_mat = arcs, Probs = input_Probs, node_names = node_names,
  cardinalities = cardinalities, num_of_nodes = nodes)
return(result)
}

```

make_Diamond

Usage

```
make_Diamond(nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
```

Arguments

```

nodes
input_Probs
node_names
cardinalities

```

Examples

```

##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
{
  if (nodes < 4) {
    stop("Need More Nodes!")
  }
  arcs = matrix(0, nodes, nodes)

```

```

arcs[1, ] = 1
arcs[1, 1] = 0
arcs[, nodes] = 1
arcs[1, nodes] = 0
arcs[nodes, nodes] = 0
checker = check_cardinalities(arcs = arcs, node_names = node_names,
                              cardinalities = cardinalities)
cardinalities = checker$cardinalities
num_of_probs = checker$num_of_probs
node_names = checker$node_names
if (is.null(input_Probs) & is.null(cardinalities)) {
  input_Probs = list()
  input_Probs[[1]] = runif(1)
  for (i in 2:(nodes - 1)) {
    input_Probs[[i]] = runif(2)
  }
  input_Probs[[nodes]] = runif(2^(nodes - 2))
}
else if (is.null(input_Probs)) {
  input_Probs = list()
  for (i in 1:length(num_of_probs)) {
    input_Probs[[i]] = runif(num_of_probs[i])
  }
}
result = list(arcs_mat = arcs, Probs = input_Probs, node_names = node_names,
              cardinalities = cardinalities, num_of_nodes = nodes)
return(result)
}

```

make_Line

Usage

```
make_Line(nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
```

Arguments

```

nodes
input_Probs
node_names
cardinalities

```

Examples

```

##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

```

```
## The function is currently defined as
function (nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
{
  if (nodes < 3) {
    stop("Need More Nodes!")
  }
  arcs = matrix(0, nodes, nodes)
  for (i in 1:(nodes - 1)) {
    arcs[i, (i + 1)] = 1
  }
  checker = check_cardinalities(arcs = arcs, node_names = node_names,
    cardinalities = cardinalities)
  cardinalities = checker$cardinalities
  num_of_probs = checker$num_of_probs
  node_names = checker$node_names
  if (is.null(input_Probs) & is.null(cardinalities)) {
    input_Probs = list()
    input_Probs[[1]] = runif(1)
    for (i in 2:nodes) {
      input_Probs[[i]] = runif(2)
    }
  }
  else if (is.null(input_Probs)) {
    input_Probs = list()
    for (i in 1:length(num_of_probs)) {
      input_Probs[[i]] = runif(num_of_probs[i])
    }
  }
  result = list(arcs_mat = arcs, Probs = input_Probs, node_names = node_names,
    cardinalities = cardinalities, num_of_nodes = nodes)
  return(result)
}
```

make_PseudoLoop

Usage

```
make_PseudoLoop(nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
```

Arguments

nodes
input_Probs
node_names
cardinalities

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
{
  if (nodes < 3) {
    stop("Need More Nodes!")
  }
  arcs = matrix(0, nodes, nodes)
  arcs[1, nodes] = 1
  for (i in 1:(nodes - 1)) {
    arcs[i, (i + 1)] = 1
  }
  checker = check_cardinalities(arcs = arcs)
  cardinalities = checker$cardinalities
  num_of_probs = checker$num_of_probs
  node_names = checker$node_names
  if (is.null(input_Probs) & is.null(cardinalities)) {
    input_Probs = list()
    input_Probs[[1]] = runif(1)
    for (i in 2:(nodes - 1)) {
      input_Probs[[i]] = runif(2)
    }
    input_Probs[[nodes]] = runif(4)
  }
  else if (is.null(input_Probs)) {
    input_Probs = list()
    for (i in 1:length(num_of_probs)) {
      input_Probs[[i]] = runif(num_of_probs[i])
    }
  }
  result = list(arcs_mat = arcs, Probs = input_Probs, node_names = node_names,
    cardinalities = cardinalities, num_of_nodes = nodes)
  return(result)
}
```

make_Rhombus

Usage

```
make_Rhombus(nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
```

Arguments

nodes


```

input_Probs
node_names
cardinalities

```

Examples

```

##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
{
  if (nodes < 4) {
    stop("Need More Nodes!")
  }
  arcs = matrix(0, nodes, nodes)
  arcs[1, ] = 1
  arcs[2, ] = 1
  arcs[(1:2), (1:2)] = 0
  arcs[nodes, nodes] = 0
  checker = check_cardinalities(arcs = arcs, node_names = node_names,
    cardinalities = cardinalities)
  cardinalities = checker$cardinalities
  num_of_probs = checker$num_of_probs
  node_names = checker$node_names
  if (is.null(input_Probs) & is.null(cardinalities)) {
    input_Probs = list()
    input_Probs[[1]] = runif(1)
    input_Probs[[2]] = runif(1)
    for (i in 3:nodes) {
      input_Probs[[i]] = runif(2^2)
    }
  }
  else if (is.null(input_Probs)) {
    input_Probs = list()
    for (i in 1:length(num_of_probs)) {
      input_Probs[[i]] = runif(num_of_probs[i])
    }
  }
  result = list(arcs_mat = arcs, Probs = input_Probs, node_names = node_names,
    cardinalities = cardinalities, num_of_nodes = nodes)
  return(result)
}

```

make_Star

Usage

```
make_Star(nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
```

Arguments

nodes
input_Probs
node_names
cardinalities

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (nodes, input_Probs = NULL, node_names = NULL, cardinalities = NULL)
{
  if (nodes < 3) {
    stop("Need More Nodes!")
  }
  arcs = matrix(0, nodes, nodes)
  arcs[1, ] = 1
  arcs[1, 1] = 0
  checker = check_cardinalities(arcs = arcs, node_names = node_names,
    cardinalities = cardinalities)
  cardinalities = checker$cardinalities
  num_of_probs = checker$num_of_probs
  node_names = checker$node_names
  if (is.null(input_Probs) & is.null(cardinalities)) {
    input_Probs = list()
    input_Probs[[1]] = runif(1)
    for (i in 2:nodes) {
      input_Probs[[i]] = runif(2)
    }
  }
  else if (is.null(input_Probs)) {
    input_Probs = list()
    for (i in 1:length(num_of_probs)) {
      input_Probs[[i]] = runif(num_of_probs[i])
    }
  }
  result = list(arcs_mat = arcs, Probs = input_Probs, node_names = node_names,
    cardinalities = cardinalities, num_of_nodes = nodes)
  return(result)
}
```

Usage

```
mat_to_fromto(arcs_mat)
```

Arguments

```
arcs_mat
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (arcs_mat)
{
  check_dag_arcs = as.matrix(arcs)
  if (is.DAG(check_dag_arcs) == FALSE) {
    stop("arcs must a DAG")
  }
  node_names = dimnames(arcs_mat)[[2]]
  num_of_nodes = length(node_names)
  result_mat = NULL
  for (i in 1:num_of_nodes) {
    where = which(arcs[i, ] == 1)
    len = length(where)
    if (len > 0) {
      for (j in 1:len) {
        temp = c(node_names[i], node_names[where[j]])
        result_mat = rbind(result_mat, temp)
      }
    }
  }
  dimnames(result_mat)[[1]] = NULL
  dimnames(result_mat)[[2]] = c("from", "to")
  return(result_mat)
}
```

```
real_alarm
```

Usage

```
real_alarm(n, rep = T)
```

Arguments

```
n
```

```
rep
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (n, rep = T)
{
  packages = c("bnlearn")
  if (length(setdiff(packages, rownames(installed.packages()))) >
      0) {
    install.packages(setdiff(packages, rownames(installed.packages())))
  }
  data(alarm, package = "bnlearn")
  data = alarm[sample(c(1:20000), n, rep = rep), ]
  res = empty.graph(names(alarm))
  modelstring(res) = paste("[HIST|LVF][CVP|LVV][PCWP|LVV][HYP][LVV|HYP:LVF]",
    "[LVF][STKV|HYP:LVF][ERLO][HRBP|ERLO:HR][HREK|ERCA:HR][ERCA]",
    "[HRSA|ERCA:HR][ANES][APL][TPR|APL][ECO2|ACO2:VLNG][KINK]",
    "[MINV|INT:VLNG][FIO2][PVS|FIO2:VALV][SAO2|PVS:SHNT][PAP|PMB][PMB]",
    "[SHNT|INT:PMB][INT][PRSS|INT:KINK:VTUB][DISC][MVS][VMCH|MVS]",
    "[VTUB|DISC:VMCH][VLNG|INT:KINK:VTUB][VALV|INT:VLNG][ACO2|VALV]",
    "[CCHL|ACO2:ANES:SAO2:TPR][HR|CCHL][CO|HR:STKV][BP|CO:TPR]",
    sep = "")
  arcs = fromto_to_mat(temp$res$arcs, dimnames(temp$data)[[2]])
  result = list(arcs_mat = arcs, node_names = dimnames(data)[[2]],
    data = data, res = res)
  return(result)
}
```

real_asia

Usage

```
real_asia(n, rep = T)
```

Arguments

```
n
rep
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
```

```

function (n, rep = T)
{
  packages = c("bnlearn")
  if (length(setdiff(packages, rownames(installed.packages()))) >
      0) {
    install.packages(setdiff(packages, rownames(installed.packages())))
  }
  data(asia, package = "bnlearn")
  data = asia[sample(c(1:5000), n, rep = rep), ]
  res = empty.graph(names(asia))
  modelstring(res) = "[A][S][T|A][L|S][B|S][D|B:E][E|T:L][X|E]"
  arcs = fromto_to_mat(temp$res$arcs, dimnames(temp$data)[[2]])
  result = list(arcs_mat = arcs, node_names = dimnames(data)[[2]],
    data = data, res = res)
  return(result)
}

```

real_hailfinder

Usage

```
real_hailfinder(n, rep = T)
```

Arguments

n
rep

Examples

```

##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (n, rep = T)
{
  packages = c("bnlearn")
  if (length(setdiff(packages, rownames(installed.packages()))) >
      0) {
    install.packages(setdiff(packages, rownames(installed.packages())))
  }
  data(hailfinder, package = "bnlearn")
  data = hailfinder[sample(c(1:20000), n, rep = rep), ]
  res = empty.graph(names(hailfinder))
  modelstring(res) = paste("[N07muVerMo][SubjVertMo][QGVertMotion][SatContMoist][RaoContMoist]",
    "[VISCloudCov][IRCloudCover][AMInstabMt][WndHodograph][MorningBound][LoLevMoistAd][Date]",
    "[MorningCIN][LIfr12ZDENSd][AMDewptCalPl][LatestCIN][LLIW]",
    "[CombVerMo|N07muVerMo:SubjVertMo:QGVertMotion][CombMoisture|SatContMoist:RaoContMoist]",

```

```

"[CombClouds|VISCloudCov:IRCloudCover][Scenario|Date][CurPropConv|LatestCIN:LLIW]",
"[AreaMesoALS|CombVerMo][ScenRelAMCIN|Scenario][ScenRelAMIns|Scenario][ScenRel34|Scenario]",
"[ScnRelPlFcst|Scenario][Dewpoints|Scenario][LowLLapse|Scenario][MeanRH|Scenario]",
"[MidLLapse|Scenario][MvmtFeatures|Scenario][RHRatio|Scenario][SfcWndShfDis|Scenario]",
"[SynForcng|Scenario][TempDis|Scenario][WindAloft|Scenario][WindFieldMt|Scenario]",
"[WindFieldPln|Scenario][AreaMoDryAir|AreaMesoALS:CombMoisture]",
"[AMCINInScen|ScenRelAMCIN:MorningCIN][AMInsWliScen|ScenRelAMIns:LIf12ZDENSd:AMDewptCalPl]",
"[CldShadeOth|AreaMesoALS:AreaMoDryAir:CombClouds][InsInMt|CldShadeOth:AMInstabMt]",
"[OutflowFrMt|InsInMt:WndHodograph][CldShadeConv|InsInMt:WndHodograph][MountainFcst|InsInMt]",
"[Boundaries|WndHodograph:OutflowFrMt:MorningBound][N34StarFcst|ScenRel34:PlainsFcst]",
"[CompPlFcst|AreaMesoALS:CldShadeOth:Boundaries:CldShadeConv][CapChange|CompPlFcst]",
"[InsChange|CompPlFcst:LoLevMoistAd][CapInScen|CapChange:AMCINInScen]",
"[InsScIInScen|InsChange:AMInsWliScen][R5Fcst|MountainFcst:N34StarFcst]",
"[PlainsFcst|CapInScen:InsScIInScen:CurPropConv:ScnRelPlFcst]",
sep = "")
arcs = fromto_to_mat(temp$res$arcs, dimnames(temp$data)[[2]])
result = list(arcs_mat = arcs, node_names = dimnames(data)[[2]],
             data = data, res = res)
return(result)
}

```

real_insurance

Usage

```
real_insurance(n, rep = T)
```

Arguments

```
n
rep
```

Examples

```

##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (n, rep = T)
{
  packages = c("bnlearn")
  if (length(setdiff(packages, rownames(installed.packages()))) >
      0) {
    install.packages(setdiff(packages, rownames(installed.packages())))
  }
  data(insurance, package = "bnlearn")
  data = insurance[sample(c(1:20000), n, rep = rep), ]
  res = empty.graph(names(insurance))

```

```

modelstring(res) = paste("[Age][Mileage][SocioEcon|Age][GoodStudent|Age:SocioEcon]",
  "[RiskAversion|Age:SocioEcon][OtherCar|SocioEcon][VehicleYear|SocioEcon:RiskAversion]",
  "[MakeModel|SocioEcon:RiskAversion][SeniorTrain|Age:RiskAversion]",
  "[HomeBase|SocioEcon:RiskAversion][AntiTheft|SocioEcon:RiskAversion]",
  "[RuggedAuto|VehicleYear:MakeModel][Antilock|VehicleYear:MakeModel]",
  "[DrivingSkill|Age:SeniorTrain][CarValue|VehicleYear:MakeModel:Mileage]",
  "[Airbag|VehicleYear:MakeModel][DrivQuality|RiskAversion:DrivingSkill]",
  "[Theft|CarValue:HomeBase:AntiTheft][Cushioning|RuggedAuto:Airbag]",
  "[DrivHist|RiskAversion:DrivingSkill][Accident|DrivQuality:Mileage:Antilock]",
  "[ThisCarDam|RuggedAuto:Accident][OtherCarCost|RuggedAuto:Accident]",
  "[MedCost|Age:Accident:Cushioning][ILiCost|Accident]",
  "[ThisCarCost|ThisCarDam:Theft:CarValue][PropCost|ThisCarCost:OtherCarCost]",
  sep = "")
arcs = fromto_to_mat(temp$res$arcs, dimnames(temp$data)[[2]])
result = list(arcs_mat = arcs, node_names = dimnames(data)[[2]],
  data = data, res = res)
return(result)
}

```

real_lizards

Usage

```
real_lizards(n, rep = T)
```

Arguments

```

n
rep

```

Examples

```

##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (n, rep = T)
{
  packages = c("bnlearn")
  if (length(setdiff(packages, rownames(installed.packages()))) >
    0) {
    install.packages(setdiff(packages, rownames(installed.packages())))
  }
  data(lizards, package = "bnlearn")
  data = lizards[sample(c(1:409), n, rep = rep), ]
  res = empty.graph(names(lizards))
  modelstring(res) = "[Species][Diameter|Species][Height|Species]"
  arcs = fromto_to_mat(temp$res$arcs, dimnames(temp$data)[[2]])

```

```

    result = list(arcs_mat = arcs, node_names = dimnames(data)[[2]],
                  data = data, res = res)
    return(result)
}

```

toss_value

Usage

```
toss_value(times, num_of_cases, makespace = FALSE)
```

Arguments

```

times
num_of_cases
makespace

```

Examples

```

##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.

## The function is currently defined as
function (times, num_of_cases, makespace = FALSE)
{
  mat_values = merge("Value", c(1:num_of_cases))
  temp <- list()
  for (i in 1:times) {
    temp[[i]] <- paste(mat_values[, 1], mat_values[, 2],
                      sep = "")
  }
  res <- expand.grid(temp, KEEP.OUT.ATTRS = FALSE)
  names(res) <- c(paste(rep("toss", times), 1:times, sep = ""))
  if (makespace)
    res$probs <- rep(1, 2^times)/2^times
  return(res)
}

```


Index

*Topic \textasciitildekw1

big_letters, 2
BN_Data_Generator, 3
C_M_WO_WC, 8
check_cardinalities, 5
fromto_to_mat, 9
gen_asia, 9
is.acyclic, 10
is.DAG, 11
make_Collapse, 12
make_Diamond, 13
make_Line, 14
make_PseudoLoop, 15
make_Rhombus, 16
make_Star, 17
mat_to_fromto, 18
real_alarm, 19
real_asia, 20
real_hailfinder, 21
real_insurance, 22
real_lizards, 23
toss_value, 24

*Topic \textasciitildekw2

big_letters, 2
BN_Data_Generator, 3
C_M_WO_WC, 8
check_cardinalities, 5
fromto_to_mat, 9
gen_asia, 9
is.acyclic, 10
is.DAG, 11
make_Collapse, 12
make_Diamond, 13
make_Line, 14
make_PseudoLoop, 15
make_Rhombus, 16
make_Star, 17
mat_to_fromto, 18
real_alarm, 19

real_asia, 20
real_hailfinder, 21
real_insurance, 22
real_lizards, 23
toss_value, 24

*Topic package

BN_Data_Generator-package, 2
<pkg>, 2

big_letters, 2
BN_Data_Generator, 3
BN_Data_Generator
(BN_Data_Generator-package), 2
BN_Data_Generator-package, 2

C_M_WO_WC, 7
check_cardinalities, 5

fromto_to_mat, 9

gen_asia, 9

is.acyclic, 10
is.DAG, 11

make_Collapse, 12
make_Diamond, 13
make_Line, 14
make_PseudoLoop, 15
make_Rhombus, 16
make_Star, 17
mat_to_fromto, 18

real_alarm, 19
real_asia, 20
real_hailfinder, 21
real_insurance, 22
real_lizards, 23

toss_value, 24