

Switch>show vlan brief

VLAN Name Status Ports

1 default active Fa0/7, Fa0/8, Fa0/9, Fa0/10

Fa0/11, Fa0/12, Fa0/13, Fa0/14

Fa0/15, Fa0/16, Fa0/17, Fa0/18

Fa0/19, Fa0/20, Fa0/21, Fa0/22

Fa0/23, Fa0/24, Gig0/1, Gig0/2

10 student active Fa0/2, Fa0/3

20 faculty active Fa0/4, Fa0/5

30 admin active Fa0/6

1002 fddi-default active

1003 token-ring-default active

1004 fddinet-default active

1005 trnet-default active

Switch>show interfaces trunk

Port Mode Encapsulation Status Native vlan

Fa0/1 on 802.1q trunking 1

Port Vlans allowed on trunk

Fa0/1 1-1005

Port Vlans allowed and active in management domain

Fa0/1 1,10,20,30

Port Vlans in spanning tree forwarding state and not pruned

Fa0/1 1,10,20,30

Switch>show running-config

^

% Invalid input detected at '^' marker.

Switch>enable

Switch#show running-config

Building configuration...

Current configuration : 1358 bytes

!

version 15.0

no service timestamps log datetime msec

no service timestamps debug datetime msec

no service password-encryption

!

hostname Switch

!

!

!

!

!

!

spanning-tree mode pvst

spanning-tree extend system-id

!

interface FastEthernet0/1

switchport mode trunk

!

interface FastEthernet0/2

switchport access vlan 10

switchport mode access

!

interface FastEthernet0/3

switchport access vlan 10

switchport mode access

!

interface FastEthernet0/4

switchport access vlan 20

switchport mode access

!

interface FastEthernet0/5

switchport access vlan 20

switchport mode access

!

interface FastEthernet0/6

switchport access vlan 30

switchport mode access

!

interface FastEthernet0/7

!

interface FastEthernet0/8

!

interface FastEthernet0/9

!

interface FastEthernet0/10

!

interface FastEthernet0/11

!

```
interface FastEthernet0/12
```

```
!
```

```
interface FastEthernet0/13
```

```
!
```

```
interface FastEthernet0/14
```

```
!
```

```
interface FastEthernet0/15
```

```
!
```

```
interface FastEthernet0/16
```

```
!
```

```
interface FastEthernet0/17
```

```
!
```

```
interface FastEthernet0/18
```

```
!
```

```
interface FastEthernet0/19
```

```
!
```

```
interface FastEthernet0/20
```

```
!
```

```
interface FastEthernet0/21
```

```
!
```

```
interface FastEthernet0/22
```

```
!
```

```
interface FastEthernet0/23
```

```
!
```

```
Switch#show vlan brief
```

```
VLAN Name Status Ports
```

```
-----
```

1 default active Fa0/7, Fa0/8, Fa0/9, Fa0/10

Fa0/11, Fa0/12, Fa0/13, Fa0/14

Fa0/15, Fa0/16, Fa0/17, Fa0/18

Fa0/19, Fa0/20, Fa0/21, Fa0/22

Fa0/23, Fa0/24, Gig0/1, Gig0/2

10 student active Fa0/2, Fa0/3

20 faculty active Fa0/4, Fa0/5

30 admin active Fa0/6

1002 fddi-default active

1003 token-ring-default active

1004 fddinet-default active

1005 trnet-default active

Switch#

Switch#show interfaces trunk

Port Mode Encapsulation Status Native vlan

Fa0/1 on 802.1q trunking 1

Port Vlans allowed on trunk

Fa0/1 1-1005

Port Vlans allowed and active in management domain

Fa0/1 1,10,20,30

Port Vlans in spanning tree forwarding state and not pruned

Fa0/1 1,10,20,30

Switch#show mac address-table

Mac Address Table

Vlan Mac Address Type Ports

```
1 00d0.ba7a.aa01 DYNAMIC Fa0/1
10 00d0.ba7a.aa01 DYNAMIC Fa0/1
20 00d0.ba7a.aa01 DYNAMIC Fa0/1
30 00d0.ba7a.aa01 DYNAMIC Fa0/1
```

Switch#

Router#show running-config

Building configuration...

Current configuration : 893 bytes

!

version 15.1

no service timestamps log datetime msec

no service timestamps debug datetime msec

no service password-encryption

!

hostname Router

!

!

!

!

!

!

!

!

ip cef

no ipv6 cef

!

!

!

!

license udi pid CISCO1941/K9 sn FTX15246C0G-

!

!

!

!

!

!

!

!

!

!

!

!

!

spanning-tree mode pvst

!

!

!

!

Switch>enable

Translating "Switch>enable"...domain server (255.255.255.255)

% Unknown command or computer name, or unable to find computer address

Router#show running-config

Building configuration...

Current configuration : 893 bytes

!

version 15.1

no service timestamps log datetime msec

no service timestamps debug datetime msec

no service password-encryption

!

hostname Router

!

!

!

!

!

!

!

!

ip cef

no ipv6 cef

!

!

Router#

pc0

Cisco Packet Tracer PC Command Line 1.0

C:\>ping 192.168.20.2

Pinging 192.168.20.2 with 32 bytes of data:

Request timed out.

Request timed out.

Request timed out.

Ping statistics for 192.168.20.2:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

Control-C

^C

C:\>

C:\>ping 192.168.10.1

Pinging 192.168.10.1 with 32 bytes of data:

Reply from 192.168.10.1: bytes=32 time<1ms TTL=255

Reply from 192.168.10.1: bytes=32 time<1ms TTL=255

Reply from 192.168.10.1: bytes=32 time<1ms TTL=255

Reply from 192.168.10.1: bytes=32 time<1ms TTL=255

Ping statistics for 192.168.10.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>ping 192.168.20.1

Pinging 192.168.20.1 with 32 bytes of data:

Reply from 192.168.20.1: bytes=32 time<1ms TTL=255

Reply from 192.168.20.1: bytes=32 time<1ms TTL=255

Reply from 192.168.20.1: bytes=32 time<1ms TTL=255

Reply from 192.168.20.1: bytes=32 time<1ms TTL=255

Ping statistics for 192.168.20.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>ifconfig

Invalid Command.

C:\>ipconfig

FastEthernet0 Connection:(default port)

Connection-specific DNS Suffix...:

Link-local IPv6 Address.....: FE80::2D0:BCFF:FE23:C81D

IPv6 Address.....: ::

IPv4 Address.....: 192.168.10.2

Subnet Mask.....: 255.255.255.0

Default Gateway.....: ::

192.168.10.1

Bluetooth Connection:

Connection-specific DNS Suffix...:

Link-local IPv6 Address.....: ::

IPv6 Address.....: ::

IPv4 Address.....: 0.0.0.0

Subnet Mask.....: 0.0.0.0

Default Gateway.....: ::

0.0.0.0

C:\>

pc1

Cisco Packet Tracer PC Command Line 1.0

C:\>ipconfig

FastEthernet0 Connection:(default port)

Connection-specific DNS Suffix...

Link-local IPv6 Address.....: FE80::202:16FF:FE01:19DB

IPv6 Address.....: ::

IPv4 Address.....: 192.168.10.3

Subnet Mask.....: 255.255.255.0

Default Gateway.....: ::

192.168.10.1

Bluetooth Connection:

Connection-specific DNS Suffix...

Link-local IPv6 Address.....: ::

IPv6 Address.....: ::

IPv4 Address.....: 0.0.0.0

Subnet Mask.....: 0.0.0.0

Default Gateway.....: ::

0.0.0.0

pc 2

Cisco Packet Tracer PC Command Line 1.0

C:\>ipconfig

FastEthernet0 Connection:(default port)

Connection-specific DNS Suffix...

Link-local IPv6 Address.....: FE80::2D0:BAFF:FE5C:297

IPv6 Address.....: ::

IPv4 Address.....: 192.168.20.2

Subnet Mask.....: 255.255.255.0

Default Gateway.....: ::

192.168.20.1

Bluetooth Connection:

Connection-specific DNS Suffix...

Link-local IPv6 Address.....: ::

IPv6 Address.....: ::

IPv4 Address.....: 0.0.0.0

Subnet Mask.....: 0.0.0.0

Default Gateway.....: ::

0.0.0.0

pc1

Cisco Packet Tracer PC Command Line 1.0

C:\>ipconfig

FastEthernet0 Connection:(default port)

Connection-specific DNS Suffix...

Link-local IPv6 Address.....: FE80::202:16FF:FE01:19DB

IPv6 Address.....: ::

IPv4 Address.....: 192.168.10.3

Subnet Mask.....: 255.255.255.0

Default Gateway.....: ::

192.168.10.1

Bluetooth Connection:

Connection-specific DNS Suffix..:

Link-local IPv6 Address.....: ::

IPv6 Address.....: ::

IPv4 Address.....: 0.0.0.0

Subnet Mask.....: 0.0.0.0

Default Gateway.....: ::

0.0.0.0

pc3

Cisco Packet Tracer PC Command Line 1.0

C:\>C:\>ipconfigFastEthernet0 Connection:(default port) Connection-specific DNS Suffix..: Link-local
IPv6 Address.....: FE80::2D0:BAFF:FE5C:297 IPv6 Address.....: :: IPv4
Address.....: 192.168.20.2 Subnet Mask.....

Invalid Command.

C:\>ipconfig

FastEthernet0 Connection:(default port)

Connection-specific DNS Suffix..:

Link-local IPv6 Address.....: FE80::250:FFF:FE42:8163

IPv6 Address.....: ::

IPv4 Address.....: 192.168.20.3

Subnet Mask.....: 255.255.255.0

Default Gateway.....: ::

192.168.20.1

Bluetooth Connection:

Connection-specific DNS Suffix...

Link-local IPv6 Address.....: ::

IPv6 Address.....: ::

IPv4 Address.....: 0.0.0.0

Subnet Mask.....: 0.0.0.0

Default Gateway.....: ::

0.0.0.0

pc4

Cisco Packet Tracer PC Command Line 1.0

C:\>ipconfig

FastEthernet0 Connection:(default port)

Connection-specific DNS Suffix...

Link-local IPv6 Address.....: FE80::202:4AFF:FE8C:2879

IPv6 Address.....: ::

IPv4 Address.....: 192.168.30.2

Subnet Mask.....: 255.255.255.0

Default Gateway.....: ::

192.168.30.1

Bluetooth Connection:

Connection-specific DNS Suffix...

Link-local IPv6 Address.....: ::

IPv6 Address.....: ::

IPv4 Address.....: 0.0.0.0

Subnet Mask.....: 0.0.0.0

Default Gateway.....: ::

0.0.0.0

C:\>

Similarity is PASSED Successfully



The Similarity Index is calculated by Levenshtein distance

Device ID : 04c61887ae0247d71ea74282965ea8d4