

Concept Description	Spec	SAS Program	R Program																				
25 entries per page Search: <table><tr><th>ROWORDER </th><th>VARIABLE_NAME </th><th>VARIABLE_LABEL </th><th>DERIVATION </th></tr><tr><td>001</td><td>TRTSDT</td><td></td><td>Using EX dataset - get TRTSDT as the numeric(datepart(EXSTDTC)) of the earliest record of a subject where EXCAT="TREATMENT PERIOD". Note that this date will be missing the subject has not been exposed to study treatment for any reason (or in case the team fails to capture the data in the EX dataset). Details: Subset the records from EX with the above given condition and sort by USUBJID and EXSTDTC and pick the earliest non-missing date.</td></tr><tr><td>002</td><td>TRTEDT</td><td></td><td>Using EX dataset - get TRTEDT as the numeric(datepart(EXENDTC)) of the latest record of a subject where EXCAT="TREATMENT PERIOD". Note that this date will be missing the subject has not been exposed to study treatment for any reason (or in case the team fails to capture the data in the EX dataset). Details: Subset the records from EX with the above given condition and sort by USUBJID and EXENDTC and pick the latest non-missing date. Also note that this is the simplest case of derivation of TRTEDT - there can be multiple conditions to check for depending on how to handle ongoing subjects - which will be protocol specific</td></tr><tr><td>003</td><td>SAFFL</td><td></td><td>Create this flag using the data collected in EX dataset. A subject would be called a safety subject if he has taken atleast one dose of study medication. In this example, populate SAFFL as Y for those subjects have taken atleast one dose of study medication (TRTSDT NE .). For the non-safety subjects this flag will be populated as N.</td></tr><tr><td>004</td><td>saf2fl</td><td></td><td>Create this flag using the data collected in EX and DA dataset. The drug accountability information is collected in DA dataset, that is, the information related to the dispensed and returned dose will be collected in DA dataset. This dataset has to be used to whether a subject has actually taken a dose or not. A subject would be called a safety subject if he has taken atleast one dose of study medication. In this example, populate saf2fl as Y for those subjects who have taken atleast one dose</td></tr></table>				ROWORDER	VARIABLE_NAME	VARIABLE_LABEL	DERIVATION	001	TRTSDT		Using EX dataset - get TRTSDT as the numeric(datepart(EXSTDTC)) of the earliest record of a subject where EXCAT="TREATMENT PERIOD". Note that this date will be missing the subject has not been exposed to study treatment for any reason (or in case the team fails to capture the data in the EX dataset). Details: Subset the records from EX with the above given condition and sort by USUBJID and EXSTDTC and pick the earliest non-missing date.	002	TRTEDT		Using EX dataset - get TRTEDT as the numeric(datepart(EXENDTC)) of the latest record of a subject where EXCAT="TREATMENT PERIOD". Note that this date will be missing the subject has not been exposed to study treatment for any reason (or in case the team fails to capture the data in the EX dataset). Details: Subset the records from EX with the above given condition and sort by USUBJID and EXENDTC and pick the latest non-missing date. Also note that this is the simplest case of derivation of TRTEDT - there can be multiple conditions to check for depending on how to handle ongoing subjects - which will be protocol specific	003	SAFFL		Create this flag using the data collected in EX dataset. A subject would be called a safety subject if he has taken atleast one dose of study medication. In this example, populate SAFFL as Y for those subjects have taken atleast one dose of study medication (TRTSDT NE .). For the non-safety subjects this flag will be populated as N.	004	saf2fl		Create this flag using the data collected in EX and DA dataset. The drug accountability information is collected in DA dataset, that is, the information related to the dispensed and returned dose will be collected in DA dataset. This dataset has to be used to whether a subject has actually taken a dose or not. A subject would be called a safety subject if he has taken atleast one dose of study medication. In this example, populate saf2fl as Y for those subjects who have taken atleast one dose
ROWORDER	VARIABLE_NAME	VARIABLE_LABEL	DERIVATION																				
001	TRTSDT		Using EX dataset - get TRTSDT as the numeric(datepart(EXSTDTC)) of the earliest record of a subject where EXCAT="TREATMENT PERIOD". Note that this date will be missing the subject has not been exposed to study treatment for any reason (or in case the team fails to capture the data in the EX dataset). Details: Subset the records from EX with the above given condition and sort by USUBJID and EXSTDTC and pick the earliest non-missing date.																				
002	TRTEDT		Using EX dataset - get TRTEDT as the numeric(datepart(EXENDTC)) of the latest record of a subject where EXCAT="TREATMENT PERIOD". Note that this date will be missing the subject has not been exposed to study treatment for any reason (or in case the team fails to capture the data in the EX dataset). Details: Subset the records from EX with the above given condition and sort by USUBJID and EXENDTC and pick the latest non-missing date. Also note that this is the simplest case of derivation of TRTEDT - there can be multiple conditions to check for depending on how to handle ongoing subjects - which will be protocol specific																				
003	SAFFL		Create this flag using the data collected in EX dataset. A subject would be called a safety subject if he has taken atleast one dose of study medication. In this example, populate SAFFL as Y for those subjects have taken atleast one dose of study medication (TRTSDT NE .). For the non-safety subjects this flag will be populated as N.																				
004	saf2fl		Create this flag using the data collected in EX and DA dataset. The drug accountability information is collected in DA dataset, that is, the information related to the dispensed and returned dose will be collected in DA dataset. This dataset has to be used to whether a subject has actually taken a dose or not. A subject would be called a safety subject if he has taken atleast one dose of study medication. In this example, populate saf2fl as Y for those subjects who have taken atleast one dose																				