

25 entries per page

Search:

ROWORDER	VARIABLE_NAME	VARIABLE_LABEL	DERIVATION
001	ADT	Analysis Date	A. For the source parameters: Extract date portion from VSDTC and convert it to numeric B. For the derived parameters, retain it from the corresponding source records
002	PARAM	Parameter	A. For the source parameters: Set to <code>propcase(VSPOS) VSTEST </code> (" VSSTRESU ") B. Create a derived parameter 'Sitting Mean Arterial Pressure (mmHg)' using the source parameters 'Sitting Systolic Blood Pressure (mmHg)' and 'Sitting Diastolic Blood Pressure (mmHg)'
003	PARAMCD	Parameter Code	A. For the source parameters: If VSPOS="SITTING" and VSTESTCD="SYSBP" then set to "STSBP" Else if VSPOS="SITTING" and VSTESTCD="DIABP" then set to "STDBP" B. For the derived parameter 'Sitting Mean Arterial Pressure (mmHg)' set to 'STMAP'
004	PARAMN	Parameter (N)	Populated using PARAMCD. Set to 1 when PARAMCD="STSBP". Set to 2 when PARAMCD="STDBP". Set to 3 then PARAMCD="STMAP".
005	PARAMTYP	Parameter Type	A. Populate it as 'DERIVED' when PARAMCD='STMAP'
006	AVAL	Analysis Value	A. For the source parameters: Set to VSSTRESN B. For the derived parameter 'Mean Arterial Pressure (mmHg)': 1. Transpose the data such that Systolic and Diastolic Blood pressure values at a timepoint are present as columns (say,STSBP and STDBP respectively) 2. Create AVAL as (STSBP+2*STDBP)/3. 3. Round the AVAL to two decimals

Showing 1 to 6 of 6 entries

<<

<

1

>

>>