

myCSG © 2026 |Area: ADaM|Concept: C1004 : ADaM BDS Derived Parameters Creation |Lesson: ADaM_C1004_L103a : Creation of New Parameter to Handle a Function of More Than One Parameter (BMI) |

Concept Description

Lesson Description

Slide

SAS Program

R Program

Introduction to ADaM data structures

- In clinical trials, data specified in the protocol is collected using case report forms
- The data collected using case report forms is called raw data
- Raw data is then transformed into CDISC compliant SDTM datasets
- SDTM data is used as input to create analysis datasets
- Analysis datasets compliant with CDISC ADaM standard are called ADaM datasets
- CDISC ADaM standard has three standard dataset structures
 - ADSL- Subject Level Analysis Dataset
 - BDS - Basic Data Structure
 - OCCDS - Occurrence Data Structure

Introduction to BDS structure

- The typical record structure in a BDS dataset is 'one or more records per subject, per analysis parameter, per analysis timepoint'
- An easy phrase to remember the structure of BDS is 'a dataset that is used to store the results of tests'
- A 'Result' is formally called an 'analysis value'
- A 'test' is formally called as 'analysis parameter'
- A 'test' could be conducted at different timepoints. Hence, we have the concept of 'analysis timepoint' as well.
- So, there are core variables prescribed in ADaM standard for 'analysis parameter' and 'analysis value'
- Variables for 'analysis parameter' are PARAMCD, PARAM, PARAMN
- Important variables for 'analysis result' are AVAL, AVALC.
- Variables for baseline value (BASE), change from baseline (CHG), and percent change from baseline (PCHG) are also considered as analysis values
- Similar to variables for 'analysis parameter' and 'analysis value', there are standard variables prescribed for 'analysis timepoint'
- Variables for 'analysis timepoint' include AVISIT, AVISITN, ADT, ATM, ADTM, ADY
- Here is a visualization of some variables for data related to vital signs

USUBJID	PARAMN	PARAMCD	PARAM	AVISIT	ADT	AVAL
CSG-1001	1	STSBP	Sitting Systolic Blood Pressure (mmHg)	Week 1	15APR2003	122
CSG-1001	2	STDBP	Sitting Diastolic Blood Pressure (mmHg)	Week 1	15APR2003	74

Introduction to rules governing addition of new parameters

- When creating analysis datasets, we typically run into the question of how to structure the derived information - whether to add rows or columns.
- ADaM implementation guide provides certain rules that guide on when to add the information as rows and when to add the information as columns
- Within the concept of rows - we end up with two options
 - Add the derived information as rows within existing parameter
 - Add the derived information as rows as a new parameter
- Of the 6 rules available, 3 rules are related to addition of new parameters

2.

Add additional derived data as needed for the analysis. The second step consists of adding derived rows and columns based on the initial set of ADaM dataset records and columns. ***The rules below govern this step.*** These rules are further described and illustrated in the remaining subsections of this section.

Rule 1: A parameter-invariant function of AVAL and BASE on the same row that does not involve a transform of BASE should be added as a new column.

Rule 2: A transformation of AVAL that does not meet the conditions of Rule 1 should be added as a new parameter, and AVAL should contain the transformed value.

Rule 3: A function of one or more rows within the same parameter for the purpose of creating an analysis timepoint should be added as a new row for the same parameter.

Rule 4: A function of multiple rows within a parameter should be added as a new parameter.

Rule 5: A function of more than one parameter should be added as a new parameter.

Rule 6: When there is more than one definition of baseline, each additional definition of baseline requires the creation of its own set of rows.