

myCSG © 2026 | Area: ADaM Concept: C1005 : ADaM BDS - Derived records creation | Lesson: ADaM_C1005_L101b : Creation of new records to hold the minimum and maximum values across postbaseline period |

Concept Description

Lesson Description

Site: SAS VideoSAS ProgramR Program

Let us say we have a TFL shell which summarizes the result and change from baseline at each visit and 'minimum value postbaseline' and 'maximum value postbaseline' as shown in the screenshot below.

	Treatment 1					
	Result			Change from Baseline		
	n	Mean	SD	n	Mean	SD
Baseline	xx	xx.x	xx.xx	xx	xx.x	xx.xx
Week 2	xx	xx.x	xx.xx	xx	xx.x	xx.xx
Week 4	xx	xx.x	xx.xx	xx	xx.x	xx.xx
Week 8	xx	xx.x	xx.xx	xx	xx.x	xx.xx
Week 24	xx	xx.x	xx.xx	xx	xx.x	xx.xx
Minimum value postbaseline	xx	xx.x	xx.xx	xx	xx.x	xx.xx
Maximum value postbaseline	xx	xx.x	xx.xx	xx	xx.x	xx.xx

For the derived datasets to be analysis-ready, we need to identify the minimum value and maximum values observed during postbaseline period. We also need to decide on how to organize the analysis dataset.

In ADaM implementation guide, there are certain rules that guide a user on when to add an analysis data point as a 'Row' and when to add it as a 'Column'.

Rule 3

A function of one or more rows within the same parameter for the purpose of creating an analysis timepoint should be added as a new row for the same parameter.

- 'Minimum value postbaseline' and 'Maximum value postbaseline' are considered as 'conceptual' analysis timepoints in the shell provided to us.
- So, we need to apply 'Rule 3' for this scenario and add new rows for the same parameter in this scenario.

In this lesson, we will see:

- How to identify the record with minimum value and append that record to parent dataset
- How to identify the record with maximum value and append that record to parent dataset
- Usage of 'DTYPE' variable to identify the derived records.