

ADVERTISEMENT

25 ▾	entries per page	Search:	ADVERTISEMENT
ROWORDER ▴	VARIABLE_NAME ▾	VARIABLE_LABEL ▾	DERIVATION ▾
001	ADT	Analysis Date	Extract the date portion from VSDTC and convert it to numeric value
002	PARAM	Parameter	Set to propcase(VSPOS) VSTEST " (" VSTRESUJ ") for the records with VSTESTCD in ("SYSBP" "DIABP").
003	PARAMCD	Parameter Code	If VSPOS="SITTING" and VSTESTCD="SYSBP" then set to "STSBP", Else if VSPOS="SITTING" and vSTESTCD="DIABP" then set to "STDBP"
004	PARAMN	Parameter (N)	If PARAMCD="STSBP" then set to 1, Else if PARAMCD="STDBP" then set to 2.
005	AVAL	Analysis Value	For the source records: Set to VSSTRESN Create a new record to hold the average result of the collections made on or before treatment start date.
006	AVISIT	Analysis Visit	A. For the souce records: If VS.VISIT="SCREEN 1" then set to "Screening 1", Else if VS.VISIT="SCREEN 2" then set to "Screening 2", Else set to propcase(VS.VISIT) B. For the record with ABLFL="Y" set to "Baseline" C. On the newly created to hold the average result of the colelctions made on or before treatment start date, set to "Screening Average".
007	AVISITN	Analysis Visit (N)	A. For the souce records: If VS.VISIT="SCREEN" then set to null, Else Set to VS.VISITNUM B. For the record with ABLFL="Y" set to 0 C. Set to -1 on the newly created record containing the average reuslt
008	DTYPE	Derivation Type	Set to 'AVERAGE' on the newly created record containg the screening average result
009	ABLFL	Baseline Record Flag	Set to 'Y' on the newly created record containing the screening average result
010	BASE	Baseline Value	Populate the AVAL from the record where ABLFL="Y" across all records of parmeter within a subject
011	CHG	Change from Baseline	Set to AVAL-BASE on the records where ADT>TRTSDT>.
012	PCHG	Percent Change from Baseline	Set to CHG/BASE*100 on records where ADT>TRTSDT>. and BASE is not in (0,.)
013	BASETYPE	Baseline Type	Set to 'AVERAGE'