

myCSG © 2026 | Area: ADaM | Concept: C1009 : ADaM BDS - Analysis Flags | Lesson: ADaM_C1009_L106 : ADLB - Creation of Analysis flags to identify worst postbaseline toxicity grades |

Concept Description

Spec

SAS Program

R Program

ADVERTISEMENT

25▼ entries per page

Search:

ROWORDER	VARIABLE_NAME	VARIABLE_LABEL	DERIVATION
001	ANL04FL	Analysis Flag 04 - Worst postbaseline - lowgrade	Populate as "Y" on worst postbaseline toxicity grade within each subject and parameter (ATOXGRL, higher the grade, worse the value). Postbaseline is identified using AVISITN (AVISITN > 1). If there exists more than one record on the same grade as worst grade, choose the earliest record when sorted by AVISITN.
002	ANL05FL	Analysis Flag 05 - Worst postbaseline - high grade	Populate as "Y" on worst postbaseline toxicity grade within each subject and parameter (ATOXGRH, higher the grade, worse the value). Postbaseline is identified using AVISITN (AVISITN > 1). If there exists more than one record on the same grade as worst grade, choose the earliest record when sorted by AVISITN.

Showing 1 to 2 of 2 entries

«

<

1

>

»

ADVERTISEMENT