

myCSG © 2026 | Area: ADaM Concept: C1013 : Time to event related variables | Lesson: ADaM_C1013_L103 : Overall Survival - Time to Death - Multiple Values for Censoring |

Spec

SAS Video

SAS Program

R Program

ADVERTISEMENT

25▼ entries per page

Search:

ROWORDER ▲	VARIABLE_NAME ▼	VARIABLE_LABEL ▼	DERIVATION ▼
001	STARTDT	Time-to-Event Origin Date for Subject	Set to TRTSDT
002	PARAM	Parameter	Create a parameter named 'Time to Death (Days)' for all safety subjects present in ADSL. See AVAL for derivation logic.
003	PARAMCD	Parameter Code	Set to 'T2DEATH' when PARAM="Time to Death (Days)"
004	ADT	Analysis Date	For PARAM="Time to Death (Days)" A. For subjects who died on the study(ADSL.DTHDT not null) after treatment start: Populate using ADSL.DTHDT B. For subjects who did not die on the study (ADSL.DTHDT is null) Populate with ADLS.EOSDT.
005	CNSR	Censor	For PARAM="Time to Death (Days)" A. For subjects who died on the study(ADSL.DTHDT not null) after treatment start: Set to 0 B. For subjects who did not die on the study (ADSL.DTHDT is null) Set to 1 when DCSREAS="Completed the study" Set to 2 when DCSREAS="Adverse Event" Set to 3 when DCSREAS="Lost to follow-up" Set to 4 when DCSREAS is not null and none of the above conditions are met
006	AVAL	Analysis Value	Set to ADT-STARTDT+1.
007	EVNTDESC	Event or Censoring Description	For PARAM="Time to Death (Days)" A. For subjects who died on the study(ADSL.DTHDT not null) after treatment start: Set to "Death" B. For subjects who did not die on the study (ADSL.DTHDT is null) Set to the end of study reason (ADSL.DCSREAS).

Showing 1 to 7 of 7 entries

« < 1 > »

ADVERTISEMENT