

Lesson Description	SAS Program	R Program	Report image								
Background • One of the word meanings for 'Shift' is ' to change direction' • Test results are always compared with a reference range to check whether they are 'normal' or 'abnormal' • The word 'range' itself indicates that there is an 'acceptable lower limit' and an 'acceptable upper limit • Anything below the lower limit of normal or above the upper limit of normal is considered 'abnormal' • In clinical trial data represented using SDTM, this abnormality is indicated using a variable called 'normal range indicator (--NRIND)' • --NRIND variable will be populated as 'Low' if the result is less than the lower limit of normal • --NRIND variable will be populated as 'High' if the result is greater than the upper limit of normal • Otherwise, it will be populated as 'Normal' • When a subject is administered a pharmaceutical product, it may have an impact on some of the body functions which could be measured by some lab tests • To assess the impact of the product, a comparison needs to be made between the subject's pre-treatment (baseline) normal range indicator vs post-treatment (post-baseline) normal range indicator for a test • 'Shift tables' are created to understand the change in pattern across subjects between baseline and postbaseline normal range indicators • Example: How many subjects had their baseline result normal but moved to 'low' post-baseline, how many subjects moved from their baseline 'Low' to post-baseline 'Normal' etc. • Some of the subjects may not have a baseline result • Some of the subjects may not have a postbaseline result • Some of the subjects may not have both baseline and postbaseline results • To leave no gaps in understanding for reviewers, shell creators may accommodate all of these scenarios in the shell by adding 'Missing' or 'No data' rows and columns in the shift tables. <tr><td colspan="4"></td></tr> <tr><td colspan="4"></td></tr>											