

Background

- In most of the databases that are used to capture clinical trial data, we get one variable for each question on the crf form
- Most of the CRF forms are designed to collect the information for different tests as separate variables
 - In the below example crf, LVEF and RVEF are being collected into two separate variables

ECHO : Echocardiogram

Question	Response
Assessment Performed? [ECHO_YN]	CVSTAT=NOT DONE when CVTESTCD=CVALL ☐ No ☐ Yes
If Yes, date performed [ECHODAT]	 CVDTC
Left ventricular ejection fraction (LVEF) (%) [LVEF]	 CVORRES/CVORRESU when CVTESTCD=LVEF
Estimated Right ventricular ejection fraction (RVEF) (%) [RVEF]	 CVORRES/CVORRESU when CVTESTCD=RVEF_E

- In most of the cases, the data from such prespecified tests are to be organized into a 'findings' domain which has a record structure of one record per test per timepoint
- This means, the data for different tests which is collected in separate variables has to be restructured in SDTM programming.

What will we learn in this lesson?

- In this lesson, we will see how to restructure the data collected in variables into rows

Visualization

SUBJECT	DATE	ITEM1	ITEM2	ITEM3	ITEM4
1001	01/JAN/2010	RESP1	RESP2	RESP3	RESP4

- | SUBJECT | DTC | TESTCD | RESULT |
|---------|------------|--------|--------|
| 1001 | 2010-01-01 | ITEM1 | RESP1 |
| 1001 | 2010-01-01 | ITEM2 | RESP2 |
| 1001 | 2010-01-01 | ITEM3 | RESP3 |
| 1001 | 2010-01-01 | ITEM4 | RESP4 |