

Background

- In clinical trials, certain data is collected at pre-specified timepoints
 - These pre-specified timepoints are called visits
 - Despite the best effort from the clinical trial personnel and subjects to stick to the schedule, collections may be missed at the specified timepoints
 - Data may be collected out of the prespecified time windows to make up for the missed assessments or to evaluate the safety of subjects on need basis
 - These out of window assessments are generally called unscheduled assessments
 - Generally, during the data collection, all of the unscheduled assessments are reported with a common 'timepoint' like 'Unscheduled'
 - When data is sorted based on the timepoint related variables (VISITNUM, VISIT), all unscheduled records get ordered together
-
- SDTM standard leaves it to the implementer on how to populate VISITNUM and VISIT on these unscheduled visits
 - One common approach used to handle this scenario is to populate the VISIT value on these unscheduled records is to use the previous scheduled visit and a suffix 'unscheduled x' to that visit
 - For example, an unscheduled visit that occurred after Day 3 scheduled visit, will have a value of 'Day 3 Unscheduled 1'.
 - This approach will need SV dataset - SDTM SV dataset will contain the start and end dates of all scheduled and unscheduled visits for all subjects

What will we learn in this lesson?

- In this lesson, we will see how to populate the visit and visitnum variables on unscheduled visits using SV dataset (which already has the re-sequenced visit values)