



Installation

Install Tailwind CSS with Vite

Setting up Tailwind CSS in a Vite project.

[Using React](#) [Using Vue](#) [Using Svelte](#)

1 Create your project

Start by creating a new Vite project if you don't have one set up already. The most common approach is to use [Create Vite](#).

Terminal



```
> npm create vite@latest my-project -- --template react
> cd my-project
```

2 Install Tailwind CSS

Install `tailwindcss` and its peer dependencies, then generate your `tailwind.config.js` and `postcss.config.js` files.

Terminal



```
> npm install -D tailwindcss postcss autoprefixer
> npx tailwindcss init -p
```

3 Configure your template paths

Add the paths to all of your template files in your `tailwind.config.js` file.

tailwind.config.js



```
/** @type {import('tailwindcss').Config} */
export default {
  content: [
    "./index.html",
    "./src/**/*.{js,ts,jsx,tsx}",
  ],
  theme: {
    extend: {},
  },
  plugins: [],
}
```

4 Add the Tailwind directives to your CSS

Add the `@tailwind` directives for each of Tailwind's layers to your `./src/index.css` file.

index.css



```
@tailwind base;
@tailwind components;
@tailwind utilities;
```

5 Start your build process

Run your build process with `npm run dev`.

Terminal



```
> npm run dev
```

6 Start using Tailwind in your project

Start using Tailwind's utility classes to style your content.

App.jsx



```
export default function App() {
```

```
return (  
  <h1 className="text-3xl font-bold underline">  
    Hello world!  
  </h1>  
)  
}
```

