

Airline Management System – DDL

Table Name: AIRPORTS

❖ COLUMN_NAME	❖ DATA_TYPE	❖ NULLABLE	DATA_DEFAULT	❖ COLUMN_ID	❖ COMMENTS
AIRPORT_CODE	VARCHAR2(3 BYTE)	No	(null)	1	(null)
AIRPORT_NAME	VARCHAR2(80 BYTE)	Yes	(null)	2	(null)
CITY	VARCHAR2(80 BYTE)	Yes	(null)	3	(null)
STATE	VARCHAR2(80 BYTE)	Yes	(null)	4	(null)
AIRPORT_CLASS	VARCHAR2(8 BYTE)	Yes	(null)	5	(null)

```
CREATE TABLE "DB101"."AIRPORTS"  
( "AIRPORT_CODE" VARCHAR2(3 BYTE) NOT NULL ENABLE,  
  "AIRPORT_NAME" VARCHAR2(80 BYTE),  
  "CITY" VARCHAR2(80 BYTE),  
  "STATE" VARCHAR2(80 BYTE),  
  "AIRPORT_CLASS" VARCHAR2(8 BYTE),  
  CONSTRAINT "AIRCODE_PK" PRIMARY KEY ("AIRPORT_CODE")  
  ENABLE  
)
```

Table Name: AIRCRAFTS

❖ COLUMN_NAME	❖ DATA_TYPE	❖ NULLABLE	DATA_DEFAULT	❖ COLUMN_ID	❖ COMMENTS
FLIGHT_NUMBER	VARCHAR2(20 BYTE)	No	(null)	1	(null)
MODEL_ID	NUMBER	No	(null)	2	(null)
TAIL_NUMBER	VARCHAR2(20 BYTE)	Yes	(null)	3	(null)

```
CREATE TABLE "DB101"."AIRCRAFT"  
( "FLIGHT_NUMBER" VARCHAR2(20 BYTE) NOT NULL ENABLE,  
  "MODEL_ID" NUMBER NOT NULL ENABLE,  
  "TAIL_NUMBER" VARCHAR2(20 BYTE),  
  CONSTRAINT "AIRCRAFT_PK" PRIMARY KEY ("FLIGHT_NUMBER")  
)
```

Table Name: AIRCRAFT_MODEL

	❖ COLUMN_NAME	❖ DATA_TYPE	❖ NULLABLE	DATA_DEFAULT	❖ COLUMN_ID	❖ COMMENTS
1	AIRCRAFT_MODEL_ID	VARCHAR2(20 BYTE)	No	(null)	1	(null)
2	MANUFACTURER	VARCHAR2(20 BYTE)	Yes	(null)	2	(null)
3	CAPACITY	VARCHAR2(20 BYTE)	Yes	(null)	3	(null)
4	MODEL	VARCHAR2(20 BYTE)	Yes	(null)	4	(null)

```
CREATE TABLE "DB101"."AIRCRAFT_MODEL"  
( "AIRCRAFT_MODEL_ID" VARCHAR2(20 BYTE) NOT NULL ENABLE,  
  "MANUFACTURER" VARCHAR2(20 BYTE),  
  "CAPACITY" VARCHAR2(20 BYTE),  
  "MODEL" VARCHAR2(20 BYTE),  
  CONSTRAINT "AIRCRAFT_MODEL_PK" PRIMARY KEY ("AIRCRAFT_MODEL_ID")  
  ENABLE  
)
```

Table Name: PASSENGER

❖ COLUMN_NAME	❖ DATA_TYPE	❖ NULLABLE	DATA_DEFAULT	❖ COLUMN_ID	❖ COMMENTS
PASSENGER_ID	VARCHAR2(128 BYTE)	No	(null)	1	(null)
FIRST_NAME	VARCHAR2(128 BYTE)	Yes	(null)	2	(null)
MIDDLE_NAME	VARCHAR2(128 BYTE)	Yes	(null)	3	(null)
LAST_NAME	VARCHAR2(128 BYTE)	Yes	(null)	4	(null)
PHONE_NUMBER	VARCHAR2(128 BYTE)	Yes	(null)	5	(null)
EMAIL_ADDRESS	VARCHAR2(128 BYTE)	Yes	(null)	6	(null)
STREET_ADDRESS	VARCHAR2(128 BYTE)	Yes	(null)	7	(null)
CITY	VARCHAR2(128 BYTE)	Yes	(null)	8	(null)
STATE	VARCHAR2(128 BYTE)	Yes	(null)	9	(null)
ZIPCODE	VARCHAR2(128 BYTE)	Yes	(null)	10	(null)

```
CREATE TABLE "DB101"."PASSENGER"
(
  "PASSENGER_ID" VARCHAR2(128 BYTE) NOT NULL ENABLE,
  "FIRST_NAME" VARCHAR2(128 BYTE),
  "MIDDLE_NAME" VARCHAR2(128 BYTE),
  "LAST_NAME" VARCHAR2(128 BYTE),
  "PHONE_NUMBER" VARCHAR2(128 BYTE),
  "EMAIL_ADDRESS" VARCHAR2(128 BYTE),
  "STREET_ADDRESS" VARCHAR2(128 BYTE),
  "CITY" VARCHAR2(128 BYTE),
  "STATE" VARCHAR2(128 BYTE),
  "ZIPCODE" VARCHAR2(128 BYTE),
  CONSTRAINT "PASSENGER_PK" PRIMARY KEY ("PASSENGER_ID")
  ENABLE
)
```

Table Name: RESERVATION

❖ COLUMN_NAME	❖ DATA_TYPE	❖ NULLABLE	DATA_DEFAULT	❖ COLUMN_ID	❖ COMMENTS
RESERVATION_ID	VARCHAR2(20 BYTE)	No	(null)	1	(null)
PASSENGER_ID	VARCHAR2(128 BYTE)	Yes	(null)	2	(null)
STATUS	VARCHAR2(20 BYTE)	Yes	(null)	3	(null)
TICKET_TYPE_ID	VARCHAR2(20 BYTE)	Yes	(null)	4	(null)
TRAVEL_CLASS	VARCHAR2(20 BYTE)	Yes	(null)	5	(null)
TRAVEL_DATE	VARCHAR2(20 BYTE)	Yes	(null)	6	(null)
RESERVATION_DATE	VARCHAR2(20 BYTE)	Yes	(null)	7	(null)

Table Name: PAYMENTS

❖ COLUMN_NAME	❖ DATA_TYPE	❖ NULLABLE	DATA_DEFAULT	❖ COLUMN_ID	❖ COMMENTS
PAYMENT_ID	VARCHAR2(20 BYTE)	No	(null)	1	(null)
RESERVATION_ID	VARCHAR2(20 BYTE)	Yes	(null)	2	(null)
PAYMENT_STATUS	VARCHAR2(20 BYTE)	Yes	(null)	3	(null)
TOTAL_PAYMENT	VARCHAR2(20 BYTE)	Yes	(null)	4	(null)
PAYMENT_DATE	DATE	Yes	(null)	5	(null)

Table Name: FLIGHT_SCHEDULE

❖ COLUMN_NAME	❖ DATA_TYPE	❖ NULLABLE	DATA_DEFAULT	❖ COLUMN_ID	❖ COMMENTS
FLIGHT_NUMBER	VARCHAR2(26 BYTE)	No	(null)	1 (null)	
ORIGIN_AIRPORT_CODE	VARCHAR2(3 BYTE)	Yes	(null)	2 (null)	
DESTINATION_AIRPORT_CODE	VARCHAR2(3 BYTE)	Yes	(null)	3 (null)	
DEPARTURE_TIME	VARCHAR2(8 BYTE)	Yes	(null)	4 (null)	
ARRIVAL_TIME	VARCHAR2(8 BYTE)	Yes	(null)	5 (null)	

```
CREATE TABLE "DB101"."FLIGHT_SCHEDULE"  
(  "FLIGHT_NUMBER" VARCHAR2(26 BYTE) NOT NULL ENABLE,  
  "ORIGIN_AIRPORT_CODE" VARCHAR2(3 BYTE),  
  "DESTINATION_AIRPORT_CODE" VARCHAR2(3 BYTE),  
  "DEPARTURE_TIME" VARCHAR2(8 BYTE),  
  "ARRIVAL_TIME" VARCHAR2(8 BYTE),  
  CONSTRAINT "FLIGHT_SCHEDULE_PK" PRIMARY KEY ("FLIGHT_NUMBER")  
  CONSTRAINT "ORIGIN_AIRPORT_CODE_F" FOREIGN KEY ("ORIGIN_AIRPORT_CODE")  
  REFERENCES "DB101"."AIRPORTS" ("AIRPORT_CODE") ENABLE,  
  CONSTRAINT "DESTINATION_AIRPORT_CODE_F" FOREIGN KEY ("DESTINATION_AIRPORT_CODE")  
  REFERENCES "DB101"."AIRPORTS" ("AIRPORT_CODE") ENABLE  
)
```

Table Name: FLIGHT_FARE

❖ COLUMN_NAME	❖ DATA_TYPE	❖ NULLABLE	DATA_DEFAULT	❖ COLUMN_ID	❖ COMMENTS
FLIGHT_LEGID	VARCHAR2(20 BYTE)	No	(null)	1 (null)	
CLASS	VARCHAR2(20 BYTE)	No	(null)	2 (null)	
FLIGHT_FARE	VARCHAR2(20 BYTE)	No	(null)	3 (null)	

```
CREATE TABLE "DB101"."FLIGHT_FARE"  
(  "FLIGHT_LEGID" VARCHAR2(20 BYTE) NOT NULL ENABLE,  
  "CLASS" VARCHAR2(20 BYTE) NOT NULL ENABLE,  
  "FLIGHT_FARE" VARCHAR2(20 BYTE) NOT NULL ENABLE,  
  CONSTRAINT "LEG_ID_FF_PK" PRIMARY KEY ("FLIGHT_LEGID", "CLASS")  
  ENABLE  
)
```

Table Name: LEGS

❖ COLUMN_NAME	❖ DATA_TYPE	❖ NULLABLE	DATA_DEFAULT	❖ COLUMN_ID	❖ COMMENTS
LEG_ID	VARCHAR2(20 BYTE)	No	(null)	1 (null)	
FLIGHT_NUMBER	VARCHAR2(20 BYTE)	No	(null)	2 (null)	
ORIGIN_AIRPORT_CODE	VARCHAR2(20 BYTE)	No	(null)	3 (null)	
DESTINATION_AIRPORT_CODE	VARCHAR2(20 BYTE)	No	(null)	4 (null)	
DEPARTURE_TIME	VARCHAR2(20 BYTE)	Yes	(null)	5 (null)	
ARRIVAL_TIME	VARCHAR2(20 BYTE)	Yes	(null)	6 (null)	

CREATE TABLE "DB101"."LEGS"

```
(  
  "LEG_ID" VARCHAR2(20 BYTE) NOT NULL ENABLE,  
  "FLIGHT_NUMBER" VARCHAR2(20 BYTE) NOT NULL ENABLE,  
  "ORIGIN_AIRPORT_CODE" VARCHAR2(20 BYTE) NOT NULL ENABLE,  
  "DESTINATION_AIRPORT_CODE" VARCHAR2(20 BYTE) NOT NULL ENABLE,  
  "DEPARTURE_TIME" VARCHAR2(20 BYTE),  
  "ARRIVAL_TIME" VARCHAR2(20 BYTE),  
  CONSTRAINT "LEG_ID_PK" PRIMARY KEY ("LEG_ID")  
  USING INDEX PCTFREE 10 INITRANS 2 MAXTRANS 255 COMPUTE STATISTICS  
  STORAGE(INITIAL 65536 NEXT 1048576 MINEXTENTS 1 MAXEXTENTS 2147483645  
  PCTINCREASE 0 FREELISTS 1 FREELIST GROUPS 1  
  BUFFER_POOL DEFAULT FLASH_CACHE DEFAULT CELL_FLASH_CACHE DEFAULT)  
  TABLESPACE "STUDENTS" ENABLE,  
  CONSTRAINT "DEST_FK" FOREIGN KEY ("DESTINATION_AIRPORT_CODE")  
  REFERENCES "DB101"."AIRPORTS" ("AIRPORT_CODE") ENABLE,  
  CONSTRAINT "ORG_FK" FOREIGN KEY ("ORIGIN_AIRPORT_CODE")  
  REFERENCES "DB101"."AIRPORTS" ("AIRPORT_CODE") ENABLE  
)
```

Table Name: ITINERARY_LEGS

❖ COLUMN_NAME	❖ DATA_TYPE	❖ NULLABLE	DATA_DEFAULT	❖ COLUMN_ID	❖ COMMENTS
LEG_ID	VARCHAR2(20 BYTE)	Yes	(null)	1 (null)	
RESERVATION_ID	VARCHAR2(20 BYTE)	Yes	(null)	2 (null)	

CREATE TABLE "DB101"."ITINERARY_LEGS"

```
(  
  "LEG_ID" VARCHAR2(20 BYTE),  
  "RESERVATION_ID" VARCHAR2(20 BYTE),  
  CONSTRAINT "RESERVATION_ID_FK" FOREIGN KEY ("RESERVATION_ID")  
  REFERENCES "DB101"."RESERVATION" ("RESERVATION_ID") ENABLE,  
  CONSTRAINT "LEG_ID_FK" FOREIGN KEY ("LEG_ID")  
  REFERENCES "DB101"."LEGS" ("LEG_ID") ENABLE  
)
```