

Integrate a passive double-walled sealed sheath around the tunneled hemodialysis catheter to create a permanently closed conduit, eliminating external fluid ingress without active valves.

Executive Technology Brief

Domain: fluidics_hydraulic

Technology Maturity: ENGINEERING_DEFINITION

Transfer Posture: Sponsored Validation

Problem: Documented problem 'patency variability' concerning tunneled hemodialysis catheter. User-submitted engineering problem (session input): "Why do tunneled hemodialysis catheters show conflicting patency outcomes across studies?". [fda_maude] 100 records retrieved live (1992-2070). Illustrative records: 'MAUDE report 1000: Injury [SAME AS ABOVE]'; 'MAUDE report 1000009: Injury [SLIP-CATH BEACON TIP CATHETER]'. LIMITS STAMPED INLINE: voluntary/regulatory reports; counts are NOT incidence rates; causality UNVERIFIED (Art. XXI.5). [europepmc] 10 records retrieved live (2025-2026). Illustrative records: 'Comprehensive management of hemodialysis catheter-related bloodstream infections: a narrative review.'; 'Central line-associated thrombosis and infections in patients with acute leukemias: The chicken or the egg dilemma.'. LIMITS STAMPED INLINE: literature context establishes the problem class, not event rates. Problem-existence basis: live records retrieved.

Mechanism: Closed-system technology that physically isolates the catheter lumen from external contaminants, thereby reducing contamination risk.

Architecture: PROPOSED architecture (no physical system exists): flow path / lumen architecture; pressure regulation element; sensing / feedback element (if closed-loop); termination interfaces (patient / reservoir) — realizing: Integrate a passive double-walled sealed sheath around the tunneled hemodialysis catheter to create a permanently closed conduit, eliminating external fluid ingress without active valves.

Governing Model: Fluid mechanics / hydraulics governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

Key Equations:

FLUID-001: Hagen-Poiseuille (laminar pipe flow). Expression: $Q = (\pi * r^4 * \Delta P) / (8 * \mu * L)$. Applicability to this invention: APPLICABLE; holds under: Newtonian fluid, laminar regime, rigid circular lumen, fully developed flow. Assumptions: CSF approximated as Newtonian (valid at shunt flow rates); no wall compliance effects. Engaged variables: r , L .

FLUID-002: Reynolds number. Expression: $Re = (\rho * v * D) / \mu$. Applicability to this invention: CONDITIONAL; holds under: circular section; single-phase flow. Assumptions: transition criterion $Re \sim 2300$ is a MODEL_DERIVED engineering rule of thumb. Engaged variables: NOT ESTABLISHED.

FLUID-003: Orifice flow (sharp-edged restriction). Expression: $Q = C_d * A * \sqrt{2 * \Delta P / \rho}$. Applicability to this invention: CONDITIONAL; holds under: turbulent orifice flow; C_d treated as MODEL_DERIVED until measured. Assumptions: $C_d \sim 0.6-0.65$ is an engineering prior, not a measurement. Engaged variables: NOT ESTABLISHED.

Kill Condition: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

Current State: ENGINEERING_DEFINITION. No physical prototype. No clinical validation.

Disclosure: This dossier distinguishes established evidence from proposals and unresolved questions.