

Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light for dissipation

Executive Technology Brief

Domain: thermal

Technology Maturity: ENGINEERING_DEFINITION

Transfer Posture: Sponsored Validation

Problem: Documented recurring problem 'onboard lithium battery thermal event' in aircraft/spacecraft installations: 10 NASA NTRS technical reports retrieved live at benchmark time on battery thermal-runaway behavior, calorimetry and fire safety. Titles: 'Enhancing Battery Safety with Fractional Thermal Runaway Calorimetry'; 'Practical Battery Thermal Modeling Techniques'; 'Comparative Analysis of Thermal Runaway Heat Output as a Function of Trigger Mechanism and Cell Format'. LIMITS STAMPED INLINE: technical-report literature establishes the problem class, NOT incident rates; single-source (NTRS) coverage disclosed (Art. XXI).

Mechanism: Thermal-optical hybrid management using semitransparent perovskite components

Architecture: PROPOSED architecture (no physical system exists): heat source characterization; conduction path / spreader; reject interface; safety limit interlock — realizing: Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light for dissipation

Governing Model: Thermal management / heat transfer governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

Key Equations:

TH-002: Convective heat transfer (Newton's law of cooling). Expression: $q = h * A * dT$. Applicability to this invention: APPLICABLE; holds under: steady state; h characterized for the actual flow geometry. Assumptions: h correlations are geometry- and regime-specific; using a correlation outside its validated range is forbidden. Engaged variables: dT .

TH-003: Series thermal resistance. Expression: $R_{total} = \sum(L_i / (k_i * A_i))$. Applicability to this invention: APPLICABLE; holds under: one-dimensional steady conduction through layers. Assumptions: interface contact resistances dominate at small scale and must be measured, not assumed zero. Engaged variables: R_{total} .

TH-001: Fourier conduction. Expression: $q = -k * A * dT/dx$. Applicability to this invention: APPLICABLE; holds under: steady state, isotropic conduction. Assumptions: steady-state conduction (no transient term); isotropic, homogeneous medium conductivity k ; one-dimensional gradient (lateral gradients neglected). Engaged variables: k , dT/dx .

Kill Condition: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

Current State: ENGINEERING_DEFINITION. No physical prototype. No clinical validation.

Disclosure: This dossier distinguishes established evidence from proposals and unresolved questions.