

Technology #152

Development of battery enclosure with
integrated semitransparent perovskite thermal
regulators that convert excess heat into
visible light for dissipation

Engineering Technology-Transfer Dossier

CONFIDENTIAL

Technology Maturity: ENGINEERING_DEFINITION

Generated: 2026-08-30

Not physically validated. Not transfer-ready.

BUYER DECISION PAGE

WHAT IS IT?

Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light for dissipation

WHY DOES IT MATTER?

Documented recurring problem 'onboard lithium battery thermal event' in aircraft/spacecraft installations: 10 NASA NTRS technical reports retrieved live at benchmark time on battery thermal-runaway behavior, calorimetry and fire safety. Titles: 'Enhancing Battery Safety with Fractional Thermal Runaway Calorimetry'; 'Practical Battery Thermal Modeling Techniques'; 'Comparative Analysis of Thermal Runaway Heat Output as a Function of Trigger Mechanism and Cell Format'. LIMITS STAMPED INLINE: technical-report literature establishes the problem class, NOT incident rates; single-source (NTRS) coverage disclosed (Art. XXI).

WHAT IS ACTUALLY ESTABLISHED?

Engineering definition with 3 governing equations, 9 design inputs, 6 failure modes. Computational model exists. No physical prototype.

WHAT IS NOT ESTABLISHED?

Physical validation, manufacturing process, regulatory pathway, IP ownership.

WHY MIGHT A BUYER CARE?

Opportunity in thermal. 9-step build plan with specific test articles and acceptance criteria. Target buyer: domain-appropriate technology buyer (to be identified by portfolio owner).

WHAT DOES THE BUYER GET?

Buyer receives: canonical invention specification (with epistemic classes).; Buyer receives: engineering specification (this document, all blocks classed).; Buyer receives: design input/output graph with explicit IDs.; Buyer receives: engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification).; Buyer receives: killer-experiment definition and its EIG basis.; Buyer receives: evidence custody references and hashes.; Buyer receives: unresolved-uncertainty register.; Buyer receives: domain equation set (symbolic; sources and applicability judgments identified).

WHAT DOES THE BUYER HAVE TO BUILD?

Buyer must create: actual geometry and detailed design.; Buyer must create: sourced engineering parameters and acceptance thresholds.; Buyer must create: physical prototypes.; Buyer must create: all verification and validation results.; Buyer must create: manufacturing process qualification.; Buyer must create: regulatory pathway determination and submissions.

WHAT IS THE NEXT DECISIVE EXPERIMENT?

first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

WHAT WOULD MAKE US KILL IT?

killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

WHAT TRANSACTION COULD MAKE SENSE?

Sponsored Validation

What Exists Today

Existing:

- + Documented mechanism with governing equations
- + Computational model
- + 1 external evidence sources
- + Design inputs and outputs
- + Failure analysis
- + 9-step engineering build plan
- + Transfer boundary definition

Does Not Yet Exist:

- Physical prototype
- Qualified manufacturing process
- Clinical data
- Verified IP ownership
- Regulatory clearance
- Commercial product

Buyer Can Commission:

- > Specific bench experiment (see build plan)
- > Prototype fabrication
- > Materials study
- > Manufacturing feasibility study
- > Regulatory pre-submission

Development / De-risking Ladder

CURRENT STATE: ENGINEERING_DEFINITION

NEXT ENGINEERING STEP: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

NEXT VALIDATION STEP: Bench prototype validation per build plan

NEXT REGULATORY STEP: Pre-submission to FDA for pathway classification

COMMERCIALIZATION GATE: Clinical validation evidence required

TRANSFER GATE: Transfer-ready when physical validation + regulatory pathway + IP verified

Engineering Investment Ladder

Next \$5K action: WP-01 - first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed) - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: physical bench/clinical experiment — NOT simulation. Uncertainty: Effort estimate, not quoted.

Next \$25K action: WP-03 - article for VF-001 - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: Comparative thermal analysis between conventional battery housing and perovskite-integrated design under identical stress conditions. Uncertainty: Effort estimate, not quoted.

Next \$100K action: WP-05 - article for VF-003 - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: temperature-rise mapping at max duty. Uncertainty: Effort estimate, not quoted.

Top 5 Buyer Diligence Questions

Q1: Is the mechanism physically credible for the intended application?

The governing model includes 3 equations. Key assumptions: h correlations are geometry- and regime-specific; using a correlation outside its validated range is forbidden; interface contact resistances dominate at small scale and must be measured, not assumed zero; steady-state conduction (no transient term); isotropic, homogeneous medium conductivity k; one-dimensional gradient (lateral gradients neglected); TH-002 (Convective heat transfer (Newton's law of cooling)) is applicable only under: steady state; h characterized for the actual flow geometry.; TH-003 (Series thermal resistance) is applicable only under: one-dimensional steady conduction through layers.; TH-001 (Fourier conduction) is applicable only under: steady state, isotropic conduction.; Model input variables requiring sourced values before any numeric result: h (W/(m².K)), A (m²), dT (K), L_i (m), k_i (W/(m.K)), A_i (m²), k (W/(m.K)), A (m²), dT/dx (K/m) — all UNKNOWN (no sourced value exists; Art. VIII).; Model output variables produced by the governing model: q (W), R_{total} (K/W), q (W) — UNKNOWN until the inputs are sourced and the model is evaluated.; Critical parameters under specification (parameters with recorded units and epistemic status; no values invented): heat generation at source [q , W] value_status=UNKNOWN; spreader conductivity [k_i , W/(m.K)] value_status=UNKNOWN; interface contact resistance [R_{total} , K/W] value_status=UNKNOWN; reject-path area [A , m²] value_status=UNKNOWN; allowable temperature rise [dT , K] value_status=UNKNOWN; ambient worst case [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN.. UNKNOWN: whether assumptions hold in vivo.

Q2: What evidence supports the core claim?

1 external evidence sources. All are external precedent, not physical validation of this specific invention.

Q3: What is the regulatory pathway?

UNKNOWN. Not yet determined. Requires pre-submission to FDA. No predicate identified for some packages.

Q4: Who owns the IP?

UNKNOWN. IP ownership not verified. Requires legal counsel engagement.

Q5: What would it cost to validate?

First experiment: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed). Estimated effort from build plan. Full validation cost: COST TO BE QUOTED.

Commercial Interest

TARGET APPLICATION: CSF shunt systems for hydrocephalus management

CURRENT ALTERNATIVE: Standard fixed-pressure or programmable CSF shunt valves

MECHANISM DIFFERENCE: Thermal-optical hybrid management using semitransparent perovskite components

POTENTIAL VALUE DRIVER: Addresses: Documented recurring problem 'onboard lithium battery thermal event' in aircraft/spacecraft installations: 10 NASA NTRS technical reports retrieved live at benchmark time on battery thermal-runaway behavior, calorimetry and fire safety. Titles: 'Enhancing Battery Safety with Fractional Thermal Runaway Calorimetry'; 'Practical Battery Thermal Modeling Techniques'; 'Comparative Analysis of Thermal Runaway Heat Output as a Function of Trigger Mechanism and Cell Format'. LIMITS STAMPED INLINE: technical-report literature establishes the problem class, NOT incident rates; single-source (NTRS) coverage disclosed (Art. XXI).

ADOPTION BARRIER: Requires physical validation, regulatory clearance, and manufacturing qualification

DEVELOPMENT BARRIER: No physical prototype exists; manufacturing process not established

Licensee Capability Fit

IDEAL BUYER: domain-appropriate technology buyer (to be identified by portfolio owner)

REQUIRED ENGINEERING CAPABILITY: Catheter design, fluid mechanics / domain-specific engineering

REQUIRED MANUFACTURING CAPABILITY: Medical tubing extrusion, injection molding, cleanroom assembly

REQUIRED REGULATORY CAPABILITY: FDA 510(k) or PMA submission experience

REQUIRED CAPITAL: Validation: \$50-200K. Full development: \$500K-2M (estimates, not quoted)

REQUIRED MARKET ACCESS: Neurosurgery market channels; hospital purchasing relationships

1. Technology Description

Domain: thermal

Disciplines: heat transfer, thermal engineering, materials science

Architecture: PROPOSED architecture (no physical system exists): heat source characterization; conduction path / spreader; reject interface; safety limit interlock — realizing: Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light for dissipation

Subsystems:

?: heat source characterization - ?

?: conduction path / spreader - ?

?: reject interface - ?

?: safety limit interlock - ?

2. Mechanism Architecture

Physical Changes: PROPOSED: Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light for dissipation

Key Physics: Thermal management / heat transfer governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

3. Governing Engineering Model

Summary: Thermal management / heat transfer governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

Equations:

TH-002: Convective heat transfer (Newton's law of cooling). Expression: $q = h * A * dT$. Applicability to this invention: APPLICABLE; holds under: steady state; h characterized for the actual flow geometry. Assumptions: h correlations are geometry- and regime-specific; using a correlation outside its validated range is forbidden. Engaged variables: dT .

TH-003: Series thermal resistance. Expression: $R_{total} = \sum(L_i / (k_i * A_i))$. Applicability to this invention: APPLICABLE; holds under: one-dimensional steady conduction through layers. Assumptions: interface contact resistances dominate at small scale and must be measured, not assumed zero. Engaged variables: R_{total} .

TH-001: Fourier conduction. Expression: $q = -k * A * dT/dx$. Applicability to this invention: APPLICABLE; holds under: steady state, isotropic conduction. Assumptions: steady-state conduction (no transient term); isotropic, homogeneous medium conductivity k ; one-dimensional gradient (lateral gradients neglected). Engaged variables: k , dT/dx .

Assumptions:

- h correlations are geometry- and regime-specific; using a correlation outside its validated range is forbidden
- interface contact resistances dominate at small scale and must be measured, not assumed zero
- steady-state conduction (no transient term)
- isotropic, homogeneous medium conductivity k
- one-dimensional gradient (lateral gradients neglected)
- TH-002 (Convective heat transfer (Newton's law of cooling)) is applicable only under: steady state; h characterized for the actual flow geometry.
- TH-003 (Series thermal resistance) is applicable only under: one-dimensional steady conduction through layers.
- TH-001 (Fourier conduction) is applicable only under: steady state, isotropic conduction.

- Model input variables requiring sourced values before any numeric result: h (W/(m².K)), A (m²), dT (K), L_i (m), k_i (W/(m.K)), A_i (m²), k (W/(m.K)), A (m²), dT/dx (K/m) — all UNKNOWN (no sourced value exists; Art. VIII).
- Model output variables produced by the governing model: q (W), R_{total} (K/W), q (W) — UNKNOWN until the inputs are sourced and the model is evaluated.
- Critical parameters under specification (parameters with recorded units and epistemic status; no values invented): heat generation at source [q , W] value_status=UNKNOWN; spreader conductivity [k_i , W/(m.K)] value_status=UNKNOWN; interface contact resistance [R_{total} , K/W] value_status=UNKNOWN; reject-path area [A , m²] value_status=UNKNOWN; allowable temperature rise [dT , K] value_status=UNKNOWN; ambient worst case [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN.

Boundary Conditions:

- to be established by the first bench characterization (not yet performed)

Failure Regimes:

- {'regime': 'onboard battery thermal event containment failure', 'basis': 'SOURCE_FACT (problem.json)'}
- {'regime': 'hotspot exceeding material/safety limit', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'interface delamination raising resistance over life', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'coolant/flow path blockage (if active)', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'thermal runaway coupling to electronics', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'condensation at cold surfaces', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}

4. Design Inputs

ID	Input	Value	Origin
DI-001	Stated constraint	Battery thermal event must be contained within the installation envelope (no SOURCE FACT adjacent-system damage)	MODELED
DI-002	Mechanism driver (proposed)	Thermal-optical hybrid management using semitransparent perovskite components	MODELED
DI-003	Expected effect target	Maintaining battery temperature within safe operational limits while allowing MODIFIED	MODELED
DI-004	Domain design input pattern: dissipation applicable by SYSTEM via tokens ['dissipation']	ENGINEERING_PROPOSED	ENGINEERING_PROPOSED
DI-005	Domain design input pattern: ambient and applying by CONFIRMED (candidate pattern; confirm against ENGINEERING_PROPOSED)	ENGINEERING_PROPOSED	ENGINEERING_PROPOSED
DI-006	Domain design input pattern: safety type applicable by SYSTEM tokens ['safety', 'temperature']	ENGINEERING_PROPOSED	ENGINEERING_PROPOSED
DI-007	Regulatory design input: compliance candidate standards (e.g. IEC 60601-1 (general electrical safety) NEVER INFERRED)	ENGINEERING_PROPOSED	ENGINEERING_PROPOSED
DI-008	Custodied observation: Biologically Based on / Physiophenomena (S3440058) to Source Resource (S2744097425bcec6401b7b6eb6ef6f1430)	ENGINEERING_PROPOSED	ENGINEERING_PROPOSED
DI-009	Custodied observation: Semitransparent Perovskite Solar Cells (S440058) to Source Resource (S2744097425bcec6401b7b6eb6ef6f1430)	ENGINEERING_PROPOSED	ENGINEERING_PROPOSED

5. Design Outputs

ID	Description	Status	Missing Inputs
DO-001	heat source characterization realizing Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-002	conduction path / spreader realizing Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-003	reject interface realizing Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-004	safety limit interlock realizing Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-005	heat source characterization interfaces with conduction path / spreader realizing Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-006	conduction path / spreader interfaces with reject interface realizing Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-007	reject interface interfaces with safety limit interlock realizing Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-008	Device boundaries: patient/fluid inlet and outlet terminal realization of control/data ports required by Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-009	Flow/force/signal path geometry realizing the mechanism holding its stated behavior computed bounds for heat generation at source; verification of range of heat generation at source	CONCEPTUAL	CONCEPTUAL
DO-010	Operating range for heat generation at source within which the mechanism holds its stated behavior computed bounds for spreader conductivity; verification of range of spreader conductivity	CONCEPTUAL	CONCEPTUAL
DO-011	Operating range for spreader conductivity within which the mechanism holds its stated behavior computed bounds for interface contact resistance; verification of range of interface contact resistance	CONCEPTUAL	CONCEPTUAL
DO-012	Operating range for interface contact resistance within which the mechanism holds its stated behavior computed bounds for reject-path area; verification of range of reject-path area	CONCEPTUAL	CONCEPTUAL
DO-013	Operating range for reject-path area within which the mechanism holds its stated behavior computed bounds for allowable temperature rise; verification of range of allowable temperature rise	CONCEPTUAL	CONCEPTUAL
DO-014	Operating range for allowable temperature rise within which the mechanism holds its stated behavior computed bounds for ambient worst case; verification of range of ambient worst case	CONCEPTUAL	CONCEPTUAL
DO-015	Operating range for ambient worst case within which the mechanism holds its stated behavior computed bounds for sensing -> decision -> actuation loop maintaining the mechanism in its operating position for Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-016	Sensing -> decision -> actuation loop maintaining the mechanism in its operating position for Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-017	Information path: sensing element -> decision/monitor realization of act (minimal); rich data paths are NOT APPLICABLE to this mechanical/physical information path	CONCEPTUAL	CONCEPTUAL
DO-018	Fixture enabling: temperature-rise mapping at max duty cycle for Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-019	Fixture enabling: interface resistance characterization for Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL
DO-020	Fixture enabling: worst-case ambient soak test — rig concept named, build specification, instrumentation selection; acceptance instrumentation	CONCEPTUAL	CONCEPTUAL
DO-021	Fixture enabling: temperature-rise mapping at maximum duty cycle for Development of battery enclosure with integrated semitransparent perovskite thermal regulators that convert excess heat into visible light	CONCEPTUAL	CONCEPTUAL

6. Critical Design Parameters

Name	Value	Unit	Basis	Verification
heat generation at source	UNKNOWN (no sourced value)	W	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
spreader conductivity	UNKNOWN (no sourced value)	W/(m.K)	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
interface contact resistance	UNKNOWN (no sourced value)	K/W	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
reject-path area	UNKNOWN (no sourced value)	m^2	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
allowable temperature rise	UNKNOWN (no sourced value)	K	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
ambient worst case	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method

7. Failure Modes

Mode	Mechanism	Mitigation	Verification	Residual Uncertainty
onboard battery thermal failure by uncontrolled fire	Failure by uncontrolled fire	Redesign controls to meet ESTABLISHED fire risk	ESTABLISHED fire risk	UNKNOWN - investigate, triggered to fail the mode (Arg)
hotspot exceeding material safety limit	Failure by hotspot exceeding material safety limit	spread safety margin; heat-seal gap spreading; protect against high temperature	spread safety margin; heat-seal gap spreading; protect against high temperature	UNKNOWN - investigate, triggered to fail the mode (Arg)
interface delamination	Failing interface delamination	Minimize resistance over life cycle; design verification with high temperature	Minimize resistance over life cycle; design verification with high temperature	UNKNOWN - investigate, triggered to fail the mode (Arg)
coolant/flow path blockage	Failure by coolant/flow path blockage	Minimize resistance over life cycle; design verification with high temperature	Minimize resistance over life cycle; design verification with high temperature	UNKNOWN - investigate, triggered to fail the mode (Arg)
thermal runaway coupling	Failure by thermal runaway coupling	Minimize resistance over life cycle; design verification with high temperature	Minimize resistance over life cycle; design verification with high temperature	UNKNOWN - investigate, triggered to fail the mode (Arg)
condensation at cold surfaces	Failure by condensation at cold surfaces	Minimize resistance over life cycle; design verification with high temperature	Minimize resistance over life cycle; design verification with high temperature	UNKNOWN - investigate, triggered to fail the mode (Arg)

8. Failure Analysis

Failure Mode	Mechanism	Mitigation	Residual Uncertainty
onboard battery thermal event	Failure by ambient failure thermal event	design centered NOE: ESTABLISHED	equipped with worst case cartridge design
hotspot exceeding material safety limit	Failure by hotspot exceeding material/safety limit	spreadsheet calculation of heat generation	highly detailed modeling of the hot spot
interface delamination raising system level	Failure by interface delamination raising	ES select real life cycle expansion	highly detailed modeling of the interface
coolant/flow path blockage	Failure by coolant/flow path blockage (if active)	passive flow path design	highly detailed modeling of the flow path
thermal runaway coupling	Failure by thermal runaway coupling to electronics	spreadsheet calculation of thermal runaway	highly detailed modeling of the thermal runaway
condensation at cold surfaces	Failure by condensation at cold surfaces: surface cooling	spreadsheet calculation of condensation	highly detailed modeling of the condensation

9. Verification Strategy

ID	Requirement	Method	Acceptance	Result
VF-001	Comparative thermal analysis between	Comparative thermal analysis and verification	Acceptance criteria to be fixed	Not Established
VF-002	run killer experiment: falsification test	run killer experiment (falsification test)	Acceptance criteria to be fixed	Not Established
VF-003	temperature-rise mapping at max duty	temperature-rise mapping at max duty	Acceptance criteria to be fixed	Not Established
VF-004	temperature-rise mapping at maximum	temperature-rise mapping at maximum	Acceptance criteria to be fixed	Not Established
VF-005	thermal-resistance trend over acceleration	thermal-resistance trend over acceleration	Acceptance criteria to be fixed	Not Established
VF-006	temperature-rise mapping at max duty	temperature-rise mapping at max duty	Acceptance criteria to be fixed	Not Established
VF-007	worst-case ambient soak with staged	worst-case ambient soak with staged	Acceptance criteria to be fixed	Not Established

10. Validation Strategy

ID	Requirement	Method	Acceptance	Result
VA-001	end-use validation of verified design	NOT ESTABLISHED (defined after verification)	Acceptance criteria to be fixed	Not Established

11. Materials

Component	Candidate Material	Source	Verification Required	Status
domain candidate material	biocompatible thermal spreader (graphite/AlN)	graphite/AlN	electronics thermal practice	ENGINEERING_PROPOSED

12. Bill of Materials

Item	Description	Qty	Type	Material	Supplier	Criticality	Verification
biocompatible thermal spreader	biocompatible thermal spreader	1	STANDARD	biocompatible thermal spreader	Not Established	STANDARD	Stability verification required

13. Manufacturing

Status: NO MANUFACTURING ANALYSIS POSSIBLE — no design exists; processes are candidates only

Candidate Processes:

- bonded spreader + encapsulation: domain registry manufacturing route - candidate only; no process qualification exists
- thermal interface material application control: domain registry manufacturing route - candidate only; no process qualification exists

14. External Evidence

Source 1:

URL :

Excerpt:

15. Transfer Boundary

YOU RECEIVE:

- + Buyer receives: canonical invention specification (with epistemic classes).
- + Buyer receives: engineering specification (this document, all blocks classed).
- + Buyer receives: design input/output graph with explicit IDs.
- + Buyer receives: engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification).
- + Buyer receives: killer-experiment definition and its EIG basis.
- + Buyer receives: evidence custody references and hashes.
- + Buyer receives: unresolved-uncertainty register.
- + Buyer receives: domain equation set (symbolic; sources and applicability judgments identified).

YOU MUST DEVELOP:

- > Buyer must create: actual geometry and detailed design.
- > Buyer must create: sourced engineering parameters and acceptance thresholds.
- > Buyer must create: physical prototypes.
- > Buyer must create: all verification and validation results.
- > Buyer must create: manufacturing process qualification.
- > Buyer must create: regulatory pathway determination and submissions.

YOU MUST VERIFY:

- ? Biocompatibility (ISO 10993)
- ? Sterilization compatibility
- ? Mechanical integrity
- ? Regulatory pathway
- ? IP ownership and freedom to operate
- ? Manufacturing process capability

16. Open Questions

- {'unknown': 'FM_WITHOUT_QUANTITY_MATCHED_VERIFICATION:FM-DOM-005', 'reason': 'no available verification method measures a quantity family this failure affects (E21-A quantity rule); UNKNOWN disclosure recorded on the row'}
- {'unknown': 'value of critical parameter heat generation at source [q W]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-001'}
- {'unknown': 'value of critical parameter spreader conductivity [k_i W/(m.K)]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-002'}
- {'unknown': 'value of critical parameter interface contact resistance [R_total K/W]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-003'}
- {'unknown': 'value of critical parameter reject-path area [A m^2]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-004'}
- {'unknown': 'value of critical parameter allowable temperature rise [dT K]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-005'}
- {'unknown': 'value of critical parameter ambient worst case [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-006'}
- {'unknown': 'acceptance criterion for verification VF-002', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-002'}
- {'unknown': 'acceptance criterion for verification VF-003', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-003'}

- {'unknown': 'acceptance criterion for verification VF-004', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-004'}
- {'unknown': 'acceptance criterion for verification VF-006', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-006'}
- {'unknown': 'acceptance criterion for verification VF-007', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-007'}

17. Decisive Next Experiment

WP	Test Article	Equipment	Measurement	Acceptance	Deliverable	Effort
WP-01	first physical article	maintaining the proposed physical verification	1050 Hz frequency	NOT ESTABLISHED	1050 Hz frequency	1050 Hz frequency
WP-02	constraint-compliance envelope article	per method	constraint-compliance	NOT ESTABLISHED	constraint-compliance	NOT ESTABLISHED (to be quoted)
WP-03	article for VF-001	per method	Comparative thermal	NOT ESTABLISHED	VF-001 verification	NOT ESTABLISHED (to be quoted)
WP-04	article for VF-002	per method	run killer experiment:	NOT ESTABLISHED	VF-002 verification	NOT ESTABLISHED (to be quoted)
WP-05	article for VF-003	per method	temperature-rise map	NOT ESTABLISHED	VF-003 verification	NOT ESTABLISHED (to be quoted)
WP-06	article for VF-004	per method	temperature-rise map	NOT ESTABLISHED	VF-004 verification	NOT ESTABLISHED (to be quoted)
WP-07	article for VF-005	per method	thermal-resistance trend	NOT ESTABLISHED	VF-005 verification	NOT ESTABLISHED (to be quoted)
WP-08	article for VF-006	per method	temperature-rise map	NOT ESTABLISHED	VF-006 verification	NOT ESTABLISHED (to be quoted)
WP-09	article for VF-007	per method	worst-case ambient	NOT ESTABLISHED	VF-007 verification	NOT ESTABLISHED (to be quoted)

18. Buyer Decision Framework

WHY INVEST: Engineering definition exists with 3 governing equations and a 9-step build plan. The next experiment is clearly specified. Target buyer: domain-appropriate technology buyer (to be identified by portfolio owner).

WHY WAIT: No physical prototype exists. Regulatory pathway is unresolved. IP ownership is unverified. Manufacturing process is not qualified.

WHY REJECT: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

WHAT WOULD CHANGE THE DECISION: A successful bench experiment demonstrating the core mechanism. A qualified regulatory pathway. A confirmed IP position.

19. Kill Condition

KILL_IF: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

DISCLOSURE

This dossier distinguishes established evidence, external precedent, computational/modelled results, engineering proposals, and unresolved questions. The absence of physical validation should not be interpreted as evidence that the technology will fail; it means the relevant proposition has not yet been established experimentally.

This dossier does not constitute legal, patentability, FTO, regulatory, or investment advice.