

Technology #35: increase the sensing threshold of the leadless pacemaker to suppress oversensing

Technology Domain: rf_wireless

Mechanism: PROPOSED architecture (no physical system exists): transmit chain + power limits; channel / tissue path (path loss model); receive chain + detection; regulatory exposure constraint (SAR) — realizing: increase the sensing threshold of the leadless pacemaker to suppress oversensing

Maturity: ENGINEERING_DEFINITION

Current State: No physical prototype. Computational model and engineering definition exist.

Key Risk: killer experiment fails: falsification_test_from_candidate (pre-registered pass/fail required before any transfer)

Next Experiment: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

Buyer Receives: canonical invention specification (with epistemic classes); engineering specification (this document, all blocks classed); design input/output graph with explicit IDs; engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification); killer-experiment definition and its EIG basis; evidence custody references and hashes; unresolved-uncertainty register; domain equation set (symbolic; sources and applicability judgments identified)

Buyer Must Build: actual geometry and detailed design; sourced engineering parameters and acceptance thresholds; physical prototypes; all verification and validation results; manufacturing process qualification; regulatory pathway determination and submissions

Transfer Posture: Sponsored Validation

Target Buyer: domain-appropriate technology buyer (to be identified by portfolio owner)

CONFIDENTIAL. See full engineering dossier for details.