

Technology #140

Implement wireless vibration and temperature sensors on draft gear mechanisms and journal bearings with onboard analytics

Engineering Technology-Transfer Dossier

CONFIDENTIAL

Technology Maturity: ENGINEERING_DEFINITION

Generated: 2026-08-30

Not physically validated. Not transfer-ready.

BUYER DECISION PAGE

WHAT IS IT?

Implement wireless vibration and temperature sensors on draft gear mechanisms and journal bearings with onboard analytics

WHY DOES IT MATTER?

Documented recurring problem 'rolling-stock mechanical/electrical equipment failure' (FRA cause family E): 3 of 25 FRA Form 54 accidents in the retrieved window stem from equipment causes. Causes observed: 'Draft gear/mechanism broken or defective (including yoke)'; 'Journal (roller bearing) failure from overheating'; 'Other coupler and draft system defects, (CAR) (Provide detailed description in narrative)'; speeds 7–37 mph. LIMITS STAMPED INLINE: carrier-reported; cause codes are classifications, not proven root causes; above-threshold events only (Art. XXI.5 analog).

WHAT IS ACTUALLY ESTABLISHED?

Engineering definition with 3 governing equations, 10 design inputs, 6 failure modes. Computational model exists. No physical prototype.

WHAT IS NOT ESTABLISHED?

Physical validation, manufacturing process, regulatory pathway, IP ownership.

WHY MIGHT A BUYER CARE?

Opportunity in thermal. 9-step build plan with specific test articles and acceptance criteria. Target buyer: domain-appropriate technology buyer (to be identified by portfolio owner).

WHAT DOES THE BUYER GET?

Buyer receives: canonical invention specification (with epistemic classes).; Buyer receives: engineering specification (this document, all blocks classed).; Buyer receives: design input/output graph with explicit IDs.; Buyer receives: engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification).; Buyer receives: killer-experiment definition and its EIG basis.; Buyer receives: evidence custody references and hashes.; Buyer receives: unresolved-uncertainty register.; Buyer receives: domain equation set (symbolic; sources and applicability judgments identified).

WHAT DOES THE BUYER HAVE TO BUILD?

Buyer must create: actual geometry and detailed design.; Buyer must create: sourced engineering parameters and acceptance thresholds.; Buyer must create: physical prototypes.; Buyer must create: all verification and validation results.; Buyer must create: manufacturing process qualification.; Buyer must create: regulatory pathway determination and submissions.

WHAT IS THE NEXT DECISIVE EXPERIMENT?

first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

WHAT WOULD MAKE US KILL IT?

killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

WHAT TRANSACTION COULD MAKE SENSE?

Sponsored Validation

What Exists Today

Existing:

- + Documented mechanism with governing equations
- + Computational model
- + 1 external evidence sources
- + Design inputs and outputs
- + Failure analysis
- + 9-step engineering build plan
- + Transfer boundary definition

Does Not Yet Exist:

- Physical prototype
- Qualified manufacturing process
- Clinical data
- Verified IP ownership
- Regulatory clearance
- Commercial product

Buyer Can Commission:

- > Specific bench experiment (see build plan)
- > Prototype fabrication
- > Materials study
- > Manufacturing feasibility study
- > Regulatory pre-submission

Development / De-risking Ladder

CURRENT STATE: ENGINEERING_DEFINITION

NEXT ENGINEERING STEP: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

NEXT VALIDATION STEP: Bench prototype validation per build plan

NEXT REGULATORY STEP: Pre-submission to FDA for pathway classification

COMMERCIALIZATION GATE: Clinical validation evidence required

TRANSFER GATE: Transfer-ready when physical validation + regulatory pathway + IP verified

Engineering Investment Ladder

Next \$5K action: WP-01 - first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed) - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: physical bench/clinical experiment — NOT simulation. Uncertainty: Effort estimate, not quoted.

Next \$25K action: WP-03 - article for VF-001 - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: Simulate bearing overheating and draft gear stress under laboratory conditions while monitoring sensor readings against actual failure th.... Uncertainty: Effort estimate, not quoted.

Next \$100K action: WP-05 - article for VF-003 - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: temperature-rise mapping at max duty. Uncertainty: Effort estimate, not quoted.

Top 5 Buyer Diligence Questions

Q1: Is the mechanism physically credible for the intended application?

The governing model includes 3 equations. Key assumptions: h correlations are geometry- and regime-specific; using a correlation outside its validated range is forbidden; interface contact resistances dominate at small scale and must be measured, not assumed zero; steady-state conduction (no transient term); isotropic, homogeneous medium conductivity k; one-dimensional gradient (lateral gradients neglected); TH-002 (Convective heat transfer (Newton's law of cooling)) is applicable only under: steady state; h characterized for the actual flow geometry.; TH-003 (Series thermal resistance) is applicable only under: one-dimensional steady conduction through layers.; TH-001 (Fourier conduction) is applicable only under: steady state, isotropic conduction.; Model input variables requiring sourced values before any numeric result: h (W/(m².K)), A (m²), dT (K), L_i (m), k_i (W/(m.K)), A_i (m²), k (W/(m.K)), A (m²), dT/dx (K/m) — all UNKNOWN (no sourced value exists; Art. VIII).; Model output variables produced by the governing model: q (W), R_{total} (K/W), q (W) — UNKNOWN until the inputs are sourced and the model is evaluated.; Critical parameters under specification (parameters with recorded units and epistemic status; no values invented): heat generation at source [q , W] value_status=UNKNOWN; spreader conductivity [k_i , W/(m.K)] value_status=UNKNOWN; interface contact resistance [R_{total} , K/W] value_status=UNKNOWN; reject-path area [A , m²] value_status=UNKNOWN; allowable temperature rise [dT , K] value_status=UNKNOWN; ambient worst case [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN.. UNKNOWN: whether assumptions hold in vivo.

Q2: What evidence supports the core claim?

1 external evidence sources. All are external precedent, not physical validation of this specific invention.

Q3: What is the regulatory pathway?

UNKNOWN. Not yet determined. Requires pre-submission to FDA. No predicate identified for some packages.

Q4: Who owns the IP?

UNKNOWN. IP ownership not verified. Requires legal counsel engagement.

Q5: What would it cost to validate?

First experiment: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed). Estimated effort from build plan. Full validation cost: COST TO BE QUOTED.

Commercial Interest

TARGET APPLICATION: CSF shunt systems for hydrocephalus management

CURRENT ALTERNATIVE: Standard fixed-pressure or programmable CSF shunt valves

MECHANISM DIFFERENCE: Condition monitoring using sensors and data processing

POTENTIAL VALUE DRIVER: Addresses: Documented recurring problem 'rolling-stock mechanical/electrical equipment failure' (FRA cause family E): 3 of 25 FRA Form 54 accidents in the retrieved window stem from equipment causes. Causes observed: 'Draft gear/mechanism broken or defective (including yoke)'; 'Journal (roller bearing) failure from overheating'; 'Other coupler and draft system defects, (CAR) (Provide detailed description in narrative)'; speeds 7–37 mph. LIMITS STAMPED INLINE: carrier-reported; cause codes are classifications, not proven root causes; above-threshold events only (Art. XXI.5 analog).

ADOPTION BARRIER: Requires physical validation, regulatory clearance, and manufacturing qualification

DEVELOPMENT BARRIER: No physical prototype exists; manufacturing process not established

Licensee Capability Fit

IDEAL BUYER: domain-appropriate technology buyer (to be identified by portfolio owner)

REQUIRED ENGINEERING CAPABILITY: Catheter design, fluid mechanics / domain-specific engineering

REQUIRED MANUFACTURING CAPABILITY: Medical tubing extrusion, injection molding, cleanroom assembly

REQUIRED REGULATORY CAPABILITY: FDA 510(k) or PMA submission experience

REQUIRED CAPITAL: Validation: \$50-200K. Full development: \$500K-2M (estimates, not quoted)

REQUIRED MARKET ACCESS: Neurosurgery market channels; hospital purchasing relationships

1. Technology Description

Domain: thermal

Disciplines: heat transfer, thermal engineering, materials science

Architecture: PROPOSED architecture (no physical system exists): heat source characterization; conduction path / spreader; reject interface; safety limit interlock — realizing: Implement wireless vibration and temperature sensors on draft gear mechanisms and journal bearings with onboard analytics

Subsystems:

?: heat source characterization - ?

?: conduction path / spreader - ?

?: reject interface - ?

?: safety limit interlock - ?

2. Mechanism Architecture

Physical Changes: PROPOSED: Implement wireless vibration and temperature sensors on draft gear mechanisms and journal bearings with onboard analytics

Key Physics: Thermal management / heat transfer governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

3. Governing Engineering Model

Summary: Thermal management / heat transfer governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

Equations:

TH-002: Convective heat transfer (Newton's law of cooling). Expression: $q = h * A * dT$. Applicability to this invention: APPLICABLE; holds under: steady state; h characterized for the actual flow geometry. Assumptions: h correlations are geometry- and regime-specific; using a correlation outside its validated range is forbidden. Engaged variables: dT .

TH-003: Series thermal resistance. Expression: $R_{total} = \sum(L_i / (k_i * A_i))$. Applicability to this invention: CONDITIONAL; holds under: one-dimensional steady conduction through layers. Assumptions: interface contact resistances dominate at small scale and must be measured, not assumed zero. Engaged variables: NOT ESTABLISHED.

TH-001: Fourier conduction. Expression: $q = -k * A * dT/dx$. Applicability to this invention: APPLICABLE; holds under: steady state, isotropic conduction. Assumptions: steady-state conduction (no transient term); isotropic, homogeneous medium conductivity k ; one-dimensional gradient (lateral gradients neglected). Engaged variables: dT/dx .

Assumptions:

- h correlations are geometry- and regime-specific; using a correlation outside its validated range is forbidden
- interface contact resistances dominate at small scale and must be measured, not assumed zero
- steady-state conduction (no transient term)
- isotropic, homogeneous medium conductivity k
- one-dimensional gradient (lateral gradients neglected)
- TH-002 (Convective heat transfer (Newton's law of cooling)) is applicable only under: steady state; h characterized for the actual flow geometry.
- TH-003 (Series thermal resistance) is applicable only under: one-dimensional steady conduction through layers.
- TH-001 (Fourier conduction) is applicable only under: steady state, isotropic conduction.

- Model input variables requiring sourced values before any numeric result: h (W/(m².K)), A (m²), dT (K), L_i (m), k_i (W/(m.K)), A_i (m²), k (W/(m.K)), A (m²), dT/dx (K/m) — all UNKNOWN (no sourced value exists; Art. VIII).
- Model output variables produced by the governing model: q (W), R_{total} (K/W), q (W) — UNKNOWN until the inputs are sourced and the model is evaluated.
- Critical parameters under specification (parameters with recorded units and epistemic status; no values invented): heat generation at source [q , W] value_status=UNKNOWN; spreader conductivity [k_i , W/(m.K)] value_status=UNKNOWN; interface contact resistance [R_{total} , K/W] value_status=UNKNOWN; reject-path area [A , m²] value_status=UNKNOWN; allowable temperature rise [dT , K] value_status=UNKNOWN; ambient worst case [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN.

Boundary Conditions:

- to be established by the first bench characterization (not yet performed)

Failure Regimes:

- {'regime': 'in-service mechanical or electrical equipment failure', 'basis': 'SOURCE_FACT (problem.json)'}
- {'regime': 'hotspot exceeding material/safety limit', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'interface delamination raising resistance over life', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'coolant/flow path blockage (if active)', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'thermal runaway coupling to electronics', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'condensation at cold surfaces', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}

4. Design Inputs

ID	Input	Value	Origin
DI-001	Stated constraint	Failure detection must catch degradation before en-route failure at mainline speed or onboard solutions must be available	SOURCE_4A10F
DI-002	Mechanism driver (proposed)	Condition monitoring using sensors and data processing	MODELLED
DI-003	Expected effect target	Early detection of mechanical degradation before failure occurs at mainline speed	MODELLED
DI-004	Domain design input pattern: dissipation applicability by system via tokens ['system']	condition applicability by TFD via tokens ['condition']	ENGINEERING_PROPOSED
DI-005	Domain design input pattern: ambient condition applicability by TFD via tokens ['condition']	safety detection applicability by TFD via tokens ['temperature']	ENGINEERING_PROPOSED
DI-006	Domain design input pattern: safety detection applicability by TFD via tokens ['temperature']	compliance with the standards standards (EN 150660) (gained electric path safety) (known) (never inferred)	ENGINEERING_PROPOSED
DI-007	Regulatory design input: compliance with the standards standards (EN 150660) (gained electric path safety) (known) (never inferred)	custodied observation: Towards the end of the project, the system is expected to be able to detect and report faults in the system	ENGINEERING_PROPOSED
DI-008	Custodied observation: Towards the end of the project, the system is expected to be able to detect and report faults in the system	custodied observation: Conditions of the system are expected to be able to detect and report faults in the system	ENGINEERING_PROPOSED
DI-009	Custodied observation: Conditions of the system are expected to be able to detect and report faults in the system	custodied observation: The New South Wales Police Progress article PAR 606580 content_hash f661ae8d4f501f006162d1f546b0f0cb114f63a33ff1aea	ENGINEERING_PROPOSED
DI-010	Custodied observation: The New South Wales Police Progress article PAR 606580 content_hash f661ae8d4f501f006162d1f546b0f0cb114f63a33ff1aea		ENGINEERING_PROPOSED

5. Design Outputs

ID	Description	Status	Missing Inputs
DO-001	heat source characterization realizing Implement wireless vibration and temperature sensors on draft gear interface mechanisms and journal bearings with onboard	CONCEPTUAL	desired sensors and draft gear interface mechanisms and journal bearings with onboard
DO-002	conduction path / spreader realizing Implement wireless vibration and temperature sensors on draft gear interface mechanisms and journal bearings with onboard	CONCEPTUAL	desired sensors and draft gear interface mechanisms and journal bearings with onboard
DO-003	reject interface realizing Implement wireless vibration and temperature sensors on draft gear interface mechanisms and journal bearings with onboard analytics	CONCEPTUAL	desired sensors and draft gear interface mechanisms and journal bearings with onboard analytics
DO-004	safety limit interlock realizing Implement wireless vibration and temperature sensors on draft gear interface mechanisms and journal bearings with onboard analytics	CONCEPTUAL	desired sensors and draft gear interface mechanisms and journal bearings with onboard analytics
DO-005	heat source characterization interfaces with conduction path / spreader: signal/energy/material hand-off (dimensional tolerances) vibration and temperature	CONCEPTUAL	signal/energy/material hand-off (dimensional tolerances) vibration and temperature
DO-006	conduction path / spreader interfaces with reject interface: signal/energy/material hand-off (dimensional tolerances) vibration and temperature sensors on draft gear	CONCEPTUAL	signal/energy/material hand-off (dimensional tolerances) vibration and temperature sensors on draft gear
DO-007	reject interface interfaces with safety limit interlock: signal/energy/material hand-off (dimensional tolerances) vibration and temperature sensors on draft gear	CONCEPTUAL	signal/energy/material hand-off (dimensional tolerances) vibration and temperature sensors on draft gear
DO-008	Device boundaries: patient/fluid inlet and outlet termination: control/data/energy/material hand-off (dimensional tolerances) vibration and temperature sensors on draft gear	CONCEPTUAL	control/data/energy/material hand-off (dimensional tolerances) vibration and temperature sensors on draft gear
DO-009	Flow/force/signal path geometry realizing the mechanism holds its stated behavior wireless vibration and temperature sensors on draft gear mechanisms and journal bearings	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings
DO-010	Operating range for heat generation at source within which the mechanism holds its stated behavior	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings
DO-011	Operating range for spreader conductivity within which the mechanism holds its stated behavior	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings
DO-012	Operating range for interface contact resistance within which the mechanism holds its stated behavior	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings
DO-013	Operating range for reject-path area within which the mechanism holds its stated behavior	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings
DO-014	Operating range for allowable temperature rise within which the mechanism holds its stated behavior	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings
DO-015	Operating range for ambient worst case within which the mechanism holds its stated behavior	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings
DO-016	Sensing -> decision -> actuation loop maintaining the mechanism operating position: sensing/energy/material hand-off (dimensional tolerances) vibration and temperature sensors on draft gear	CONCEPTUAL	desired sensors and draft gear mechanisms and journal bearings
DO-017	Information path: sensing element -> decision/monitor -> actuation (minimal); rich data paths are NOT APPLICABLE to this mechanical/physical information	CONCEPTUAL	desired sensors and draft gear mechanisms and journal bearings
DO-018	Fixture enabling: temperature-rise mapping at max duty cycle: concept named, build specification, instrumentation selection; acceptance instrumentation	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings
DO-019	Fixture enabling: interface resistance characterization: concept named, build specification, instrumentation selection; acceptance instrumentation	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings
DO-020	Fixture enabling: worst-case ambient soak test — rig concept named, build specification, instrumentation selection; acceptance instrumentation	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings
DO-021	Fixture enabling: temperature-rise mapping at maximum duty cycle: concept named, build specification, instrumentation selection; acceptance instrumentation	UNKNOWN	desired sensors and draft gear mechanisms and journal bearings

6. Critical Design Parameters

Name	Value	Unit	Basis	Verification
heat generation at source	UNKNOWN (no sourced value)	W	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
spreader conductivity	UNKNOWN (no sourced value)	W/(m.K)	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
interface contact resistance	UNKNOWN (no sourced value)	K/W	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
reject-path area	UNKNOWN (no sourced value)	m^2	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
allowable temperature rise	UNKNOWN (no sourced value)	K	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
ambient worst case	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method

7. Failure Modes

Mode	Mechanism	Mitigation	Verification	Residual Uncertainty
in-service mechanical failure	Failure of equipment mechanical design	Electrical equipment STAB (device failure)	UNKNOWN	the invested, degraded failure mode (Att)
hotspot exceeding material safety limit	Failure of hotspot exceeding material safety limit	spread safety limit; heat-seal spreading; overheating; heat-seal spreading; overheating; heat-seal spreading; overheating	UNKNOWN	the hotspot modes (As)
interface delamination	Failing interface delamination	Massive resistance over life cycle; excessive vibration with high frequency and high amplitude	UNKNOWN	the interface delamination modes (As)
coolant/flow path blockage	Failure of active/flow path blockage	Failure of active/flow path blockage	UNKNOWN	the coolant/flow path blockage modes (As)
thermal runaway coupling	Failure of thermal runaway coupling	Failure of thermal runaway coupling	UNKNOWN	the thermal runaway coupling modes (As)
condensation at cold surfaces	Failure of condensation at cold surfaces	Failure of condensation at cold surfaces	UNKNOWN	the condensation at cold surfaces modes (As)

8. Failure Analysis

Failure Mode	Mechanism	Mitigation	Residual Uncertainty
in-service mechanical or electrical equipment failure	Failure by equipment failure	design equipment NOT ESTABLISHED (retained for review and design)	in-service mechanical or electrical equipment failure
hotspot exceeding material safety limit	Failure by hotspot exceeding material/safety limit	under gear heavy gear station on speed limit (20% increase in speed limit)	hotspot exceeding material safety limit
interface delamination raising risk of structural failure	Failure by interface delamination raising risk of structural failure	selective real time cyclic expansion joint	interface delamination raising risk of structural failure
coolant/flow path blockage (if active)	Failure by coolant/flow path blockage (if active)	passive flow path blockage (if active)	coolant/flow path blockage (if active)
thermal runaway coupling	Failure by thermal runaway coupling	electronic safety temperature analysis	thermal runaway coupling
condensation at cold surfaces	Failure by condensation at cold surfaces	surface strength in operating point	condensation at cold surfaces

9. Verification Strategy

ID	Requirement	Method	Acceptance	Result
VF-001	Simulate bearing overheating and draft	Simulate bearing overheating and draft	Simulate bearing overheating and draft	Simulate bearing overheating and draft
VF-002	run killer experiment: falsification_test	run killer experiment: falsification_test	run killer experiment: falsification_test	run killer experiment: falsification_test
VF-003	temperature-rise mapping at max duty	Acceptance criteria (ENGINEERING PROPOSED) precision fixed	Acceptance criteria (ENGINEERING PROPOSED) precision fixed	temperature-rise mapping at max duty
VF-004	temperature-rise mapping at maximum	temperature-rise mapping sensing (one played)	temperature-rise mapping sensing (one played)	temperature-rise mapping at maximum
VF-005	thermal-resistance trend over acceleration	thermal-resistance trend over acceleration	thermal-resistance trend over acceleration	thermal-resistance trend over acceleration
VF-006	temperature-rise mapping at max duty	Acceptance criteria (ENGINEERING PROPOSED) precision fixed	Acceptance criteria (ENGINEERING PROPOSED) precision fixed	temperature-rise mapping at max duty
VF-007	worst-case ambient soak with staged	worst-case ambient soak with staged	worst-case ambient soak with staged	worst-case ambient soak with staged

10. Validation Strategy

ID	Requirement	Method	Acceptance	Result
VA-001	end-use validation of verified design	NOT ESTABLISHED (defined after verification)	acceptance criteria to be fixed	Validation of verified design

11. Materials

Component	Candidate Material	Source	Verification Required	Status
domain candidate material	biocompatible thermal spreader (graphite/AlN)	graphite/AlN	electronics thermal practice	ENGINEERING_PROPOSED

12. Bill of Materials

Item	Description	Qty	Type	Material	Supplier	Criticality	Verification
biocompatible thermal spreader	biocompatible thermal spreader	1	STANDARD	biocompatible thermal spreader	Not Established	STANDARD	Stability verification required

13. Manufacturing

Status: NO MANUFACTURING ANALYSIS POSSIBLE — no design exists; processes are candidates only

Candidate Processes:

- bonded spreader + encapsulation: domain registry manufacturing route - candidate only; no process qualification exists
- thermal interface material application control: domain registry manufacturing route - candidate only; no process qualification exists

14. External Evidence

Source 1:

URL :

Excerpt:

15. Transfer Boundary

YOU RECEIVE:

- + Buyer receives: canonical invention specification (with epistemic classes).
- + Buyer receives: engineering specification (this document, all blocks classed).
- + Buyer receives: design input/output graph with explicit IDs.
- + Buyer receives: engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification).
- + Buyer receives: killer-experiment definition and its EIG basis.
- + Buyer receives: evidence custody references and hashes.
- + Buyer receives: unresolved-uncertainty register.
- + Buyer receives: domain equation set (symbolic; sources and applicability judgments identified).

YOU MUST DEVELOP:

- > Buyer must create: actual geometry and detailed design.
- > Buyer must create: sourced engineering parameters and acceptance thresholds.
- > Buyer must create: physical prototypes.
- > Buyer must create: all verification and validation results.
- > Buyer must create: manufacturing process qualification.
- > Buyer must create: regulatory pathway determination and submissions.

YOU MUST VERIFY:

- ? Biocompatibility (ISO 10993)
- ? Sterilization compatibility
- ? Mechanical integrity
- ? Regulatory pathway
- ? IP ownership and freedom to operate
- ? Manufacturing process capability

16. Open Questions

- {'unknown': 'FM_WITHOUT_QUANTITY_MATCHED_VERIFICATION:FM-DOM-005', 'reason': 'no available verification method measures a quantity family this failure affects (E21-A quantity rule); UNKNOWN disclosure recorded on the row'}
- {'unknown': 'value of critical parameter heat generation at source [q W]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-001'}
- {'unknown': 'value of critical parameter spreader conductivity [k_i W/(m.K)]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-002'}
- {'unknown': 'value of critical parameter interface contact resistance [R_total K/W]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-003'}
- {'unknown': 'value of critical parameter reject-path area [A m^2]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-004'}
- {'unknown': 'value of critical parameter allowable temperature rise [dT K]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-005'}
- {'unknown': 'value of critical parameter ambient worst case [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-006'}
- {'unknown': 'acceptance criterion for verification VF-001', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-001'}
- {'unknown': 'acceptance criterion for verification VF-002', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-002'}

- {'unknown': 'acceptance criterion for verification VF-003', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-003'}
- {'unknown': 'acceptance criterion for verification VF-004', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-004'}
- {'unknown': 'acceptance criterion for verification VF-006', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-006'}
- {'unknown': 'acceptance criterion for verification VF-007', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-007'}

17. Decisive Next Experiment

WP	Test Article	Equipment	Measurement	Acceptance	Deliverable	Effort
WP-01	first physical article	implementing the proposed physical verification (to be quoted)	physical verification (to be quoted)	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	first physical article	1000 hours (to be quoted)
WP-02	constraint-compliance envelope article	per method	constraint-compliance envelope article	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	constraint-compliance envelope article	1000 hours (to be quoted)
WP-03	article for VF-001	per method	Simulate bearing over-heating and brush gear stress verification (to be quoted)	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	article for VF-001	1000 hours (to be quoted)
WP-04	article for VF-002	per method	run killer experiment: NOT ESTABLISHED (to be quoted)	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	article for VF-002	1000 hours (to be quoted)
WP-05	article for VF-003	per method	temperature-rise mapping: NOT ESTABLISHED (to be quoted)	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	article for VF-003	1000 hours (to be quoted)
WP-06	article for VF-004	per method	temperature-rise mapping: NOT ESTABLISHED (to be quoted)	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	article for VF-004	1000 hours (to be quoted)
WP-07	article for VF-005	per method	thermal-resistance trend: NOT ESTABLISHED (to be quoted)	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	article for VF-005	1000 hours (to be quoted)
WP-08	article for VF-006	per method	temperature-rise mapping: NOT ESTABLISHED (to be quoted)	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	article for VF-006	1000 hours (to be quoted)
WP-09	article for VF-007	per method	worst-case ambient sound level target: NOT ESTABLISHED (to be quoted)	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	article for VF-007	1000 hours (to be quoted)

18. Buyer Decision Framework

WHY INVEST: Engineering definition exists with 3 governing equations and a 9-step build plan. The next experiment is clearly specified. Target buyer: domain-appropriate technology buyer (to be identified by portfolio owner).

WHY WAIT: No physical prototype exists. Regulatory pathway is unresolved. IP ownership is unverified. Manufacturing process is not qualified.

WHY REJECT: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

WHAT WOULD CHANGE THE DECISION: A successful bench experiment demonstrating the core mechanism. A qualified regulatory pathway. A confirmed IP position.

19. Kill Condition

KILL_IF: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

DISCLOSURE

This dossier distinguishes established evidence, external precedent, computational/modelled results, engineering proposals, and unresolved questions. The absence of physical validation should not be interpreted as evidence that the technology will fail; it means the relevant proposition has not yet been established experimentally.

This dossier does not constitute legal, patentability, FTO, regulatory, or investment advice.