

Technology #90: Optimize pacemaker programming (e.g., increase sensing threshold) to mitigate oversensing

Technology Domain: rf_wireless

Mechanism: PROPOSED architecture (no physical system exists): transmit chain + power limits; channel / tissue path (path loss model); receive chain + detection; regulatory exposure constraint (SAR)

Maturity: EARLY_CONCEPT

Current State: No physical prototype. Computational model and engineering definition exist.

Key Risk: killer experiment fails: falsification_test_from_candidate (pre-registered pass/fail required before any transfer)

Next Experiment: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

Buyer Receives: canonical invention specification (with epistemic classes); engineering specification (this document, all blocks classed); design input/output graph with explicit IDs; killer-experiment definition and its EIG basis; evidence custody references and hashes; unresolved-uncertainty register; domain equation set (symbolic; sources identified)

Buyer Must Build: actual geometry and detailed design; sourced engineering parameters and acceptance thresholds; physical prototypes; all verification and validation results; manufacturing process qualification; regulatory submissions

Transfer Posture: Research Partnership

Target Buyer: domain-appropriate technology buyer (to be identified by portfolio owner)

CONFIDENTIAL. See full engineering dossier for details.