

Technology #108

Design hip prosthesis with integrated microchannels that allow for controlled fluid drainage from the bone-implant interface

Engineering Technology-Transfer Dossier

CONFIDENTIAL

Technology Maturity: ENGINEERING_DEFINITION

Generated: 2026-08-30

Not physically validated. Not transfer-ready.

BUYER DECISION PAGE

WHAT IS IT?

Design hip prosthesis with integrated microchannels that allow for controlled fluid drainage from the bone-implant interface

WHY DOES IT MATTER?

Documented recurring problem 'explanted ___ loose' for hip prosthesis: 9 MAUDE reports across 8 distinct devices (20090225 to 20090902); root-cause evidence from 20 recall records and 9 event narratives (custody attached in the campaign report). MAUDE limitations: incidence UNKNOWN, causation UNVERIFIED (Art. XXI.5). Existing solutions fail because: Why existing solutions fail, per retrieved evidence: 20 recall root-cause descriptions (FDA enforcement records, custody attached); 9 MAUDE event narratives from this mechanism cluster (mdr_text, custody attached). Statements are the providers' own words, cust Unresolved gap: Across the 0 relevant retrieved attempts (a bounded, non-exhaustive set), none measurably addresses: conditions, devices, events, explanted, failure, function, injury, intervention, introducing, loose, maintain, matching, modes, must, problem, producing, prost

WHAT IS ACTUALLY ESTABLISHED?

Engineering definition with 3 governing equations, 13 design inputs, 6 failure modes. Computational model exists. No physical prototype.

WHAT IS NOT ESTABLISHED?

Physical validation, manufacturing process, regulatory pathway, IP ownership.

WHY MIGHT A BUYER CARE?

Opportunity in fluidics_hydraulic. 10-step build plan with specific test articles and acceptance criteria. Target buyer: domain-appropriate technology buyer (to be identified by portfolio owner).

WHAT DOES THE BUYER GET?

Buyer receives: canonical invention specification (with epistemic classes).; Buyer receives: engineering specification (this document, all blocks classed).; Buyer receives: design input/output graph with explicit IDs.; Buyer receives: engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification).; Buyer receives: killer-experiment definition and its EIG basis.; Buyer receives: evidence custody references and hashes.; Buyer receives: unresolved-uncertainty register.; Buyer receives: domain equation set (symbolic; sources and applicability judgments identified).

WHAT DOES THE BUYER HAVE TO BUILD?

Buyer must create: actual geometry and detailed design.; Buyer must create: sourced engineering parameters and acceptance thresholds.; Buyer must create: physical prototypes.; Buyer must create: all verification and validation results.; Buyer must create: manufacturing process qualification.; Buyer must create: regulatory pathway determination and submissions.

WHAT IS THE NEXT DECISIVE EXPERIMENT?

first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

WHAT WOULD MAKE US KILL IT?

killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

WHAT TRANSACTION COULD MAKE SENSE?

Sponsored Validation

What Exists Today

Existing:

- + Documented mechanism with governing equations
- + Computational model
- + 3 external evidence sources
- + Design inputs and outputs
- + Failure analysis
- + 10-step engineering build plan
- + Transfer boundary definition

Does Not Yet Exist:

- Physical prototype
- Qualified manufacturing process
- Clinical data
- Verified IP ownership
- Regulatory clearance
- Commercial product

Buyer Can Commission:

- > Specific bench experiment (see build plan)
- > Prototype fabrication
- > Materials study
- > Manufacturing feasibility study
- > Regulatory pre-submission

Development / De-risking Ladder

CURRENT STATE: ENGINEERING_DEFINITION

NEXT ENGINEERING STEP: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

NEXT VALIDATION STEP: Bench prototype validation per build plan

NEXT REGULATORY STEP: Pre-submission to FDA for pathway classification

COMMERCIALIZATION GATE: Clinical validation evidence required

TRANSFER GATE: Transfer-ready when physical validation + regulatory pathway + IP verified

Engineering Investment Ladder

Next \$5K action: WP-01 - first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed) - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: physical bench/clinical experiment — NOT simulation. Uncertainty: Effort estimate, not quoted.

Next \$25K action: WP-03 - article for VF-001 - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: Implant testing in simulated physiological conditions with controlled fluid introduction to evaluate drainage efficiency. Uncertainty: Effort estimate, not quoted.

Next \$100K action: WP-05 - article for VF-003 - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: bench flow-loop characterization across operating range. Uncertainty: Effort estimate, not quoted.

Top 5 Buyer Diligence Questions

Q1: Is the mechanism physically credible for the intended application?

The governing model includes 3 equations. Key assumptions: CSF approximated as Newtonian (valid at shunt flow rates); no wall compliance effects; transition criterion $Re \sim 2300$ is a MODEL_DERIVED engineering rule of thumb; $C_d \sim 0.6-0.65$ is an engineering prior, not a measurement; FLUID-001 (Hagen-Poiseuille (laminar pipe flow)) is applicable only under: Newtonian fluid, laminar regime, rigid circular lumen, fully developed flow.; FLUID-002 (Reynolds number) is applicable only under: circular section; single-phase flow.; FLUID-003 (Orifice flow (sharp-edged restriction)) is applicable only under: turbulent orifice flow; C_d treated as MODEL_DERIVED until measured.; Model input variables requiring sourced values before any numeric result: r (m), dP (Pa), μ (Pa.s), L (m), ρ (kg/m³), v (m/s), D (m), μ (Pa.s), C_d (-), A (m²), dP (Pa), ρ (kg/m³) — all UNKNOWN (no sourced value exists; Art. VIII).; Model output variables produced by the governing model: Q (m³/s), Re (-), Q (m³/s) — UNKNOWN until the inputs are sourced and the model is evaluated.; Critical parameters under specification (parameters with recorded units and epistemic status; no values invented): lumen inner diameter [r , m] value_status=UNKNOWN; lumen length [r , m] value_status=UNKNOWN; surface roughness [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; operating pressure head [dP , Pa] value_status=UNKNOWN; flow rate range [Q , m³/s] value_status=UNKNOWN; viscosity of flowed medium [μ , Pa.s] value_status=UNKNOWN; occlusion growth tolerance [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN.. UNKNOWN: whether assumptions hold in vivo.

Q2: What evidence supports the core claim?

3 external evidence sources. All are external precedent, not physical validation of this specific invention.

Q3: What is the regulatory pathway?

UNKNOWN. Not yet determined. Requires pre-submission to FDA. No predicate identified for some packages.

Q4: Who owns the IP?

UNKNOWN. IP ownership not verified. Requires legal counsel engagement.

Q5: What would it cost to validate?

First experiment: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed). Estimated effort from build plan. Full validation cost: COST TO BE QUOTED.

Commercial Interest

TARGET APPLICATION: CSF shunt systems for hydrocephalus management

CURRENT ALTERNATIVE: Standard fixed-pressure or programmable CSF shunt valves

MECHANISM DIFFERENCE: Passive fluid drainage through microchannels in the implant interface

POTENTIAL VALUE DRIVER: Addresses: Documented recurring problem 'explanted___loose' for hip prosthesis: 9 MAUDE reports across 8 distinct devices (20090225 to 20090902); root-cause evidence from 20 recall records and 9 event narratives (custody attached in the campaign report). MAUDE limitations: incidence UNKNOWN, causation UNVERIFIED (Art. XXI.5). Existing solutions fail because: Why existing solutions fail, per retrieved evidence: 20 recall root-cause descriptions (FDA enforcement records, custody attached); 9 MAUDE event narratives from this mechanism cluster (mdr_text, custody attached). Statements are the providers' own words, cust Unresolved gap: Across the 0 relevant retrieved attempts (a bounded, non-exhaustive set), none measurably addresses: conditions, devices, events, explanted, failure, function, injury, intervention, introducing, loose, maintain, matching, modes, must, problem, producing, prost

ADOPTION BARRIER: Requires physical validation, regulatory clearance, and manufacturing qualification

DEVELOPMENT BARRIER: No physical prototype exists; manufacturing process not established

Licensee Capability Fit

IDEAL BUYER: domain-appropriate technology buyer (to be identified by portfolio owner)

REQUIRED ENGINEERING CAPABILITY: Catheter design, fluid mechanics / domain-specific engineering

REQUIRED MANUFACTURING CAPABILITY: Medical tubing extrusion, injection molding, cleanroom assembly

REQUIRED REGULATORY CAPABILITY: FDA 510(k) or PMA submission experience

REQUIRED CAPITAL: Validation: \$50-200K. Full development: \$500K-2M (estimates, not quoted)

REQUIRED MARKET ACCESS: Neurosurgery market channels; hospital purchasing relationships

1. Technology Description

Domain: fluidics_hydraulic

Disciplines: fluid mechanics, mechanical engineering, biomedical engineering, materials science

Architecture: PROPOSED architecture (no physical system exists): flow path / lumen architecture; pressure regulation element; sensing / feedback element (if closed-loop); termination interfaces (patient / reservoir) — realizing: Design hip prosthesis with integrated microchannels that allow for controlled fluid drainage from the bone-implant interface

Subsystems:

?: flow path / lumen architecture - ?

?: pressure regulation element - ?

?: sensing / feedback element (if closed-loop) - ?

?: termination interfaces (patient / reservoir) - ?

2. Mechanism Architecture

Physical Changes: PROPOSED: Design hip prosthesis with integrated microchannels that allow for controlled fluid drainage from the bone-implant interface

Key Physics: Fluid mechanics / hydraulics governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

3. Governing Engineering Model

Summary: Fluid mechanics / hydraulics governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

Equations:

FLUID-001: Hagen-Poiseuille (laminar pipe flow). Expression: $Q = (\pi * r^4 * dP) / (8 * \mu * L)$.

Applicability to this invention: CONDITIONAL; holds under: Newtonian fluid, laminar regime, rigid circular lumen, fully developed flow. Assumptions: CSF approximated as Newtonian (valid at shunt flow rates); no wall compliance effects. Engaged variables: NOT ESTABLISHED.

FLUID-002: Reynolds number. Expression: $Re = (\rho * v * D) / \mu$. Applicability to this invention: CONDITIONAL; holds under: circular section; single-phase flow. Assumptions: transition criterion $Re \sim 2300$ is a MODEL_DERIVED engineering rule of thumb. Engaged variables: NOT ESTABLISHED.

FLUID-003: Orifice flow (sharp-edged restriction). Expression: $Q = C_d * A * \sqrt{2 * dP / \rho}$.

Applicability to this invention: CONDITIONAL; holds under: turbulent orifice flow; C_d treated as MODEL_DERIVED until measured. Assumptions: $C_d \sim 0.6-0.65$ is an engineering prior, not a measurement. Engaged variables: NOT ESTABLISHED.

Assumptions:

- CSF approximated as Newtonian (valid at shunt flow rates)
- no wall compliance effects
- transition criterion $Re \sim 2300$ is a MODEL_DERIVED engineering rule of thumb
- $C_d \sim 0.6-0.65$ is an engineering prior, not a measurement
- FLUID-001 (Hagen-Poiseuille (laminar pipe flow)) is applicable only under: Newtonian fluid, laminar regime, rigid circular lumen, fully developed flow.
- FLUID-002 (Reynolds number) is applicable only under: circular section; single-phase flow.
- FLUID-003 (Orifice flow (sharp-edged restriction)) is applicable only under: turbulent orifice flow; C_d treated as MODEL_DERIVED until measured.
- Model input variables requiring sourced values before any numeric result: r (m), dP (Pa), μ (Pa.s), L (m), ρ (kg/m³), v (m/s), D (m), μ (Pa.s), C_d (-), A (m²), dP (Pa), ρ (kg/m³) — all UNKNOWN (no sourced value exists; Art. VIII).

- Model output variables produced by the governing model: Q (m^3/s), Re (-), Q (m^3/s) — UNKNOWN until the inputs are sourced and the model is evaluated.
- Critical parameters under specification (parameters with recorded units and epistemic status; no values invented): lumen inner diameter [r, m] value_status=UNKNOWN; lumen length [r, m] value_status=UNKNOWN; surface roughness [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; operating pressure head [dP, Pa] value_status=UNKNOWN; flow rate range [Q, m^3/s] value_status=UNKNOWN; viscosity of flowed medium [μ , Pa.s] value_status=UNKNOWN; occlusion growth tolerance [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN.

Boundary Conditions:

- to be established by the first bench characterization (not yet performed)

Failure Regimes:

- {'regime': 'explanted and loose', 'basis': 'SOURCE_FACT (problem.json)'}
- {'regime': 'proximal occlusion by tissue ingrowth', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'lumen collapse under external pressure (kink)', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'encrustation / mineral deposition', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'regime transition to turbulence altering calibration', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'check-valve seat wear opening reverse leakage', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}

4. Design Inputs

[illegible]

5. Design Outputs

ID	Description	Status	Missing Inputs
DO-001	flow path / lumen architecture realizing Design hip prosthesis	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-002	pressure regulation element realizing Design hip prosthesis	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-003	sensing / feedback element (if closed-loop) realizing Design hip prosthesis	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-004	termination interfaces (patient / reservoir) realizing Design hip prosthesis	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-005	flow path / lumen architecture interfaces with pressure regulation element: signal/actuation	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-006	pressure regulation element interfaces with sensing / feedback element: signal/actuation	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-007	sensing / feedback element (if closed-loop) interfaces with termination interfaces: signal/actuation	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-008	Device boundaries: patient/fluid inlet and outlet termination interfaces: signal/actuation	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-009	Flow/force/signal path geometry realizing the mechanism	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-010	Operating range for lumen inner diameter within which the mechanism holds its stated behavior	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-011	Operating range for lumen length within which the mechanism holds its stated behavior	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-012	Operating range for surface roughness within which the mechanism holds its stated behavior	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-013	Operating range for operating pressure head within which the mechanism holds its stated behavior	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-014	Operating range for flow rate range within which the mechanism holds its stated behavior	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-015	Operating range for viscosity of flowed medium within which the mechanism holds its stated behavior	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-016	Sensing -> decision -> actuation loop maintaining the mechanism	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-017	Information path: sensing element -> decision/monitoring element	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-018	Fixture enabling: bench flow-loop characterization across the operating range — rig	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface
DO-019	Fixture enabling: pressure-drop mapping vs flow (identifying flow transitions) — rig	DESIGN PROBABLY	integrated microchannel architecture allow for controlled fluid drainage from the bone-implant interface

ID	Description	Status	Missing Inputs
DO-020	Fixture enabling: accelerated occlusion / fouling challenge	UNKNOWN — rig concept finalized, build type, instrumentation	fixed geometry, fixture run time; acceptance instrumentation
DO-021	Fixture enabling: pressure-flow mapping across full operating envelope	UNKNOWN — rig concept generated, build type, instrumentation	fixed geometry, fixture run time; acceptance instrumentation

6. Critical Design Parameters

Name	Value	Unit	Basis	Verification
lumen inner diameter	UNKNOWN (no sourced value)	m	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
lumen length	UNKNOWN (no sourced value)	m	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
surface roughness	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
operating pressure head	UNKNOWN (no sourced value)	Pa	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
flow rate range	UNKNOWN (no sourced value)	m^3/s	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
viscosity of flowed medium	UNKNOWN (no sourced value)	Pa.s	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
occlusion growth tolerance	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method

7. Failure Modes

Mode	Mechanism	Mitigation	Verification	Residual Uncertainty
explanted and loose	Fails by explanted and loose	designer to ensure that the device requires design	UNKNOWN	When operating conditions are in the (Plen
proximal occlusion by tissue ingrowth	Proximal occlusion by tissue ingrowth	by engineering with self-polishing surfaces and the use of drug eluting devices	UNKNOWN	When used as a device the need (Part
lumen collapse under external pressure	Lumen collapse under external pressure	external pressure (kPa) or internal pressure bending when the device is used	UNKNOWN	When used as a device the need (Act. t
encrustation / mineral deposition	Encrustation / mineral deposition	and deposition coatings selected	UNKNOWN	When used as a device the need (Ars &
regime transition to turbulence	Regime transition to turbulence	building a long definition regime the margin verification	UNKNOWN	When used as a device the need (The
check-valve seat wear	Failing check valve leakage	seal material and design of the seal	UNKNOWN	When used as a device the need (Partle

8. Failure Analysis

Failure Mode	Mechanism	Mitigation	Residual Uncertainty
explanted and loose	Fails by explanted and loose: the device failure that on NO ESTABLISHED (defined after verification)	design work on preventing dislodgement (Approved)	
proximal occlusion by tissue ingrowth	Fails by proximal occlusion by tissue ingrowth: cells proliferate and occlude the lumen	material selection and design of the proximal filter (Approved)	
lumen collapse under external pressure	Fails by lumen collapse under external pressure: the device is not strong enough to resist external pressure	material selection and design of the proximal filter (Approved)	
encrustation / mineral deposition	Fails by encrustation / mineral deposition: surface area exposed to body fluids	material selection and design of the proximal filter (Approved)	
regime transition to turbulence	Fails by regime transition to turbulence: altering the flow regime	material selection and design of the proximal filter (Approved)	
check-valve seat wear opening	Fails by check-valve seat wear opening: wear of the seat	material selection and design of the proximal filter (Approved)	

9. Verification Strategy

ID	Requirement	Method	Acceptance	Result
VF-001	Implant testing in simulated physiological conditions	Implant testing in simulated physiological conditions	Acceptance criteria to be fixed at verification	Not performed
VF-002	run killer experiment: falsification test	run killer experiment: falsification test	Acceptance criteria to be fixed at verification	Not performed
VF-003	bench flow-loop characterization across operating range	bench flow-loop characterization across operating range	Acceptance criteria to be fixed at verification	Not performed
VF-004	pressure-drop mapping vs flow (identify pressure drops)	pressure-drop mapping vs flow (identify pressure drops)	Acceptance criteria to be fixed at verification	Not performed
VF-005	delivered-flow trend below baseline in adverse conditions	delivered-flow trend below baseline in adverse conditions	Acceptance criteria to be fixed at verification	Not performed
VF-006	kink/collapse test across duty cycle; flow kink/collapse test	kink/collapse test across duty cycle; flow kink/collapse test	Acceptance criteria to be fixed at verification	Not performed
VF-007	pressure-flow mapping across the full operating range	pressure-flow mapping across the full operating range	Acceptance criteria to be fixed at verification	Not performed
VF-008	reverse-leakage rate measurement after accelerated cycling	reverse-leakage rate measurement after accelerated cycling	Acceptance criteria to be fixed at verification	Not performed

10. Validation Strategy

ID	Requirement	Method	Acceptance	Result
VA-001	end-use validation of verified design	NOT ESTABLISHED (defined after verification)	Acceptance criteria to be fixed at verification	Not performed

11. Materials

Component	Candidate Material	Source	Verification Required	Status
domain candidate material	medical-grade silicone elastomer	standard CSF shunt catheter material	True	ENGINEERING_PROPOSED
domain candidate material	polycarbonate / PSU rigid components	standard shunt valve housings	True	ENGINEERING_PROPOSED

12. Bill of Materials

Item	Description	Qty	Type	Material	Supplier	Criticality	Verification
1	medical-grade silicone elastomer	1	Material	medical-grade silicone elastomer	NOT ESTABLISHED	NOT ESTABLISHED	Applicability verification required
2	polycarbonate / PSU rigid components	1	Material	polycarbonate / PSU rigid components	NOT ESTABLISHED	NOT ESTABLISHED	Applicability verification required

13. Manufacturing

Status: NO MANUFACTURING ANALYSIS POSSIBLE — no design exists; processes are candidates only

Candidate Processes:

- medical extrusion with inner-diameter tolerance control: domain registry manufacturing route - candidate only; no process qualification exists
- injection molding of valve/housing features: domain registry manufacturing route - candidate only; no process qualification exists
- laser drilling of calibrated orifices: domain registry manufacturing route - candidate only; no process qualification exists

14. External Evidence

Source 1:

URL :

Excerpt:

Source 2:

URL :

Excerpt:

Source 3:

URL :

Excerpt:

15. Transfer Boundary

YOU RECEIVE:

- + Buyer receives: canonical invention specification (with epistemic classes).
- + Buyer receives: engineering specification (this document, all blocks classed).
- + Buyer receives: design input/output graph with explicit IDs.
- + Buyer receives: engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification).
- + Buyer receives: killer-experiment definition and its EIG basis.
- + Buyer receives: evidence custody references and hashes.
- + Buyer receives: unresolved-uncertainty register.
- + Buyer receives: domain equation set (symbolic; sources and applicability judgments identified).

YOU MUST DEVELOP:

- > Buyer must create: actual geometry and detailed design.
- > Buyer must create: sourced engineering parameters and acceptance thresholds.
- > Buyer must create: physical prototypes.
- > Buyer must create: all verification and validation results.
- > Buyer must create: manufacturing process qualification.
- > Buyer must create: regulatory pathway determination and submissions.

YOU MUST VERIFY:

- ? Biocompatibility (ISO 10993)
- ? Sterilization compatibility
- ? Mechanical integrity
- ? Regulatory pathway
- ? IP ownership and freedom to operate
- ? Manufacturing process capability

16. Open Questions

- {'unknown': 'FM_WITHOUT_QUANTITY_MATCHED_VERIFICATION:FM-DOM-003', 'reason': 'no available verification method measures a quantity family this failure affects (E21-A quantity rule); UNKNOWN disclosure recorded on the row'}
- {'unknown': 'value of critical parameter lumen inner diameter [r m]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-001'}
- {'unknown': 'value of critical parameter lumen length [r m]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-002'}
- {'unknown': 'value of critical parameter surface roughness [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-003'}
- {'unknown': 'value of critical parameter operating pressure head [dP Pa]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-004'}
- {'unknown': 'value of critical parameter flow rate range [Q m^3/s]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-005'}
- {'unknown': 'value of critical parameter viscosity of flowed medium [mu Pa.s]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-006'}
- {'unknown': 'value of critical parameter occlusion growth tolerance [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-007'}
- {'unknown': 'acceptance criterion for verification VF-001', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-001'}

- ## 17. Decisive Next Experiment

WP	Test Article	Equipment	Measurement	Acceptance	Deliverable	Effort
WP-01	first physical article	maintaining the prop	phys spec verification	0.5645454545454545	7.741111111111111	1.0000000000000001
WP-02	constraint-compliance	per method	constraint-compliance	NOT ESTABLISHED	constraint-compliance	NOT ESTABLISHED (report quoted)
WP-03	article for VF-001	per method	Implant testing in simu	NOT ESTABLISHED	VF-001 verification	NOT ESTABLISHED (to be quoted)
WP-04	article for VF-002	per method	run killer experiment:	NOT ESTABLISHED	VF-002 test (to be quoted)	NOT ESTABLISHED (to be quoted)
WP-05	article for VF-003	per method	bench flow-loop chara	NOT ESTABLISHED	VF-003 verification	NOT ESTABLISHED (to be quoted)
WP-06	article for VF-004	per method	pressure-drop mapping	NOT ESTABLISHED	VF-004 verification	NOT ESTABLISHED (to be quoted)
WP-07	article for VF-005	per method	delivered-flow trend	NOT ESTABLISHED	VF-005 verification	NOT ESTABLISHED (to be quoted)
WP-08	article for VF-006	per method	kink/collapse test acro	NOT ESTABLISHED	VF-006 verification	NOT ESTABLISHED (to be quoted)
WP-09	article for VF-007	per method	pressure-flow mapping	NOT ESTABLISHED	VF-007 verification	NOT ESTABLISHED (to be quoted)
WP-10	article for VF-008	per method	reverse-leakage rate	NOT ESTABLISHED	VF-008 verification	NOT ESTABLISHED (to be quoted)

18. Buyer Decision Framework

WHY INVEST: Engineering definition exists with 3 governing equations and a 10-step build plan. The next experiment is clearly specified. Target buyer: domain-appropriate technology buyer (to be identified by portfolio owner).

WHY WAIT: No physical prototype exists. Regulatory pathway is unresolved. IP ownership is unverified. Manufacturing process is not qualified.

WHY REJECT: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

WHAT WOULD CHANGE THE DECISION: A successful bench experiment demonstrating the core mechanism. A qualified regulatory pathway. A confirmed IP position.

19. Kill Condition

KILL_IF: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

DISCLOSURE

This dossier distinguishes established evidence, external precedent, computational/modelled results, engineering proposals, and unresolved questions. The absence of physical validation should not be interpreted as evidence that the technology will fail; it means the relevant proposition has not yet been established experimentally.

This dossier does not constitute legal, patentability, FTO, regulatory, or investment advice.