

Technology #122

Incorporate carbon fiber reinforced polymer (CFRP) components at stress points in the knee prosthesis design to distribute mechanical loads more evenly and prevent detachment

Engineering Technology-Transfer Dossier

CONFIDENTIAL

Technology Maturity: ENGINEERING_DEFINITION

Generated: 2026-08-30

Not physically validated. Not transfer-ready.

BUYER DECISION PAGE

WHAT IS IT?

Incorporate carbon fiber reinforced polymer (CFRP) components at stress points in the knee prosthesis design to distribute mechanical loads more evenly and prevent detachment

WHY DOES IT MATTER?

Documented recurring problem 'detachment_of_device_or_device_component' for knee prosthesis: 15 MAUDE reports across 4 distinct devices (20220805 to 20240904); root-cause evidence from 4 recall records and 10 event narratives (custody attached in the campaign report). MAUDE limitations: incidence UNKNOWN, causation UNVERIFIED (Art. XXI.5). Existing solutions fail because: Why existing solutions fail, per retrieved evidence: 4 recall root-cause descriptions (FDA enforcement records, custody attached); 10 MAUDE event narratives from this mechanism cluster (mdr_text, custody attached). Statements are the providers' own words, cust Unresolved gap: Across the 4 relevant retrieved attempts (a bounded, non-exhaustive set), none measurably addresses: conditions, devices, events, failure, function, injury, intervention, introducing, maintain, matching, modes, must, problem, producing, recurring, reported, un

WHAT IS ACTUALLY ESTABLISHED?

Engineering definition with 3 governing equations, 12 design inputs, 6 failure modes. Computational model exists. No physical prototype.

WHAT IS NOT ESTABLISHED?

Physical validation, manufacturing process, regulatory pathway, IP ownership.

WHY MIGHT A BUYER CARE?

Opportunity in mechanical_structural. 10-step build plan with specific test articles and acceptance criteria. Target buyer: domain-appropriate technology buyer (to be identified by portfolio owner).

WHAT DOES THE BUYER GET?

Buyer receives: canonical invention specification (with epistemic classes).; Buyer receives: engineering specification (this document, all blocks classed).; Buyer receives: design input/output graph with explicit IDs.; Buyer receives: engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification).; Buyer receives: killer-experiment definition and its EIG basis.; Buyer receives: evidence custody references and hashes.; Buyer receives: unresolved-uncertainty register.; Buyer receives: domain equation set (symbolic; sources and applicability judgments identified).

WHAT DOES THE BUYER HAVE TO BUILD?

Buyer must create: actual geometry and detailed design.; Buyer must create: sourced engineering parameters and acceptance thresholds.; Buyer must create: physical prototypes.; Buyer must create: all verification and validation results.; Buyer must create: manufacturing process qualification.; Buyer must create: regulatory pathway determination and submissions.

WHAT IS THE NEXT DECISIVE EXPERIMENT?

first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

WHAT WOULD MAKE US KILL IT?

killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

WHAT TRANSACTION COULD MAKE SENSE?

Sponsored Validation

What Exists Today

Existing:

- + Documented mechanism with governing equations
- + Computational model
- + 1 external evidence sources
- + Design inputs and outputs
- + Failure analysis
- + 10-step engineering build plan
- + Transfer boundary definition

Does Not Yet Exist:

- Physical prototype
- Qualified manufacturing process
- Clinical data
- Verified IP ownership
- Regulatory clearance
- Commercial product

Buyer Can Commission:

- > Specific bench experiment (see build plan)
- > Prototype fabrication
- > Materials study
- > Manufacturing feasibility study
- > Regulatory pre-submission

Development / De-risking Ladder

CURRENT STATE: ENGINEERING_DEFINITION

NEXT ENGINEERING STEP: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

NEXT VALIDATION STEP: Bench prototype validation per build plan

NEXT REGULATORY STEP: Pre-submission to FDA for pathway classification

COMMERCIALIZATION GATE: Clinical validation evidence required

TRANSFER GATE: Transfer-ready when physical validation + regulatory pathway + IP verified

Engineering Investment Ladder

Next \$5K action: WP-01 - first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed) - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: physical bench/clinical experiment — NOT simulation. Uncertainty: Effort estimate, not quoted.

Next \$25K action: WP-03 - article for VF-001 - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: Accelerated fatigue testing comparing traditional metal components versus CFRP-reinforced components under simulated walking cycles with.... Uncertainty: Effort estimate, not quoted.

Next \$100K action: WP-05 - article for VF-003 - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: buckling / kink margin tests across duty cycle. Uncertainty: Effort estimate, not quoted.

Top 5 Buyer Diligence Questions

Q1: Is the mechanism physically credible for the intended application?

The governing model includes 3 equations. Key assumptions: stress concentrators multiply local stress above the nominal value — geometry factors must be applied from the actual design; superelastic members (e.g. nitinol) do not follow linear elasticity through transformation — use their measured plateau relations instead; K for catheter constraint conditions is MODEL_DERIVED; MEC-002 (Section bending stress) is applicable only under: linear-elastic material; small deflection; prismatic section.; MEC-003 (Hooke's law (linear elasticity)) is applicable only under: below proportional limit; isothermal.; MEC-001 (Euler buckling load) is applicable only under: elastic, slender column, small deflection.; Model input variables requiring sourced values before any numeric result: M (N.m), c (m), I (m⁴), E (Pa), epsilon (-), E (Pa), I (m⁴), K (-), L (m) — all UNKNOWN (no sourced value exists; Art. VIII).; Model output variables produced by the governing model: sigma (Pa), sigma (Pa), P_cr (N) — UNKNOWN until the inputs are sourced and the model is evaluated.; Critical parameters under specification (parameters with recorded units and epistemic status; no values invented): member slenderness ratio [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; yield/ultimate strength [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; applied cyclic load amplitude [P_cr, N] value_status=UNKNOWN; required run-out cycles [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; articulation radius [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; friction coefficient at guides [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN.. UNKNOWN: whether assumptions hold in vivo.

Q2: What evidence supports the core claim?

1 external evidence sources. All are external precedent, not physical validation of this specific invention.

Q3: What is the regulatory pathway?

UNKNOWN. Not yet determined. Requires pre-submission to FDA. No predicate identified for some packages.

Q4: Who owns the IP?

UNKNOWN. IP ownership not verified. Requires legal counsel engagement.

Q5: What would it cost to validate?

First experiment: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed). Estimated effort from build plan. Full validation cost: COST TO BE QUOTED.

Commercial Interest

TARGET APPLICATION: CSF shunt systems for hydrocephalus management

CURRENT ALTERNATIVE: Standard fixed-pressure or programmable CSF shunt valves

MECHANISM DIFFERENCE: Structural reinforcement through composite materials with stress-distribution properties

POTENTIAL VALUE DRIVER: Addresses: Documented recurring problem 'detachment_of_device_or_device_component' for knee prosthesis: 15 MAUDE reports across 4 distinct devices (20220805 to 20240904); root-cause evidence from 4 recall records and 10 event narratives (custody attached in the campaign report). MAUDE limitations: incidence UNKNOWN, causation UNVERIFIED (Art. XXI.5). Existing solutions fail because: Why existing solutions fail, per retrieved evidence: 4 recall root-cause descriptions (FDA enforcement records, custody attached); 10 MAUDE event narratives from this mechanism cluster (mdr_text, custody attached). Statements are the providers' own words, cust Unresolved gap: Across the 4 relevant retrieved attempts (a bounded, non-exhaustive set), none measurably addresses: conditions, devices, events, failure, function, injury, intervention, introducing, maintain, matching, modes, must, problem, producing, recurring, reported, un

ADOPTION BARRIER: Requires physical validation, regulatory clearance, and manufacturing qualification

DEVELOPMENT BARRIER: No physical prototype exists; manufacturing process not established

Licensee Capability Fit

IDEAL BUYER: domain-appropriate technology buyer (to be identified by portfolio owner)

REQUIRED ENGINEERING CAPABILITY: Catheter design, fluid mechanics / domain-specific engineering

REQUIRED MANUFACTURING CAPABILITY: Medical tubing extrusion, injection molding, cleanroom assembly

REQUIRED REGULATORY CAPABILITY: FDA 510(k) or PMA submission experience

REQUIRED CAPITAL: Validation: \$50-200K. Full development: \$500K-2M (estimates, not quoted)

REQUIRED MARKET ACCESS: Neurosurgery market channels; hospital purchasing relationships

1. Technology Description

Domain: mechanical_structural

Disciplines: mechanical engineering, structural analysis, fatigue and fracture, materials science

Architecture: PROPOSED architecture (no physical system exists): load path / structural backbone; actuation or compliance element; guidance / bearing interfaces; fatigue-critical features register — realizing: Incorporate carbon fiber reinforced polymer (CFRP) components at stress points in the knee prosthesis design to distribute mechanical loads more evenly and prevent detachment

Subsystems:

?: load path / structural backbone - ?

?: actuation or compliance element - ?

?: guidance / bearing interfaces - ?

?: fatigue-critical features register - ?

2. Mechanism Architecture

Physical Changes: PROPOSED: Incorporate carbon fiber reinforced polymer (CFRP) components at stress points in the knee prosthesis design to distribute mechanical loads more evenly and prevent detachment

Key Physics: Mechanics / structures governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

3. Governing Engineering Model

Summary: Mechanics / structures governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

Equations:

MEC-002: Section bending stress. Expression: $\sigma = M * c / I$. Applicability to this invention: APPLICABLE; holds under: linear-elastic material; small deflection; prismatic section. Assumptions: stress concentrators multiply local stress above the nominal value — geometry factors must be applied from the actual design. Engaged variables: σ , c .

MEC-003: Hooke's law (linear elasticity). Expression: $\sigma = E * \epsilon$. Applicability to this invention: APPLICABLE; holds under: below proportional limit; isothermal. Assumptions: superelastic members (e.g. nitinol) do not follow linear elasticity through transformation — use their measured plateau relations instead. Engaged variables: σ .

MEC-001: Euler buckling load. Expression: $P_{cr} = \pi^2 * E * I / (K * L)^2$. Applicability to this invention: CONDITIONAL; holds under: elastic, slender column, small deflection. Assumptions: K for catheter constraint conditions is MODEL_DERIVED. Engaged variables: NOT ESTABLISHED.

Assumptions:

- stress concentrators multiply local stress above the nominal value — geometry factors must be applied from the actual design
- superelastic members (e.g. nitinol) do not follow linear elasticity through transformation — use their measured plateau relations instead
- K for catheter constraint conditions is MODEL_DERIVED
- MEC-002 (Section bending stress) is applicable only under: linear-elastic material; small deflection; prismatic section.
- MEC-003 (Hooke's law (linear elasticity)) is applicable only under: below proportional limit; isothermal.
- MEC-001 (Euler buckling load) is applicable only under: elastic, slender column, small deflection.
- Model input variables requiring sourced values before any numeric result: M (N.m), c (m), I (m⁴), E (Pa), ϵ (-), E (Pa), I (m⁴), K (-), L (m) — all UNKNOWN (no sourced value exists; Art. VIII).
- Model output variables produced by the governing model: σ (Pa), σ (Pa), P_{cr} (N) — UNKNOWN until the inputs are sourced and the model is evaluated.

- Critical parameters under specification (parameters with recorded units and epistemic status; no values invented): member slenderness ratio [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; yield/ultimate strength [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; applied cyclic load amplitude [P_cr, N] value_status=UNKNOWN; required run-out cycles [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; articulation radius [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; friction coefficient at guides [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN.

Boundary Conditions:

- to be established by the first bench characterization (not yet performed)

Failure Regimes:

- {'regime': 'detachment of device or device component', 'basis': 'SOURCE_FACT (problem.json)'}
- {'regime': 'kink/buckling below required push ability', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'fatigue crack initiation at stress concentrator', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'wear debris generation at sliding interfaces', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'joint separation under overload', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'set-release of superelastic shape after set', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}

4. Design Inputs

ID	Input	Value	Origin
DI-001	Stated constraint	Devices matching 'knee prosthesis' must maintain function under the condition of occurring injury events with re	Source: Figs 10a, 10b
DI-002	Mechanism driver (proposed)	Structural reinforcement through composite materials with stress-distribution	Model: Fig 10c
DI-003	Expected effect target	Reduced stress concentration points that lead to component detachment while maintaining flexibility and function	Model: Fig 10d
DI-004	Domain design input pattern: delivery applicability	NOT_ESTABLISHED (candidate pattern; confirm against Fig 10e)	ENGINEERING: PROPOSED
DI-005	Domain design input pattern: activation applicability	NOT_ESTABLISHED (candidate pattern; confirm against Fig 10f)	ENGINEERING: PROPOSED
DI-006	Domain design input pattern: duty cycle applicability	NOT_ESTABLISHED (candidate pattern; confirm against Fig 10g)	ENGINEERING: PROPOSED
DI-007	Regulatory design input: compliance standards	ASTM F2516 (tissue integration pathway UNKNOWN) (PROPOSED) is never inferred	ENGINEERING: PROPOSED
DI-008	Custodied observation: Frequent safety signals from scientific literature	https://pubmed.ncbi.nlm.nih.gov/35573989/ features highlights https://pubmed.ncbi.nlm.nih.gov/35573989/	Source: Fig 10h
DI-009	Custodied observation: Staphylococcus aureus pathogenesis	https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4151189/ , its pathogenesis is https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4151189/	Source: Fig 10i
DI-010	Custodied observation: Medial femoral condyle resorption	https://pubmed.ncbi.nlm.nih.gov/24144576/ centeropharynx. 2b3d86dea4687028223440c314176f9a4783c7604267e15	Source: Fig 10j
DI-011	Custodied observation: Short-term oral optomechanical	https://pubmed.ncbi.nlm.nih.gov/22040741/ , the next hash https://pubmed.ncbi.nlm.nih.gov/22040741/	Source: Fig 10k
DI-012	Custodied observation: Short-term oral and radiographic	https://pubmed.ncbi.nlm.nih.gov/22734921/ , vco-shap Flashing Process https://pubmed.ncbi.nlm.nih.gov/22734921/	Source: Fig 10l

5. Design Outputs

ID	Description	Status	Missing Inputs
DO-001	load path / structural backbone realizing Incorporate carbon fiber reinforced polymer (CFRP) into knee prosthesis design to	CONCEPTUAL	data (CFRP) incorporation details
DO-002	actuation or compliance element realizing Incorporate carbon fiber reinforced polymer (CFRP) into knee prosthesis design to	CONCEPTUAL	data (CFRP) incorporation details
DO-003	guidance / bearing interfaces realizing Incorporate carbon fiber reinforced polymer (CFRP) into knee prosthesis design to	CONCEPTUAL	data (CFRP) incorporation details
DO-004	fatigue-critical features register realizing Incorporate carbon fiber reinforced polymer (CFRP) into knee prosthesis design to	CONCEPTUAL	data (CFRP) incorporation details
DO-005	load path / structural backbone interfaces with actuation or compliance element: signal/energy/actuation (dimensions, tolerances)	CONCEPTUAL	signal/energy/actuation (dimensions, tolerances)
DO-006	actuation or compliance element interfaces with guidance / bearing interfaces: signal/energy/actuation (dimensions, tolerances)	CONCEPTUAL	signal/energy/actuation (dimensions, tolerances)
DO-007	guidance / bearing interfaces interfaces with fatigue-critical features register: signal/energy/actuation (dimensions, tolerances)	CONCEPTUAL	signal/energy/actuation (dimensions, tolerances)
DO-008	Device boundaries: patient/fluid inlet and outlet termination, control/data ports required by selection, seal definition	CONCEPTUAL	control/data ports required by selection, seal definition
DO-009	Flow/force/signal path geometry realizing the mechanical reinforcement of carbon fiber reinforced polymer (CFRP) reinforcement at stress points in the knee p	UNKNOWN	carbon fiber reinforced polymer (CFRP) reinforcement
DO-010	Operating range for member slenderness ratio within which the mechanism holds its stated behavior	UNKNOWN	mechanism holds its stated behavior
DO-011	Operating range for yield/ultimate strength within which the mechanism holds its stated behavior	UNKNOWN	mechanism holds its stated behavior
DO-012	Operating range for applied cyclic load amplitude within which the mechanism holds its stated behavior	UNKNOWN	mechanism holds its stated behavior
DO-013	Operating range for required run-out cycles within which the mechanism holds its stated behavior	UNKNOWN	mechanism holds its stated behavior
DO-014	Operating range for articulation radius within which the mechanism holds its stated behavior	UNKNOWN	mechanism holds its stated behavior
DO-015	Operating range for friction coefficient at guides within which the mechanism holds its stated behavior	UNKNOWN	mechanism holds its stated behavior
DO-016	No closed-loop control is proposed: the invention operates as an open-loop as specified; this record exists so the omission is explicit and auditable	DEFENSIVE	open-loop as specified; this record exists so the omission is explicit and auditable
DO-017	Information path: sensing element -> decision/monitor	CONCEPTUAL	act (minimal); rich data paths are NOT APPLICABLE to this mechanical/physical in
DO-018	Fixture enabling: buckling / kink margin tests across duty cycle	UNKNOWN	rig concept named, build specific instrumentation selection; acceptance instrumentation
DO-019	Fixture enabling: fatigue life (run-out) testing — rig control	UNKNOWN	named, build specific instrumentation selection; acceptance instrumentation
DO-020	Fixture enabling: friction and wear characterization — rig control	UNKNOWN	named, build specific instrumentation selection; acceptance instrumentation

ID	Description	Status	Missing Inputs
DO-021	Fixture enabling: buckling/kink margin test across duty cycle	UNKNOWN	Unknown concept name; fixture specification; instrument selection; acceptance instrumentation

6. Critical Design Parameters

Name	Value	Unit	Basis	Verification
member slenderness ratio	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned and target) value and verification method k
yield/ultimate strength	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned and target) value and verification method k
applied cyclic load amplitude	UNKNOWN (no sourced value)	N	ENGINEERING_PROPOSED	(design assigned and target) value and verification method k
required run-out cycles	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned and target) value and verification method k
articulation radius	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned and target) value and verification method k
friction coefficient at guides	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned and target) value and verification method k

7. Failure Modes

[illegible]

8. Failure Analysis

Failure Mode	Mechanism	Mitigation	Residual Uncertainty
detachment of device or device displacement	Failure by detachment of device or device displacement	design point to NOT ESTABLISHED (retained design point tested against the failure mode)	detachment of device or device displacement (Annex V)
kink/buckling below required capacity	Failure by kink/buckling below required capacity	pushability test to demonstrate the added kink/buckling capacity below the required capacity	kink/buckling below required capacity (Annex V)
fatigue crack initiation at stress concentration	Failure by fatigue crack initiation at stress concentration	concentration of stress at interfaces, stress concentration factor, fatigue crack growth rate	fatigue crack initiation at stress concentration (Annex V)
wear debris generation at sliding interfaces	Failure by wear debris generation at sliding interfaces	wear debris generation, wear debris generation, wear debris generation	wear debris generation at sliding interfaces (Annex V)
joint separation under overload	Failure by joint separation under overload	load on a larger size of device to demonstrate the joint separation under overload	joint separation under overload (Annex V)
set-release of superelastic shape	Failure by set-release of superelastic shape	set-release of superelastic shape, set-release of superelastic shape	set-release of superelastic shape (Annex V)

9. Verification Strategy

ID	Requirement	Method	Acceptance	Result
VF-001	Accelerated fatigue testing comparing	Accelerated fatigue testing comparing	Accelerated fatigue testing comparing	Accelerated fatigue testing comparing
VF-002	run killer experiment: falsification_test	run killer experiment: falsification_test	run killer experiment: falsification_test	run killer experiment: falsification_test
VF-003	buckling / kink margin tests across duty	buckling / kink margin tests across duty	buckling / kink margin tests across duty	buckling / kink margin tests across duty
VF-004	fatigue life (run-out) testing. Acceptance	fatigue life (run-out) testing. Acceptance	fatigue life (run-out) testing. Acceptance	fatigue life (run-out) testing. Acceptance
VF-005	buckling/kink margin test across the duty	buckling/kink margin test across the duty	buckling/kink margin test across the duty	buckling/kink margin test across the duty
VF-006	fatigue run-out at worst-case loading	fatigue run-out at worst-case loading	fatigue run-out at worst-case loading	fatigue run-out at worst-case loading
VF-007	buckling / kink margin tests across duty	buckling / kink margin tests across duty	buckling / kink margin tests across duty	buckling / kink margin tests across duty
VF-008	overload margin demonstration to worst	overload margin demonstration to worst	overload margin demonstration to worst	overload margin demonstration to worst

10. Validation Strategy

ID	Requirement	Method	Acceptance	Result
VA-001	end-use validation of verified design	NOT ESTABLISHED (defined after verification)	NOT ESTABLISHED (defined after verification)	NOT ESTABLISHED (defined after verification)

11. Materials

Component	Candidate Material	Source	Verification Required	Status
domain candidate material	nitinol / polymer composite membrane	minimally invasive device practice	True	ENGINEERING_PROPOSED

12. Bill of Materials

Item	Description	Qty	Type	Material	Supplier	Criticality	Verification
nitinol / polymer composite membrane	nitinol / polymer composite membrane	1	Material	nitinol / polymer composite membrane	NOT ESTABLISHED	NOT ESTABLISHED	Reliability verification required

13. Manufacturing

Status: NO MANUFACTURING ANALYSIS POSSIBLE — no design exists; processes are candidates only

Candidate Processes:

- laser-cut hypotube / braided composite shaft: domain registry manufacturing route - candidate only; no process qualification exists
- passivation and surface finish control: domain registry manufacturing route - candidate only; no process qualification exists

14. External Evidence

Source 1:

URL :

Excerpt:

15. Transfer Boundary

YOU RECEIVE:

- + Buyer receives: canonical invention specification (with epistemic classes).
- + Buyer receives: engineering specification (this document, all blocks classed).
- + Buyer receives: design input/output graph with explicit IDs.
- + Buyer receives: engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification).
- + Buyer receives: killer-experiment definition and its EIG basis.
- + Buyer receives: evidence custody references and hashes.
- + Buyer receives: unresolved-uncertainty register.
- + Buyer receives: domain equation set (symbolic; sources and applicability judgments identified).

YOU MUST DEVELOP:

- > Buyer must create: actual geometry and detailed design.
- > Buyer must create: sourced engineering parameters and acceptance thresholds.
- > Buyer must create: physical prototypes.
- > Buyer must create: all verification and validation results.
- > Buyer must create: manufacturing process qualification.
- > Buyer must create: regulatory pathway determination and submissions.

YOU MUST VERIFY:

- ? Biocompatibility (ISO 10993)
- ? Sterilization compatibility
- ? Mechanical integrity
- ? Regulatory pathway
- ? IP ownership and freedom to operate
- ? Manufacturing process capability

16. Open Questions

- {'unknown': 'FM_WITHOUT_QUANTITY_MATCHED_VERIFICATION:FM-DOM-005', 'reason': 'no available verification method measures a quantity family this failure affects (E21-A quantity rule); UNKNOWN disclosure recorded on the row'}
- {'unknown': 'value of critical parameter member slenderness ratio [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-001'}
- {'unknown': 'value of critical parameter yield/ultimate strength [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-002'}
- {'unknown': 'value of critical parameter applied cyclic load amplitude [P_cr N]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-003'}
- {'unknown': 'value of critical parameter required run-out cycles [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-004'}
- {'unknown': 'value of critical parameter articulation radius [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-005'}
- {'unknown': 'value of critical parameter friction coefficient at guides [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-006'}
- {'unknown': 'acceptance criterion for verification VF-001', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-001'}
- {'unknown': 'acceptance criterion for verification VF-002', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-002'}

- {'unknown': 'acceptance criterion for verification VF-003', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-003'}
- {'unknown': 'acceptance criterion for verification VF-004', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-004'}
- {'unknown': 'acceptance criterion for verification VF-005', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-005'}
- {'unknown': 'acceptance criterion for verification VF-006', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-006'}
- {'unknown': 'acceptance criterion for verification VF-007', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-007'}
- {'unknown': 'acceptance criterion for verification VF-008', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-008'}

17. Decisive Next Experiment

WP	Test Article	Equipment	Measurement	Acceptance	Deliverable	Effort
WP-01	first physical article	maintaining the proposed envelope	constraint-compliance	NOT ESTABLISHED	constraint-compliance	NOT ESTABLISHED
WP-02	constraint-compliance envelope article	per method	Accelerated fatigue test	NOT ESTABLISHED	fatigue life (run-out)	NOT ESTABLISHED
WP-03	article for VF-001	per method	run killer experiment	NOT ESTABLISHED	buckling / kink margin	NOT ESTABLISHED
WP-04	article for VF-002	per method	fatigue life (run-out) test	NOT ESTABLISHED	fatigue life (run-out)	NOT ESTABLISHED
WP-05	article for VF-003	per method	buckling / kink margin test	NOT ESTABLISHED	fatigue life (run-out)	NOT ESTABLISHED
WP-06	article for VF-004	per method	fatigue life (run-out) test	NOT ESTABLISHED	buckling / kink margin	NOT ESTABLISHED
WP-07	article for VF-005	per method	buckling / kink margin test	NOT ESTABLISHED	fatigue life (run-out)	NOT ESTABLISHED
WP-08	article for VF-006	per method	fatigue life (run-out) test	NOT ESTABLISHED	buckling / kink margin	NOT ESTABLISHED
WP-09	article for VF-007	per method	buckling / kink margin test	NOT ESTABLISHED	fatigue life (run-out)	NOT ESTABLISHED
WP-10	article for VF-008	per method	overload margin demonstration	NOT ESTABLISHED	fatigue life (run-out)	NOT ESTABLISHED

18. Buyer Decision Framework

WHY INVEST: Engineering definition exists with 3 governing equations and a 10-step build plan. The next experiment is clearly specified. Target buyer: domain-appropriate technology buyer (to be identified by portfolio owner).

WHY WAIT: No physical prototype exists. Regulatory pathway is unresolved. IP ownership is unverified. Manufacturing process is not qualified.

WHY REJECT: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

WHAT WOULD CHANGE THE DECISION: A successful bench experiment demonstrating the core mechanism. A qualified regulatory pathway. A confirmed IP position.

19. Kill Condition

KILL_IF: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

DISCLOSURE

This dossier distinguishes established evidence, external precedent, computational/modelled results, engineering proposals, and unresolved questions. The absence of physical validation should not be interpreted as evidence that the technology will fail; it means the relevant proposition has not yet been established experimentally.

This dossier does not constitute legal, patentability, FTO, regulatory, or investment advice.