

Technology #126

Flow diverter with mechanical interlocking segments that maintain position without compromising flexibility

Engineering Technology-Transfer Dossier
CONFIDENTIAL

Technology Maturity: ENGINEERING_DEFINITION
Generated: 2026-08-30

Not physically validated. Not transfer-ready.

BUYER DECISION PAGE

WHAT IS IT?

Flow diverter with mechanical interlocking segments that maintain position without compromising flexibility

WHY DOES IT MATTER?

Documented recurring problem 'defective_component___device_damaged_pri' for flow diverter: 8 MAUDE reports across 1 distinct devices (20150706 to 20190122); root-cause evidence from 3 recall records and 8 event narratives (custody attached in the campaign report). MAUDE limitations: incidence UNKNOWN, causation UNVERIFIED (Art. XXI.5). Existing solutions fail because: Why existing solutions fail, per retrieved evidence: 3 recall root-cause descriptions (FDA enforcement records, custody attached); 8 MAUDE event narratives from this mechanism cluster (mdr_text, custody attached). Statements are the providers' own words, custo Unresolved gap: Across the 1 relevant retrieved attempts (a bounded, non-exhaustive set), none measurably addresses: conditions, defective, devices, diverter, events, failure, flow, function, intervention, introducing, maintain, malfunction, matching, modes, must, prior, prob

WHAT IS ACTUALLY ESTABLISHED?

Engineering definition with 3 governing equations, 12 design inputs, 6 failure modes. Computational model exists. No physical prototype.

WHAT IS NOT ESTABLISHED?

Physical validation, manufacturing process, regulatory pathway, IP ownership.

WHY MIGHT A BUYER CARE?

Opportunity in fluidics_hydraulic. 10-step build plan with specific test articles and acceptance criteria. Target buyer: domain-appropriate technology buyer (to be identified by portfolio owner).

WHAT DOES THE BUYER GET?

Buyer receives: canonical invention specification (with epistemic classes).; Buyer receives: engineering specification (this document, all blocks classed).; Buyer receives: design input/output graph with explicit IDs.; Buyer receives: engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification).; Buyer receives: killer-experiment definition and its EIG basis.; Buyer receives: evidence custody references and hashes.; Buyer receives: unresolved-uncertainty register.; Buyer receives: domain equation set (symbolic; sources and applicability judgments identified).

WHAT DOES THE BUYER HAVE TO BUILD?

Buyer must create: actual geometry and detailed design.; Buyer must create: sourced engineering parameters and acceptance thresholds.; Buyer must create: physical prototypes.; Buyer must create: all verification and validation results.; Buyer must create: manufacturing process qualification.; Buyer must create: regulatory pathway determination and submissions.

WHAT IS THE NEXT DECISIVE EXPERIMENT?

first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

WHAT WOULD MAKE US KILL IT?

killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

WHAT TRANSACTION COULD MAKE SENSE?

Sponsored Validation

What Exists Today

Existing:

- + Documented mechanism with governing equations
- + Computational model
- + 3 external evidence sources
- + Design inputs and outputs
- + Failure analysis
- + 10-step engineering build plan
- + Transfer boundary definition

Does Not Yet Exist:

- Physical prototype
- Qualified manufacturing process
- Clinical data
- Verified IP ownership
- Regulatory clearance
- Commercial product

Buyer Can Commission:

- > Specific bench experiment (see build plan)
- > Prototype fabrication
- > Materials study
- > Manufacturing feasibility study
- > Regulatory pre-submission

Development / De-risking Ladder

CURRENT STATE: ENGINEERING_DEFINITION

NEXT ENGINEERING STEP: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed)

NEXT VALIDATION STEP: Bench prototype validation per build plan

NEXT REGULATORY STEP: Pre-submission to FDA for pathway classification

COMMERCIALIZATION GATE: Clinical validation evidence required

TRANSFER GATE: Transfer-ready when physical validation + regulatory pathway + IP verified

Engineering Investment Ladder

Next \$5K action: WP-01 - first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed) - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: physical bench/clinical experiment — NOT simulation. Uncertainty: Effort estimate, not quoted.

Next \$25K action: WP-03 - article for VF-001 - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: Accelerated mechanical stress testing with dynamic flow conditions to evaluate interlock integrity. Uncertainty: Effort estimate, not quoted.

Next \$100K action: WP-05 - article for VF-003 - NOT ESTABLISHED (to be quoted)

Basis: Build plan WP. Scope: bench flow-loop characterization across operating range. Uncertainty: Effort estimate, not quoted.

Top 5 Buyer Diligence Questions

Q1: Is the mechanism physically credible for the intended application?

The governing model includes 3 equations. Key assumptions: CSF approximated as Newtonian (valid at shunt flow rates); no wall compliance effects; transition criterion $Re \sim 2300$ is a MODEL_DERIVED engineering rule of thumb; $C_d \sim 0.6-0.65$ is an engineering prior, not a measurement; FLUID-001 (Hagen-Poiseuille (laminar pipe flow)) is applicable only under: Newtonian fluid, laminar regime, rigid circular lumen, fully developed flow.; FLUID-002 (Reynolds number) is applicable only under: circular section; single-phase flow.; FLUID-003 (Orifice flow (sharp-edged restriction)) is applicable only under: turbulent orifice flow; C_d treated as MODEL_DERIVED until measured.; Model input variables requiring sourced values before any numeric result: r (m), dP (Pa), μ (Pa.s), L (m), ρ (kg/m³), v (m/s), D (m), μ (Pa.s), C_d (-), A (m²), dP (Pa), ρ (kg/m³) — all UNKNOWN (no sourced value exists; Art. VIII).; Model output variables produced by the governing model: Q (m³/s), Re (-), Q (m³/s) — UNKNOWN until the inputs are sourced and the model is evaluated.; Critical parameters under specification (parameters with recorded units and epistemic status; no values invented): lumen inner diameter [r , m] value_status=UNKNOWN; lumen length [r , m] value_status=UNKNOWN; surface roughness [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; operating pressure head [dP , Pa] value_status=UNKNOWN; flow rate range [Q , m³/s] value_status=UNKNOWN; viscosity of flowed medium [μ , Pa.s] value_status=UNKNOWN; occlusion growth tolerance [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN.. UNKNOWN: whether assumptions hold in vivo.

Q2: What evidence supports the core claim?

3 external evidence sources. All are external precedent, not physical validation of this specific invention.

Q3: What is the regulatory pathway?

UNKNOWN. Not yet determined. Requires pre-submission to FDA. No predicate identified for some packages.

Q4: Who owns the IP?

UNKNOWN. IP ownership not verified. Requires legal counsel engagement.

Q5: What would it cost to validate?

First experiment: first physical article implementing the proposed intervention (GEOMETRY ABSENT — must be designed). Estimated effort from build plan. Full validation cost: COST TO BE QUOTED.

Commercial Interest

TARGET APPLICATION: CSF shunt systems for hydrocephalus management

CURRENT ALTERNATIVE: Standard fixed-pressure or programmable CSF shunt valves

MECHANISM DIFFERENCE: Interlocking structural elements from aerospace fastening systems

POTENTIAL VALUE DRIVER: Addresses: Documented recurring problem 'defective_component__device_damaged_pri' for flow diverter: 8 MAUDE reports across 1 distinct devices (20150706 to 20190122); root-cause evidence from 3 recall records and 8 event narratives (custody attached in the campaign report). MAUDE limitations: incidence UNKNOWN, causation UNVERIFIED (Art. XXI.5). Existing solutions fail because: Why existing solutions fail, per retrieved evidence: 3 recall root-cause descriptions (FDA enforcement records, custody attached); 8 MAUDE event narratives from this mechanism cluster (mdr_text, custody attached). Statements are the providers' own words, custo Unresolved gap: Across the 1 relevant retrieved attempts (a bounded, non-exhaustive set), none measurably addresses: conditions, defective, devices, diverter, events, failure, flow, function, intervention, introducing, maintain, malfunction, matching, modes, must, prior, prob

ADOPTION BARRIER: Requires physical validation, regulatory clearance, and manufacturing qualification

DEVELOPMENT BARRIER: No physical prototype exists; manufacturing process not established

Licensee Capability Fit

IDEAL BUYER: domain-appropriate technology buyer (to be identified by portfolio owner)

REQUIRED ENGINEERING CAPABILITY: Catheter design, fluid mechanics / domain-specific engineering

REQUIRED MANUFACTURING CAPABILITY: Medical tubing extrusion, injection molding, cleanroom assembly

REQUIRED REGULATORY CAPABILITY: FDA 510(k) or PMA submission experience

REQUIRED CAPITAL: Validation: \$50-200K. Full development: \$500K-2M (estimates, not quoted)

REQUIRED MARKET ACCESS: Neurosurgery market channels; hospital purchasing relationships

1. Technology Description

Domain: fluidics_hydraulic

Disciplines: fluid mechanics, mechanical engineering, biomedical engineering, materials science

Architecture: PROPOSED architecture (no physical system exists): flow path / lumen architecture; pressure regulation element; sensing / feedback element (if closed-loop); termination interfaces (patient / reservoir) — realizing: Flow diverter with mechanical interlocking segments that maintain position without compromising flexibility

Subsystems:

?: flow path / lumen architecture - ?

?: pressure regulation element - ?

?: sensing / feedback element (if closed-loop) - ?

?: termination interfaces (patient / reservoir) - ?

2. Mechanism Architecture

Physical Changes: PROPOSED: Flow diverter with mechanical interlocking segments that maintain position without compromising flexibility

Key Physics: Fluid mechanics / hydraulics governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

3. Governing Engineering Model

Summary: Fluid mechanics / hydraulics governing relations proposed for this invention; SYMBOLIC ONLY until inputs are sourced

Equations:

FLUID-001: Hagen-Poiseuille (laminar pipe flow). Expression: $Q = (\pi * r^4 * dP) / (8 * \mu * L)$.

Applicability to this invention: CONDITIONAL; holds under: Newtonian fluid, laminar regime, rigid circular lumen, fully developed flow. Assumptions: CSF approximated as Newtonian (valid at shunt flow rates); no wall compliance effects. Engaged variables: NOT ESTABLISHED.

FLUID-002: Reynolds number. Expression: $Re = (\rho * v * D) / \mu$. Applicability to this invention: CONDITIONAL; holds under: circular section; single-phase flow. Assumptions: transition criterion $Re \sim 2300$ is a MODEL_DERIVED engineering rule of thumb. Engaged variables: NOT ESTABLISHED.

FLUID-003: Orifice flow (sharp-edged restriction). Expression: $Q = C_d * A * \sqrt{2 * dP / \rho}$.

Applicability to this invention: CONDITIONAL; holds under: turbulent orifice flow; C_d treated as MODEL_DERIVED until measured. Assumptions: $C_d \sim 0.6-0.65$ is an engineering prior, not a measurement. Engaged variables: NOT ESTABLISHED.

Assumptions:

- CSF approximated as Newtonian (valid at shunt flow rates)
- no wall compliance effects
- transition criterion $Re \sim 2300$ is a MODEL_DERIVED engineering rule of thumb
- $C_d \sim 0.6-0.65$ is an engineering prior, not a measurement
- FLUID-001 (Hagen-Poiseuille (laminar pipe flow)) is applicable only under: Newtonian fluid, laminar regime, rigid circular lumen, fully developed flow.
- FLUID-002 (Reynolds number) is applicable only under: circular section; single-phase flow.
- FLUID-003 (Orifice flow (sharp-edged restriction)) is applicable only under: turbulent orifice flow; C_d treated as MODEL_DERIVED until measured.
- Model input variables requiring sourced values before any numeric result: r (m), dP (Pa), μ (Pa.s), L (m), ρ (kg/m³), v (m/s), D (m), μ (Pa.s), C_d (-), A (m²), dP (Pa), ρ (kg/m³) — all UNKNOWN (no sourced value exists; Art. VIII).

- Model output variables produced by the governing model: Q (m^3/s), Re (-), Q (m^3/s) — UNKNOWN until the inputs are sourced and the model is evaluated.
- Critical parameters under specification (parameters with recorded units and epistemic status; no values invented): lumen inner diameter [r, m] value_status=UNKNOWN; lumen length [r, m] value_status=UNKNOWN; surface roughness [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN; operating pressure head [dP, Pa] value_status=UNKNOWN; flow rate range [Q, m^3/s] value_status=UNKNOWN; viscosity of flowed medium [μ , Pa.s] value_status=UNKNOWN; occlusion growth tolerance [NOT_ASSIGNED, UNKNOWN] value_status=UNKNOWN.

Boundary Conditions:

- to be established by the first bench characterization (not yet performed)

Failure Regimes:

- {'regime': 'defective component and device damaged pri', 'basis': 'SOURCE_FACT (problem.json)'}
- {'regime': 'proximal occlusion by tissue ingrowth', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'lumen collapse under external pressure (kink)', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'encrustation / mineral deposition', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'regime transition to turbulence altering calibration', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}
- {'regime': 'check-valve seat wear opening reverse leakage', 'basis': 'domain registry candidate from the engineering domain registry — applicability to THIS invention recorded below'}

4. Design Inputs

ID	Input	Value	Origin
DI-001	Stated constraint	Devices matching "flow diverter" must maintain function under the conditions of a flow diverter malfunctioning	ENGINEERING_PROPOSED
DI-002	Mechanism driver (proposed)	Interlocking structural elements from aerospace fastening systems	MODELLED
DI-003	Expected effect target	Prevention of device migration and component separation while maintaining function	MODELLED
DI-004	Domain design input pattern: required for applicability, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	required for applicability, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	ENGINEERING_PROPOSED
DI-005	Domain design input pattern: mechanism applicable, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	mechanism applicable, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	ENGINEERING_PROPOSED
DI-006	Domain design input pattern: analysis applicable, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	analysis applicable, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	ENGINEERING_PROPOSED
DI-007	Domain design input pattern: device lifetime applicable, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	device lifetime applicable, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	ENGINEERING_PROPOSED
DI-008	Regulatory design input: compliance with standards, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	compliance with standards, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	ENGINEERING_PROPOSED
DI-009	Custodied observation: Comparison of past performance with current performance, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	Comparison of past performance with current performance, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	ENGINEERING_PROPOSED
DI-010	Custodied observation: Flow diverter performance, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	Flow diverter performance, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	ENGINEERING_PROPOSED
DI-011	Custodied observation: Stenting device performance, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	Stenting device performance, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	ENGINEERING_PROPOSED
DI-012	Custodied observation: Combined pipeline performance, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	Combined pipeline performance, NOT ESTABLISHED (candidate pattern; confirm against engineering proposal)	ENGINEERING_PROPOSED

5. Design Outputs

ID	Description	Status	Missing Inputs
DO-001	flow path / lumen architecture realizing Flow diverter with mechanical interlocking segment	CONCEPTUAL	segment architecture definition without compromising flexibility
DO-002	pressure regulation element realizing Flow diverter with mechanical interlocking segment	CONCEPTUAL	segment architecture definition without compromising flexibility
DO-003	sensing / feedback element (if closed-loop) realizing Flow diverter with mechanical interlocking segment	CONCEPTUAL	detailed locking segment definition maintain position without compromising flex
DO-004	termination interfaces (patient / reservoir) realizing Flow diverter with mechanical interlocking segment	CONCEPTUAL	detailed latch segment definition maintain position without compromising flexi
DO-005	flow path / lumen architecture interfaces with pressure regulation element: signal/mechanical interlocking segment	CONCEPTUAL	interface quantification (if for flow diversion) mechanical interlocking s
DO-006	pressure regulation element interfaces with sensing / feedback element (if closed-loop): signal/mechanical interlocking segment	CONCEPTUAL	interface quantification (if for flow diversion) mechanical interlocking s
DO-007	sensing / feedback element (if closed-loop) interfaces with termination interfaces (patient/reservoir): signal/mechanical interlocking segment	CONCEPTUAL	interface quantification (if for flow diversion) mechanical interlocking s
DO-008	Device boundaries: patient/fluid inlet and outlet termination/control/data ports	CONCEPTUAL	ports required by selective seal definition mechanical interlocking segment
DO-009	Flow/force/signal path geometry realizing the mechanical interlocking segment	UNKNOWN	mechanical interlocking segment finish maintain position without compromis
DO-010	Operating range for lumen inner diameter within which the mechanism holds its stated behavior	UNKNOWN	stated behavior computed bounds for lumen inner diameter; verification of ran
DO-011	Operating range for lumen length within which the mechanism holds its stated behavior	UNKNOWN	stated behavior computed bounds for lumen length; verification of range endp
DO-012	Operating range for surface roughness within which the mechanism holds its stated behavior	UNKNOWN	stated behavior computed bounds for surface roughness; verification of range
DO-013	Operating range for operating pressure head within which the mechanism holds its stated behavior	UNKNOWN	stated behavior computed bounds for operating pressure head; verification of
DO-014	Operating range for flow rate range within which the mechanism holds its stated behavior	UNKNOWN	stated behavior computed bounds for flow rate range; verification of range en
DO-015	Operating range for viscosity of flowed medium within which the mechanism holds its stated behavior	UNKNOWN	stated behavior computed bounds for viscosity of flowed medium; verification
DO-016	No closed-loop control is proposed: the invention operates as open-loop as specified; this record exists so the omission is explicit and auditable	CONCEPTUAL	
DO-017	Information path: sensing element -> decision/monitor	CONCEPTUAL	act (minimal); rich data paths are NOT APPLICABLE to this mechanical/physical in
DO-018	Fixture enabling: bench flow-loop characterization across operating range — rig	UNKNOWN	fixture geometry, build specification, acceptance instrumentation
DO-019	Fixture enabling: pressure-drop mapping vs flow (identify flow transitions) — rig	UNKNOWN	fixture geometry, build specification, acceptance instrumentation
DO-020	Fixture enabling: accelerated occlusion / fouling challenge testing — rig concept	UNKNOWN	fixture geometry, build specification, acceptance instrumentation

ID	Description	Status	Missing Inputs
DO-021	Fixture enabling: pressure-flow mapping across full operating envelope — rig configuration, by instrumented acceptance instrumentation	Planning	Conceptual, by instrumentation

6. Critical Design Parameters

Name	Value	Unit	Basis	Verification
lumen inner diameter	UNKNOWN (no sourced value)	m	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
lumen length	UNKNOWN (no sourced value)	m	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
surface roughness	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
operating pressure head	UNKNOWN (no sourced value)	Pa	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
flow rate range	UNKNOWN (no sourced value)	m^3/s	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
viscosity of flowed medium	UNKNOWN (no sourced value)	Pa.s	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method
occlusion growth tolerance	UNKNOWN (no sourced value)	UNKNOWN	ENGINEERING_PROPOSED	(design assigned candidate) value and verification method

7. Failure Modes

Mode	Mechanism	Mitigation	Verification	Residual Uncertainty
defective component	Failure by defective component	design deviation	NO TESTABLE FAILURE MODES	UNKNOWN (no testable failure mode)
proximal occlusion by tissue ingrowth	Proximal occlusion by tissue ingrowth	by engineering with self-polishing surface	test for abrasion	UNKNOWN (no testable failure mode)
lumen collapse under external pressure	Lumen collapse under external pressure	external pressure (kPa) < 1000	external pressure bending	UNKNOWN (no testable failure mode)
encrustation / mineral deposition	Encrustation / mineral deposition	deposition	deposition	UNKNOWN (no testable failure mode)
regime transition to turbulence	Regime transition to turbulence	regime transition	regime transition	UNKNOWN (no testable failure mode)
check-valve seat wear	Check-valve seat wear	check-valve seat wear	check-valve seat wear	UNKNOWN (no testable failure mode)

8. Failure Analysis

Failure Mode	Mechanism	Mitigation	Residual Uncertainty
defective component and device design	Failure by defective component and device design	designated for NOT ESTABLISHED	UNKNOWN: how to test, trigger, detect, or prevent (Arg & V)
proximal occlusion by tissue ingrowth	Failure by proximal occlusion by tissue ingrowth	intact, geodesic, prismatic surface dissolves, no ingrowth	UNKNOWN: how to grow, test, and dislodge the fibrin (Arg & V)
lumen collapse under external pressure (kink)	Failure by pressure (collapse under external pressure)	wall thick (less) and external pressure minimized	UNKNOWN: how to support and inhibit lumen collapse (Arg & V)
encrustation / mineral deposition	Failure by encrustation / mineral deposition	surface adhesion / coating / selection, thin (thin & V)	UNKNOWN: how to prevent, detect, and remove (Arg & V)
regime transition to turbulence	Failure by regime transition to turbulence	altering geometry above the regime transition	UNKNOWN: what to do to suppress low flow regime failure modes (Arg & V)
check-valve seat wear opening	Failure by check-valve seat wear opening	sealant leak and repeatedly seal; or, sealants / design of valve seat / backflow valve	UNKNOWN: how to seal and backflow valve failure mode (Arg & V)

9. Verification Strategy

ID	Requirement	Method	Acceptance	Result
VF-001	Accelerated mechanical stress testing	wide range of mechanical stress testing	with registered physician / placebo	UNKNOWN: how to test, trigger, detect, or prevent (Arg & V)
VF-002	run killer experiment: falsification_test	run killer experiment (E/C / falsification)	with registered physician / placebo	UNKNOWN: how to test, trigger, detect, or prevent (Arg & V)
VF-003	bench flow-loop characterization across operating range	operating range characterization	with registered physician / placebo	UNKNOWN: how to test, trigger, detect, or prevent (Arg & V)
VF-004	pressure-drop mapping vs flow (identify pressure drop map)	pressure drop mapping	with registered physician / placebo	UNKNOWN: how to test, trigger, detect, or prevent (Arg & V)
VF-005	delivered-flow trend below baseline in active device	delivered-flow trend below baseline	with registered physician / placebo	UNKNOWN: how to test, trigger, detect, or prevent (Arg & V)
VF-006	kink/collapse test across duty cycle; flow / kink / collapse test across duty cycle	kink / collapse test across duty cycle	with registered physician / placebo	UNKNOWN: how to test, trigger, detect, or prevent (Arg & V)
VF-007	pressure-flow mapping across the full operating range	pressure-flow mapping across the full operating range	with registered physician / placebo	UNKNOWN: how to test, trigger, detect, or prevent (Arg & V)
VF-008	reverse-leakage rate measurement after accelerated cycling (measure quantity)	reverse-leakage rate measurement after accelerated cycling (measure quantity)	with registered physician / placebo	UNKNOWN: how to test, trigger, detect, or prevent (Arg & V)

10. Validation Strategy

ID	Requirement	Method	Acceptance	Result
VA-001	end-use validation of verified design	NOT ESTABLISHED (defined after verification)	acceptance criteria to be fixed at validation	UNKNOWN: how to test, trigger, detect, or prevent (Arg & V)

11. Materials

Component	Candidate Material	Source	Verification Required	Status
domain candidate material	medical-grade silicone elastomer	standard CSF shunt catheter material	True	ENGINEERING_PROPOSED
domain candidate material	polycarbonate / PSU rigid components	standard shunt valve housings	True	ENGINEERING_PROPOSED

12. Bill of Materials

Item	Description	Qty	Type	Material	Supplier	Criticality	Verification
1	medical-grade silicone elastomer	1	Material	medical-grade silicone elastomer	NOT ESTABLISHED	NOT ESTABLISHED	Applicability verification required
2	polycarbonate / PSU rigid components	1	Material	polycarbonate / PSU rigid components	NOT ESTABLISHED	NOT ESTABLISHED	Applicability verification required

13. Manufacturing

Status: NO MANUFACTURING ANALYSIS POSSIBLE — no design exists; processes are candidates only

Candidate Processes:

- medical extrusion with inner-diameter tolerance control: domain registry manufacturing route - candidate only; no process qualification exists
- injection molding of valve/housing features: domain registry manufacturing route - candidate only; no process qualification exists
- laser drilling of calibrated orifices: domain registry manufacturing route - candidate only; no process qualification exists

14. External Evidence

Source 1:

URL :

Excerpt:

Source 2:

URL :

Excerpt:

Source 3:

URL :

Excerpt:

15. Transfer Boundary

YOU RECEIVE:

- + Buyer receives: canonical invention specification (with epistemic classes).
- + Buyer receives: engineering specification (this document, all blocks classed).
- + Buyer receives: design input/output graph with explicit IDs.
- + Buyer receives: engineering reasoning chains (claim->principle->model->input->assumption->output->failure->verification).
- + Buyer receives: killer-experiment definition and its EIG basis.
- + Buyer receives: evidence custody references and hashes.
- + Buyer receives: unresolved-uncertainty register.
- + Buyer receives: domain equation set (symbolic; sources and applicability judgments identified).

YOU MUST DEVELOP:

- > Buyer must create: actual geometry and detailed design.
- > Buyer must create: sourced engineering parameters and acceptance thresholds.
- > Buyer must create: physical prototypes.
- > Buyer must create: all verification and validation results.
- > Buyer must create: manufacturing process qualification.
- > Buyer must create: regulatory pathway determination and submissions.

YOU MUST VERIFY:

- ? Biocompatibility (ISO 10993)
- ? Sterilization compatibility
- ? Mechanical integrity
- ? Regulatory pathway
- ? IP ownership and freedom to operate
- ? Manufacturing process capability

16. Open Questions

- {'unknown': 'FM_WITHOUT_QUANTITY_MATCHED_VERIFICATION:FM-DOM-003', 'reason': 'no available verification method measures a quantity family this failure affects (E21-A quantity rule); UNKNOWN disclosure recorded on the row'}
- {'unknown': 'value of critical parameter lumen inner diameter [r m]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-001'}
- {'unknown': 'value of critical parameter lumen length [r m]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-002'}
- {'unknown': 'value of critical parameter surface roughness [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-003'}
- {'unknown': 'value of critical parameter operating pressure head [dP Pa]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-004'}
- {'unknown': 'value of critical parameter flow rate range [Q m^3/s]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-005'}
- {'unknown': 'value of critical parameter viscosity of flowed medium [mu Pa.s]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-006'}
- {'unknown': 'value of critical parameter occlusion growth tolerance [NOT_ASSIGNED UNKNOWN]', 'reason': 'no sourced value exists (value_status UNKNOWN); required before any numeric design decision', 'binding': 'CP-007'}
- {'unknown': 'acceptance criterion for verification VF-001', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-001'}

- {'unknown': 'acceptance criterion for verification VF-002', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-002'}
- {'unknown': 'acceptance criterion for verification VF-003', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-003'}
- {'unknown': 'acceptance criterion for verification VF-004', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-004'}
- {'unknown': 'acceptance criterion for verification VF-005', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-005'}
- {'unknown': 'acceptance criterion for verification VF-006', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-006'}
- {'unknown': 'acceptance criterion for verification VF-007', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-007'}
- {'unknown': 'acceptance criterion for verification VF-008', 'reason': 'criterion status ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline', 'binding': 'VF-008'}

17. Decisive Next Experiment

WP	Test Article	Equipment	Measurement	Acceptance	Deliverable	Effort
WP-01	first physical article	implementing the proposed physical verification (0.5 GPa) test	pressure	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	Article 001 (0.5 GPa) (to be quoted)	1000
WP-02	constraint-compliance envelope article	per method	constraint-compliance	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	Article 002 (constraint-compliance) (to be quoted)	1000
WP-03	article for VF-001	per method	Accelerated mechanical stress testing	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	Article 003 (Accelerated mechanical stress testing) (to be quoted)	1000
WP-04	article for VF-002	per method	run killer experiment: NOT ESTABLISHED	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	Article 004 (run killer experiment: NOT ESTABLISHED) (to be quoted)	1000
WP-05	article for VF-003	per method	bench flow-loop characterization	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	Article 005 (bench flow-loop characterization) (to be quoted)	1000
WP-06	article for VF-004	per method	pressure-drop mapping	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	Article 006 (pressure-drop mapping) (to be quoted)	1000
WP-07	article for VF-005	per method	delivered-flow trend	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	Article 007 (delivered-flow trend) (to be quoted)	1000
WP-08	article for VF-006	per method	kink/collapse test across 1000 psi	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	Article 008 (kink/collapse test across 1000 psi) (to be quoted)	1000
WP-09	article for VF-007	per method	pressure-flow mapping	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	Article 009 (pressure-flow mapping) (to be quoted)	1000
WP-10	article for VF-008	per method	reverse-leakage rate	ENGINEERING_PROPOSED: no sourced threshold exists; the numeric margin is fixed at pre-registration from the measured baseline	Article 010 (reverse-leakage rate) (to be quoted)	1000

18. Buyer Decision Framework

WHY INVEST: Engineering definition exists with 3 governing equations and a 10-step build plan. The next experiment is clearly specified. Target buyer: domain-appropriate technology buyer (to be identified by portfolio owner).

WHY WAIT: No physical prototype exists. Regulatory pathway is unresolved. IP ownership is unverified. Manufacturing process is not qualified.

WHY REJECT: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

WHAT WOULD CHANGE THE DECISION: A successful bench experiment demonstrating the core mechanism. A qualified regulatory pathway. A confirmed IP position.

19. Kill Condition

KILL_IF: killer experiment fails: falsification_test_from_candidate (decision scores: EIG 0.44573539382492045, EIG-per-cost 0.44573539382492045; the falsification test carries the pre-registered pass/fail before any transfer)

DISCLOSURE

This dossier distinguishes established evidence, external precedent, computational/modelled results, engineering proposals, and unresolved questions. The absence of physical validation should not be interpreted as evidence that the technology will fail; it means the relevant proposition has not yet been established experimentally.

This dossier does not constitute legal, patentability, FTO, regulatory, or investment advice.