

Package #125

Implement a multi-haptic configuration that distributes forces across the anterior chamber angle rather than relying on single-point fixation, reducing mechanical stress at any one point

Technology Maturity: ENGINEERING_DEFINITION

Transfer Posture: Sponsored Validation

Problem: Documented recurring problem 'device_dislodged_or_dislocated' for intraocular lens: 12 MAUDE reports across 3 distinct devices (20200707 to 20210129); root-cause evidence from 14 recall records and 10 event narratives (custody attached in the campaign report). MAUDE limitations: incidence UNKNOWN, causation UNVERIFIED (Art. XXI.5). Existing solutions fail because: Why existing solutions fail, per retrieved evidence: 14 recall root-cause descriptions (FDA enforcement records, custody attached); 10 MAUDE event narratives from this mechanism cluster (mdr_text, custody attached). Statements are the providers' own words, cus Unresolved gap: Across the 10 relevant retrieved attempts (a bounded, non-exhaustive set), none measurably addresses: conditions, devices, dislodged, events, failure, function, injury, intervention, introducing, maintain, matching, modes, must, problem, producing, recurring,

Mechanism: Three-haptic angle-supported design for fixation in absence of standard anatomical prerequisites

Contents:

- 01 - Executive Technology Brief
- 02 - Engineering Technology-Transfer Dossier
- 03 - Buyer Decision Card
- 04 - Evidence Summary
- 05 - Transfer Manifest

Status: ENGINEERING_DEFINITION. Not physically validated.