Skill-Level Experts with Grounded Targets: Modularity and Generality in Language-Conditioned Manipulation

Prateek Pawar
Independent researcher
prateekspawar@gmail.com

***Abstract*—Vision-language-action (VLA) models are increasingly specialised by attaching small task-specific experts to a shared, frozen backbone. We ask at which granularity such experts should be defined. We compare three ways of organising the same model capacity, data and compute for language-conditioned pick-and-place on a 5-DoF arm in simulation: one monolithic model, *task-level* experts (one per instruction, as in recent LoRA-expert systems), and *skill-level* experts (one per primitive such as find, pick, place and stack, composed into tasks), all conditioned on a target pose provided by an open-vocabulary perception and tracking stack. In seeded, paired evaluations of 50-150 episodes per condition we find that (i) splitting by skill does not improve per-skill accuracy over a monolithic model trained on the same data; (ii) skill-level experts generalise far better than task-level experts, on seen (90-98% vs. 56-72% success) and unseen instructions (94% vs. 48-58%), because every skill learns from all episodes; (iii) a new skill can be added in isolation without any access to old data or risk to deployed skills, while naive fine-tuning of a monolithic model erases its previous skills (0%), and fine-tuning with replay retains them but requires the old data and full re-validation; (iv) on unseen multi-step tasks, skills compose almost independently for both organisations, and composite success is bounded by the weakest skill, here stacking onto raised targets.**

***Index Terms*—vision-language-action models, modular policies, skill composition, imitation learning, robot manipulation**

I. Introduction

Generalist VLA policies such as OpenVLA [1], π_0 [2] and SmolVLA [3] map images and an instruction to robot actions. Adapting them to new tasks without degrading old ones is an open problem: fine-tuning one model on new data causes interference and forgetting [4]. A recent and effective answer is to freeze the backbone and attach a lightweight expert per task, selected at run time from the instruction [5].

This raises a design question that, to our knowledge, has not been studied in a controlled way: *what should an expert be responsible for?* Experts can be defined per task ("put the blue cube on the blue plate") or per skill ("pick", "place"), with a planner composing skills into tasks [6], [7]. The two choices partition the same data very differently. A task expert sees only the demonstrations of its instruction; a skill expert sees the corresponding segment of every demonstration, regardless of which objects are involved, provided it is told *which* object to act on. We provide that information explicitly as a target pose from an open-vocabulary detection, stereo and tracking stack, building on evidence that grounded 3-D targets strongly improve VLA generalisation [8], [9].

Figure 3 contrasts the three organisations we compare.

a) Contributions.:

- A modular architecture of skill-level experts on a shared frozen VLA backbone, each conditioned on a tracked 9-D target pose and emitting a pass/fail verdict, with a robot-agnostic action space (§III).
- A controlled comparison of monolithic, task-level and skill-level organisations at equal data and compute (§V-A, §V-C), of how each absorbs a new skill (§V-D), and of how each executes unseen multi-step compositions (§V-B).
- An evaluation protocol with seeded, paired episodes and sign tests on the discordant pairs, so that conditions are compared on identical scenes.

II. Related Work

a) Vision-language-action models.: OpenVLA [1], π_0 [2] and SmolVLA [3] predict actions from images and language. Hierarchical systems such as Hi Robot [10] and $\pi_{0.5}$ [11] add a high-level reasoner that issues sub-goals to a low-level policy. Our low-level policies are SmolVLA-based skill experts; the high-level sequencing is given (oracle) in this study to isolate execution.

b) Experts on a frozen backbone.: CORAL [5] attaches one LoRA [12] expert per task to a frozen VLA and routes by instruction, which avoids interference and supports adding tasks. Our task-level condition mirrors this granularity (with full action-expert training instead of LoRA); our skill-level condition changes the granularity, which is the variable we study.

c) Grounded targets.: MOO [8] conditions a policy on object locations from an open-vocabulary detector, and recent work injects a grounded 3-D point into the action head of $\pi_{0.5}$ and GR00T [9], with large gains under position and task perturbation. We use a 9-D target pose (position and symmetry-folded orientation) that is *tracked* during execution (SAM 2 [13]), and train on targets that imitate the tracker's error model.

d) Skill libraries and planners.: SayCan [6] and Code as Policies [7] compose pre-defined skills with a language model.




Fig. 1. A successful evaluation episode seen from the left head camera: "put the blue cube on the orange plate". (a) Initial scene with randomly coloured plates; (b) `find` looks from a preset viewpoint; (c) `pick` grasps the tracked cube; (d) `place` releases it on the plate.

We compose learned skill experts; the LLM planner is left out of the experiments reported here.

e) Failure detection.: SAFE [14] predicts failure from VLA features. Our experts emit a learned verdict, and the executor additionally verifies each grasp from the gripper opening.

III. System

a) Overview.: Figure 2 shows the system. An instruction ("put the red cube on the green plate") is mapped to a sequence of skill calls: `find(cube)`, `find(plate)`, `pick(cube)`, `place(plate)`. Each skill is executed by a VLA expert that receives the left and right images of a stereo head camera, a point map from stereo depth, the step text, and a 19-D state: the tool-centre-point (TCP) pose (position, 6-D rotation, gripper opening) and the 9-D pose of the skill's target object, all in the head frame. It outputs chunks of 12-D actions: TCP pose, gripper opening, and a verdict $[\mathit{done}, \mathit{success}]$. A robot-specific adapter and inverse kinematics map the head-frame TCP command to joint targets, so the experts do not depend on the arm.

b) Skill experts on a shared backbone.: All experts share one frozen SmolVLA vision-language backbone (350 M parameters); each skill has its own action expert and depth branch (101 M trainable parameters). Switching skills swaps only these weights (0.8 ms). The skills are `find` (move until the object is clearly visible), `pick`, `place` and, added later, `stack`.

c) Perception and target poses.: OWLv2 [15] proposes candidate boxes; each candidate is scored by detector confidence for the request and for the noun, a stereo size likelihood, and a learned colour posterior of the object's own pixels (one CIELab Gaussian per colour name, fitted on rendered training images). Depth comes from a stereo network [16]. The target's yaw is reported modulo the object's symmetry (90° for cubes), as perception measures it, and the training targets use the same convention. `find` fuses detections from the find view and three preset viewpoints; afterwards a SAM 2 [13] tracker per object, with a locked/following state machine on trusted measurements, publishes the target during execution.

d) Executor.: A skill ends when the expert reports *done* on two consecutive current-frame readings, or after 16 s. After `pick`, a *grasp check* reads the gripper opening: closed on nothing reads 0.00-0.01, holding a cube ≈0.10. On a miss the executor opens, returns home, re-detects the cube and retries (up to twice). During `place`, a *release gate* suppresses any opening command while the TCP is more than 4 cm sideways or 6.5 cm above the perceived target.

IV. Experimental Setup

a) Environment.: A simulated SO-101 arm (5-DoF + gripper) in Isaac Lab [17] with four 3 cm cubes and two plates whose colours are drawn per episode from nine colours (including the cube colours). The stereo head (2×512^2, 6 cm baseline) is mounted like a human head relative to the arm. Pushes: the target cube is slid 3-6 cm during the pick approach.

b) Data.: A scripted expert with DART-style noise [18] generates 1000 static and 1000 moving-target pick-and-place demonstrations, 500 in which the cube moves during the descent, and 400 failure demonstrations (grasp miss or slip, off-plate release, drop) whose motion before the failure is masked from the loss so that only the verdict is learnt there; in total 2,900 episodes (563k frames). Recording continues through the release so that the success label covers frames with the gripper open. Training targets imitate the tracker: detection noise, update rate, dead-band and freezing near the gripper.

c) Training.: All models are trained with LeRobot [19] using the same recipe (batch 32, frozen backbone, cosine schedule) from the same base. Skill experts: 15k steps each for pick and place; find: 15k steps on 1,200 find demonstrations.

d) Protocol.: Every evaluation uses the same seeded scene sequence, so conditions are paired episode by episode; we report success rates and two-sided sign tests on the discordant pairs. Even with seeding, about 8% of individual outcomes differ between identical runs (GPU non-determinism), so we treat differences of a few episodes as noise. *Pick* = cube lifted; *full* = cube resting on the target and released.




Fig. 2. System overview. An instruction becomes a sequence of skill calls. Perception turns the stereo images into a tracked 9-D target pose for the active skill. Each skill is an expert (101 M trainable parameters) on one frozen, shared vision-language backbone; only the active expert's weights are swapped. The executor ends skills on the expert's verdict, checks the grasp from the gripper opening (retrying a missed pick) and gates the release; a robot adapter and IK map head-frame TCP commands to the arm.

TABLE I
EXPERIMENT 1: MONOLITHIC VS. PER-SKILL EXPERTS, SAME DATA AND COMPUTE (150 PAIRED EPISODES).

	Monolithic	Skill experts	sign test
Stationary pick	94%	91%	p=0.13
Stationary full	93%	91%	p=0.22
Push pick	81%[†]	87%	p=0.04
Push full	81%	87%	p=0.12

[†]2 further picks were confirmed only in the final check (logging fixed later): 82%.

TABLE II
EXPERIMENT 2: FULL SUCCESS, 50 PAIRED EPISODES PER INSTRUCTION. TASK EXPERTS ARE TRAINED ONLY ON THEIR INSTRUCTION; FOR UNSEEN INSTRUCTIONS, THE EXPERT WITH THE SAME CUBE COLOUR IS USED.

	Instruction	Task exp.	Skill exp.	sign test
seen	blue cube → blue plate	72%	90%	p=0.02
	red cube → yellow plate	58%	96%	$p=2\cdot10^{-5}$
	blue cube → white plate	72%	96%	$p=5\cdot10^{-4}$
	red cube → green plate	56%	98%	$p=6\cdot10^{-6}$
unseen	blue cube → orange plate	48%	94%	$p=2\cdot10^{-6}$
	red cube → purple plate	58%	94%	$p=4\cdot10^{-5}$

V. RESULTS

A. Experiment 1: one model or one expert per skill?

We train a single model on exactly the frames the pick and place experts saw (with the same per-segment labelling) for 30k steps, matching the 2×15k steps of the two experts. Table I shows no consistent advantage: the monolith is slightly better on stationary scenes and slightly worse under pushes; only the push pick difference reaches $p < 0.05$. **Splitting by skill does not, by itself, make skills better.**

B. Experiment 2: task-level vs. skill-level experts

We train four task experts, each a complete pick-and-place model on the 110-121 episodes of one instruction, for 7.5k steps each (30k total, as in Exp. 1), and evaluate each on 50 episodes of its own instruction alongside the skill experts (same scenes). For two unseen instructions we route to the expert with the same cube colour (Table II, Fig. 4a). Skill experts reach 90-98% on seen and 94% on unseen instructions; task experts reach 56-72% even on their own instruction and 48-58% on unseen ones (all $p \leq 0.02$). Task experts do not collapse on unseen instructions, which we attribute to the grounded target pose. **Organising experts by skill lets each expert use all the data; organising by task partitions it.**

C. Experiment 3: adding a new skill

We add `stack` (place a cube on another cube), a geometrically different target, from 300 new demonstrations (Table III, Fig. 4b). A new stack expert, trained in isolation, stacks 53% (33% with 100 demonstrations, $p < 10^{-4}$), and 59% when initialised from the place expert. The existing place expert used for stacking without training fails entirely: it lowers




Fig. 3. Three organisations of the same capacity, data and compute. (a) One model for all instructions and skills. (b) One expert per instruction, selected by a router, each trained only on its instruction's episodes (CORAL-style granularity). (c) One expert per skill, composed by a planner and told its target by perception; each expert trains on that skill's segment of every episode.



Fig. 4. (a) Experiment 2: full success of task-level and skill-level experts on four seen and two unseen instructions (50 paired episodes each; all differences $p \leq 0.02$). (b) Experiment 3: stacking success when the `stack` skill is added in different ways (150 paired episodes); for the monolith, the success on its original pick-and-place task afterwards is given.

the cube as onto a plate and knocks it out of the gripper. Fine-tuning the monolith on the stack data alone erases its previous skills (0% on stacking and on its original pick-and-place task); fine-tuning with replay [20] of 290 old episodes reaches 68% stacking and retains pick-and-place at 92% (vs. 93%, $p = 0.69$). Training compute is identical (5k steps); the difference is operational. **The skill expert is added without old data and cannot affect deployed skills; the monolith transfers more but must be retrained with the old data and re-validated on every change.**

TABLE III
EXPERIMENT 3: ADDING `STACK` (150 PAIRED EPISODES; 5K TRAINING STEPS WHERE TRAINED).

Method	Stacked	Old pick+place
Place expert reused, no training	0%	unchanged
Stack expert, 100 demos	33%	unchanged
Stack expert, 300 demos	53%	unchanged
Stack expert, 300 demos, from place	59%	unchanged
Monolith, fine-tuned on stack only	0%	0%
Monolith, fine-tuned with replay	**68%**	92%

TABLE IV
EXPERIMENT 4: COMPOSED SUCCESS (50 PAIRED EPISODES) AND STEP SUCCESS (SECOND STEP GIVEN THE FIRST).

Task	Skill experts	Monolith+replay	sign test
two plates	86%	88%	p=1.0
plate-stack	42%	62%	p=0.08
tower	16%	18%	p=1.0
second step given the first			
2nd cube → plate	91%	94%	
stack on a cube on a plate	45%	65%	
stack on a two-cube tower	26%	26%	

D. Experiment 4: composed multi-step tasks

We evaluate three compositions that never occur as training episodes, each with 50 seeded episodes and the oracle skill sequence, so that only execution is compared: *two plates* (two cubes onto the two plates), *plate-stack* (a cube onto a plate, then a second cube stacked on it) and *tower* (a three-cube tower). The skill condition uses the pick, place and find experts with the place-initialised stack expert; the monolithic condition is the monolith fine-tuned with replay, which performs all skills. Success requires every sub-task to be on target in the final scene.

Table IV and Fig. 5 show three effects. First, pick-and-place steps compose almost independently: with 94% on the first step and 91-94% on the second, both approaches complete 86-88% of the two-plate tasks, close to the product of the step rates. In no episode did a later step disturb an earlier completed one. Second, the composite rate is limited by the weakest skill: on plate-stack the first step succeeds in 94-96% of episodes for both, and the gap (42% vs. 62%, $p = 0.08$) comes entirely from the stacking step, in line with Exp. 3. Third, stacking onto raised targets degrades for both approaches: stacking on a cube that rests on a plate drops to 45%/65%, and stacking on a two-cube tower to 26% for both, against 59%/68% on the table (Exp. 3). Those target heights never occur in the stacking demonstrations, so neither organisation extrapolates in height. **Composition itself works for both organisations; composite success is bounded by the individual skills, and both fail to extrapolate a skill to target geometry outside its demonstrations.**

VI. DISCUSSION AND LIMITATIONS

a) What modularity buys.: In our setting skill-level experts do not improve the accuracy of individual skills (Exp. 1), but they generalise across objects and instructions far better than task-level experts at equal compute (Exp. 2), and they allow new skills to be added safely (Exp. 3). Their cost is reduced transfer between skills: a monolith trained with replay stacks better than an isolated stack expert, and warm-starting the new expert from a related one recovers part of the gap. The same difference carries over to composed tasks (Exp. 4), where composite success follows the weakest skill.

b) The role of grounding.: The target pose is what makes a single pick expert serve every object, and it also keeps task experts from failing completely on unseen instructions. It does not transfer across target *geometry*: a place expert cannot stack.

c) Limitations.: All results are in simulation, with one arm and one family of objects (cubes and plates). Our task-level condition re-implements the granularity of CORAL [5] rather than the method itself. The planner is an oracle in the experiments. We have not yet evaluated on a standard benchmark such as LIBERO [21] or on real hardware; both are the next steps.

VII. CONCLUSION

We studied at which granularity to define experts on a shared VLA backbone. Defining them per skill and grounding each skill in a tracked target pose gave much better generalisation than per-task experts, no loss against a monolithic model, and safe extension with new skills. Composed tasks succeed when their skills do: composition itself added no failures, which makes the remaining gap a matter of individual skills and their training distribution.

ACKNOWLEDGMENT

Claude (Anthropic), used through Claude Code, assisted throughout this work: implementing the simulation, data, training and evaluation code, running and analysing the experiments, and drafting the text and figures under the author's direction. The author designed the study, reviewed all results and takes full responsibility for the content of this paper.

REFERENCES

[1] M. J. Kim, K. Pertsch, S. Karamcheti *et al.*, "OpenVLA: An open-source vision-language-action model," in *Conference on Robot Learning (CoRL)*, 2024.

[2] K. Black, N. Brown, D. Driess *et al.*, "π_0: A vision-language-action flow model for general robot control," *arXiv preprint arXiv:2410.24164*, 2024.

[3] M. Shukor *et al.*, "SmolVLA: A vision-language-action model for affordable and efficient robotics," *arXiv preprint arXiv:2506.01844*, 2025.

[4] M. McCloskey and N. J. Cohen, "Catastrophic interference in connectionist networks: The sequential learning problem," in *Psychology of Learning and Motivation*, 1989, vol. 24, pp. 109–165.

[5] Y. Luo, W. Chen, T. Liang, and Z. Li, "CORAL: Scalable multi-task robot learning via LoRA experts," *arXiv preprint arXiv:2603.09298*, 2026.

[6] M. Ahn, A. Brohan, N. Brown *et al.*, "Do as I can, not as I say: Grounding language in robotic affordances," in *Conference on Robot Learning (CoRL)*, 2022.

[7] J. Liang, W. Huang, F. Xia, P. Xu, K. Hausman, B. Ichter, P. Florence, and A. Zeng, "Code as policies: Language model programs for embodied control," in *IEEE International Conference on Robotics and Automation (ICRA)*, 2023.

[8] A. Stone, T. Xiao, Y. Lu, K. Gopalakrishnan, K.-H. Lee, Q. Vuong, P. Wohlhart, S. Kirmani, B. Zitkovich, F. Xia, C. Finn, and K. Hausman, "Open-world object manipulation using pre-trained vision-language models," in *Proceedings of The 7th Conference on Robot Learning*, ser. Proceedings of Machine Learning Research, vol. 229, 2023, pp. 3397–3417.

[9] S.-F. Tsai, J.-C. Jhang, Y.-L. Tai, J.-H. Lai, S.-Y. Wong, K.-T. Hsu, and Y.-T. Chen, "Direct action-head injection of a grounded 3D point unlocks spatial and task generalization," *arXiv preprint arXiv:2606.27663*, 2026.

[10] L. X. Shi *et al.*, "Hi Robot: Open-ended instruction following with hierarchical vision-language-action models," in *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 267, 2025, pp. 54 919–54 933.




Fig. 5. Experiment 4. (a) Composed success on three unseen multi-step tasks (50 paired episodes each). (b) Success of each step: the first sub-task, and the second given that the first succeeded. Pick-and-place steps compose almost independently; stacking onto raised targets (a cube on a plate, a two-cube tower) is the bottleneck.

[11] Physical Intelligence, "$\pi_{0.5}$: a vision-language-action model with open-world generalization," *arXiv preprint arXiv:2504.16054*, 2025.

[12] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, "LoRA: Low-rank adaptation of large language models," in *International Conference on Learning Representations (ICLR)*, 2022.

[13] N. Ravi, V. Gabeur, Y.-T. Hu *et al.*, "SAM 2: Segment anything in images and videos," *arXiv preprint arXiv:2408.00714*, 2024.

[14] Q. Gu, Y. Ju, S. Sun, I. Gilitschenski, H. Nishimura, M. Itkina, and F. Shkurti, "SAFE: Multitask failure detection for vision-language-action models," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2025.

[15] M. Minderer, A. Gritsenko, and N. Houlsby, "Scaling open-vocabulary object detection," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

[16] B. Wen, M. Trepte, J. Aribido, J. Kautz, O. Gallo, and S. Birchfield, "FoundationStereo: Zero-shot stereo matching," in *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025.

[17] M. Mittal, C. Yu, Q. Yu *et al.*, "Orbit: A unified simulation framework for interactive robot learning environments," *IEEE Robotics and Automation Letters*, 2023.

[18] M. Laskey, J. Lee, R. Fox, A. Dragan, and K. Goldberg, "DART: Noise injection for robust imitation learning," in *Conference on Robot Learning (CoRL)*, 2017.

[19] R. Cadene, S. Alibert, A. Soare *et al.*, "LeRobot: State-of-the-art machine learning for real-world robotics in PyTorch," https://github.com/huggingface/lerobot, 2024.

[20] D. Rolnick, A. Ahuja, J. Schwarz, T. Lillicrap, and G. Wayne, "Experience replay for continual learning," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[21] B. Liu, Y. Zhu, C. Gao, Y. Feng, Q. Liu, Y. Zhu, and P. Stone, "LIBERO: Benchmarking knowledge transfer for lifelong robot learning," in *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*, 2023.