ASTER-6 | BASE & TOOL INTERFACES

Orthographic end views; original flange pattern; all holes explicitly modeled.

BASE: 8 × Ø10.5 THRU
Ø17 counterbore, 7 deep
PCD 180 / pilot cable bore Ø44
Plate thickness 20



TOOL: 6 × Ø5.5 THRU
PCD 46 / cable bore Ø16
Flange thickness 8
Adapter pilot bore Ø30.2



DIMENSIONS: mm | Concept interface drawing | Parameter source: config/robot.yaml
No manufacturing tolerances assigned. Fit, fastener length, thread engagement and assembly require detailed design.

ASTER-6 | LINK SECTIONS & JOINT CENTERS

Side outline and nominal extrusion section. Access windows require a separate structural refinement.





FOREARM: 280 center spacing; 65 × 80 × 4 wall.
Longitudinal fillets R9 outside / R5 inside; service cover mounting Ø3.4.
Joint barrels, fork bridges and material overlap are structural assembly interfaces.

DIMENSIONS: mm | Concept interface drawing | Parameter source: config/robot.yaml
No manufacturing tolerances assigned. Fit, fastener length, thread engagement and assembly require detailed design.

ASTER-6 | SYMMETRIC PARALLEL GRIPPER

Top view: transverse opposite-hand screw and two guides; fingers translate along ±Y.



Finger section 10 × 18; replaceable 1.5-thick pads. TCP at X=110, jaw mid-plane.
Selected positions are visualized at maximum opening; no screw thread/gear tooth detail.

DIMENSIONS: mm | Concept interface drawing | Parameter source: config/robot.yaml
No manufacturing tolerances assigned. Fit, fastener length, thread engagement and assembly require detailed design.