
DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION


18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.

J1




EXTERNAL SUPERVISOR AND HOST RAILS

J2




FLOATING AFE RAILS AND OBSERVED CONTROLS

J3




RAW CONTROL / STATUS

J4




EXISTING MONITOR OBSERVATIONS

J5



EXPORTED NATIVE HEALTH / PERMISSION

J6



DRIVER INTERNAL DIFFERENTIAL VOLTAGES

GLOBAL

SUP_3V3

SUP_5

HOST_3V3

HOST_5

HOST_15

VH_24

GND

AFE_3V3

AFE_P5

AFE_N5

AFEAGND

guards

File: guards.kicad_sch

host_rails

File: host_rails.kicad_sch

host_rails_2

File: host_rails_2.kicad_sch

afe_rails

File: afe_rails.kicad_sch

afe_rails_2

File: afe_rails_2.kicad_sch

watchdog

File: watchdog.kicad_sch

quiescence

File: quiescence.kicad_sch

voltage

File: voltage.kicad_sch

duration

File: duration.kicad_sch

admission

File: admission.kicad_sch

admission_2

File: admission_2.kicad_sch

phase0

File: phase0.kicad_sch

phase1

File: phase1.kicad_sch

afe_bank0

File: afe_bank0.kicad_sch

afe_bank1

File: afe_bank1.kicad_sch

afe_bank2

File: afe_bank2.kicad_sch

afe_bank3

File: afe_bank3.kicad_sch

afe_bank4

File: afe_bank4.kicad_sch

afe_logic

File: afe_logic.kicad_sch

afe_logic_2

File: afe_logic_2.kicad_sch

defaults

File: defaults.kicad_sch

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /


File: supervision.kicad_sch

Title: Project SCCI RH S4 / Interfaces and handoff

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 1/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.

































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /guards/


File: guards.kicad_sch

Title: Project SCCI RH S4 / 18 body-side terminal guards

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 2/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.













































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH


Sheet: /host_rails/
File: host_rails.kicad_sch

Title: Project SCCI RH S4 / Host supply windows

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 3/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.













































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH


Sheet: /host_rails_2/
File: host_rails_2.kicad_sch

Title: Project SCCI RH S4 / Host supply windows / 2

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 4/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.



































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /afe_rails/
File: afe_rails.kicad_sch

Title: Project SCCI RH S4 / AFE supply windows

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 5/22


DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /afe_rails_2/
File: afe_rails_2.kicad_sch

Title: Project SCCI RH S4 / AFE supply windows / 2

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 6/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.




























































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /watchdog/
File: watchdog.kicad_sch

Title: Project SCCI RH S4 / Heartbeat and startup

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 7/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.

































































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /quiescence/
File: quiescence.kicad_sch

Title: Project SCCI RH S4 / Current quiet window

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 8/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.
























































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /voltage/

File: voltage.kicad_sch

Title: Project SCCI RH S4 / Differential compliance

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 9/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.


















































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH


Sheet: /duration/
File: duration.kicad_sch

Title: Project SCCI RH S4 / Secondary phase duration


Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 10/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.


















































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /admission/

File: admission.kicad_sch

Title: Project SCCI RH S4 / Sticky permission and rearm

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 11/22


DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.



































































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /admission_2/


File: admission_2.kicad_sch

Title: Project SCCI RH S4 / Sticky permission and rearm / 2


Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 12/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.






























































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /phase0/


File: phase0.kicad_sch

Title: Project SCCI RH S4 / Source 0 phase permission


Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 13/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION


18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.

































































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /phase1/

File: phase1.kicad_sch

Title: Project SCCI RH S4 / Source 1 phase permission

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 14/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.




































































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /afe_bank0/
File: afe_bank0.kicad_sch

Title: Project SCCI RH S4 / RHD input windows 0

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 15/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.
































































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /afe_bank1/
File: afe_bank1.kicad_sch

Title: Project SCCI RH S4 / RHD input windows 1

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 16/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.































































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /afe_bank2/
File: afe_bank2.kicad_sch

Title: Project SCCI RH S4 / RHD input windows 2

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 17/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.



































































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH


Sheet: /afe_bank3/
File: afe_bank3.kicad_sch

Title: Project SCCI RH S4 / RHD input windows 3

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 18/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.















All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH


Sheet: /afe_bank4/
File: afe_bank4.kicad_sch

Title: Project SCCI RH S4 / RHD input windows 4


Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 19/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.










































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH


Sheet: /afe_logic/
File: afe_logic.kicad_sch

Title: Project SCCI RH S4 / AFE blank and isolated status


Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 20/22

DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION


18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.












































All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /afe_logic_2/
File: afe_logic_2.kicad_sch

Title: Project SCCI RH S4 / AFE blank and isolated status / 2

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 21/22


DIGITAL SCCI ENGINEERING / ARTIFICIAL LOADS / NATIVE INDEPENDENT SUPERVISION

18 guarded stimulation conductors, 17 measured RHD-side windows; conditional healthy-switch blanking is not proven isolation.


























All net labels are native electrical connections. Actual physical delay, leakage, failed switches and shared supplies remain bounded limitations.

Independent phase cap, heartbeat watchdog, rail windows and deliberate rearm have different functions. No automatic retry or reverse pulse.

Native supervision; converters, firmware, PCB and implant qualification remain

Project SCCI RH

Sheet: /defaults/
File: defaults.kicad_sch

Title: Project SCCI RH S4 / External defaults

Size: A2	Date: 2026-10-14	**Rev: 0.1**
KiCad E.D.A. 10.0.6		Id: 22/22