

MessFinder API

Postman Testing Guide

Base URL: `http://localhost:8080/api/v1`

SECTION 1 — Authentication Tests

TEST 1 — Signup Student

Method: POST

URL:

`http://localhost:8080/api/v1/auth/signup`

Body → raw → JSON:

```
{ "name": "Rahul Sharma", "email": "rahul@gmail.com", "password": "rahul123", "role": "STUDENT" }
```

■ Expected: token in response

TEST 2 — Signup Mess Owner

Method: POST

URL:

`http://localhost:8080/api/v1/auth/signup`

Body → raw → JSON:

```
{ "name": "Suresh Patil", "email": "suresh@gmail.com", "password": "suresh123", "role": "MESS_OWNER" }
```

■ Expected: token in response

TEST 3 — Login

Method: POST

URL:

`http://localhost:8080/api/v1/auth/login`

Body → raw → JSON:

```
{ "email": "rahul@gmail.com", "password": "rahul123" }
```

■ Expected: token in response

TEST 4 — Get All Messes (Public)

Method: GET

URL:

`http://localhost:8080/api/v1/public/messes`

Headers: None required (public route)

■ Expected: empty list []

TEST 5 — Create Mess (Owner)

Method: POST

URL:

http://localhost:8080/api/v1/owner/mess

Headers:

Authorization: Bearer <suresh_token>

How to add token in Postman (2 ways):

Way 1 — Headers Tab	Way 2 — Authorization Tab (Easier)
Go to Headers tab Key → Authorization Value → Bearer <your_token>	Go to Authorization tab → Type → Bearer Token → Paste token directly → Postman adds Bearer automatically

Body → raw → JSON:

```
{ "name": "Suresh Tiffin Centre", "address": "Shop 5, Rajapeth, Amravati", "nearbyLandmark": "Near SBI Bank", "phone": "9876543210", "pricePerMonth": 2500, "isVeg": true, "breakfast": true, "lunch": "Dal, Rice, Roti, Sabzi", "dinner": "Roti, Sabzi, Dal", "area": "Rajapeth" }
```

■ Expected: mess created successfully

SECTION 2 — Database Verification (pgAdmin)

After running the tests above, verify data is saved in the database.

Step 1: Open pgAdmin on your PC

Step 2: Left panel → Servers → PostgreSQL → Databases → messfinder

Step 3: Right-click on messfinder → Click Query Tool

Step 4: You should see: • users table → your test users (Rahul, Suresh) • messes table → your test mess (Suresh Tiffin Centre)

SECTION 3 — Create Super Admin

Method A — Using Postman Signup (Recommended)

■■ If you already tried the SQL method and got 'bad credentials', delete the wrong record first:

Run this in pgAdmin Query Tool:

```
DELETE FROM users WHERE email = 'admin@messfinder.com';
```

Step 1 — Signup Admin via Postman:

POST http://localhost:8080/api/v1/auth/signup

```
{ "name": "Admin", "email": "admin@messfinder.com", "password": "admin123", "role": "SUPER_ADMIN" }
```

Step 2 — Login Admin:

POST http://localhost:8080/api/v1/auth/login

```
{ "email": "admin@messfinder.com", "password": "admin123" }
```

■ You will get the admin token!

Method B — SQL Insert (pgAdmin Query Tool)

Open pgAdmin → Right-click messfinder → Query Tool → Paste and press F5 or ■ Play:

```
INSERT INTO users (name, email, password, role, is_active, created_at) VALUES ( 'Admin', 'admin@messfinder.com', '$2a$10$N9qo8uL0ickgx2ZMRZoMyeIjZAgcfl7p92ldGxad68LJZdL17lHHi', 'SUPER_ADMIN', true, NOW() );
```

■■ **Note:** This bcrypt hash may not match admin123 — use Method A to be safe!

Verify the insert:

```
SELECT * FROM users;
```

SECTION 4 — Admin API Tests

Copy the admin token from the login response and use it in all requests below.

GET Admin Stats

Method: GET

URL:

```
http://localhost:8080/api/v1/admin/stats
```

Headers:

```
Authorization: Bearer <admin_token>
```

Expected Response:

```
{ "success": true, "message": "Stats fetched!", "data": { "totalMesses": 1, "activeMesses": 1, "totalUsers": 3, "totalOwners": 1, "avgRating": 0.0 } }
```

■ **Expected: success**

GET All Messes (Admin)

Method: GET

URL:

```
http://localhost:8080/api/v1/admin/messes
```

Headers:

```
Authorization: Bearer <admin_token>
```

Expected Response:

```
List of all messes
```

■ **Expected: success**

GET All Users (Admin)

Method: GET

URL:

```
http://localhost:8080/api/v1/admin/users
```

Headers:

```
Authorization: Bearer <admin_token>
```

Expected Response:

```
List of all users
```

■ **Expected: success**

SECTION 5 — Quick Reference Table

#	Test Name	Method	Endpoint	Auth Required
1	Signup Student	POST	/auth/signup	No
2	Signup Mess Owner	POST	/auth/signup	No
3	Login	POST	/auth/login	No

4	Get All Messes	GET	/public/messes	No
5	Create Mess	POST	/owner/mess	Yes (MESS_OWNER)
6	Admin Stats	GET	/admin/stats	Yes (SUPER_ADMIN)
7	Admin All Messes	GET	/admin/messes	Yes (SUPER_ADMIN)
8	Admin All Users	GET	/admin/users	Yes (SUPER_ADMIN)

MessFinder API Testing Guide | All routes: <http://localhost:8080/api/v1>