1) What will be the output of the following pseudocode?

```
Integer p,q,r
Set p=4 , q=2 , r= 5
p=(q+p)+p
If ((q+p)<(r-q) && 3>p)
p=(q+r)+p
if ((p+r)+(r+q)>(p+r+q))
r=q+p
Else
r=(p+r)+p
End if
p=(9&6)+q
Else
q=r&r
If
((q-5)< (5-q))
r=(6+6)&q
q=(q+7)+r
End if
p=(1^11)+q
End if
Print p+q+r
```

A) 32
B) 25
C) 24
D) 27

Answer : B

Code Bashers

2) What will be the output of the following pseudocode?

```
Integer p,q,r
Set p=4 , q=2 , r= 8
if((7+r)<q || (p+r)<q)
if((2+3)<q)
r=(7+11)+p
End if
Else
r=(6+4)&p
if((p+4)<(9+p))
q=(p+6)&r
End if
r=(q+4)&p
End if
q=p^p
Print p+q+r
```

A) 21
B) 11
C) 8
D) 2

Answer : C

Code Bashers

3) What will be the output of the following pseudocode?

```
Integer a,b,c
Set a=2, b=4 , c= 7
b=7+a
if(c>b)
b=b+b
End If
b=6+a
if((a+b)<(b-a) || c<a)
b=(c+4)+c
Else
a=c+b
End if
c=c+9^a
Print a+b+c
```

A) 71
B) 56
C) 47
D) 54

Answer : D

Code Bashers

4) What will be the output of the following pseudocode?

```
Integer a,b,c
Set a=1, b=6, c=7
b=(a&b)+b
for(each c from 3 to 5)
b=(a+a)^a
b=(12+5)+a
End for
a=(a^9)+a
Print a+b
```

A) 22
B) 28
C) 37
D) 36

Answer : C

Code Bashers

5) What will be the output of the following pseudocode for a=7 ,b=8?

```
Integer funn(Integer a, Integer b)
if((4-a)<(a-b) && a<b)
a=2+1+a
b=(a+3)+b
a=3+1+b
return funn(a,b)+funn(a,a)+1
End if
a=(a+2)+a
return a-1
```

A) 105
B) 100
C) 103
D) 112

Answer : C

6) What will be the output of the following pseudocode?

Code Bashers

```
Integer p,q,r
Set p=6 , q=4 , r= 7
p=(r+5)+p
if((q&r&p)<(p&6))
r=3^r
q=q&q
End if
Print p+q+r
```

A) 44
B) 31
C) 11
D) 26

Answer : D

7) What will be the output of the following pseudocode?

```
Integer pp, qq, rr
Set pp = 0, qq = 7, rr = 9
if((qq + pp) < (pp + qq) && pp < rr)
pp=11+qq
End if
Print pp+ qq + rr
```

Answer: 16

8) What will be the output of the following pseudocode for a=4, b=4,c=7?

Code Bashers

```
Integer funn(Integer a, Integer b, Integer c)
for(each c from 3 to 5)
a=(c+c)^b
if((a+c)<(c+a))
b=(a+11)+c
Else
c=b+b
a=3+b
Continue
End if
End for
return a+b
```

Answer: 11

9) What will be the output of the following pseudocode?

```
Integer p,q,r
Set p=0 , q=4 , r= 4
if((p^q)<r)
p=(8&2)+r
q=8+p
if((p+r)<(r+p))
r=(r+q)+p
r=(4+11)+p
End if
End if
Print p+q+r
```

Answer: 8

Code Bashers

10) What will be the output of the following pseudocode for a=7,b=4?

```
Integer funn(Integer a, Integer b)
Integer c
Set c = a+a+b+b
b=c+c+b+b
a=b-a
return a + b
End function funn()
```

A) 113
B) 100
C) 97
D) 90

Answer : C

11) What will be the output of the following pseudocode?

```
Integer a, b, c
Set a = 4, b=9, c=9
if (b & (c >> 1))
a=a+1
End if
Print a+b+c
```

Answer : 22

Code Bashers

12) What will be the output of the following pseudocode for a=5,b=2?

```
Integer funn(Integer a, Integer b)
if(a>0 && b>0)
return b+funn(a-2,b-1)
Else
a=a^b
return a
End if
End function funn()
```

Answer : 4

13) What will be the output of the following pseudocode?

```
Integer a, b, c
Set a=0, b=1, c=2
if (b^c || a&b  || a>>1)
C = 9
a = b + c
Else
c = 1
a = a + c
End if
Print a + b + c
```

Answer : 20

14) What will be the output of the following pseudocode?

Code Bashers

```
Integer p,q,r
Set p=2, q=3,r=5
q= (q+10)+p
p=(p+p) +q
if ((p&8&r) < (7&p))
q= (r+5)*&r
q=q^p
End if
Print p+q+r
```

Answer : 43

15) What will be the output of the following pseudocode?

```
a=7 b=2 c=8
If ((b^a)<a && (2^7)<c)
a=b+c
Else
c=(4+12)+a
b=11+a
print(a+b+c)
```

A) 18
B) 20
C) 23
D) 30

Answer : B

Code Bashers

16) What will be the output of the following pseudocode?
Integer p,q,r

```
Set p = 3,q=7,r = 9
p=(1+4)+r
p = (p + 3) & q
p = (q & 3) +q
Print p + q +r
```

Answer: 26

17) What will be the output of the following pseudocode?
Integer a,b,c

```
Set a=4, b=3, c=10
c=(b+12)+b
c=(b&c)+c
if((c-5)<(5+c))
a=(c&c)^a
a=(2+7)+b
a=(a&2)+c
End if
Print a+b+c
```

Answer : 43

18) What will be the output of the following pseudocode?

Code Bashers

```
Integer a,b,c
Set a=8, b=6, c=7
for(each c from 2 to 5)
a=(2+10)+b
if((b+c)>(c-b))
Continue
Else
c=12+c
b=c+c
End if
End for
Print a+b
```

Answer: 24

19) What will be the output of the following pseudocode for a2,b=2,c=7?

```
Integer funn(Integer a, Integer b, Integer c)
for(each c from 4 to 7)
b=(6+8)+a
if((a^c)<c)
Continue
Else
jump out of the loop
End if
b=(a+5)+b
End for
return a+b
```

Answer: 8

Code Bashers

20) What will be the output of the following pseudocode?

```
Integer p,q,r
Set p=3, q=4, r=4
for(each from 5 to 8)
if((q+r)<(r-q))
Continue
End if
p=(p+7)+r
q=p+p
End for
Print p+q
```

Answer : 171

21) What will be the output of the following pseudocode?

```
Integer a,b,c
Set a=7, b=10, c=9
for(each c from 3 to 4)
a=b
if((b-a+c)<(c+b))
Continue
Else
Jump out of the loop
End if
a=(5+6)^c
End for
Print a+b
```

Answer : 20

Code Bashers

22) What will be the output of the following pseudocode?

```
Integer a,b
Set a=2, b=50
while(b>0)
a = b MOD 2 +a
if(a MOD 3 IS EQUAL TO 0)
Print (a)
else
Print(b-1)
b=b/5
a=a+1
end while
```

A) 3,3,3
B) 49,3,1
C) 50,10,2
D) 50,3,2
Answer : B

23) What will be the output of the following pseudocode?

Code Bashers

```
Integer p,q,r
Set p=0, q=2, r=9
r=7+p
q=q+r
for(each from 4 to 7)
p=(p+p)&q
if((p+q)<(r-p) || 8<p)
p=(p+2)+q
Jump out of the loop
End if
End for
Print p+q
```

A) 9
B) 5
C) 19
D) 10

Answer : A

24) What will be the output of the following pseudocode?

```
Set x to 0;
Set n to 1;
while (n <= 100)
x = x + n;
n = n + 1;
end write x
```

a. 5050

Code Bashers

b. 100

c. 4950

d. 5151

Answer : a

25) What will be the output of the following pseudocode?

```
Integer a, b, c, d, e
Set a=50, b=3, c=3
while(c>0)
d=a mod b
e=e + d + a
c=c-1
End while
Print e
```

a. 52

b. 100

c. 156

d. 153

Answer : c

26) What will be the output of the following pseudocode for i = 140?

Code Bashers

```
Integer fun(integer i)
if((i MOD 2) NOT EQUALS 0)
Return i
Else
Return fun (fun(i-1))
End function fun()
```

a. 139

b. 138

c. 140

d. None of the above

Answer : a

27) What will be the output of the following code?

Code Bashers

```c
#include <stdio.h>

int main()

{

int x=9, y=2, z=6;

int a = x&y|z;

printf("%d",a);

return 0;

}
```

a. Error

b. 2

c. 6

d. 3

Answer : c

28) What will be the output of the following pseudocode?

Code Bashers

```
Input f = 6, g = 9 and set sum = 0

Integer n

if (g > f)

for(n=f; n<g; n=n+1)

sum=sum+n

End of loop

else

print Error messages

print sum
```

a. 21

b. 15

c. 12

d. 9

Answer : a

29) What will be the output of the following pseudocode?

Code Bashers

```
p=6 q=3 r=5

q=1+r

q=5+q

If (5<r or (p+r)>(r-p))

p=(9&7)+pp

q=5+qq

print(p+q+r)
```

a) 28

b) 20

c) 30

d) 38

Answer : a

30) What will be the output of the following pseudocode for arr[] = 1,2,3,4,5

Code Bashers

```
Initialize i, n

Set arr[]= 1, 2, 3, 4, 5 for i = 0 ton 2

arr[i] = arr[i] + arr[i+1]

End for
```

Answer : 3 5 7 9 5

31) Predict the output of the following pseudocode.

Code Bashers

```
Integer x, y, z

Set x = 0, y = 3, z = 11

if(x + (1| 2) && y + (2 | 3))

x = x-2

y = x

Else

x = z

y = y ^ 2

End if

Print x + y + z
```

A. 15

B. 10

C. 13

D. 7

Answer : D

32) Predict the output of the following pseudocode for x = 10, y = 5

Code Bashers

```
Integer solve (Integer x, Integer y)

if(y > 0)

if (x > 0)

return x + y + solve(2, y- 5) + solve(x- 10, 1)

End if

End if

return x + y

End function solve()
```

A. 15

B. 18

C. 13

D. 17

Answer : B

33) What will be the output of the following pseudocode for arr[] = 5, 4, 3, 2, 17

Code Bashers

```
Initialize i, n

Initialize an array of size n

Take the values for the array

for i = 0 to n - 2

arr[i] = arr[i] - arr[i+1]

End for
```

A. 3 3 4 9 5
B. 1 1 1 1 1
C. 3 5 7 9 5
D. 2 2 2 2 2

Answer : B

34) Predict the output of the following pseudocode for n = 5, m = 6.

Code Bashers

```
Integer solve (Integer n, Integer m )

if(n > 4 && m < 7)

return solve(n +1, m + 1)

Else

Return n + m

End if

End function solve()
```

A.15

B.21

C.13

D.10

Answer : C

35) What will be the output of the following pseudocode?

Code Bashers

```
Integer x, y, z

Set x = 10, y = 16,z = 3

if(x > y)

x = 2 * y

Else

y = x / 2 End if

if(z > y)

z = 2 * y

Else y = z / 2

End if

Print x + y + z
```

Answer : 14

36) What will be the output of the following pseudocode for arr[] = 5, 4, 3, 2, 1

Code Bashers

```
Initialize i, n

Initialize an array of size n

Take the values for the array

for i = 0 to n - 2

arr[i] = arr[i] * arr[i+1]

End for
```

A. 10 12 8 2 1

B. 20 12 6 2 1

C. 5 10 6 2 0

D. 20 4 6 1 1

Answer : B

37) What will be the output of the following pseudocode?

Code Bashers

```
Integer w, x, y, z

Set w 21, x = 11

for (each y from 21 to 30 )

for (each z from 1 to 0) w=w-1

if (w > y)

Continue

End if

w=1

if(w > z)

Jump out of the loop
End if

End for

End for
Print w + x
```

Code Bashers

A) 8
B) 12
C) 13
D) 2

Answer : B

38) What will be the output of the following pseudocode?

```
Integer x, y, z

Set x = -2, y = 3, z = 1

if(x + (2 & 2) && y + (3 & 3) && z + (2^2))

x = x - 2

y = x

Else

x = z

y = y ^ 2

End if

Print x+ y+ z
```

A) 2
B) 11
C) 13
D) 0

Answer : c

39) Print the output of the following pseudocode for x = 9, y = 7.

Code Bashers

```
Integer funn (Integer x, Integer y)

Integer z

Set z = 2

y = y mod z

x = x mod z

return x + y

End function funn()
```

A.2
B.3
C.17
D.5

Answer: A

40) What will be the output of the following pseudocode?

Code Bashers

```
Integer x, y, z

Set x = 8, y = 6, z= 4

if(x > y)

x = y

Else

y = x

End if

if(z > y)

z = y

Else

y = z

End if

Print x + y + z
```

Code Bashers

a.13

b.17

c.14

d.23

Answer : c

41) Calculate the output of the following pseudocode for input p = 3, q = 8, r = 1.

```
Integer p, q, r, sum

Read p, q, r

Set sum=p+q+r

if ((p NOT EQUALS 0) and (sum EQUALS 11) and (q EQUALS 4) and (r NOT
    EQUALS 0))

Print "Success"

Otherwise

Print "Fail"

End if
```

a.Success

b.Fail

c.Error

d.None of the above

Answer : b

42) What will be the output of the following pseudocode?

Code Bashers

```
Integer x, y, z

Set x = 10, y = 16, z= 3

if(x > y)

x = y

Else y = x

End if

if(z > y)

z = y

Else

y = z

End if

Print x + y + z
```

Code Bashers

a.13

b.12

c.16

d.20

Answer : c

43) Predict the output of the following pseudocode for a = 11, b = 12.

```
Integer solve (Integer a, Integer b)

if(a< 3 && b < 4)

return solve(a + 1, b + 1)

Else

Return a + b

End if

End function solve()
```

a.13

b.12

c.22

d.23

Answer : d

Code Bashers

44) What will be the output of the following pseudocode?

```
Integer pp, qq, rr
Set pp=0, qq=6, rr=7
pp=rr+pp
pp=(rr&4)^rr
if((qq&pp&rr)<(rr&qq))
if((qq^pp)<(rr+qq))
rr=(3+1)^pp
End if
End if
Print pp+qq+rr
```

A) 29
B) 18
C) 10
D) 16

Answer : D

45) What will be the output of the following pseudo code?

```
Integer p,q,r
Set p=9, q=6, r=10
if((q^p^r)>(r^q))
r=(11&12)+q
End if
if((q^6^8)>(p^4))
p=(r+3)&r
End if
Print p+q+r
```

Code Bashers

a.20

B.27

c.25

d.36

Answer : c

46) What will be the output of the following pseudo code?

```
Integer p,q,r
Set p=8, q=4, r=5
if((r+q) < (q-r) || p>q)
q=(q&8) &r
End if
Print p+q+r
```

a.17

b.10

c.23

d.13

Answer : d

47) What will be the output of the following pseudocode?

Code Bashers

```
Integer pp,qq,rr 2
Set pp=1, qq=2, rr=8
if((5+8)<(7+qq))
if((qq+pp)<(pp=qq))
rr=(rr+6)+rr
rr=(qq+pp)+pp
End if
rr=rr+pp
Else
if((pp+qq-rr)<(rr+pp))
pp=pp+rr
End if
rr=(pp&rr)+pp
End if
Print pp+qq+rr
```

A.35
B.49
C.19
D.28

Answer : D

48) What will be the output of the following pseudocode?

Code Bashers

```
Integer a,b,c

Set a=1, b=2, c=9

if((b+c)>(c-b))

c=a+a

End if

if((7+3)<(6+a))

b=12+a

End if

Print a+b+c
```

A.5
B.1
C.9
D.20

Answer : A

49)

Code Bashers

```
Create a stack
Push 1 on to the stack
Push 2 on to the stack
Push 3 on to the stack
pop from the stack
pop from the stack
Push 4 on to the stack
Push 5 on to the stack
Push 6 on to the stack
pop from the stack
Push 7 on to the stack
pop from the stack
pop from the stack
pop from the stack
```

A.1
B.1,7
C.7
D.1,6,7

Answer : A

50) What will be the output of the following pseudocode?

Code Bashers

```
Integer pp, qq, rr
Set pp=3, qq=5, rr=10
for (each rr from 4 to 5)
if((5-rr+pp)>(pp+qq))
End if
Jump out of the loop
pp=qq+rr qq=rr+pp
End for
Print pp+qq
```

A.41
B.45
C.37
D.55

Answer : A

51) What will be the output of the following pseudocode?

Code Bashers

```
Integer a,b,c
Set a-3, b-2, c-4
c=(c&3)+b
if((9&a)<(c^9)) 5
c=(a+c)+b
a=3+b
Else
a=(11+1)+c
if((c-a+b)<(b-c))
b=(7+1)+b
End if b=(b^a)+b
b=10+c
End if
Print a+b+c
```

A.28
B.3
C.21
D.12

Answer : D

52) What will be the output of the following pseudocode?

Code Bashers

```
Integer a,b,c
Set a=8, b=4, C=4
for(each c from 2 to 3)
b=c+b
if((a+9)<(9-a))
Continue
Else
Jump out of the loop
End if
b=(2+8)+a
End for
Print a+b
```

A.14
B.7
C.19
D.25

Answer : A

53) What will be the output of the following pseudocode?

```
Integer a,b,c
Set a=1, b=7, c=10
3 if(b>a)
c=2&a
if((a&c&b)<(c+b-a))
End if
c=(a^6)^c
End if
Print a+b+c
```

Code Bashers

A.29
B.20
C.15
D.12

Answer : C

54) What will be the output of the following pseudocode at a=5,b=5,c=5?

```
Integer funn(Integer a, Integer b, Integer c)
if((c&a)<a && (a^b)<b)
c=(a^2)+b
End if
return a+b+c
```

A.14
B.27
C.22
D.15

Answer : D

55) What will be the output of the following pseudocode?

Code Bashers

```
Integer a,b,c
Set a=7, b=2, c=8
if((b^a)<a && (2^7)c)
Else
c=(4+12)+a
a=b+c
b-11+a
End if
Print a+b+c
```

A.18
B.20
C.23
D.30

Answer : C

56) What will be the output of the following pseudocode?

```
Integer a, b, c
Set a=2, b=6, c=8
a=(10+9)+c
if((c+b)>(a-c))
a=b+c
b=b+b
End if
Print a+b+c
```

A.23
B.41

Code Bashers

C.48
D.58

Answer : B

57) What will be the output of the following pseudocode for a=0, b=2, c=10?

```
Integer funn (Integer a, Integer b, Integer c)
b=7+a
a=(a+c)+a
b=(b+b)+c
c=1+b
return a+b+c
End function funn()
```

A.59
B.68
C.70
D.39

Answer : A

58) What will be the output of the following pseudocode?

Code Bashers

```
Integer a,b,c
Set a =2, b=2, c=6
b=(c+9)+c
if((a-c)<(c-a))
c=a^a
Else
if((c+b)<(a-c))
a=(a^b)+b
b=a+a
Else
b=10+a
End if
b=4+a
End if
b=4+a
Print a+b+c
```

Answer : 8

59) What will be the output of the following pseudocode?

Code Bashers

```
Integer p,q,r
Set p=9, q=5, r=4
if((q+p)<(6-q))
p=12+p
if(5<q)
if((p+9)<(9-p))
p=2+p
End if
End if
r=(p+8)^q
End if
Print p+q+r
```

Answer : 18

60) What will be the output of the following pseudocode for a=2 , b=3?

```
Integer funn(Integer a, Integer b)
if((a+b)>(3&a) && a<3)
a=2+1+a
b=3+b+b
return funn(a,b+a)+a+funn(a,b)
End if
return b-a+1
```

A.31
B.22

Code Bashers

C.20
D.16

Answer : C

61) What will be the output of the following pseudocode?

```
Integer pp,qq,rr
Set pp=4, qq=2, rr-10
if(4<qq)
qq=(pp+pp)+qq if((3+qq+pp)<(qq+pp+3))
qq=(pp+rr)+rr
Else
rr=pp+rr
End if
End if
rr=6+pp
Print pp+qq+rr
```

Answer : 16

62) What will be the output of the following pseudocode?

Code Bashers

```
Integer a,b,c
Set a=5, b=5, c=5
if(axb && (a&c)<b)
b=c+a
End if
if((c+a)<(a-c)) c=(12+2)+b
End if
Print a+b+c
```

A.21
B.15
C.14
D.19

Answer : B

63) What will be the output of the following pseudocode?

```
Integer a,b,c
Set a=0, b=4, c=7
if(acc || (a+b)<c)
b=4&c
if((a+b)>(c-a)) a=(b+2)&a
End if
c=(1+5)^c
End if
c=(a+b)^c
Print a+b+c
```

Answer : 9

Code Bashers

64) What will be the output of the following pseudocode?

```
Integer a,b,c
Set a=2, b=8, c=6
if((c+a)<(b-c))
b=c+c
Else
b=(9+9)&c
if((c+b+a)<(b&a&c))
a=(c+c)^b
Else b=(12&3)+a
End if
End if
a=(b+a)^c
Print a+b+c
```

Answer : 10

65) What will be the output of the following pseudo code for a=4, b=8, c=57

Code Bashers

```
Integer funn(Integer a, Integer b, Integer c)
b=(a^11)&b
for(each c from 3 to 6)
b=3+c
if(1<b || (a&c)<(5-a))
a(c+2)+c
b=c+c
Jump out of the loop
End if
End for
return a+b
```

Answer : 14

66) What will be the output of the following pseudocode?

```
Integer p,q,r
Set p=0, q=2, r=9
r=7+p
q=q+r
for(each r from 4 to 7)
p=(p+p)&q
if((p+q)<(r-p) || 8<p)
p=(p+2)+q
Jump out of the loop
End if
End for
Print p+q
```

Answer : 9

Code Bashers

67) What will be the output of the following pseudocode?

```
Integer p,q,r
Set p = 6, q = 4, r = 7
p = (r + 5) + p
if((q&r&p)<(p&6))
r = 3 ^ r
q=q&q
End if
Print p + q + r
```

Answer : 26

68) What will be the output of the following pseudocode?

```
Integer pp,qq,rr
Set pp=4, qq=3, rr=9
pp=3^rr
if((pp&qq&rr)<(qq+rr-pp))
pp=(11810)^pp
rr=(10+3)&pp
End if
Print pp+qq+rr
```

Code Bashers

Answer : 3

69) What will be the output of the following pseudocode?

```
Integer p,q,r
Set p=4, q=2, r=9
for (each rfrom 5 to 8)
if(3<q && 6<q)
p=(q^r)^q
End if
if((p+8)<(8+p))
p=(6&1)+q
End if
q=(p+1)+r
End for
Print p+q+r
```

Answer : 34

70) What will be the output of the following pseudocode?

Code Bashers

```
Integer p,q,r
Set pass p=0, q=5, r=6
q=(q&2)+r
if((p^3)<3 && 5>r)
q=1+r
Else
q=5^r
for(each r from 2 to 6)
q=10+p
End for
End if
q=r+r
Print p+q+r
```

Answer : 27

71) What will be the output of the following pseudo code for a=3, b=3?

```
Integer funn(Integer a, Integer b)
if((a+b)>(b^a) && a<4)
b=b+1
b=2+b+b
a=b+3
return funn(b+2,b+1)+funn(b,b)+b
End if
a=a+1
return b-a+1
```

A.9

Code Bashers

B.15
C.4
D.19

Answer : A

72) What will be the output of the following pseudocode?

```
Integer p,q,r
Set p = 5 ,q=8,r=5
if((9&p)<r||q>r)
q=5&q
End if
q=11+p
if ((q + p) > (p - q))
r= (p + p) +q
End if
p  = (p + r) + q
Print p + q + r
```

A.90
B.87
C.89
D.96

Answer : C

73) What will be the output of the following pseudocode?

Code Bashers

```
Integer pp,qq,rr
set pp=5, qq=6, rr=4
qq=(pp+qq)+qq
for(each rr from 3 to 6)
qq=(qq^qq)^qq
qq=(rr+pp)+rr
End for
pp=(1^7)^rr
Print pp+qq
```

A.16
B.24
C.18
D.19

Answer : C

74) What will be the output of the following pseudocode?

Code Bashers

```
Integer a,b,c
Set a=8, b=4, C=4
for(each c from 2 to 3)
b=c+b
if((a+9)<(9-a))
Continue
Else
Jump out of the loop
End if
b=(2+8)+a
End for
Print a+b
```

A.28
B.3
C.21
D.12

Answer : D

75) What will be the output of the following pseudocode for a=7, b=4?

```
Integer funn(Integer a, Integer b)
if(b<6 && (b&a)<(a+b))
b=1+b+a
b=3+1+a
return b-funn(b,b)
End if
b=1+b+b
return b
```

Code Bashers

A.-19
B.-7
C.-12
D.7

Answer : C

76) What will be the output of the following pseudocode?

```
Num=11

if((num&1)==1)

print HeyAnshika

else

printHeySubscribers
```

Answer : HeyAnshika

77) What will be the output of the following pseudocode?

Code Bashers

```
integer a,b,c

set a=6, b=5, c=4

if((a^9)<(9+a))

a=b+b

else if

((a&b&c)>(c&a))
b=(1+3)^c
end if
end if
print a+b+c
```

Answer : 15

78) What will be the output of the following pseudocode?

Code Bashers

```
integer a,b,c

set a=3, b=5, c=4

c=(6^2)+b

for(each c from 3 to 5)

b=(b+2)&c

a=3&b

b=(c^a)+c

a= (5+2)&a

end for

print a+b
```

Answer : 10

79) What will be the output of the following pseudocode?

Code Bashers

```
int HeyThere (int n, int r){

if(n>0)

return (n%r + HeyThere (n/r, r));

else

return 0;

int ans =HeyThere(257,2);

print ans;
```

Answer : 2

80) What will be the output of the following pseudocode?

Code Bashers

```
int fun(int n){ if(n==1)

else

return 1;

return 1 + fun(n-1);

}

int main(){

n=3;

printf("%d", fun(n));

}

return 0;
```

Answer : 2

81) What will be the output of the following pseudocode?

Code Bashers

```
Integer p,q,r
Set p=5, q=8,r=4
if((p^9)<(10p))
p=q+q
Else
if((p&q&r)>(r&p))
q=(1+))^r
End if
End if
Print p+q+r
```

A.19
B.25
C.36
D.28

Answer : D

82) What will be the output of the following pseudocode?

Code Bashers

```
Integer p,q,r
Set p=8, q=7, r=8
r=11+q
if((r+p+q)<(p-q-r))
q=r+p
if((r+9)<(8+r)) p=(r+9)+r
Else
p=(p+12)+p
End if
Else
q=(1+7)+r
((q+p+5)<(p+r+q))
q=(q+p)+r
End if
End if
p=(r+r) r
Print p+q+r
```

A.108
B.114
C.104
D.124

Answer : D

83) What will be the output of the following pseudocode?

Code Bashers

```
Set a=3, b=5, c=4
if((1+c+8)<(8+1))
if((1-7)>(b+1))
a=a+b
Else
a=(b+3)+c
End if
a=5+b
Else
if((c+9)+(9+3)>(c+a+b))
a=(4+4)+b
Else
c=(4+8)+a
End if
a=3+c
End if
c=(8+7)+c
print a+b+c
```

A.31
B.11
C.14
D.24

Answer : A

84) What will be the output of the following program?

Code Bashers

```c
#include <stdio.h>
void main()
{
printf("10!=9: %5d",10!=9);
```

A.1
B.0
C.error
D.none of these

Answer : A

85) What will be the output of the following program?

```c
#include <stdio.h>
int main()
{
int y = 10000;
int y = 34;
printf("Hello World! %d\n", y);
return 0;
}
```

A.Compile time error
B.Hello World!34
C.Hello World!1000
D.Hello World! Followed by a junk value

Answer : A

86) What will be the output of the following pseudocode?

Code Bashers

```
Integer pp, qq, rr
Set pp = 6, qq = 3, rr = 5
 qq = 1 +rr
 qq = 5 + qq
 if(5<rr OR (pp+rr) > (rr-pp))
 pp = (9 & 7) + pp
 qq = 5 + qq
 End if
 Print pp + qq + rr
```

A.28
B.20
C.30
D.38

Answer : A

87) What will be the output of the following pseudocode?

Code Bashers

```
 Integer p, q, r
Set p=2, q=5
q=p+q
for (each r from q to 8)
q=p
End for
if (p > q)
q=0
Else
q=1
End if
Print p+q+r
```

A.12
B.20
C.7
D.15

Answer : A

88) What will be the output of the following pseudocode?

```
Integer pp,qq,rr
Set pp = 1, qq = 2, rr= 7
rr = (rr + 9) + qq
pp=pp
qq = (pp + 7) & rr
rr = 1 + rr
Print pp + qq + rr
```

A. 17

Code Bashers

B.25
C.20
D.28

Answer : C

89) What will be the output of the following pseudocode?

```
Integer p, q, r
Set p=5, q=8,r=4
if((p^9)<10+p))
p=q+q
Else
if((p&q&r)>(r&p))
q=(1+3)^r
End if
End if
Print p+q+r
```

A. 17
B.25
C.20
D.28

Answer D

90) What will be the output of the following pseudocode?

Code Bashers

```
Integer p=1, q=2

for(Integer i=0;i<=6;i=i+2)

p=p+q+i

p=p+q

q=p-q

print q

End for
```

Answer : 3 10 27 70

91) What will be the output of the following pseudocode?

```
Integer m

for(m=3;m!=0;m--)

print m

m=m-1

End for
```

Answer : Infinite

Code Bashers

92) What will be the output of the following pseudocode?

```
Integer a,b,c

set a=24, b=8

c= b<<a

print c
```

Answer : 8 * 2^24

93) What will be the output of the following pseudocode?

```
int main(){

int p=10, q=20, r=30;

if(r>q>p)

print("True")

else

print("false")

return 0;

}
```

Code Bashers

Answer : False

94) What will be the output of the following pseudocode?

```
Initialize Integer x, y, z

Set y = 1, x = 2

z = x^y

Print z
```

A.1
B.2
C.4
D.3

Answer D

95) What will be the output of the following pseudocode?

```
Integer value, n

Set value = 1, n = 45
while(value less than equal to n) value value << 1

end loop

Print value
```

Code Bashers

A.16
B.32
C.64
D.36

Answer: C

96) What will be the output of the following pseudocode?

```
3. #include<stdio.h> int main()

{

int x=9,y=2,z=6;

int a=x&y|z;

printf("%d", a);

return 0;

}
```

A.Error
B.2
C.6
D.3

Answer: C

97) What will be the output of the following pseudocode?

Code Bashers

```
Set Character m='a
Set Integer count=0

while(m>'a')

count++

m-

end-while

display count
```

Answer : 0

98) What will be the output of the following pseudocode?

```
Integer x, y Set x 15, y = 12

y=x-1

do {

Print x

x= y+(x-2)
}

while(x < 40) end do while
```

Code Bashers

A.14 26
B.15 27 39
C.27 39
D.15

Answer: B

99) What will be the output of the following pseudocode?

```
Integer p,q,r

Set p=7, q=4, r=5

if((p+r)<(q-p)||r<p)

r=q&p

r=(r+3)&p

End if

Print p+q+r
```

Answer : 18

100) What will be the output of the following pseudocode?

Code Bashers

```c
#include<stdio.h>

int main()

{

int x=11, y=4, z=3;

y = !x;

z= !!x;

printf("%d %d", y,z);
return 0;
}
```

Answer : 0,1

101) What will be the output of the following pseudocode?

Code Bashers

```c
#include<stdio.h>

int main ()

{

char c,a,b;

c='f';

a='s';

b='x';

int sum= c+a+b;

printf ("%d", sum);

}
```

Answer : 337

102) What will be the output of the following pseudocode?

Code Bashers

```
Integer funn (Integer a, Integer b)

a=a<<(a-2)

b=b>>(b-5)

a=a+1

b=b+1

return a+b

End function funn()
```

Answer : 21

103) Predict the output of the following pseudo-code if x= 1 and y=2?

```
Integer solve(int x, int y)

if(x > 1)

solve(x1, y + 3)

end if

print y

End function solve()
```

Code Bashers

A.2
B.3
C.6
D.4

Answer: A

104) What will be the output of the following pseudocode?

```
#include<stdio.h>
int main()
{
   char c= 'Z';
   printf("%d",c);
}
```

Answer : 90

105) What will be the value of the following pseudocode?

```
Integer value, n,  num

Set value = 1,  n = 45

num = num >> 1

num = num + value

Print num
```

Code Bashers

A.44

B.0

C.1

D.12

Answer - Option C

106) What will be the value of the following pseudocode?

```
Integer x, y

for(each x from 1 to 11)

x = x + 2

end for

Print x
```

A.11

B.10

C.12

D.13

Code Bashers

Answer - Option D

107) What will be the value of the following pseudocode?

```
Integer j, m

Set m = 1, j = 1

Integer a[3] = {0, 1, 0}

a[0] = a[0] + a[1]

a[1] = a[1] + a[2]

a[2] = a[2] + a[0]

if(a[0])

a[j] = 5

End if

m = m + a[j]

Print m
```

Code Bashers

A.3

B.2

C.6

D.4

Answer - Option C

108) What will be the value of the following pseudocode for k=150?

```
fun(integer k)

if(k>155)

return

end if

print k

fun(k+2)

print k

End of function fun()
```

A. 150 152 154

B. 150 152 154 154 152 150

C. 150

Code Bashers

D. None of the mentioned

Answer - Option B

109) What will be the output of the following pseudocode?

```
Integer a[5], b[5], c[5], k, l

Set a[5] = {5, 9, 7, 3, 1}

Set b[5] = {2, 4, 6, 8, 10}

for(each k from 0 to 4)

c[k] = a[k] - b[k]

end for

for(each 1 from 0 to 4)

Print c[1]

end for
```

Code Bashers

A. 7 13 13 11 11

B. 3 5 1 -5 -9

C. -3 -5 -1 5 9

D. None

Answer - Option B

110) How many times “A” will be printed in the following pseudocode?

```
Integer a, b, c

for(a = 0 to 4)

for(b = 0 to 2)

if(a is greater than b)

Print “A”

End for

End for
End if
```

A.8

B.7

C.9

D.10

Answer - Option C

Code Bashers

111) What will be the output of the following pseudocode?

```
Integer p, q, r

Set q = 13

for(each p from 1 to 4)

r = q mod p

p = p + 5

q = p + r

end  for r = q / 5

Print q, r
```

A.6 4

B.1 3

C.7 2

D.6 1

Answer - Option D

112) What will be the output of the following pseudocode?

Code Bashers

```
Integer x

Set x = 259 if(x EQUALS 0)

Print "0"

otherwise if(x MOD 9 EQUALS 0)

Print "9"

otherwise

Print x MOD 9

end if
```

A. 8

B. 16

C. 7

D. None

Answer - Option C

113) What will be the output of the following pseudocode?

Code Bashers

```
Integer a, b

Set a = 12, b = 25

a = (a + b) MOD 2

b = b = a

a = a + b - 13

Print a, b
```

A. -11 1

B. -12 00

C. 11 22

D. 37 24

Answer - Option A

114) What will be the output of the following pseudocode?

Code Bashers

```
Set a = 4, b = 4, c = 4

if (a & (b ^ b) & c)

a = a >> 1

End if

Print a + b + c
```

A.16

B.24

C.8

D.12

Answer - Option D

115) What will be the output of the following pseudocode for a = 10, b = 11?

Code Bashers

```
Integer funn(Integer a, Integer b)

if(0)

return a - b - funn(-7, -1)

End if

a = a + a + a + a

return a

End function funn()
```

A.40

B.30

C.44

D.0

Answer - Option A

Code Bashers