DS ASSIGNMENT 15

Name:Prathiksha Harish Baleri

USN:4CB22CB044

Domain:Data science

MY SQL Commands practice3

```
mysql> select Name,age,salary from Sample1 where dept = 'Acct';
+-------+-----+--------+
| Name  | Age | Salary |
+-------+-----+--------+
| Anil  |  23 |  15000 |
| Vikas |  35 |  20000 |
| Roy   |  37 |  20000 |
| Ganesh|  30 |  22000 |
+-------+-----+--------+
4 rows in set (0.00 sec)

mysql> select Name,age,salary from Sample1 where dept = 'Acct' or dept='Admin';
+---------+-----+--------+
| Name    | Age | Salary |
+---------+-----+--------+
| Anil    |  23 |  15000 |
| Sunil   |  40 |  18000 |
| Vikas   |  35 |  20000 |
| Roy     |  37 |  20000 |
| Rock    |  35 |  21000 |
```

```
| Ganesh  |  30 |  22000 |
| Sathesh |  40 |  23000 |
| James   |  38 |  32000 |
+---------+-----+--------+
8 rows in set (0.00 sec)

mysql> select Name,age,salary from Sample1 where age>=30 or age<=45;
+---------+-----+--------+
| Name    | Age | Salary |
+---------+-----+--------+
| Vikas   |  35 |  20000 |
| Roy     |  37 |  20000 |
| Rock    |  35 |  21000 |
| Ganesh  |  30 |  22000 |
| Sathesh |  40 |  23000 |
| James   |  38 |  32000 |
| Monica  |  48 |  50000 |
+---------+-----+--------+
7 rows in set (0.00 sec)

mysql> select Name,salary from Sample1 where age>=30 or age<=45;
+---------+--------+
| Name    | Salary |
+---------+--------+
| Vikas   |  20000 |
| Roy     |  20000 |
```

```
| Rock    |  21000 |
| Ganesh  |  22000 |
| Sathesh |  23000 |
| James   |  32000 |
| Monica  |  50000 |
+---------+--------+
7 rows in set (0.00 sec)

mysql> select Name,salary from Sample1 where age>=30 and age<=45;
+---------+--------+
| Name    | Salary |
+---------+--------+
| Vikas   |  20000 |
| Roy     |  20000 |
| Rock    |  21000 |
| Ganesh  |  22000 |
| Sathesh |  23000 |
| James   |  32000 |
+---------+--------+
6 rows in set (0.00 sec)

mysql> select * from sample1;
+-----+---------+---------+-----+-----------+--------+
| EID | Name    | Dept    | Age | Addr      | Salary |
+-----+---------+---------+-----+-----------+--------+
|   1 | Anil    | Acct    |  23 | Chennai   |  15000 |
```

```
|   2 | Sunil   | Admin   |  40 | Goa       |  18000 |
|   3 | Vikas   | Acct    |  35 | Bangalore |  20000 |
|   4 | Roy     | Acct    |  37 | Bangalore |  20000 |
|   5 | Rock    | Admin   |  35 | Mangalore |  21000 |
|   7 | Sathesh | Admin   |  40 | Chennai   |  23000 |
|   6 | Ganesh  | Acct    |  30 | Cochin    |  22000 |
|   8 | James   | Admin   |  38 | Cochin    |  32000 |
|   9 | Mark    | Quality |  58 | US        |  60000 |
|  10 | Monica  | Quality |  48 | US        |  50000 |
+-----+---------+---------+-----+-----------+--------+
10 rows in set (0.00 sec)

mysql> select * from sample1 where addr='chennai' or addr='us' or addr='cochin';
+-----+---------+---------+-----+---------+--------+
| EID | Name    | Dept    | Age | Addr    | Salary |
+-----+---------+---------+-----+---------+--------+
|   1 | Anil    | Acct    |  23 | Chennai |  15000 |
|   7 | Sathesh | Admin   |  40 | Chennai |  23000 |
|   6 | Ganesh  | Acct    |  30 | Cochin  |  22000 |
|   8 | James   | Admin   |  38 | Cochin  |  32000 |
|   9 | Mark    | Quality |  58 | US      |  60000 |
|  10 | Monica  | Quality |  48 | US      |  50000 |
+-----+---------+---------+-----+---------+--------+
6 rows in set (0.00 sec)

mysql> select * from sample1 where age>=35 and addr='cochin';
```

```
+-----+-------+-------+-----+--------+--------+
| EID | Name  | Dept  | Age | Addr   | Salary |
+-----+-------+-------+-----+--------+--------+
|   8 | James | Admin |  38 | Cochin |  32000 |
+-----+-------+-------+-----+--------+--------+
1 row in set (0.00 sec)

mysql> Desc Sample1;
+--------+--------------+------+-----+---------+-------+
| Field  | Type         | Null | Key | Default | Extra |
+--------+--------------+------+-----+---------+-------+
| EID    | int          | YES  |     | NULL    |       |
| Name   | varchar(25)  | YES  |     | NULL    |       |
| Dept   | varchar(10)  | YES  |     | NULL    |       |
| Age    | int          | YES  |     | NULL    |       |
| Addr   | varchar(15)  | YES  |     | NULL    |       |
| Salary | int          | YES  |     | NULL    |       |
+--------+--------------+------+-----+---------+-------+
6 rows in set (0.00 sec)

mysql> create table Employee(age tinyint);
Query OK, 0 rows affected (0.01 sec)

mysql> desc Employee;
+------+---------+------+-----+---------+-------+
| Field| Type    | Null | Key | Default | Extra |
```

```
+------+---------+------+-----+---------+-------+
| age  | tinyint | YES  |     | NULL    |       |
+------+---------+------+-----+---------+-------+
1 row in set (0.00 sec)

mysql> create table Employee1(salary float(10,2));
Query OK, 0 rows affected (0.01 sec)

mysql> desc Employee1;
+--------+-------------+------+-----+---------+-------+
| Field  | Type        | Null | Key | Default | Extra |
+--------+-------------+------+-----+---------+-------+
| salary | float(10,2) | YES  |     | NULL    |       |
+--------+-------------+------+-----+---------+-------+
1 row in set (0.00 sec)

mysql> create table Employee2(AADH Bigint);
Query OK, 0 rows affected (0.01 sec)

mysql> Desc Employee2;
+-------+--------+------+-----+---------+-------+
| Field | Type   | Null | Key | Default | Extra |
+-------+--------+------+-----+---------+-------+
| AADH  | bigint | YES  |     | NULL    |       |
+-------+--------+------+-----+---------+-------+
1 row in set (0.00 sec)
```

```
mysql> create table Employee3(Eid mediumint);
Query OK, 0 rows affected (0.01 sec)

mysql> Desc Employee3;
+------+-----------+------+-----+---------+-------+
| Field| Type      | Null | Key | Default | Extra |
+------+-----------+------+-----+---------+-------+
| Eid  | mediumint | YES  |     | NULL    |       |
+------+-----------+------+-----+---------+-------+
1 row in set (0.00 sec)

mysql> create table Employee4(EXP Smallint);
Query OK, 0 rows affected (0.01 sec)

mysql> Desc Employee4;
+------+----------+------+-----+---------+-------+
| Field| Type     | Null | Key | Default | Extra |
+------+----------+------+-----+---------+-------+
| EXP  | smallint | YES  |     | NULL    |       |
+------+----------+------+-----+---------+-------+
1 row in set (0.00 sec)

mysql> create table Employee5(DOJ Date);
Query OK, 0 rows
mysql> create table employee6(login Datetime);
```

```
Query OK, 0 rows affected (0.01 sec)

mysql> Desc employee6;
+-------+----------+------+-----+---------+-------+
| Field | Type     | Null | Key | Default | Extra |
+-------+----------+------+-----+---------+-------+
| login | datetime | YES  |     | NULL    |       |
+-------+----------+------+-----+---------+-------+
1 row in set (0.00 sec)

mysql> insert into employee6 values('1990/8/10 15:30');
Query OK, 1 row affected (0.00 sec)

mysql> create table employee7(DOB Year);
Query OK, 0 rows affected (0.01 sec)

mysql> Desc Employee7;
+-------+------+------+-----+---------+-------+
| Field | Type | Null | Key | Default | Extra |
+-------+------+------+-----+---------+-------+
| DOB   | year | YES  |     | NULL    |       |
+-------+------+------+-----+---------+-------+
1 row in set (0.00 sec)

mysql> insert into employee7 values('1990');
Query OK, 1 row affected (0.00 sec)
```

```
mysql> select * from Employee7;
+------+
| DOB  |
+------+
| 1990 |
+------+
1 row in set (0.00 sec)
```