DS ASSIGNMENT 13

Name:Prathiksha Harish Baleri

USN:4CB22CB044

Domain:Data Science

MySQL 8.0 Command Line Cli

```
Enter password: **********
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 20
Server version: 8.0.44 MySQL Community Server - GPL

Copyright (c) 2000, 2025, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> create database prati;
Query OK, 1 row affected (0.03 sec)

mysql> connect prati;
Connection id:    21
Current database: prati

mysql> create table Sample (EID int, Name Varchar(25));
Query OK, 0 rows affected (0.05 sec)

mysql> desc sample;
+-------+-------------+------+-----+---------+-------+
| Field | Type        | Null | Key | Default | Extra |
+-------+-------------+------+-----+---------+-------+
| EID   | int         | YES  |     | NULL    |       |
| Name  | varchar(25) | YES  |     | NULL    |       |
+-------+-------------+------+-----+---------+-------+
2 rows in set (0.01 sec)

mysql> Insert into sample values(11,'Anil');
Query OK, 1 row affected (0.02 sec)

mysql> Insert into sample values(22,'Sunil');
Query OK, 1 row affected (0.02 sec)

mysql> Insert into sample values(33,'vikas');
Query OK, 1 row affected (0.02 sec)
```

MySQL 8.0 Command Line Cli

```
mysql> Insert into sample values(22,'Sunil');
Query OK, 1 row affected (0.02 sec)

mysql> Insert into sample values(33,'vikas');
Query OK, 1 row affected (0.02 sec)

mysql> Insert into sample values(44,'roy');
Query OK, 1 row affected (0.01 sec)

mysql> Insert into sample values(55,'Rock');
Query OK, 1 row affected (0.02 sec)

mysql> Insert into sample values(66,'Ganesh');
Query OK, 1 row affected (0.02 sec)

mysql> Insert into sample values(77,'Satish');
Query OK, 1 row affected (0.01 sec)

mysql> select * from sample;
+------+--------+
| EID  | Name   |
+------+--------+
|   11 | Anil   |
|   22 | Sunil  |
|   33 | vikas  |
|   44 | roy    |
|   55 | Rock   |
|   66 | Ganesh |
|   77 | Satish |
+------+--------+
7 rows in set (0.00 sec)

mysql> Insert into sample values(88,'James');
Query OK, 1 row affected (0.02 sec)

mysql> Insert into sample values(99,'Mark');
Query OK, 1 row affected (0.02 sec)

mysql> Insert into sample values(100,'Monica');
Query OK, 1 row affected (0.02 sec)
```

MySQL 8.0 Command Line Cli

```
mysql> select * from sample where EID=77;
+------+--------+
| EID  | Name   |
+------+--------+
|   77 | Satish |
+------+--------+
1 row in set (0.00 sec)

mysql> select * from sample where EID>55;
+------+--------+
| EID  | Name   |
+------+--------+
|   66 | Ganesh |
|   77 | Satish |
|   88 | James  |
|   99 | Mark   |
|  100 | Monica |
+------+--------+
5 rows in set (0.00 sec)

mysql>  select * from sample where Name ='Anil';
+------+------+
| EID  | Name |
+------+------+
|   11 | Anil |
+------+------+
1 row in set (0.00 sec)

mysql>  select Name from sample ;
+--------+
| Name   |
+--------+
| Anil   |
| Sunil  |
| vikas  |
| roy    |
| Rock   |
| Ganesh |
| Satish |
| James  |
| Mark   |
| Monica |
+--------+
10 rows in set (0.00 sec)
```

MySQL 8.0 Command Line Cli

```
mysql>  select EID from sample ;
+------+
| EID  |
+------+
|   11 |
|   22 |
|   33 |
|   44 |
|   55 |
|   66 |
|   77 |
|   88 |
|   99 |
|  100 |
+------+
10 rows in set (0.00 sec)

mysql> create table Sample1 (EID int, Name Varchar(25), Dept Varchar(10), Age int, Addr Varchar(15), Salary int);
Query OK, 0 rows affected (0.04 sec)

mysql> desc Sample1;
+--------+-------------+------+-----+---------+-------+
| Field  | Type        | Null | Key | Default | Extra |
+--------+-------------+------+-----+---------+-------+
| EID    | int         | YES  |     | NULL    |       |
| Name   | varchar(25) | YES  |     | NULL    |       |
| Dept   | varchar(10) | YES  |     | NULL    |       |
| Age    | int         | YES  |     | NULL    |       |
| Addr   | varchar(15) | YES  |     | NULL    |       |
| Salary | int         | YES  |     | NULL    |       |
+--------+-------------+------+-----+---------+-------+
6 rows in set (0.01 sec)

mysql> insert into sample1 values(1,'Anil','Acct',23,'Chennai',15000);
Query OK, 1 row affected (0.02 sec)

mysql> insert into sample1 values(2,'Sunil','Admin',40,'Goa',18000);
Query OK, 1 row affected (0.02 sec)

mysql> insert into sample1 values(3,'Vikas','Acct',35,'Bangalore',20000);
Query OK, 1 row affected (0.02 sec)

mysql> insert into sample1 values(4,'Roy','Acct',37,'Bangalore',20000);
Query OK, 1 row affected (0.02 sec)
```

MySQL 8.0 Command Line Cli

```
mysql> insert into sample1 values(5,'Rock','Admin',35,'mangalore',21000);
Query OK, 1 row affected (0.02 sec)

mysql>  insert into sample1 values(6,'Ganesh','Acct',30,'Cochin',22000);
Query OK, 1 row affected (0.01 sec)

mysql> insert into sample1 values(6,'sathesh','Admin',40,'Chennai',20000);
Query OK, 1 row affected (0.02 sec)

mysql> insert into sample1 values(6,'Ganesh','Acct',30,'Cochin',22000);
Query OK, 1 row affected (0.02 sec)

mysql>  insert into sample1 values(7,'sathesh','Admin',40,'Chennai',23000);
Query OK, 1 row affected (0.02 sec)

mysql>  select * from sample1;
+------+---------+-------+------+-----------+--------+
| EID  | Name    | Dept  | Age  | Addr      | Salary |
+------+---------+-------+------+-----------+--------+
|    1 | Anil    | Acct  |   23 | Chennai   |  15000 |
|    2 | Sunil   | Admin |   40 | Goa       |  18000 |
|    3 | Vikas   | Acct  |   35 | Bangalore |  20000 |
|    4 | Roy     | Acct  |   37 | Bangalore |  20000 |
|    5 | Rock    | Admin |   35 | mangalore |  21000 |
|    6 | Ganesh  | Acct  |   30 | Cochin    |  22000 |
|    6 | sathesh | Admin |   40 | Chennai   |  20000 |
|    6 | Ganesh  | Acct  |   30 | Cochin    |  22000 |
|    7 | sathesh | Admin |   40 | Chennai   |  23000 |
+------+---------+-------+------+-----------+--------+
9 rows in set (0.00 sec)

mysql> delete from sample1 where eid=6;
Query OK, 3 rows affected (0.02 sec)

mysql>  select * from sample1;
+------+---------+-------+------+-----------+--------+
| EID  | Name    | Dept  | Age  | Addr      | Salary |
+------+---------+-------+------+-----------+--------+
|    1 | Anil    | Acct  |   23 | Chennai   |  15000 |
|    2 | Sunil   | Admin |   40 | Goa       |  18000 |
|    3 | Vikas   | Acct  |   35 | Bangalore |  20000 |
|    4 | Roy     | Acct  |   37 | Bangalore |  20000 |
|    5 | Rock    | Admin |   35 | mangalore |  21000 |
|    7 | sathesh | Admin |   40 | Chennai   |  23000 |
+------+---------+-------+------+-----------+--------+
```

MySQL 8.0 Command Line Cli

```
mysql> insert into sample1 values(6,'Ganesh','Acct',30,'Cochin',22000);
Query OK, 1 row affected (0.02 sec)

mysql> insert into sample1 values(8,'James','Admin',38,'Cochin',32000);
Query OK, 1 row affected (0.02 sec)

mysql> insert into sample1 values(9,'Mark','Quality',58,'US',60000);
Query OK, 1 row affected (0.02 sec)

mysql> insert into sample1 values(10,'Monica','Quality',48,'US',50000);
Query OK, 1 row affected (0.02 sec)

mysql>  select * from sample1;
+------+---------+---------+------+-----------+--------+
| EID  | Name    | Dept    | Age  | Addr      | Salary |
+------+---------+---------+------+-----------+--------+
|    1 | Anil    | Acct    |   23 | Chennai   |  15000 |
|    2 | Sunil   | Admin   |   40 | Goa       |  18000 |
|    3 | Vikas   | Acct    |   35 | Bangalore |  20000 |
|    4 | Roy     | Acct    |   37 | Bangalore |  20000 |
|    5 | Rock    | Admin   |   35 | mangalore |  21000 |
|    7 | sathesh | Admin   |   40 | Chennai   |  23000 |
|    6 | Ganesh  | Acct    |   30 | Cochin    |  22000 |
|    8 | James   | Admin   |   38 | Cochin    |  32000 |
|    9 | Mark    | Quality |   58 | US        |  60000 |
|   10 | Monica  | Quality |   48 | US        |  50000 |
+------+---------+---------+------+-----------+--------+
10 rows in set (0.00 sec)

mysql> select Name,age,salary from Sample1 where dept = 'Acct';
+--------+------+--------+
| Name   | age  | salary |
+--------+------+--------+
| Anil   |   23 |  15000 |
| Vikas  |   35 |  20000 |
| Roy    |   37 |  20000 |
| Ganesh |   30 |  22000 |
+--------+------+--------+
4 rows in set (0.00 sec)
```

MySQL 8.0 Command Line Cli

```
mysql> select Name,age,salary from Sample1 where dept = 'Acct' or dept='admin';
+---------+------+--------+
| Name    | age  | salary |
+---------+------+--------+
| Anil    |   23 |  15000 |
| Sunil   |   40 |  18000 |
| Vikas   |   35 |  20000 |
| Roy     |   37 |  20000 |
| Rock    |   35 |  21000 |
| sathesh |   40 |  23000 |
| Ganesh  |   30 |  22000 |
| James   |   38 |  32000 |
+---------+------+--------+
8 rows in set (0.00 sec)

mysql> select Name,age,salary from Sample1 where age>=30 or age<=45;
+---------+------+--------+
| Name    | age  | salary |
+---------+------+--------+
| Anil    |   23 |  15000 |
| Sunil   |   40 |  18000 |
| Vikas   |   35 |  20000 |
| Roy     |   37 |  20000 |
| Rock    |   35 |  21000 |
| sathesh |   40 |  23000 |
| Ganesh  |   30 |  22000 |
| James   |   38 |  32000 |
| Mark    |   58 |  60000 |
| Monica  |   48 |  50000 |
+---------+------+--------+
10 rows in set (0.00 sec)

mysql>  select Name,salary from Sample1 where age>=30 and age<=45;
+---------+--------+
| Name    | salary |
+---------+--------+
| Sunil   |  18000 |
| Vikas   |  20000 |
| Roy     |  20000 |
| Rock    |  21000 |
| sathesh |  23000 |
| Ganesh  |  22000 |
| James   |  32000 |
+---------+--------+
```

MySQL 8.0 Command Line Cli

```
7 rows in set (0.00 sec)

mysql>  select * from sample1;
+------+---------+---------+------+-----------+--------+
| EID  | Name    | Dept    | Age  | Addr      | Salary |
+------+---------+---------+------+-----------+--------+
|    1 | Anil    | Acct    |   23 | Chennai   |  15000 |
|    2 | Sunil   | Admin   |   40 | Goa       |  18000 |
|    3 | Vikas   | Acct    |   35 | Bangalore |  20000 |
|    4 | Roy     | Acct    |   37 | Bangalore |  20000 |
|    5 | Rock    | Admin   |   35 | mangalore |  21000 |
|    7 | sathesh | Admin   |   40 | Chennai   |  23000 |
|    6 | Ganesh  | Acct    |   30 | Cochin    |  22000 |
|    8 | James   | Admin   |   38 | Cochin    |  32000 |
|    9 | Mark    | Quality |   58 | US        |  60000 |
|   10 | Monica  | Quality |   48 | US        |  50000 |
+------+---------+---------+------+-----------+--------+
10 rows in set (0.00 sec)

mysql> select * from sample1 where addr='chennai' or addr='us' or addr='cochin';
+------+---------+---------+------+---------+--------+
| EID  | Name    | Dept    | Age  | Addr    | Salary |
+------+---------+---------+------+---------+--------+
|    1 | Anil    | Acct    |   23 | Chennai |  15000 |
|    7 | sathesh | Admin   |   40 | Chennai |  23000 |
|    6 | Ganesh  | Acct    |   30 | Cochin  |  22000 |
|    8 | James   | Admin   |   38 | Cochin  |  32000 |
|    9 | Mark    | Quality |   58 | US      |  60000 |
|   10 | Monica  | Quality |   48 | US      |  50000 |
+------+---------+---------+------+---------+--------+
6 rows in set (0.00 sec)

mysql> select * from sample1 where addr='chennai' or addr='us' and addr='cochin';
+------+---------+-------+------+---------+--------+
| EID  | Name    | Dept  | Age  | Addr    | Salary |
+------+---------+-------+------+---------+--------+
|    1 | Anil    | Acct  |   23 | Chennai |  15000 |
|    7 | sathesh | Admin |   40 | Chennai |  23000 |
+------+---------+-------+------+---------+--------+
2 rows in set (0.00 sec)

mysql> create table Employee(age tinyint);
Query OK, 0 rows affected (0.05 sec)

mysql> desc Employee;
```

MySQL 8.0 Command Line Cli

```
mysql> desc Employee;
+-------+---------+------+-----+---------+-------+
| Field | Type    | Null | Key | Default | Extra |
+-------+---------+------+-----+---------+-------+
| age   | tinyint | YES  |     | NULL    |       |
+-------+---------+------+-----+---------+-------+
1 row in set (0.01 sec)

mysql> create table Employee1(salary float(10,2));
Query OK, 0 rows affected, 1 warning (0.05 sec)

mysql> create table Employee2(AADH Bigint);
Query OK, 0 rows affected (0.04 sec)

mysql> desc Employee1;
+--------+-------------+------+-----+---------+-------+
| Field  | Type        | Null | Key | Default | Extra |
+--------+-------------+------+-----+---------+-------+
| salary | float(10,2) | YES  |     | NULL    |       |
+--------+-------------+------+-----+---------+-------+
1 row in set (0.00 sec)

mysql> desc Employee2;
+-------+--------+------+-----+---------+-------+
| Field | Type   | Null | Key | Default | Extra |
+-------+--------+------+-----+---------+-------+
| AADH  | bigint | YES  |     | NULL    |       |
+-------+--------+------+-----+---------+-------+
1 row in set (0.00 sec)

mysql> create table Employee3(Eid mediumint);
Query OK, 0 rows affected (0.05 sec)

mysql>  create table Employee4(EXP Smallint);
Query OK, 0 rows affected (0.05 sec)

mysql> desc Employee3;
+-------+-----------+------+-----+---------+-------+
| Field | Type      | Null | Key | Default | Extra |
+-------+-----------+------+-----+---------+-------+
| Eid   | mediumint | YES  |     | NULL    |       |
+-------+-----------+------+-----+---------+-------+
1 row in set (0.00 sec)
```

```
mysql> desc Employee4;
+-------+----------+------+-----+---------+-------+
| Field | Type     | Null | Key | Default | Extra |
+-------+----------+------+-----+---------+-------+
| EXP   | smallint | YES  |     | NULL    |       |
+-------+----------+------+-----+---------+-------+
1 row in set (0.00 sec)

mysql>
```