

ARTIFICIAL INTELLIGENCE RECORD:

NAME: PRATHIKSHA KAMATH

USN: 1BM19CS118

PROGRAM 6:

Create a knowledgebase using prepositional logic and show that the given query entails the knowledge base or not

```
combinations = [(True, True, True), (True, True, False), (True, False, True), (True, False, False),
                 (False, True, True), (False, True, False), (False, False, True),
                 (False, False, False)]
variable = {'p': 0, 'q': 1, 'r': 2}
kb = ''
q = ''
priority = {'~': 3, 'v': 1, '^': 2}

def input_rules():
    global kb, q
    kb = (input("Enter rule: "))
    q = input("Enter the Query: ")

def entailment():
    global kb, q
    print('*'*10+"Truth Table Reference"+"*"*10)
    print('kb', 'alpha')
    print('*'*10)
    for comb in combinations:
        s = evaluatePostfix(toPostfix(kb), comb)
        f = evaluatePostfix(toPostfix(q), comb)
        print(s, f)
        print('-'*10)
        if s and not f:
            return False
    return True

def isOperand(c):
    return c.isalpha() and c != 'v'
```

```
def isLeftParanthesis(c):
    return c == '('

def isRightParanthesis(c):
    return c == ')'

def isEmpty(stack):
    return len(stack) == 0

def peek(stack):
    return stack[-1]

def hasLessOrEqualPriority(c1, c2):
    try:
        return priority[c1] <= priority[c2]
    except KeyError:
        return False

def toPostfix(infix):
    stack = []
    postfix = ''
    for c in infix:
        if isOperand(c):
            postfix += c
        else:
            if isLeftParanthesis(c):
                stack.append(c)
            elif isRightParanthesis(c):
                operator = stack.pop()
                while not isLeftParanthesis(operator):
                    postfix += operator
                    operator = stack.pop()
            else:
                while (not isEmpty(stack)) and hasLessOrEqualPriority(c,
peek(stack)):
                    postfix += stack.pop()
                stack.append(c)
    while (not isEmpty(stack)):
```

```

        postfix += stack.pop()

    return postfix

def evaluatePostfix(exp, comb):
    stack = []
    for i in exp:
        if isOperand(i):
            stack.append(comb[variable[i]])
        elif i == '~':
            val1 = stack.pop()
            stack.append(not val1)
        else:
            val1 = stack.pop()
            val2 = stack.pop()
            stack.append(_eval(i, val2, val1))
    return stack.pop()

def _eval(i, val1, val2):
    if i == '^':
        return val2 and val1
    return val2 or val1

# Test 1
input_rules()
ans = entailment()
if ans:
    print("The Knowledge Base entails query")
else:
    print("The Knowledge Base does not entail query")

```

OUTPUT:

```

Enter rule: (pvq)^(~rvp)
Enter the Query: p^r
*****Truth Table Reference*****
kb alpha
*****
True True
-----
True False
-----
The Knowledge Base does not entail query
PS C:\ai_lab> python -u "c:\ai_lab\entailment.py"
Enter rule: (~qv~pvr)^(~q^p)^q
Enter the Query: r
*****Truth Table Reference*****
kb alpha
*****
False True
-----
False False
-----
False True
-----
False False
-----
False True
-----
False False
-----
False True
-----
False False
-----
The Knowledge Base entails query
PS C:\ai_lab>

```

PROGRAM 7:

Create a knowledge base using prepositional logic and prove the given query using resolution.

```

import re

def negate(term):
    return f'~{term}' if term[0] != '~' else term[1]

def reverse(clause):
    if len(clause) > 2:

```

```

        t = split_terms(clause)
        return f'{t[1]}v{t[0]}'
    return ''

def split_terms(rule):
    exp = '(~*[PQRS])'
    terms = re.findall(exp, rule)
    return terms

def contradiction(query, clause):
    contradictions = [f'{query}v{negate(query)}', f'{negate(query)}v{query}']
    return clause in contradictions or reverse(clause) in contradictions

def resolve(kb, query):
    temp = kb.copy()
    temp += [negate(query)]
    steps = dict()
    for rule in temp:
        steps[rule] = 'Given.'
    steps[negate(query)] = 'Negated conclusion.'
    i = 0
    while i < len(temp):
        n = len(temp)
        j = (i + 1) % n
        clauses = []
        while j != i:
            terms1 = split_terms(temp[i])
            terms2 = split_terms(temp[j])
            for c in terms1:
                if negate(c) in terms2:
                    t1 = [t for t in terms1 if t != c]
                    t2 = [t for t in terms2 if t != negate(c)]
                    gen = t1 + t2
                    if len(gen) == 2:
                        if gen[0] != negate(gen[1]):
                            clauses += [f'{gen[0]}v{gen[1]}']
                        else:
                            if contradiction(query, f'{gen[0]}v{gen[1]}'):
                                temp.append(f'{gen[0]}v{gen[1]}')
                                steps[''] = f"Resolved {temp[i]} and {temp[j]} to
{temp[-1]}, which is in turn null. \

```

```

        \nA contradiction is found when {negate(query)} is
assumed as true. Hence, {query} is true."
        return steps
    elif len(gen) == 1:
        clauses += [f'{gen[0]}']
    else:
        if contradiction(query, f'{terms1[0]}v{terms2[0]}'):
            temp.append(f'{terms1[0]}v{terms2[0]}')
            steps[''] = f"Resolved {temp[i]} and {temp[j]} to
{temp[-1]}, which is in turn null. \
        \nA contradiction is found when {negate(query)} is
assumed as true. Hence, {query} is true."
            return steps
        for clause in clauses:
            if clause not in temp and clause != reverse(clause) and
reverse(clause) not in temp:
                temp.append(clause)
                steps[clause] = f'Resolved from {temp[i]} and {temp[j]}.'
            j = (j + 1) % n
        i += 1
    return steps

def resolution(kb, query):
    kb = kb.split(' ')
    steps = resolve(kb, query)
    print('\nStep\t|Clause\t|Derivation\t')
    print('-' * 30)
    i = 1
    for step in steps:
        print(f' {i}.\t| {step}\t| {steps[step]}\t')
        i += 1

def main():
    print("Enter the kb:")
    kb = input()
    print("Enter the query:")
    query = input()
    resolution(kb, query)

main()

```

OUTPUT:

```
PS C:\ai_lab> python -u "c:\ai_lab\resolution.py"
Enter the kb:
PvQ PvR ~PvR RvS Rv~Q ~Sv~Q
Enter the query:
R

Step    | Clause | Derivation
-----|-----|-----
1.      | PvQ    | Given.
2.      | PvR    | Given.
3.      | ~PvR   | Given.
4.      | RvS    | Given.
5.      | Rv~Q   | Given.
6.      | ~Sv~Q  | Given.
7.      | ~R     | Negated conclusion.
8.      | QvR    | Resolved from PvQ and ~PvR.
9.      | Pv~S   | Resolved from PvQ and ~Sv~Q.
10.     | P      | Resolved from PvR and ~R.
11.     | ~P     | Resolved from ~PvR and ~R.
12.     | Rv~S   | Resolved from ~PvR and Pv~S.
13.     | R      | Resolved from ~PvR and P.
14.     | S      | Resolved from RvS and ~R.
15.     | ~Q     | Resolved from Rv~Q and ~R.
16.     | Q      | Resolved from ~R and QvR.
17.     | ~S     | Resolved from ~R and Rv~S.
18.     |        | Resolved ~R and R to ~RvR, which is in turn null.
A contradiction is found when ~R is assumed as true. Hence, R is true.
PS C:\ai_lab> █
```

PROGRAM 8:

Implement unification in first order logic.

```
import re

def getAttributes(expression):
    expression = expression.split("(")[1:]
    expression = "(" .join(expression)
    expression = expression.split(")")[:-1]
    expression = ")" .join(expression)
    attributes = expression.split(',')
    return attributes
```

```
def getInitialPredicate(expression):
    return expression.split("(")[0]

def isConstant(char):
    return char.isupper() and len(char) == 1

def isVariable(char):
    return char.islower() and len(char) == 1

def replaceAttributes(exp, old, new):
    attributes = getAttributes(exp)
    predicate = getInitialPredicate(exp)
    for index, val in enumerate(attributes):
        if val == old:
            attributes[index] = new
    return predicate + "(" + ",".join(attributes) + ")"

def apply(exp, substitutions):
    for substitution in substitutions:
        new, old = substitution
        exp = replaceAttributes(exp, old, new)
    return exp

def checkOccurs(var, exp):
    if exp.find(var) == -1:
        return False
    return True

def getFirstPart(expression):
    attributes = getAttributes(expression)
    return attributes[0]

def getRemainingPart(expression):
    predicate = getInitialPredicate(expression)
    attributes = getAttributes(expression)
    newExpression = predicate + "(" + ",".join(attributes[1:]) + ")"
    return newExpression
```



```

def unify(exp1, exp2):
    if exp1 == exp2:
        return []

    if isConstant(exp1) and isConstant(exp2):
        if exp1 != exp2:
            print(f"{exp1} and {exp2} are constants. Cannot be unified")
            return []

    if isConstant(exp1):
        return [(exp1, exp2)]

    if isConstant(exp2):
        return [(exp2, exp1)]

    if isVariable(exp1):
        return [(exp2, exp1)] if not checkOccurs(exp1, exp2) else []

    if isVariable(exp2):
        return [(exp1, exp2)] if not checkOccurs(exp2, exp1) else []

    if getInitialPredicate(exp1) != getInitialPredicate(exp2):
        print("Cannot be unified as the predicates do not match!")
        return []

    attributeCount1 = len(getAttributes(exp1))
    attributeCount2 = len(getAttributes(exp2))
    if attributeCount1 != attributeCount2:
        print(
            f"Length of attributes {attributeCount1} and {attributeCount2} do not
match. Cannot be unified")
        return []

    head1 = getFirstPart(exp1)
    head2 = getFirstPart(exp2)
    initialSubstitution = unify(head1, head2)
    if not initialSubstitution:
        return []

    if attributeCount1 == 1:
        return initialSubstitution

    tail1 = getRemainingPart(exp1)

```

```

tail2 = getRemainingPart(exp2)

if initialSubstitution != []:
    tail1 = apply(tail1, initialSubstitution)
    tail2 = apply(tail2, initialSubstitution)

remainingSubstitution = unify(tail1, tail2)
if not remainingSubstitution:
    return []

return initialSubstitution + remainingSubstitution

def main():
    print("Enter the first expression")
    e1 = input()
    print("Enter the second expression")
    e2 = input()
    substitutions = unify(e1, e2)
    print("The substitutions are:")
    print([' / '.join(substitution) for substitution in substitutions])

main()

```

OUTPUT:

```

PS C:\ai_lab> python -u "c:\ai_lab\tempCodeRunnerFile.py"
Enter the first expression
student(Rose)
Enter the second expression
Techer(Mary)
Cannot be unified as the predicates do not match!
The substitutions are:
[]
PS C:\ai_lab> python -u "c:\ai_lab\tempCodeRunnerFile.py"
Enter the first expression
king(x)
Enter the second expression
king(John)
The substitutions are:
['John / x']
PS C:\ai_lab> █

```

PROGRAM 9:

Convert given first order logic statement into Conjunctive normal form.

```
import re

def getAttributes(string):
    expr = '\([^)]+\)'
    matches = re.findall(expr, string)
    return [m for m in str(matches) if m.isalpha()]

def getPredicates(string):
    expr = '[a-z~]+\([A-Za-z,]+\)'
    return re.findall(expr, string)

def DeMorgan(sentence):
    string = ''.join(list(sentence).copy())
    string = string.replace('~~', '')
    flag = '[' in string
    string = string.replace('~[', '')
    string = string.strip(']')
    for predicate in getPredicates(string):
        string = string.replace(predicate, f'~{predicate}')
    s = list(string)
    for i, c in enumerate(string):
        if c == 'V':
            s[i] = '^'
        elif c == '^':
            s[i] = 'V'
    string = ''.join(s)
    string = string.replace('~~', '')
    return f'[{string}]' if flag else string

def Skolemization(sentence):
    SKOLEM_CONSTANTS = [f'{chr(c)}' for c in range(ord('A'), ord('Z')+1)]
    statement = ''.join(list(sentence).copy())
    matches = re.findall('[∀∃].', statement)
    for match in matches[::-1]:
        statement = statement.replace(match, '')
        statements = re.findall('\[[^\]]+\]', statement)
        for s in statements:
```

```

        statement = statement.replace(s, s[1:-1])
    for predicate in getPredicates(statement):
        attributes = getAttributes(predicate)
        if ''.join(attributes).islower():
            statement = statement.replace(
                match[1], SKOLEM_CONSTANTS.pop(0))
        else:
            aL = [a for a in attributes if a.islower()]
            aU = [a for a in attributes if not a.islower()][0]
            statement = statement.replace(
                aU, f'{SKOLEM_CONSTANTS.pop(0)}({aL[0] if len(aL) else
match[1]})')
    return statement

def fol_to_cnf(fol):

    statement = fol.replace("<=>", "_")
    while '_' in statement:
        i = statement.index('_')
        new_statement = '[' + statement[:i] + '=>' + statement[i +
                                                                    1:] + '^[' +
statement[i+1:] + '=>' + statement[:i] + ']'
        statement = new_statement
    statement = statement.replace("=>", "-")
    expr = '\\([([\\^])+)\\]'
    statements = re.findall(expr, statement)
    for i, s in enumerate(statements):
        if '[' in s and ']' not in s:
            statements[i] += ']'
    for s in statements:
        statement = statement.replace(s, fol_to_cnf(s))
    while '-' in statement:
        i = statement.index('-')
        br = statement.index('[') if '[' in statement else 0
        new_statement = '~' + statement[br:i] + 'V' + statement[i+1:]
        statement = statement[:br] + new_statement if br > 0 else new_statement
    while '~V' in statement:
        i = statement.index('~V')
        statement = list(statement)
        statement[i], statement[i+1], statement[i+2] = 'E', statement[i+2], '~'
        statement = ''.join(statement)
    while '~E' in statement:
        i = statement.index('~E')

```

```

        s = list(statement)
        s[i], s[i+1], s[i+2] = '∀', s[i+2], '~'
        statement = ''.join(s)
        statement = statement.replace('~[∀', '[~∀')
        statement = statement.replace('~[∃', '[~∃')
        expr = '([~∀∃])'
        statements = re.findall(expr, statement)
        for s in statements:
            statement = statement.replace(s, fol_to_cnf(s))
        expr = '~\[([^\]]+)\]'
        statements = re.findall(expr, statement)
        for s in statements:
            statement = statement.replace(s, DeMorgan(s))
        return statement

def main():
    print("Enter FOL:")
    fol = input()
    print("The CNF form of the given FOL is: ")
    print(Skolemization(fol_to_cnf(fol)))

# Test 1
main()

```

OUTPUT:

```

Enter FOL:
∀x food(x) => likes(John, x)
The CNF form of the given FOL is:
~ food(A) V likes(John, A)
PS C:\ai_lab> python -u "c:\ai_lab\FOL_CNF.py"
Enter FOL:
[american(x) ^ weapon(y) ^ sells(x, y, z) ^ hostile(z)] => criminal(x)
The CNF form of the given FOL is:
[~american(x) V ~weapon(y) V sells(x, y, z) V ~hostile(z)] V criminal(x)
PS C:\ai_lab> 

```

PROGRAM 10:

Create a knowledgebase consisting of first order logic statements and prove the given query using forward reasoning.

```

import re

def isVariable(x):
    return len(x) == 1 and x.islower() and x.isalpha()

def getAttributes(string):
    expr = '\([^)]+\)'
    matches = re.findall(expr, string)
    return matches

def getPredicates(string):
    expr = '([a-z~+)]\([^&|]+\)'
    return re.findall(expr, string)

class Fact:
    def __init__(self, expression):
        self.expression = expression
        predicate, params = self.splitExpression(expression)
        self.predicate = predicate
        self.params = params
        self.result = any(self.getConstants())

    def splitExpression(self, expression):
        predicate = getPredicates(expression)[0]
        params = getAttributes(expression)[0].strip('()').split(',')
        return [predicate, params]

    def getResult(self):
        return self.result

    def getConstants(self):
        return [None if isVariable(c) else c for c in self.params]

    def getVariables(self):
        return [v if isVariable(v) else None for v in self.params]

    def substitute(self, constants):
        c = constants.copy()
        f = f"{self.predicate}({'.'.join([constants.pop(0) if isVariable(p) else p
for p in self.params])})"

```

```
    return Fact(f)
```

```
class Implication:
```

```
    def __init__(self, expression):
```

```
        self.expression = expression
```

```
        l = expression.split('=>')
```

```
        self.lhs = [Fact(f) for f in l[0].split('&')]
```

```
        self.rhs = Fact(l[1])
```

```
    def evaluate(self, facts):
```

```
        constants = {}
```

```
        new_lhs = []
```

```
        for fact in facts:
```

```
            for val in self.lhs:
```

```
                if val.predicate == fact.predicate:
```

```
                    for i, v in enumerate(val.getVariables()):
```

```
                        if v:
```

```
                            constants[v] = fact.getConstants()[i]
```

```
                            new_lhs.append(fact)
```

```
        predicate, attributes = getPredicates(self.rhs.expression)[
```

```
            0], str(getAttributes(self.rhs.expression)[0])
```

```
        for key in constants:
```

```
            if constants[key]:
```

```
                attributes = attributes.replace(key, constants[key])
```

```
        expr = f'{predicate}{attributes}'
```

```
        return Fact(expr) if len(new_lhs) and all([f.getResult() for f in new_lhs])
```

```
    else None
```

```
class KB:
```

```
    def __init__(self):
```

```
        self.facts = set()
```

```
        self.implications = set()
```

```
    def tell(self, e):
```

```
        if '=>' in e:
```

```
            self.implications.add(Implication(e))
```

```
        else:
```

```
            self.facts.add(Fact(e))
```

```
        for i in self.implications:
```

```
            res = i.evaluate(self.facts)
```

```
            if res:
```

```
                self.facts.add(res)
```

```

def query(self, e):
    facts = set([f.expression for f in self.facts])
    i = 1
    print(f'Querying {e}:')
    for f in facts:
        if Fact(f).predicate == Fact(e).predicate:
            print(f'\t{i}. {f}')
            i += 1

def display(self):
    print("All facts: ")
    for i, f in enumerate(set([f.expression for f in self.facts])):
        print(f'\t{i+1}. {f}')

def main():
    kb = KB()
    print("Enter KB: (enter e to exit)")
    while True:
        t = input()
        if(t == 'e'):
            break
        kb.tell(t)
    print("Enter Query:")
    q = input()
    kb.query(q)
    kb.display()

main()

```

OUTPUT:


```
PS C:\ai_lab> python -u "c:\ai_lab\forward_reasoning.py"
Enter KB: (enter e to exit)
missile(x) = >weapon(x)
missile(M1)
enemy(x, America) = >hostile(x)
american(West)
enemy(Nono, America)
owns(Nono, M1)
missile(x) & owns(Nono, x) = >sells(West, x, Nono)
american(x) & weapon(y) & sells(x, y, z) & hostile(z) =>
criminal(x)
e
Enter Query:
criminal(x)
Querying criminal(x):
    1. criminal(West)
All facts:
    1. enemy(x, America) = >hostile(x)
    2. missile(M1)
    3. criminal(West)
    4. missile(x) = >weapon(x)
    5. missile(x) & owns(Nono, x) = >sells(West, x, Nono)
    6. owns(Nono, M1)
    7. american(West)
    8. enemy(Nono, America)
PS C:\ai_lab> █
```